



Meezan Bank
The Premier Islamic Bank

Meezan Bank E-commerce Payment Gateway API Specification

PRODUCT
DOCUMENTATION



Notice

All information contained in this documentation, as well as the software described in it, is proprietary to Meezan Bank and its affiliates. Meezan Bank reserves any and all intellectual property rights in respect of this document.

The Customer is granted the right to use this document in accordance with the relevant agreement entered into with authorized EPG distributors within Meezan Bank. Except as permitted by the relevant license agreement, no part of this documentation may be reproduced, stored in a retrieval system, or transmitted in any form or by electronic, mechanical, recording, or any other means, without the prior written permission of Meezan Bank.

The limited warranties provided in respect of this document are described in the relevant legal agreement entered into with Meezan Bank. Meezan Bank provides no other warranties, explicit or implied.

This document is confidential and proprietary and is not intended for use by any person other than a named Customer.

EPG is the registered trademark of Meezan Bank entities. Other company, product or service names mentioned herein may be trademarks or service marks of their respective owners.

For information regarding permissions, write to:

Meezan House
C-25, Estate Avenue,
SITE Karachi
Pakistan

Phone: +92 21 38103500

Web: <https://www.meezanbank.com/>

Contents

1	Introduction	1
2	Web API	2
2.1	Order registration request	2
2.2	Order completion request (for two-phase payments)	9
2.3	Payment request	11
2.3.1	Check 3DS Card	16
2.3.2	Browser data collection request	17
2.3.3	Browser data transfer request	18
2.3.3	Service to get a 3DS Method completion notification	21
2.4	Alternative payment request	22
2.5	Finish3dsPayment request	26
2.6	Recurring payment request	28
2.7	Recurring payment update request	29
2.8	Recurring payment details request	31
2.9	Recurring payment report request	33
2.10	Order reversal request	34
2.11	Refund request	36
2.12	Order Status Request	38
2.13	Extended Order Status Request	41
2.14	Request for checking a card for 3-D Secure enrollment	46
2.15	Managing bindings	48
2.15.1	Creating bindings without payments	48
2.15.2	Creating bindings without payments anonymously	50
2.15.3	Processing payments with bindings	53
2.15.4	Modifying the card expiration date in a binding	55
2.15.5	Deactivating a binding	57

2.15.6	Deactivating a binding anonymously	58
2.15.7	Reactivating a binding	60
2.15.8	Checking activation of a binding	61
2.15.9	Getting the list of bindings	62
2.15.10	Getting the list of bindings by PAN or bindingId	64
3	SOAP interface	67
3.1	Order registration request	67
3.2	Order payment request	73
3.3	Registration request for orders with preauthorization	78
3.4	Order payment completion request	84
3.5	finishThreeDs request	86
3.6	Alternative payment request	88
3.7	Recurring payment request	93
3.8	Recurring payment details request	94
3.9	Recurring payment update request	97
3.10	Recurring payment report request	99
3.11	Order reversal request	101
3.12	Refund request	103
3.13	Request for checking a card for 3-D Secure enrollment	105
3.14	Managing bindings	107
3.14.1	Request for creating bindings without payments	108
3.14.2	Request for processing a payment by a binding	110
3.14.3	Request for a binding deactivation	114
3.14.4	Request for a binding activation	116
3.14.5	Request for changing the validity period of a binding	117
3.14.6	Request for the list of bindings of a customer	119
3.14.7	Request for the list of bindings of a bank card	121
4	Reference information	124

4.1	3-D Secure 2 parameter list.....	124
4.2	Response codes	128
5	Glossary	134

1 Introduction

Internet acquiring is used to sell goods and services via the public Internet, allowing customers to use their regular bank cards to make purchases. A merchant planning to sell goods or services via the Internet must ensure the security of the payments being processed by taking the following measures:

- Key data (such as personal data and bank cards details) must be transferred via a secure (SSL or TLS) connection.
- Information about the current payment (amount, currency, or description of the order) and the result of the payment must be protected from and not be accessed by intruders.
- Before the payment is made, the customer's card parameters (for example, the expiration date, cardholder name and so on) should be checked.

The 3-D Secure protocol is used to provide an additional security layer. The major payments networks have introduced their own services based on the 3-D Secure protocol, for example, Mastercard has "Mastercard SecureCode" and Visa has "Verified by Visa".

The Meezan Bank E-commerce Payment Gateway is used as a technology platform. It enables a merchant to perform the necessary safety procedures without the need to significantly restructure their Internet store site and existing business processes.

2 Web API

Interactions between the merchant and the Meezan Bank E-commerce Payment Gateway are implemented as HTTP requests with GET or POST methods to specific URLs. These are separate for each individual request type.

The parameters used in the interactions are sent as parameters of GET or POST requests; their values must be URL-encoded.

The result of processing a request return as a JSON object, for example:

```
{"errorCode": "12", "errorMessage": "Empty amount"}
```

For authorization purposes, each request must include the login and password of the user who manages merchants that were generated during the user's registration. The values are sent as the following parameters:

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	Login of the user generated during registration.
password	AN 1..30	Yes	Password of the user generated during registration.

Either one-phase or two-phase payment schemes may be used:

- **One-phase payment** — a payment for goods or services executed through the Internet with the use of a bank card. It is executed as one action that does not require additional confirmation.
- **Two-phase payment** — a payment for goods or services executed through the Internet with the use of a bank card and requiring additional confirmation. The two-phase mechanism splits the process into checking whether the card is capable of paying (authorization) and debiting the money from the account (financial confirmation). During the first step of a two-phase payment, the bank card paying capacity is checked and money on the customer's account are put on hold. The second step is a confirmation of the funds transfer.

Requests for each of these schemes, which may differ, are described below. One-phase and two-phase payment web API requests include the following:

Note: Order registration request will initiate first in all transactions except MOTO.

2.1 Order registration request

Depending on whether one-phase or two-phase payments are used, one of the following methods is used to register an order:

- register.do — for one-phase payments
- registerPreAuth.do — for two-phase payments

These requests are designed to register orders in the Meezan Bank E-commerce Payment Gateway and have the same set of parameters.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
orderNumber	AN 1..32	Yes	Number (identifier) of the order in the merchant's online store system. It is unique for every store in the system and is generated on the order registration.
amount	N 1..19	Yes	Order amount in the minor denomination (for example, cents).
currency	N3	Yes	Payment currency code in the ISO 4217 format.
returnUrl	AN 1..512	Yes	URL to which the customer is redirected after a successful payment.
description	AN..512	No	Free form description of the order.
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.
clientId	AN 1..255	No	Customer identifier in the merchant system. It is used in bindings.
email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.

Name	Type	Mandatory	Description
phone	AN..255	No	If notifying customers is enabled, the customer's phone number to send SMS notifications to.
jsonParams[]	AN..1024	No	Fields used to store additional information. The type is as follows:
			<code>{"param": "value", "param2": "value2"}</code>
sessionTimeoutSecs	N...9	No	Lifespan of the order, in seconds. The order lifespan duration can be taken from the following parameters (from the highest priority to the lowest): • sessionTimeoutSecs transferred in a request. It overrides all other order timeout settings. • If the sessionTimeoutSecs parameter is not specified, the value from the merchant's settings is used. It is configured by the Alternative session timeout option that must be enabled and the Session duration additional parameter that must be specified. • If none of the above mentioned settings is specified (neither sessionTimeoutSecs nor merchant's timeout), the default value set in Administration > System settings by the default.session.timeout.milliseconds system setting is used (the default value is 1200 seconds) . If the request contains the expirationDate parameter, the sessionTimeoutSecs parameter is ignored.
expirationDate	ANS	No	Date and time when the order is terminated. The following format is used: yyyy-MM-ddTHH:mm:ss If this parameter is not specified, the sessionTimeoutSecs parameter is used to determine the date and time when the order is terminated.

bindingId	AN..255	No	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where the CVC must be entered.
-----------	---------	----	--

features	String	No	Parameter that enables switching on 3-D Secure check for a merchant. The available values are: • FORCE_SSL — in this case, the SSL payment allowed option must be enabled for the merchant. • FORCE_3DS — in this case, the following options must be enabled for the merchant for 3-D Secure checks in different networks: ○ Can use Verified by Visa ○ SecureCode payment allowed
paymentWay	AN..32	No	Payment method used for the payment. The possible values are: • Alternative — payment made using other services, a custom payment method • Apple Pay — payment made using the Apple Pay service • Batch Binding Payment — payment made using a binding that was uploaded by a file • Binding — payment made using a binding • Card — payment made by entering the card details • Card (MOTO) — payment made using the call center

			- Recurrent — recurring payment using an identifier received with an initial payment - Masterpass — payment made using a Masterpass e-wallet - UnionPay — payment made through UnionPay - UPOP MOTO — UPOP payment made using the call center.
			Note: If you need to use custom payment methods, they can be defined through <code>jsonParams[]</code> .
recurrenceType	String	Yes for recurring payments	Way in which subsequent recurring payments are processed: - MANUAL — for manual processing of recurring payments scheduled on the merchant side. - AUTO — for automatic handling of payments scheduled on the EPG side. This parameter is mandatory to register a recurring payment.
recurrenceFrequency	String	For MANUAL: No For AUTO: Yes	Parameter is used only for automatic recurring payments. It is not required for manual payments.
recurrenceStartDate	N8	No	Date when the recurring payment is first sent. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. By default, the current date of the initial payment is used. The value format is <yyyymmdd> .
recurrenceEndDate	N8	No	Date when the recurring payment ends. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory.

			The EPAY.RESP_CODE.EXP_DATE parameter indicates that a recurrence period of a payment is finished. The default EPAY.RESP_CODE.EXP_DATE value is 33. The value format is <yyyymmdd>.
threeDS2Params[]		Conditional	Parameters of the 3-D Secure 2 protocol authentication. The threeDS2Params parameter is a JSON-based structure. This parameter is used for 3-D Secure 2 authentication (for 3-D Secure 1 it is unnecessary). Depending on the type of channel interface that is used to initiate the transaction (deviceChannel), the parameter is mandatory or optional: • Browser-based authentication — optional • Application-based authentication — mandatory

Response parameters

Name	Type	Mandatory	Description
orderId	ANS36	No	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter). It is absent if the order registration has failed (the error is described in the ErrorCode field).
formUrl	AN..512	No	URL of the payment page to which the customer should be redirected. If the order registration has failed, this parameter is absent (the error is described in the ErrorCode field).

errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
recurrenceId	N6	Yes for recurring payments	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Error codes

Value	Description
0	No system error.
1	Order with given order number has already been processed or the childId is incorrect.
	Order with this number was registered, but was not paid.
	Submerchant is blocked or deleted.
3	Unknown currency.
4	Order number is not specified.
	Merchant user name is not specified.
	Amount is not specified.
	Return URL cannot be empty.
	Password cannot be empty.
5	Incorrect value of a request parameter.
	Incorrect value in the Language parameter.

	Access is denied.
	Merchant must change the password.
	Invalid jsonParams[].
7	System error.
14	PaymentWay is invalid.

Request example

```
http://<host:port>/payment/rest/register.do?userName=apiuser&password=apiuserpassword&orderNumber=26122017090900&amount=888&currency=978&returnUrl=http://www.return.url.com
```

Response example

```
{"orderId":"5f9adf5a-4796-4668-9285-07adf3c9a1aa","formUrl":  
"http://10.7.32.60/payment/merchants/Merchant/payment_en.html?mdOrder=5f9adf5a-4796-4668-9285-07adf3c9a1aa"}
```

2.2 Order completion request (for two-phase payments)

The `deposit.do` request is used to complete a preauthorized payment in the case of a two-phase payment.

A merchant can perform this request if it has the relevant permissions in the system.

Request parameters

Name	Type	Mandatory	Description
username	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
amount	N 1..19	Yes	Order amount in the minor denomination (for example, cents).

IMPORTANT: If you specify 0 in the DepositAmount parameter, completion occurs for the entire preauthorized amount.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: 0 in case of a successful transaction - Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes (errorCode) and messages (errorMessage)

Value	Message	Description
0	No system error.	No system error.
5	Erroneous value of a request parameter.	Access is denied.
		The user who processes the merchant's payments must change their password.
		Invalid amount.
		Deposit amount must be zero, or more than 1 currency unit (for example, 1 euro).
6	Incorrect order number.	Unregistered OrderId.
7	System error.	System error.

Request example

```
http://<host:port>/payment/rest/deposit.do?userName=apiuser&password=apiuserpassword&amount=100&orderId=a2565183-fa21-4b8b-84dc-15b34933424d
```

Response example

```
{"errorCode": "0", "errorMessage": "Success"}
```

2.3 Payment request

The payment card data is validated in accordance with the table below:

Name	Description	Validation
PAN	Full card number	Luhn validation (checking if the card number is real) — the number of digits in the card number ranges from 13 to 20.
CVC	Card Verification Code (CVC)	Three digits.
YYYY, MM	Year, month of card expiration	Date (the current or a future one). If the card expires in the current month, a payment is possible until the end of the month.
TEXT	Cardholder name	This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, -, ., a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 26 characters - Null is valid - Uppercase and lowercase are acceptable

The `paymentorder.do` method is used for a payment request.

Only POST requests are supported.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
MDORDER	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the <code>mdOrder</code> parameter).
\$PAN	N 12...19	Yes	Card number.

\$CVC	N..3	Conditional	Card security code: CVV2 (Card Verification Value 2), CVC2 (Card Verification Code 2) and analogous codes. Whether this parameter is mandatory for payments that use the respective payment method, depends on the Can pay by binding without CVV2/CVC2 and Can pay by card without CVV2/CVC2 options: • If the option is selected for a merchant, this parameter is optional for this merchant • If the option is not selected, this parameter is mandatory for the merchant.
YYYY	N..4	Yes	Year when the card expires.
MM	N..2	Yes	Month when the card expires.
TEXT	A..512	No	Cardholder name.
language	A..2	Yes	Language of the information (or error) message that is to be sent in a response to this request.
ip	AN..19	No	IP address of the customer.
email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.
bindingNotNeeded	Boolean	No	Binding settings: • true — disables the creation of a binding after a successful payment (the client identifier sent with the order registration request is deleted from the order details after the payment) • false — a successful payment may result in the creation of a binding (under the relevant conditions). This is the default option.
jsonParams[]	AN..1024	No	Fields used to store additional information. The type is as follows:

			{ "param": "value", "param2": "value2" }
threeDS2Params[]		Conditional	Parameters of the 3-D Secure 2 protocol authentication. The threeDS2Params parameter is a JSON-based structure. This parameter is used for 3-D Secure 2 authentication (for 3-D Secure 1 it is unnecessary). Depending on the type of channel interface that is used to initiate the transaction (deviceChannel), the parameter is mandatory or optional: • Browser-based authentication — optional • Application-based authentication — mandatory

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Code of the error that occurred during the process of a refund.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
info	AN..512	No	Result of the payment attempt. Possible values: • Your order is proceeded, redirecting... • Operation declined. Please check the data and available balance of the card. Redirecting... • Sorry, payment cannot be completed. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact your bank. Redirecting...

			- Payment declined. Please, contact your bank. Redirecting... - Cannot connect to your bank. Please, contact your bank. Redirecting... - Processing timeout. Please, try again later. Redirecting...
redirect	AN..512	No	URL to which the customer is redirected after executing the payment, depending on the payment result.
termUrl	AN..512	No	Return address from ACS for the customer to complete the payment. This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
acsUrl	AN..512	No	URL of the ACS server. This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
paReq	AN..512	Conditional	Payer Authentication Request, a message sent from the MPI to ACS via the cardholder device. PAREq requests the issuer to authenticate its cardholder and contains the cardholder, merchant, and transaction-specific information necessary to perform authentication. It is used in 3-D Secure 1. This parameter is not used in payments that do not require additional authentication on the issuing bank ACS.
cReq	AN..512	Conditional	Challenge Request message. EMV 3-D Secure message sent by the 3DS SDK or 3DS Server where additional information is sent from the cardholder to the ACS to support the authentication process. It must be present for 3-D Secure 2 if a cardholder challenge is required.

cardholderInfo	ANS..128	No	Optional information displayed to the cardholder by the merchant on a Frictionless transaction authentication. The information is received from ACS or the issuer. It provides the details on the authentication, for example, a request to call the issuer if additional authentication is needed. This field is passed for 3-D Secure 2 transactions.
additionalResponseCodes	AN..1024	No	This parameter is transferred in case the AVS (Address Verification Service) check is used (the AVS enabled option must be enabled for the merchant). It contains the result of the cardholder billing address check.

Parameters of the additionalResponseCodes block

Name	Type	Mandatory	Description
type	AN..3	No	Type of additional response code. The available value is AVS.
responseCode	A1	No	AVS response code.
responseMessage	AN..512	No	AVS response message.

Error codes (values of the errorCode field)

Value	Description
0	No system error.
5	There are no more payment attempts.
5	System or internal error.

Request example

```
http://<host:port>/payment/rest/paymentorder.do?userName=apiuser&password=apiuserpassword&MDORDER=aca0f48d-9e99-4437-9335-a50a42c363da&$PAN=400001xx0050&$CVC=123&YYYY=2020&MM=06&TEXT=Card Holder&language=EN
```

Response example in case of a payment that does not require additional authentication on the issuing bank ACS

```
{
  "redirect": "http://www.return.url.com?orderId=aca0f48d-9e99-4437-9335-a50a42c363da",
  "info": "Your order is proceeded, redirecting...",
  "errorCode": 0
}
```

2.3.1 Check 3DS Card

The **/payment/check** method described that provided card in **paymentOrder.do** is eligible for 3DS flow.

The POST method is used to send the request.

Request parameter

Name	Type	Mandatory	Description
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).

Response

The response structure contents

The following parameters are returned in a JSON structure:

Name	Type	Description
is3Ds2Eligible	B	Indicates whether card is eligible for 3DS2.
threeDSServerTransID	AN36	Unique 3DS Server transaction identifier Must be passed in the subsequent authentication request
threeDSMethodURL	ANS..256	ACS URL to collect cardholder browser data
threeDSMethodURLServer	ANS..256	3DS Server URL to collect cardholder browser data. 3DS Requestor should open iframe and send POST request with threeDSServerTransID to this URL

errorCode	N 1..3	Response code: • 0 in case of a successful transaction Other code if an error occurred when processing the request.
completed	B	Indicates whether check completed the process.
error	B	Indicates whether error occurred while processing.

2.3.2 Browser data collection request

The **/api/v1/client/gather** method described below returns the HTML-page used for collection of the data about the cardholder's browser and device when a challenge (additional cardholder's interaction) is necessary. The HTML-page is displayed through the iframe.

Note: There are equivalent methods with different names. Those methods are obsolete, use the method mentioned above.

The POST method is used to send the request.

Request parameter

Name	Type	Mandatory	Description
threeDSServerTransID	string	Yes	Universally unique transaction identifier assigned by the 3DS Server to a single transaction to identify it.

Response

An HTTP status (with a code) is returned as a response. In the case of a success status (200), it is returned with an HTML-page for the browser information collection.

Name	Type	Mandatory	Description
------	------	-----------	-------------

HTTP/<version> <status_code>	N3	No	Response code that reflects the status: 200 – OK This code is returned with an HTML-page for the information collection from the browser in the UTF-8 format. 500 – any error
---	----	----	--

2.3.3 Browser data transfer request

The `/api/v1/client` method described below is used to transmit the cardholder's browser information and device details when a challenge (additional cardholder's interaction) is necessary.

Note: There are equivalent methods with different names. Those methods are obsolete, use the method mentioned above.

The POST method is used to send the request.

Request parameter

Name	Type	Mandatory	Description
clientInfo	string	Yes	Browser information and device details. See the clientInfo parameter description below.
threeDSSTransID	string	Yes	Universally unique transaction identifier assigned by the 3DS Server to a single transaction to identify it.

The **clientInfo** parameter contains the following JSON structure:

Name	Type	Mandatory	Description
------	------	-----------	-------------

userAgent	String	Yes	Information the cardholder's web browser sends in the User-Agent HTTP header when making requests to web sites. It is a string containing information about the cardholder's browser, operating system, device type and other details. The User-Agent format varies for different browsers.
colorDepth	String	Yes	Bit depth of the color palette for displaying images on the cardholder's device screen.
screenHeight	Integer	Yes	Height of the cardholder's device screen.
screenWidth	Integer	Yes	Width of the cardholder's device screen.
javaEnabled	boolean	Yes	Parameter that specifies whether supporting Java is enabled for the cardholder's browser. The available values are: • True • False
browserLanguage	String	Yes	Language of the cardholder's browser.
browserTimeZoneOffset	Integer	Yes	Difference between UTC time and the cardholder's browser local time, in minutes.
browserAcceptHeader	String	Yes	Parameter that informs the server, to which the browser sends a request, on what file formats (MIME-types) are acceptable for the browser as a response.
browserIpAddress	String	Yes	IP address of the cardholder's browser.

fingerprint	String	No	Information collected from the device browser for subsequent identification.
OS	String	No	Operating system used by the cardholder's device.
OSVersion	String	No	Version of the operating system used by the cardholder's device.
device	String	No	Information about the cardholder's device (model, version, and so on).
deviceType	String	No	Type of device on which the browser is running (mobile phone, desktop, tablet, and so on).
isMobile	boolean	No	Parameter that specifies whether the cardholder's device is mobile. The available values are: • true • false
screenPrint	String	No	Information on the the cardholder's device screen resolution.
plugins	String	No	List of plug-ins installed to the cardholder's device browser.
browserTimeZone	String	No	Time zone of the cardholder's browser.

Response

An HTTP status (with a code) is returned as a response.

Name	Type	Mandatory	Description
------	------	-----------	-------------

HTTP/<version> <status_code>	N3	No	Response code that reflects the status: • 200 – OK
			• 500 – any error

2.3.3 Service to get a 3DS Method completion notification

To receive notifications about 3DS Method completion from ACS, the `/api/v1/acs/notification` method is used.

Note: There are equivalent methods with different names (such as `/acs/notification` or `handleAcsNotification`). Those methods are obsolete, use the method mentioned above.

The POST method is used to send the request.

Request parameter

Name	Type	Mandatory	Description
threeDSServerTransID	string	Yes	Universally unique transaction identifier assigned by the 3DS Server to a single transaction to identify it.

Response

An HTTP status (with a code) is returned as a response.

Name	Type	Mandatory	Description
HTTP/<version> <status_code>	N3	No	Response code that reflects the status: • 200 – OK • 400 – Bad request (the required threeDSServerTransID was not found) • 405 – Wrong method is used to send the request

Response example in case of a 3DS-payment that requires additional authentication on the issuing bank ACS

```
{
  "info": "Your order is proceeded, redirecting...",
  "acsUrl": "http://10.7.32.60:6001/acs/pareq",
  "paReq": "eJxVUdFygjAQ/BWG9xKioNQ54tCi
rQ+oo/QDKNwAVYIGENuvbyJQ60Nmdu8um80ezK/FUbugqPKS\nuzo1TF1DHpdJz1NX/wiXT4
4+ZxBmAtHfY9wIZBBgVUUpanni6kWVG1RnsPV2eGbQKzEpZIyADFre\nEXEW8ZpBFJ9fVmtm
jaYT0wTSUyhQrHw2BdIB4FGBbI8X5Is8zep1zhHirQhx2fBafLOJNQYyEGjE\nnkWV1fZoR0r
atkZZ1ekRDNEBUB8jdwbZRqJJk1zxhge+13Vn8bMLD9yZM7eDLs4Lw4AJRE5BENbKR\nnSS3T
Nm2NOjPTmVnS+600UaEsMGrKrvpQR+GkXvEee/9rILMUMurhHwMDvJ5KjnJC5veHgdxdv76r
\nFONaxuSveRivnyfeWxjsNk4QHxJaFZ/V+NIuVba3IawYy4ioTTtJRYAoGdKvjfQr1ehh1b
8e17SS\n",
  "termUrl": "http://10.7.32.60/payment/rest/finish3ds.do",
  "errorCode": 0
}
```

If 3-D Secure is required to perform a payment, then after the response to the payment request has been received, the merchant must redirect the customer to ACS.

To redirect the customer to ACS, the merchant must perform redirection to the address specified in the `acsUrl` parameter with the body of the request.

The request must be in the POST format.

Depending on the integration scheme, after passing the authentication on ACS, the customer is redirected to the merchant or to Meezan Bank E-commerce Payment Gateway. The processes of payment completion for each of these cases are listed below.

Return to the payment gate from ACS

In the classic scheme, the issuing bank's ACS authenticates the cardholder and redirects them to the Meezan Bank E-commerce Payment Gateway sending the Payer Authentication Response (PAREs). If the cardholder was authorized by the ACS successfully, the Meezan Bank E-commerce Payment Gateway authorizes the order. Having received PAREs, EPG processes the authentication results and sends the authorization request to the acquirer's system.

Return to the merchant from ACS. The scheme with the use of an additional method Finish 3DS

In this scheme, the issuing bank's ACS authenticates a cardholder and redirects the cardholder to the merchant. The PAREs from ACS is sent to the merchant. The merchant then transfers it to the Meezan Bank E-commerce Payment Gateway via the `finish3dsPayment.do` method.

2.4 Alternative payment request

The `paymentotherway.do` method is used to configure alternative payment methods, such as through the UnionPay Online Payment (UPOP) system.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.

password	AN 1..30	Yes	User's password.
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order.
paymentWay	AN..32	No	Payment method used for the payment. The possible values are: • Alternative — payment made using other services, a custom payment method • Batch Binding Payment — payment made using a binding that was uploaded by a file • Binding — payment made using a binding • Card — payment made by entering the card details • Card (MOTO) — payment made using the call center • Recurrent — recurring payment using an identifier received with an initial payment • UnionPay — payment made through UnionPay • UPOP MOTO — UPOP payment made using the call center
email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.
phone	AN..255	No	If notifying customers is enabled, the customer's phone number to send SMS notifications to.
jsonParams[]	AN..1024	No	Fields used to store additional information. The type is as follows: <pre>{ "param": "value", "param2": "value2" }</pre>
threeDS2Params[]		No	Parameters of the 3-D Secure 2 protocol authentication. The threeDS2Params parameter is a JSON-based structure. This parameter is used for 3-D Secure 2 authentication (for 3-D Secure 1 it is unnecessary).

			Depending on the type of channel interface that is used to initiate the transaction (deviceChannel), the parameter is mandatory or optional: • Browser-based authentication — optional • Application-based authentication — mandatory
--	--	--	--

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Code of the error that occurred during the process of a refund.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
info	AN..512	No	Result of the payment attempt. Possible values: • Your order is proceeded, redirecting... • Operation declined. Please check the data and available balance of the card. Redirecting... • Sorry, payment cannot be completed. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Cannot connect to your bank. Please, contact your bank. Redirecting... • Processing timeout. Please, try again later. Redirecting...
redirect	AN..512	No	URL to which the customer is redirected after executing the payment, depending on the payment result.
termUrl	AN..512	No	Return address from ACS for the customer to complete the payment.

			This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
acsUrl	AN..512	No	URL of the ACS server. This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
paReq	AN..512	Conditional	Payer Authentication Request, a message sent from the MPI to ACS via the cardholder device. PAREq requests the issuer to authenticate its cardholder and contains the cardholder, merchant, and transaction-specific information necessary to perform authentication. It is used in 3-D Secure 1. This parameter is not used in payments that do not require additional authentication on the issuing bank ACS.
cReq	AN..512	Conditional	Challenge Request message. EMV 3-D Secure message sent by the 3DS SDK or 3DS Server where additional information is sent from the cardholder to the ACS to support the authentication process. It must be present for 3-D Secure 2 if a cardholder challenge is required.

For UPOP payments, `purchaseUpopRedirect.do` is automatically executed after a successful execution of `paymentOtherway.do`. The `purchaseUpopRedirect.do` method generates and sends a form for the cardholder's purchase submission.

Error codes

Value	Description
0	Success.
2	No order found.
5	Access denied.
5	User must change his or her password.
7	Wrong merchant configuration.
7	General error.

Request example

Use a POST request:

```
https://wls01-ecom.bpc.in/epg/rest/paymentotherway.do?userName=ATLoginAPIISO&password=atloginapi&MDORDER=07052148-7cea-4cb2-b323-a61167443794&paymentWay=UPOP
```

Response example

```
https://wls01-ecom.bpc.in/epg/rest/paymentotherway.do?userName=ATLoginAPIISO&password=atloginapi&MDORDER=07052148-7cea-4cb2-b323-a61167443794&paymentWay=UPOP
```

2.5 Finish3dsPayment request

The finish3dsPayment.do request is for the cardholder authentication. It is used to transfer data to the Meezan Bank E-commerce Payment Gateway.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order.
paRes	ANS	Yes	Payer Authentication Response.

Response parameters

Name	Type	Mandatory	Description
redirect	ANS 1..512	No	URL to which the customer is redirected after a successful payment.
errorCode	N 1..3	Yes	Code of the error that occurred in the process of the refund (or a successful operation code).
errorMessage	AN..512	Yes	Description of the error in the language that was sent in the language parameter of the request.

additionalResponseCodes	AN..1024	No	This parameter is transferred in case the AVS (Address Verification Service) check is used (the AVS enabled option must be enabled for the merchant, see MBL EPG User Guide). It contains the result of the cardholder billing address check.
-------------------------	----------	----	---

Parameters of the additionalResponseCodes block

Name	Type	Mandatory	Description
type	AN..3	No	Type of additional response code. The available value is AVS.
responseCode	A1	No	AVS response code.
responseMessage	AN..512	No	AVS response message.

Error codes (values of the errorCode field)

Value	Description
0	Transaction successfully processed.
5	Access is denied.
5	The user that process payments for the merchant must change their password.
6	The order was not found.
7	The order was not found.
7	System error.

Request example

```
http://<host:port>/payment/rest/finish3dsPayment.do?userName=apiuser&password=apiuserpassword&mdOrder=aca0f48d-9e99-4437-9335-a50a42c363da&paRes=eJzFV2uTokoS%2FSsTcz8aPYCC6A3Hi0KNCshT8BtCyRuUN%2Fz6RXu6p%2B9s78bsbtXyIgyLE5VJnso8%0D%0oNjhQeAXWshEyYMHvu0QYbYGGuOL%0D%0AuhK6Mm4o0rGcS60D7KU0ETskYXSWu5SB2xP3qh1UJmKsBncxEd602JvfrYrq2LkLrd0Mk8hjnB%2FG%0D%0A7naxy1HVT7rQOJ15iTuXhZuMtic3BxPzTK7rDX0s46D%2FDwnIu9nx5%2Bnyud19Hk7ftyfPt6a%2FwFG%0D%0ADPms%0D%0A
```

Response example

```
{"redirect":"http://www.return.url.com?orderId= aca0f48d-9e99-4437-9335-a50a42c363da","errorCode":0}
```

2.6 Recurring payment request

The recurringPayment.do method processes subsequent recurring payments based on a respective recurrenceId generated on the first payment registration.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
recurrenceId	N22	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Note: The amount of the current recurring payment can be changed if the following conditions are met:

- At the moment of creation of the initial recurring payment the recurrenceType parameter was set to MANUAL.
- The Recurrent payment with fluctuated amount allowed option is enabled for the merchant.
- The Amount parameter with the new amount specified is added to the current recurringPayment.do request. The amount will be changed only for this particular instance of the recurring payment, all subsequent payments by default will have the amount specified on the first payment instance.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes (errorCode) and messages (errorMessage)

Value	Description
0	No system error.
5	Access denied.
5	The user must change their password.

Request example

```
http://<host:port>/payment/rest/recurrentPayment.do?userName=apiuser&password=apiuserpassword&recurrenceId=46
```

Response example

```
{"error": "Successful recurring payment 61 completed", "errorCode": 0, "errorMessage": "Successful recurring payment 61 completed"}
```

2.7 Recurring payment update request

To update information about a recurring payment the `updateRecurrent.do` service is used.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.
recurrenceType	String	Yes	Way in which subsequent recurring payments are processed: - MANUAL — for manual processing of recurring payments scheduled on the merchant side. - AUTO — for automatic handling of payments scheduled on the EPG side.
recurrenceFrequency	String	For MANUAL: No For AUTO: Yes	Parameter is used only for automatic recurring payments. It is not required for manual payments. ☐
recurrenceStartDate	N8	No	Date when the recurring payment is first sent. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. By default, the current date of the initial payment is used. The value format is <yyyymmdd>.
recurrenceEndDate	N8	No	Date when the recurring payment ends. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. The EPAY.RESP_CODE.EXP_DATE parameter indicates that a recurrence period of a payment is finished. The default EPAY.RESP_CODE.EXP_DATE value is 33. The value format is <yyyymmdd>.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Request example

```
http://<host:port>/payment/rest/updateRecurrent.do?userName=apiuser&password=apiuserpassword&recurrenceId=61&recurrenceType=AUTO&recurrenceFrequency=0 0 * * * ?
```

Response example

```
{"errorCode":0,"recurrenceId":61}
```

2.8 Recurring payment details request

To obtain information about a particular recurring payment, the `getRecurrentDetails` service is used.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends. It is returned for the purpose of validation.
recurrenceType	string	Yes	Way in which subsequent recurring payments are processed: • MANUAL — for manual processing of recurring payments scheduled on the merchant side. • AUTO — for automatic handling of payments scheduled on the EPG side.
recurrenceFrequency	String	For MANUAL: • No For AUTO: • Yes	Parameter is used only for automatic recurring payments. It is not required for manual payments.
recurrenceStartDate	N8	No	Date when the recurring payment is first sent. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. By default, the current date of the initial payment is used. The value format is <yyyymmdd>.

recurrenceEndDate	N8	No	Date when the recurring payment ends. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. The EPAY.RESP_CODE.EXP_DATE parameter indicates that a recurrence period of a payment is finished. The default EPAY.RESP_CODE.EXP_DATE value is 33. The value format is <yyyymmdd>.
-------------------	----	----	---

Request example

```
http://<host:port>/payment/rest/getRecurrentDetails.do?
userName=apiuser&password=apiuserpassword&recurrenceId=61
```

Response example

```
{"errorCode":0,"recurrenceList":[{"frequency":"0 0 * * * ?",
"recurrenceId":61,"startDate":1536872400000,"type":"AUTO"}]}
```

2.9 Recurring payment report request

The service getRecurrentReport is available to obtain a list of transactions processed for a recurring payment.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Response parameters

Name	Type	Mandatory	Description
------	------	-----------	-------------

errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
report[]		Yes	Block containing the list of transactions and their details for the specified recurring payment.

The report block

Name	Type	Mandatory	Description
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends. It is returned for the purpose of validation.
transactionId	N8	Yes	Identifier of the currently processed recurring payment.
status	string	Yes	Status of the current payment.
date		Yes	Date of the payment in the format <yyyymmdd hh:mm:ss>.

Request example

```
https://<host:port>/payment/rest/getRecurrentReport.do?
userName=apiuser&password=apiuserpassword&recurrenceId=61
```

Response example

```
{"errorCode":0,"report":[{"recurrenceId":61,"transactionId":
11220039,"status":"DEPOSITED","date":"2018-09-14 07:44:53"},
{"recurrenceId":61,"transactionId":11220040,"status":"DEPOSITED",
"date":"2018-09-14 07:45:40"}]}
```

2.10 Order reversal request

The reverse.do request is used to cancel a payment for an order. This functionality is available within a limited period (specified by the bank) after a payment has been executed.

The reversal transaction may be performed only once for a payment. If a reversal request results in an error, the next try will fail.

Reversals are available to a merchant only if the merchant has an agreement with its bank to perform reversals. To perform the reversal request, a user must have the relevant permissions.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.
email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.
phone	AN..255	No	If notifying customers is enabled, the customer's phone number to send SMS notifications to.
jsonParams[]	AN..1024	No	Fields used to store additional information. The type is as follows:
			<code>{"param": "value", "param2": "value2"}</code>

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes (errorCode) and messages (errorMessage)

Value	Message	Description
0	No system error.	No system error.
5	Erroneous value of a request parameter.	Access is denied.
		The user must change their password.
		Invalid amount.
		Deposit amount must be zero, or more than 1 currency unit (for example, 1 euro).
6	Incorrect order number.	Unregistered OrderId.
7	System error.	System error.
	Reversal is impossible.	Incorrect internal values, check the hold and deposited amounts.
	Payment must be in a correct state.	Payment must be in a correct state.

Request example

```
http://<host:port>/payment/rest/reverse.do?userName=apiuser&password=apiuserpassword&orderId=aca0f48d-9e99-4437-9335-a50a42c363da
```

Response example

```
{"errorCode": "0", "errorMessage": "Success"}
```

2.11 Refund request

A refund.do request is used to refund deposited money.

This request returns the funds paid for the order back to the customer. The request results in an error if the customer was not charged. Under NDA only the request allows multiple refunds, but their total amount cannot exceed the amount that was deposited from the customer's account as a result of the order.

A merchant's user must have a corresponding permission in the system to perform a refund request.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.

password	AN 1..30	Yes	User's password.
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
amount	N 1..19	Yes	Order amount in the minor denomination (for example, cents).
email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.
phone	AN..255	No	If notifying customers is enabled, the customer's phone number to send SMS notifications to.
jsonParams[]	AN..1024	No	Fields used to store additional information. The type is as follows:
			<code>{"param": "value", "param2": "value2"}</code>

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: 0 in case of a successful transaction - Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes (errorCode) and messages (errorMessage)

Value	Message	Description
0	No system error.	No system error.
5	Incorrect value of a request parameter.	Access is denied.
		The user must change their password.
		Invalid amount.

		Deposit amount must be zero, or more than 1 currency unit (for example, 1 euro).
6	Incorrect order number.	Unregistered OrderId.
7	System error.	System error.
	Payment must be in a correct state.	Payment must be in a correct state.

Request example

```
http://<host:port>/payment/rest/refund.do?userName=apiuser&password=apiuserpassword&amount=333&orderId=a2565183-fa21-4b8b-84dc-15b34933424d
```

Response example

```
{"errorCode": "0", "errorMessage": "Success"}
```

2.12 Order Status Request

To obtain the current state of a registered order, send data with `getOrderStatus.do` method (GET or POST) to the corresponding URL. The order status is determined by the value of the `OrderStatus` parameter.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the <code>mdOrder</code> parameter).
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.

Response parameters

Name	Type	Mandatory	Description
depositAmount	N...5	Yes	Amount to be debited in the order currency. The amount can be less or equal to the preauthorization amount. Note: If the amount parameter is not specified, the operation will be completed for the whole preauthorization amount.
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
currency	N3	Yes	Payment currency code in the ISO 4217 format.
orderStatus	N1	Yes	Displays the order status in MBL EPG. The possible values of the field are listed in the OrderStatus values table below. This parameter is absent if no order with the specified ID is found.
orderNumber	ANS 1..32	No	Number (identifier) of the order in the merchant's online store system. It is unique for every store in the system and is generated on the order registration.
pan	NS 13..19	No	Masked number of the card that was used in payment. It is specified only for paid
expiration	N6	No	Card expiration date in the YYYYMM format. It is specified only for paid orders.
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. • Acceptable characters are: Latin letters, 0-9, \$,), (, - , . , a space • Cardholder name must start with a letter • Minimum length: one Latin letter • Maximum length: 25 characters • Null is valid • Uppercase and lowercase are acceptable
Amount	N 1..19	No	Order amount in the minor denomination (for example, cents).
authorizationResponseId (the deprecated name is approvalCode)	AN6	No	Payments network authorization code. The field has fixed length of six characters; it can contain both numbers and

Ip	NS 15..39	No	IP address of the customer who paid for the orde
clientID	AN 1..255	No	Identifier of the customer in the merchant's system. It is used to implement the binding functional. It may be present, if the merchant has the permissions to create and manage bindings (the Merchant is allowed to use bindings merchant option and other, see "Main information tab" in the Merchants section of EPG user guide.
bindingId	ANS..255	No	Identifier of the binding created when paying this order or created earlier and used to pay for this order. It is present only if the merchant has the permission to create bindings.

The OrderStatus values:

The OrderStatus field may have the following values:

Value	Description
0	Order registered, but not paid.
1	Transaction has been approved (for a one-phase payment).
1	Preauthorization amount was put on hold (for a two-phase payment).
2	Amount was deposited successfully.
3	Authorization has been reversed.
4	Transaction has been refunded.
6	Authorization is declined.

Error codes (values of the errorCode field)

Value	Description
0	Success
2	The order is declined because of an error in the payment credentials.
5	Access is denied.
5	The user must change their password.
5	orderId is empty.

6	orderId is empty.
7	System error

Request example

```
https://<host:port>/epg/rest/getOrderStatus.do?orderId=a2565183-fa21-4b8b-84dc-15b34933424d&language=en&password=apiuserpassword&userName=apiuser
```

Response example

```
{ "expiration": "202006", "cardholderName": "Card Holder", "depositAmount": 100,
  "currency": "978", "authorizationResponseId": "077807", "ErrorCode": "0",
  "ErrorMessage": "Success", "OrderStatus": 2, "OrderNumber": "26122017090903",
  "Pan": "400001**0050", "Amount": 888 }
```

2.13 Extended Order Status Request

The `getOrderStatusExtended.do` is used to obtain the status of a registered order.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
orderId	ANS36	Yes*	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
orderNumber	AN 1..32	Yes*	Number (identifier) of the order in the merchant's online store system. It is unique for every store in the system and is generated on the order registration.
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.

* It is necessary to specify whether `orderId` or `orderNumber` is in the request. If the request contains both parameters, `orderId` has priority. There are three sets of response parameters.

These sets depend on the getOrderStatusExtended version that is specified in the merchant settings.

Response parameters for versions 01, 02, 03

The following parameters are returned regardless of the getOrderStatusExtended version:

Name	Type	Mandatory	Description
OrderNumber	ANS 1..32	No	Number (identifier) of the order in the merchant's online store system. It is unique for every store in the system and is generated on the order registration.
OrderStatus	N1	Yes	Displays the order status in MBL EPG. The possible values of the field are listed in the OrderStatus values table below. This parameter is absent if no order with the specified ID is found.
actionCode	N3	Yes	Processing system authorization code
actionCodeDescription	AN..512	Yes	Action code description in the language specified in the Language parameter.
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
currency	N3	Yes	Payment currency code in the ISO 4217 format.
Amount	N 1..19	No	Order amount in the minor denomination (for example, cents).
date	ANS	Yes	Date of order registration
orderDescription	AN..512	No	Free form description of the order
Ip	NS 15..39	No	IP address of the customer who paid for the order
cardAuthInfo[]		No	Tag containing the payment attributes.
BindingInfo[]		No	Tag containing information about the binding with which the payment is performed.

The orderStatus values:

The OrderStatus field may have the following values:

Value	Description
0	Order registered, but not paid.
1	Transaction has been approved (for a one-phase payment).
1	Preauthorization amount was put on hold (for a two-phase payment).
2	Amount was deposited successfully.
3	Authorization has been reversed.
4	Transaction has been refunded.
6	Authorization is declined.

The cardAuthInfo block parameters

Name	Type	Mandatory	Description
pan	NS 13..19	No	Masked number of the card that was used in payment. It is specified only for paid
expiration	N6	No	Card expiration date in the YYYYMM format. It is specified only for paid orders.
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, - , . , a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 25 characters - Null is valid - Uppercase and lowercase are acceptable
authorizationResponseId (the deprecated name is approvalCode)	AN6	No	Payments network authorization code. The field has fixed length of six characters; it can contain both numbers and
secureAuthInfo[]		No	Tag containing information about the binding with which the payment is performed.

The secureAuthInfo[] block parameters

Note: To exclude the secureAuthInfo block from the method response, disable the Receive 3DS requisites of transactions option for the merchant. See Main information tab in the Merchants section of SmartVista EPG User Guide.

Name	Type	Mandatory	Description
eci	AN2	No	Electronic Commerce Indicator.
cavv	ANS..200	No	Cardholder Authentication Verification Value.
xid	ANS..80	No	Electronic Commerce Transaction Identifier.

Name	Type	Mandatory	Description
clientId	AN 1..255	No	Identifier of the customer in the merchant's system. It is used to implement the binding functional. It may be present, if the merchant has the permissions to create and manage bindings
bindingId	ANS..255	No	Identifier of the binding created when paying this order or created earlier and used to pay for this order. It is present only if the merchant has the permission to create bindings.

Response parameters for versions 02, 03

If getOrderStatusExtended version is 02 or higher, the following parameters are also returned along with the parameters described above

Name	Type	Mandatory	Description
authDateTime	ANS	No	Authorization Date and Time
authRefNum	AN..24	No	Reference Number

TerminalId	AN..10	No	Terminal ID
------------	--------	----	-------------

Response parameters for versions 03

If getOrderStatusExtended version is 03, the following parameters are also returned along with the parameters described above

Name	Type	Mandatory	Description
paymentAmountInfo[]		No	Tag containing information about the confirmation amount, debit amount, and refund amount.
bankInfo[]		No	Tag containing information about the issuing bank.

The paymentAmountInfo block Parameters

Name	Type	Mandatory	Description
paymentState	N..9	No	Payment Status
approvedAmount	N 1..19	No	Amount confirmed to be debited.
depositedAmount	N 1..19	No	Amount confirmed debited from the card
refundedAmount	N 1..19	No	The refund amount

The bankInfo block Parameters

Name	Type	Mandatory	Description
bankName	N..200	No	Name of the issuing bank.

bankCountryCode	N..200	No	Code of the issuing bank country.
bankCountryName	AN..160	No	Name of the country of the issuing bank passed in the language parameter of the request or in the language of the user who has called the method if the language has not been specified in the

Error codes (values of the errorCode field)

Value	Description
0	No System error
1	Expected orderId or orderNumber
2	Order is declined due to an error in the payment credential.
5	Access is denied.
5	The user who processes payments for the merchant must change their password.
6	Unregistered orderId
7	System error

Request example

```
http:///payment/rest/getOrderStatusExtended.do?
userName=apiuser&password=apiuserpassword&orderId= 9249a590-f528-4299-af01-
7c4c92319213
```

Response example

```
{ "errorCode": "0", "errorMessage": "Success", "orderNumber": "20180914104438907",
  "orderStatus": 3, "actionCode": 0, "actionCodeDescription": "", "amount": 5670,
  "currency": "840", "date": 1536911093674, "ip": "10.0.1.223",
  "merchantOrderParams": [], "attributes": [{"name": "mdOrder", "value": "9249a590-f528-4299-af01-7c4c92319213"}], "cardAuthInfo":
  { "expiration": "202107", "cardholderName": "IVAN", "approvalCode":
  "590152", "pan": "440000****0600", "recurrentPaymentId": "61" }
```

2.14 Request for checking a card for 3-D Secure enrollment

The `verifyEnrollment.do` request is used to check a card for enrollment to 3-D Secure.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	User's login.
password	AN 1..30	Yes	User's password.
Pan	N 12...19	Yes	Card number.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
enrolled	A1	No	The flag signifying enrollment of the card to 3-D Secure. The available values are: Y, N, U.
emitterName	AN..160	No	Name of the issuing bank.
emitterCountryCode	AN..4	No	Country codes of the issuing bank.

Error codes (values of the errorCode field)

Value	Description
0	The request has been processed without system errors.
1	The card number is not specified.
1	The card number must be a number containing 13 to 19 digits.
5	Access is denied.
5	The user must change their password.
6	No information is found for the specified card number.
7	System error.

Request example GET

```
http://<host:port>/payment/rest/verifyEnrollment.do?userName=apiuser&password=apiuserpassword&pan=440000xx0700
```

Response example

```
{ "errorCode": "0", "errorMessage": "Success", "emitterName": "TEST CARD",
  "emitterCountryCode": "RU", "enrolled": "Y" }
```

2.15 Managing bindings

A **binding** links together in a merchant system the identifier of a customer of the merchant (`clientId`) and the number of the customer card (PAN). A binding is created on a successful payment for goods or services (a payment without errors, with the response containing `"errorCode": "0", "errorMessage": "Success"`).

If a binding is deleted by the customer, it becomes inactive in the EPG system.

Bindings can be used only if a merchant has the permission to create and manage bindings.

The following database tables are used for the binding:

- BINDING — stores bindings.
- BINDING_HISTORY — stores all binding operations (create, update).

The `bindingId` parameter can be passed to EPG during registration of an order. In that case, the order can be paid only with this binding.

Note: To be able to use binding, a merchant must have the Merchant is allowed to use bindings permission.

2.15.1 Creating bindings without payments

The `createBindingNoPayment.do` method is used to create a binding without a payment. It deactivates other bindings for the same merchant, `clientId`, and PAN.

Note: To be able to execute this method a merchant must have the Can create bindings without payment permission enabled.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.
Pan	N12..19	Yes	Card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM.

cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, , . , a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 25 characters - Null is valid - Uppercase and lowercase are acceptable
Clientid	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.

Response parameters

Name	Type	Mandatory	Description
maskedPan	N12..19	Yes	Masked card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM.
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, , . , a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 25 characters - Null is valid - Uppercase and lowercase are acceptable
clientid	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.

bindingId	AN..255	Yes	Identifier of the binding created. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
error	AN..512	No	Description of the error.

Error codes

Value	Description
0	No system error.
1	Access is denied.
1	Some field is invalid.
1	Binding already exists.
1	System error.

Request example

```
http://<host:port>/payment/rest/createBindingNoPayment.do?
userName=apiuser&password=apiuserpassword&pan=
220000xx0500&expiryDate=202107&cardholderName=IVAN&ClientId=888
```

Response example

```
{"maskedPan":"220000****0500","expiryDate":"202107","cardholderName":
"IVAN","clientId":"888","bindingId":"e3ada8ba-2615-452c-a3f7-cf7e2f400c8b",
"errorCode":0,"error":false}
```

2.15.2 Creating bindings without payments anonymously

The createBindingNoPaymentAnonymous.do method is used to create a binding without a payment anonymously. The method deactivates other bindings for the same merchant and clientId.

Note: To be able to execute this method a merchant must have the Can create bindings without payment permission enabled.

Request parameters

Name	Type	Mandatory	Description
merchantLogin	AN..255	Yes	API user login.
Pan	N12..19	Yes	Card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM.
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, , . , a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 25 characters - Null is valid - Uppercase and lowercase are acceptable
Clientid	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.

Response parameters

Name	Type	Mandatory	Description
maskedPan	N12..19	Yes	Masked card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM.

cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, , . , a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 25 characters - Null is valid - Uppercase and lowercase are acceptable
clientid	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.
bindingId	AN..255	Yes	Identifier of the binding created. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: - This order can be paid only by binding. - The payer is redirected to a payment page where theCVC must be entered.
errorCode	N 1..3	No	Response code: 0 in the case of a successful transaction - Other code if an error occurred when processing the request.
error	AN..512	No	Description of the error.

Error codes

Value	Description
0	No system error.
1	Access is denied.
1	Some field is invalid.
1	Binding already exists.
1	System error.

Request example

```
http://<host:port>/payment/rest/createBindingNoPaymentAnonymous.do?
merchantLogin=Merchant888&pan=220000xx0500&expiryDate=
202107&cardholderName=IVAN&ClientId=888
```

Response example

```
{"maskedPan":"220000****0500","expiryDate":"202107","cardholderName":
"IVAN","clientId":"888","bindingId":"7ced41cd-521f-41a7-9d1e-8b6ffebe9e4"
,"errorCode":0,"error":false}
```

2.15.3 Processing payments with bindings

The paymentOrderBinding.do method is used to perform a payment using a binding.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
bindingId	AN..255	Yes	Identifier of the binding that was created earlier (see Managing bindings). It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: - This order can be paid only by binding. - The payer is redirected to a payment page where theCVC must be entered.
Cvc	N..3	Conditional	Card security code: CVV2 (Card Verification Value 2), CVC2 (Card Verification Code 2) and analogous codes. If the Can pay by binding without CVV2/CVC2 option is selected (see "Main information tab" in SmartVista Ecommerce Payment Gateway: User Guide), this parameter is optional for this merchant, Otherwise, the parameter is mandatory.

language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.
----------	----	----	--

Response parameters

Name	Type	Mandatory	Description
redirect	AN..512	No	URL to which the customer is redirected after executing the payment, depending on the payment result.
info	AN..512	No	Result of the payment attempt. Possible values: • Your order is proceeded, redirecting... • Operation declined. Please check the data and available balance of the card. Redirecting... • Sorry, payment cannot be completed. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Cannot connect to your bank. Please, contact your bank. Redirecting... • Processing timeout. Please, try again later. Redirecting...
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.

Error codes

Value	Description
0	No system error.
1	A required field is absent or invalid.
2	Order not found.
2	Binding not found.
5	Access is denied.
5	User must change the password.
5	ClientId is empty or the merchant does not have a permission (the Merchant is allowed to use bindings merchant option) to execute the method.
7	System error.

Request example

```
http://<host:port>/payment/rest/paymentOrderBinding.do?userName=
apiuser&password=apiuserpassword&mdOrder=
7911c014-6ad3-478c-b8cf-b5d5bce3eacd&bindingId= 7ced41cd-521f-41a7-9d1e-8b6ffebec9e4
```

Response example

```
{"redirect":"https://wls01-
ecom.bpc.in:443/epg/merchants/root/finish.html? orderId=7911c014-6ad3-
478c-b8cf-b5d5bce3eacd&lang=en","info": "Your order is proceeded,
redirecting...","errorCode":0}
```

2.15.4 Modifying the card expiration date in a binding

The `extendBinding.do` method is used to modify the card expiration date in a binding.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.
newExpiry	N6	Yes	New expiration date (year and month) of the card in the following format: YYYYMM

bindingId	AN..255	Yes	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes

Value	Description
0	No system error.
1	A required field is absent or invalid.
2	Binding is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/extendBinding.do?
userName=apiuser&password=apiuserpassword&newExpiry=203107&bindingId=7ced41cd-521f-
41a7-9d1e-8b6ffebec9e4
```

Response example

```
{"errorCode": "0", "errorMessage": "Success"}
```

2.15.5 Deactivating a binding

The `unBindCard.do` method is used to deactivate a binding.

Note: To be able to execute this method a merchant must have the Bindings deactivation on a payment page is allowed permission enabled.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.
bindingId	AN..255	Yes	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes

Value	Description
0	No system error.
1	Invalid state.
2	Binding is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/unBindCard.do?
userName=apiuser&password=apiuserpassword&bindingId= 7ced41cd-521f-41a7-9d1e-
8b6ffebe9e4
```

Response example

```
{"errorCode": "0", "errorMessage": "Success"}
```

2.15.6 Deactivating a binding anonymously

The unbindcardanon.do method is used to deactivate a binding anonymously.

Note: To be able to execute this method a merchant must have the Bindings deactivation on a payment page is allowed permission enabled.

Request parameters

Name	Type	Mandatory	Description
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order.
bindingId	AN..255	Yes	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes

Value	Description
0	No system error.
2	Invalid state.
2	Binding is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/unbindcardanon.do? mdOrder=7c84747b-47b3-430d-ac2a-421e056e8a45&bindingId= e3ada8ba-2615-452c-a3f7-cf7e2f400c8b
```

Response example

```
{"errorCode":0,"errorMessage":"Success"}
```

2.15.7 Reactivating a binding

The `bindCard.do` method is used to activate a binding that was deactivated.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.
bindingId	AN..255	Yes	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the <code>registerOrder</code> request, the following actions apply: - This order can be paid only by binding. - The payer is redirected to a payment page where the CVC must be entered.
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: 0 in case of a successful transaction - Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Error codes

Value	Description
0	No system error.
1	Invalid state.

2	Binding is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/bindCard.do?userName=
apiuser&password=apiuserpassword&bindingId= e3ada8ba-2615-452c-a3f7-
cf7e2f400c8b
```

Response example

```
{"errorCode":0,"errorMessage":"Success"}
```

2.15.8 Checking activation of a binding

The `isBindingEnabled.do` method is used to check whether a binding is active.

Request parameters

Name	Type	Mandatory	Description
merchantLogin	AN 1..100	Yes	Merchant login to access EPG.
bindingId	AN..255	Yes	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where the CVC must be entered.

Response parameter

Name	Type	Mandatory	Description
result	Boolean	Yes	Result of the binding activation check:
			- true — the binding is active. - false — the binding is deactivated.

Error codes

Value	Description
0	No system error.
2	Binding is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/isBindingEnabled.do?
merchantLogin=Merchant888&bindingId= e3ada8ba-2615-452c-a3f7-cf7e2f400c8b
```

Response example

```
{"result":true}
```

2.15.9 Getting the list of bindings

The `getBindings.do` method is used to obtain the list of existing bindings for the customer via `clientId` or `bindingId`.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.
clientId	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.

bindingId	AN..255	No	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.
showExpired	B	No	Flag that specifies whether to include binding of expired cards: • TRUE • FALSE (default value).

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
error	AN..512	No	Description of the error.
bindings[]	AN..1024	No	Array of parameters for each binding. The bindings block parameters are described below.

The bindings block parameters

Name	Type	Mandatory	Description
bindingId	AN..255	Yes	Identifier of the binding created. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where the CVC must be entered.

maskedPan	N12..19	Yes	Masked card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM

Error codes

Value	Description
0	No system errors.
1	clientId is missing.
2	Data is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/getBindings.do?
userName=apiuser&password=apiuserpassword&clientId=888
```

Response example

```
{ "errorCode": "0", "errorMessage": "Success", "bindings":
[ { "bindingId": "e3ada8ba-2615-452c-a3f7-cf7e2f400c8b", "maskedPan":
"220000****0500", "expiryDate": "202107" }, { "bindingId":
"3752a0cd-f6be-4eb3-8309-d2d6a40d4add", "maskedPan":
"440000****0600", "expiryDate": "202107" } ] }
```

2.15.10 Getting the list of bindings by PAN or bindingId

The `getBindingsByCardOrId.do` method is used to obtain the list of existing bindings for the customer via PAN or bindingId.

Note: To be able to execute this method a merchant must have the Can get bindings by card number and bindingId permission enabled.

Request parameters

Name	Type	Mandatory	Description
userName	AN 1..30	Yes	API user login.
password	AN 1..30	Yes	API user password.

pan	N 12...19	No	Card number. This parameter is required if bindingId is not specified.
bindingId	AN..255	No	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where the CVC must be entered. This parameter is required if PAN is not specified.
showExpired	B	No	Flag that specifies whether to include expired bindings in the search result. The available values are TRUE and FALSE (FALSE is default).

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • sOther code if an error occurred when processing the request.
error	AN..512	No	Description of the error.
bindings[]	AN..1024	No	Array of parameters for each binding that are described below.

The bindings block parameters

Name	Type	Mandatory	Description
bindingId	AN..255	Yes	Identifier of the binding created. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.

maskedPan	N12..19	Yes	Masked card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM
clientId	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.

Error codes

Value	Description
0	No system errors.
1	Both PAN and bindingId are missing.
2	Data is not found.
5	Access is denied.
5	User must change the password.
7	System error.

Request example

```
http://<host:port>/payment/rest/getBindingsByCardOrId.do?
userName=apiuser&password=apiuserpassword&pan=440000xx0600
```

Response example

```
{"errorCode": "0", "errorMessage": "Success", "bindings":
[{"bindingId": "3752a0cd-f6be-4eb3-8309-d2d6a40d4add", "maskedPan":
"440000****0600", "expiryDate": "202107", "clientId": "888"}]}
```

3 SOAP interface

3.1 Order registration request

The order registration request, `registerOrder`, is described in Web Services Description Language (WSDL) of the service.

This request is used to register orders.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
merchantOrderNumber	AN 1..32	Yes	Number (identifier) of the order in the merchant's online store system. It is unique for every store in the system and is generated on the order registration.
description	AN..512	No	Free form description of the order.
amount	N 1..19	Yes	Order amount in the minor denomination (for example, cents).
currency	N3	Yes	Payment currency code in the ISO 4217 format.
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.

sessionTimeoutSecs	N...9	No	Lifespan of the order, in seconds. The order lifespan duration can be taken from the following parameters (from the highest priority to the lowest): • sessionTimeoutSecs transferred in a request. It overrides all other order timeout settings. • If the sessionTimeoutSecs parameter is not specified, the value from the merchant's settings is used. It is configured by the Alternative session timeout option that must be enabled and the Session duration additional parameter that must be specified. If none of the above mentioned settings is specified (neither sessionTimeoutSecs nor merchant's timeout), the default value set in Administration > System settings by the default.session.timeout.milliseconds system setting is used (the default value is 1200 seconds) . • If the request contains the expirationDate parameter, the sessionTimeoutSecs parameter is ignored.
bindingId	AN..255	No	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where the CVC must be entered.
expirationDate	ANS	No	Date and time when the order is terminated. The following format is used: yyyy-MM-ddTHH:mm:ss If this parameter is not specified, the sessionTimeoutSecs parameter is used to determine the date and time when the order is terminated.

returnUrl	AN 1..512	Yes	URL to which the customer is redirected after a successful payment.
failUrl	AN..512	No	Web address to which the customer is redirected if the payment fails.
params[]	AN..1024	No	An additional tag with attributes used to pass the additional parameters of a merchant. The limit is 99 characters, and the following characters cannot be used: %, +, \r (end of a line), and \n (line break). To pass N parameters, the request must contain N Params tags in which the name attribute contains the name of a parameter and the value attribute contains its value. The tag description is provided below.
clientId	AN 1..255	No	Customer identifier in the merchant system. It is used in bindings. Note: Specifying this parameter when processing payments with the use of bindings is mandatory. Otherwise, a payment will be unsuccessful.

Name	Type	Mandatory	Description
merchantLogin	AN 1..100	No	Specify the merchant login in this parameter to register an order on behalf of a child merchant.

paymentWay	AN..32	No	Payment method used for the payment. The possible values are: • Alternative — payment made using other services, a custom payment method • Apple Pay — payment made using the Apple Pay service • Batch Binding Payment — payment made using a binding that was uploaded by a file • Binding — payment made using a binding • Card — payment made by entering the card details • Card (MOTO) — payment made using the call center • Recurrent — recurring payment using an identifier received with an initial payment • Masterpass — payment made using a Masterpass e-wallet • UnionPay — payment made through UnionPay • UPOP MOTO — UPOP payment made using the call center Note: If you need to use custom payment methods, they can be defined through <code>jsonParams[]</code>.
features[]	String	No	Parameter that enables switching on 3-D Secure check for a merchant. The available values are: • FORCE_SSL — in this case, the SSL payment allowed option must be enabled for the merchant. • FORCE_3DS — in this case, the following options must be enabled for the merchant for 3-D Secure checks in different networks: ○ Can use Verified by Visa ○ aSecureCode payment allowed

threeDS2Params[]		Conditional	Parameters of the 3-D Secure 2 protocol authentication. The threeDS2Params parameter is a JSON-based structure. This parameter is used for 3-D Secure 2 authentication (for 3-D Secure 1 it is unnecessary). Depending on the type of channel interface that is used to initiate the transaction (deviceChannel), the parameter is mandatory or optional: • Browser-based authentication — optional • Application-based authentication — mandatory
------------------	--	-------------	---

Format of the params block

Name	Type	Mandatory	Description
name	ANS..255	Yes	Name of an additional parameter.
value	ANS..1024	Yes	Value of the additional parameter.

Response parameters

Name	Type	Mandatory	Description
orderId	ANS36	No	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter). It is absent if the order registration has failed (the error is described in the ErrorCode field).
formUrl	AN..512	No	URL of the payment page to which the customer should be redirected. If the order registration has failed, this parameter is absent (the error is described in the ErrorCode field).
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.

recurrenceId	N6	Yes for recurring payments	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.
--------------	----	----------------------------	--

Error codes (errorCode) and messages (errorMessage)

Value	Message	Description
0	Success.	Success.
1	Order number is duplicated.	Order with given order number has already been processed or the childId is incorrect.
		Order with this number was registered, but was not paid.
	Submerchant is not found.	Submerchant is blocked or deleted.
3	Unknown currency.	Unknown currency.
4	Mandatory request parameter is not specified.	Order number is not specified.
		Amount is not specified.
		Return URL cannot be empty.
5	Invalid value of one of the parameters.	Incorrect value of a request parameter.
		Amount is invalid.
		Access is denied.
		The user who manages the merchant's operations must change the password.
7	System error.	System error.
14	PaymentWay is invalid.	PaymentWay is invalid.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/
oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPI</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:registerOrder>
      <order merchantOrderNumber="1557999218552" description="SOAP check"
amount="1" currency="840" sessionTimeoutSecs="5400">
        <returnUrl>http://ya.ru</returnUrl>
        <failUrl>http://failUrl.ru</failUrl>
        <params name="paramName" value="paramValue"/>
      </order>
    </mer:registerOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:registerOrderResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return orderId="539135f4-292e-4905-877c-76b560bda286"
errorCode="0" errorMessage="Success">
        <formUrl>https://wls01-ecom.bpc.in/epg/merchants/ATMerchantAPI/
payment.html?mdOrder=539135f4-292e-4905-877c-76b560bda286&language=en</formUrl>
      </return>
    </ns1:registerOrderResponse>
  </soap:Body>
</soap:Envelope>
```

3.2 Order payment request

The paymentOrder method is used for a payment request.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
year	N..4	Yes	Year when the card expires. The format is YYYY .
month	N..2	Yes	Month when the card expires. The format is MM .
pan	N 12...19	Yes	Card number.
cvc	N..3	Conditional	Card security code: CVV2 (Card Verification Value 2), CVC2 (Card Verification Code 2) and analogous codes. Whether this parameter is mandatory for payments that use the respective payment method, depends on the Can pay by binding without CVV2/CVC2 and Can pay by card without CVV2/CVC2 options: • If the option is selected for a merchant, this parameter is optional for this merchant. • If the option is not selected, this parameter is mandatory for the merchant. The options are configured through the administrative portal UI, see Meezan Bank E-commerce Payment Gateway User Guide.
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. • Acceptable characters are: Latin letters, 0-9, \$,), (, , . , a space • Cardholder name must start with a letter • Minimum length: one Latin letter • Maximum length: 25 characters • Null is valid • Uppercase and lowercase are acceptable
language	A..2	Yes	Language of the information (or error) message that is to be sent in a response to this request.
ip	AN..19	No	IP address of the customer.

email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.
params[]	AN..1024	No	An additional tag with attributes used to pass the additional parameters of a merchant. The limit is 99 characters, and the following characters cannot be used: %, +, \r (end of a line), and \n (line break). To pass N parameters, the request must contain N Params tags in which the name attribute contains the name of a parameter and the value attribute contains its value. The tag description is provided below.

Format of the params tag

Name	Type	Mandatory	Description
name	ANS..255	Yes	Name of an additional parameter.
value	ANS..1024	Yes	Value of the additional parameter.

Response parameters

Name	Type	Mandatory	Description
info	AN..512	No	Result of the payment attempt. Possible values: • Your order is proceeded, redirecting... • Operation declined. Please check the data and available balance of the card. Redirecting... • Sorry, payment cannot be completed. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Cannot connect to your bank. Please, contact your bank. Redirecting... • Processing timeout. Please, try again later. Redirecting...
redirect	AN..512	No	URL to which the customer is redirected after executing the payment, depending on the payment result.
errorCode	N 1..3	Yes	Code of the error that occurred during the process of a refund.
cardholderInfo	ANS..128	No	Optional information displayed to the cardholder by the merchant on a Frictionless transaction authentication. The information is received from ACS or the issuer. It provides the details on the authentication, for example, a request to call the issuer if additional authentication is needed. This field is passed for 3-D Secure 2 transactions.

additionalResponseCodes[]	AN..1024	No	This parameter is transferred in case the AVS (Address Verification Service) check is used (the AVS enabled option must be enabled for the merchant, see SmartVista EPG User Guide). It contains the result of the cardholder billing address check.
---------------------------	----------	----	--

The additionalResponseCodes block parameters

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/
oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPI</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:paymentOrder>
      <order orderId="d12e5540-408b-49c6-8361-274b327e7f89" year="2021"
month="07" pan="440000xx0600" cvc="071" cardholderName="John Doe" language="en" ip="? "
email="? "> <!--Zero or more repetitions:-->
      <params name="? " value="? "/>
    </mer:paymentOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Request example

Name	Type	Mandatory	Description
type	AN..3	No	Type of additional response code. The available value is AVS.
responseCode	A1	No	AVS response code.
responseMessage	AN..512	No	AVS response message.

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:paymentOrderResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant"
      <return info="Your order is proceeded, redirecting..."
redirect="http://localhost:7001/epg/merchants/probe/finish.html?
orderId=ca2303c2-dbfd-46bd-890f-3b3f1cbfdb72&
lang=en&status=payment_deposited" cardholderInfo="Card is not enrolled for 3- D Secure,
please contact your administrator"
    </ns1:paymentOrderResponse>
  </soap:Body>
</soap:Envelope>
```

3.3 Registration request for orders with preauthorization

The order preauthorization request is called registerOrderPreAuth. It is used to register an order in the case of a two-phase payment scheme.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
merchantOrderNumber	AN 1..32	Yes	Number (identifier) of the order in the merchant's online store system. It is unique for every store in the system and is generated on the order registration.

Name	Type	Mandatory	Description
description	AN..512	No	Free form description of the order.
amount	N 1..19	Yes	Order amount in the minor denomination (for example, cents).
currency	N3	Yes	Payment currency code in the ISO 4217 format.
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.

sessionTimeoutSecs	N...9	No	Lifespan of the order, in seconds. The order lifespan duration can be taken from the following parameters (from the highest priority to the lowest): • sessionTimeoutSecs transferred in a request. It overrides all other order timeout settings. • If the sessionTimeoutSecs parameter is not specified, the value from the merchant's settings is used. It is configured by the Alternative session timeout option that must be enabled and the Session duration additional parameter that must be specified. • If none of the above mentioned settings is specified (neither sessionTimeoutSecs nor merchant's timeout), the default value set in Administration > System settings by the default.session.timeout.milliseconds system setting is used (the default value is 1200 seconds). • If the request contains the expirationDate parameter, the sessionTimeoutSecs parameter is ignored.
bindingId	AN..255	No	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where the CVC must be entered.

Name	Type	Mandatory	Description
expirationDate	ANS	No	Date and time when the order is terminated. The following format is used: yyyy-MM-ddTHH:mm:ss If this parameter is not specified, the

			sessionTimeoutSecs parameter is used to determine the date and time when the order is terminated.
returnUrl	AN 1..512	Yes	URL to which the customer is redirected after a successful payment.
failUrl	AN..512	No	Web address to which the customer is redirected if the payment fails.
params	AN..1024	No	Fields used to store additional information. The type is as follows: {"param": "value", "param2": "value2"}
clientId	AN 1..255	No	Customer identifier in the merchant system. It is used in bindings. Note: Specifying this parameter when processing payments with the use of bindings is mandatory. Otherwise, a payment will be unsuccessful.
paymentWay	AN..32	No	Payment method used for the payment. The possible values are: - Alternative — payment made using other services, a custom payment method - Apple Pay — payment made using the Apple Pay service - Batch Binding Payment — payment made using a binding that was uploaded by a file - Binding — payment made using a binding - Card — payment made by entering the card details - Card (MOTO) — payment made using the call center - Recurrent — recurring payment using an identifier received with an initial payment - Masterpass — payment made using a Masterpass e-wallet

			• UnionPay — payment made through UnionPay • UPOP MOTO — UPOP payment made using the call center
features	AN..255	No	Container for the feature parameter, the available values for the parameter are: • AUTO_PAYMENT – if the order registration request initiates executing auto-payments. • VERIFY – If this parameter is specified after the order registration request, the cardholder is to be verified without debiting funds from the cardholder account. Thus it is possible to pass a zero amount in the request. This verification allow the merchant to ensure that a card is used by the cardholder and to debit this card in the future without verifying authentication data (CVC, 3-D Secure) on processing subsequent payments. The details of passing the VERIFY value • Even if the payment amount is to be passed in the request, it will not be debited from the account. • After the order has been successfully registered, it is passed to the REVERSED (canceled) status. Example: <pre><features> <feature>AUTO_PAYMENT</feature> </features></pre>

threeDS2Params[]		Conditional	Parameters of the 3-D Secure 2 protocol authentication. The threeDS2Params parameter is a JSON-based structure. This parameter is used for 3-D Secure 2 authentication (for 3-D Secure 1 it is unnecessary). Depending on the type of channel interface that is used to initiate the transaction (deviceChannel), the parameter is mandatory or optional: • Browser-based authentication — optional • Application-based authentication — mandatory
------------------	--	-------------	---

Response parameters

Name	Type	Mandatory	Description
orderId	ANS36	No	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter). It is absent if the order registration has failed (the error is described in the ErrorCode field).
formUrl	AN..512	No	URL of the payment page to which the customer should be redirected. If the order registration has failed, this parameter is absent (the error is described in the ErrorCode field).
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
recurrenceId	N6	Yes for recurring payments	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Error codes (errorCode) and messages (errorMessage)

Value	Message	Description
0	No system error.	No system error.
1	Order number is duplicated.	Order with given order number has already been processed or the childId is incorrect.
	Submerchant is not found.	Order with this number was registered, but it was not paid. Submerchant is blocked or deleted.
3	Unknown currency.	Unknown currency.
4	Mandatory request parameter is not specified.	Order number is not specified.
		Amount is not specified.
		Return URL cannot be empty.
5	Invalid value of one of the parameters.	Incorrect value of a request parameter.
		Amount is invalid.
		Access is denied.
		The user who manages the merchant's operations must change the password.
7	System error.	System error.
14	PaymentWay is invalid.	PaymentWay is invalid.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/
oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPI</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:registerOrderPreAuth>
      <order merchantOrderNumber="1561616155613"
amount="100" currency="840" sessionTimeoutSecs="0">
        <returnUrl>http://ya.ru</returnUrl>
      </order>
    </mer:registerOrderPreAuth>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"> <soap:Body>
  <ns1:registerOrderPreAuthResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
    <return orderId="ed6a3052-e562-495d-b3ae-3c57f8e950e4"
errorCode="0" errorMessage="Success">
      <formUrl>https://wls01-
ecom.bpc.in/epg/merchants/ATMerchantAPIISO/payment.
html?mdOrder=ed6a3052-e562-495d-b3ae-3c57f8e950e4&language=en</formUrl>
    </return>
  </ns1:registerOrderPreAuthResponse>
</soap:Body>
</soap:Envelope>
```

3.4 Order payment completion request

The `depositOrder` request is used to debit an earlier preauthorized order. This operation can be executed provided that the user who processes the merchant's payments has the corresponding permissions in the system.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
depositAmount	N...5	Yes	Amount to be debited in the order currency. The amount can be less or equal to the preauthorization amount. Note: If the amount parameter is not specified, the operation will be completed for the whole preauthorization amount.
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error.

Error codes (errorCode) and messages (errorMessage)

Value	Description
0	The request has been processed without system errors.
5	The deposit amount exceeds the amount put on hold.
	The deposit amount must be more than zero and not less than one rouble.
	Access denied.
	The user who processes payments for the merchant must change their password.
	orderId is empty.
6	Unknown OrderId.
7	Payment must be in the correct status.

System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu=
"http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">
Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:depositOrder>
      <order
orderId="ed6a3052-e562-495d-b3ae-3c57f8e950e4" depositAmount="100"/>
    </mer:depositOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:depositOrderResponse
xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Success"/>
    </ns1:depositOrderResponse>
  </soap:Body>
</soap:Envelope>
```

3.5 finishThreeDs request

The finishThreeDs request is for the cardholder authentication. It is used to transfer data to the Meezan Bank E-commerce Payment Gateway.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order.

paRes	ANS	Yes	Payer Authentication Response.
-------	-----	-----	--------------------------------

Response parameters

Name	Type	Mandatory	Description
redirect	ANS 1..512	No	URL to which the customer is redirected after a successful payment.
errorCode	N 1..3	Yes	Code of the error that occurred in the process of the refund (or a successful operation code).
errorMessage	AN..512	Yes	Description of the error in the language that was sent in the language parameter of the request.
additionalResponseCodes	AN..1024	No	This parameter is transferred in case the AVS (Address Verification Service) check is used (the AVS enabled option must be enabled for the merchant, see SmartVista EPG User Guide). It contains the result of the cardholder billing address check.

Parameters of the additionalResponseCodes block

Name	Type	Mandatory	Description
type	AN..3	No	Type of additional response code. The available value is AVS.
responseCode	A1	No	AVS response code.
responseMessage	AN..512	No	AVS response message.

Error codes (values of the errorCode field)

Value	Description
0	Transaction successfully processed.
5	Access is denied.
5	The user that process payments for the merchant must change their password.
6	The order was not found.

7	System error.
---	---------------

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu=
"http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd"
    <wsse:UsernameToken wsu:Id="UsernameToken-87">
      <wsse:Username>Login</wsse:Username>
      <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">
        Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:finishThreeDs>
      <order
        mdOrder="ed6a3052-e562-495d-b3ae-3c57f8e950e4" paRes="eJzFV2uTok
oS%2FSsTcz8aPYCC6A3Hi0KNCshT8BtCyRuUN%2Fz6RXu6p%2B9s78bsbtXyIgyLE5VJnso8%0D%0
...
oNJhQeAXWshEyYMHvu0QYbYGGuOL%0D%0AuhK6Mm4oOrGcS60D7KU0ETskYXSWu5SB2xP3qh1UJmK
sBncxEd602JvfrYrq2LkLrd0Mk8hjnB%2FG%0D%0A7naxy1HVT7rQ0J15iTUuXhZuMtic3BxPzTK7
rDX0s46D%2FDwnIu9nx5%2Bnyud19Hk7ftyfPt6a%2FwFG%0D%0ADPms%0D%0A"/>
    </mer:finishThreeDs>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
{"redirect": "http://www.return.url.com?orderId= aca0f48d-9e99-4437-9335-
a50a42c363da", "errorCode": 0}
```

3.6 Alternative payment request

The paymentotherway method is used to configure alternative payment methods, such as through the UnionPay Online Payment (UPOP) system.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order.
paymentWay	AN..32	No	Payment method used for the payment. The possible values are: - Alternative — payment made using other services, a custom payment method - Apple Pay — payment made using the Apple Pay service - Batch Binding Payment — payment made using a binding that was uploaded by a file - Binding — payment made using a binding - Card — payment made by entering the card details - Card (MOTO) — payment made using the call center - Recurrent — recurring payment using an identifier received with an initial payment - Masterpass — payment made using a Masterpass ewallet - UnionPay — payment made through UnionPay - UPOP MOTO — UPOP payment made using the call center
email	ANS..*	No	If notifying customers is enabled, the customer's email address to send notifications to.
phone	AN..255	No	If notifying customers is enabled, the customer's phone number to send SMS notifications to.
jsonParams[]	AN..1024	No	Fields used to store additional information. The type is as follows: <pre>{ "param": "value", "param2": "value2" }</pre>

threeDS2Params[]		Conditional	Parameters of the 3-D Secure 2 protocol authentication. The threeDS2Params parameter is a JSON-based structure. This parameter is used for 3-D Secure 2 authentication (for 3-D Secure 1 it is unnecessary). Depending on the type of channel interface that is used to initiate the transaction (deviceChannel), the parameter is mandatory or optional: • Browser-based authentication — optional • Application-based authentication — mandatory
------------------	--	-------------	---

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Code of the error that occurred during the process of a refund.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.

info	AN..512	No	Result of the payment attempt. Possible values: Your order is proceeded, redirecting... • Operation declined. Please check the data and available balance of the card. Redirecting... • Sorry, payment cannot be completed. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact the merchant. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Payment declined. Please, contact your bank. Redirecting... • Cannot connect to your bank. Please, contact your bank. Redirecting... • Processing timeout. Please, try again later. Redirecting...
redirect	AN..512	No	URL to which the customer is redirected after executing the payment, depending on the payment result.
termUrl	AN..512	No	Return address from ACS for the customer to complete the payment. This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
acsUrl	AN..512	No	URL of the ACS server. This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
paReq	AN..512	No	Payer Authentication Request, a message sent from the MPI to ACS via the cardholder device. PAREq requests the issuer to authenticate its cardholder and contains the cardholder, merchant, and transaction-specific information necessary to perform authentication. It is used in 3-D Secure 1. This parameter is not used in payments that do not require additional authentication on the issuing bank ACS.

For UPOP payments, `purchaseUpopRedirect.do` is automatically executed after a successful execution of `paymentOtherWay.do`. The `purchaseUpopRedirect.do` method generates and sends a form for the cardholder's purchase submission.

Error codes

Value	Description
0	Success.
2	No order found.
5	Access denied.
5	User must change his or her password.
7	Wrong merchant configuration.
7	General error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="
      http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
      xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-
        1.0.xs">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPIISO</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
          username-token-profile-1.0#PasswordText">atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>mer:paymentOrderOtherWay>
    <order orderId="34f99fd9-4b74-4477-b615-101a31856d8a"
      paymentWay="UPOP"></order>
    </mer:paymentOrderOtherWay>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:paymentOrderOtherWayResponse xmlns:ns1="
      http://engine.paymentgate.ru/webservices/merchant">
      <return redirect="
        https://wls01-ecom.bpc.in/epg/upop/purchaseUpopRedirect.do?mdOrder=
        34f99fd9-4b74-4477-b615-101a31856d8a" errorCode="0"/>
    </ns1:paymentOrderOtherWayResponse>
  </soap:Body>
```

```
</soap:Envelope>
```

3.7 Recurring payment request

The recurringPayment method processes subsequent recurring payments based on a respective recurrenceId generated on the first payment registration.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
recurrenceId	N22	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.
updateAccount			The available values are: • YES • NO • FORCE

Response parameters

Name	Type	Mandatory	Description
error	AN 1..512	No	
errorCode	N 1..3	No	Response code: • 0 in case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Information message about the transaction result: a success message or the description of an error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu=
"http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:recurringPayment>
      <request recurrenceId="2322"/>
    </mer:recurringPayment>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:recurringPaymentResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return>
        <error>Successful recurring payment</error>
        <errorCode>0</errorCode>
        <errorMessage>Successful recurring payment</errorMessage>
      </return>
    </ns1:recurringPaymentResponse>
  </soap:Body>
</soap:Envelope>
```

3.8 Recurring payment details request

The getRecurrenceDetails service is used to obtain information about a particular recurring payment.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends. It is returned for the purpose of validation.
recurrenceType	string	Yes	Way in which subsequent recurring payments are processed: • MANUAL — for manual processing of recurring payments scheduled on the merchant side. • AUTO — for automatic handling of payments scheduled on the EPG side.
recurrenceFrequency	String	For MANUAL: • No For AUTO: • Yes	Parameter is used only for automatic recurring payments. It is not required for manual payments.
recurrenceStartDate	N8	No	Date when the recurring payment is first sent. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. By default, the current date of the initial payment is used. The value format is <yyyymmdd>.

recurrenceEndDate	N8	No	Date when the recurring payment ends. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. The EPAY.RESP_CODE.EXP_DATE parameter indicates that a recurrence period of a payment is finished. The default EPAY.RESP_CODE.EXP_DATE value is 33. The value format is <yyyymmdd>.
-------------------	----	----	---

Request example

>

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu=
"http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:getRecurrenceDetails>
      <recurrenceId>2330</recurrenceId>
    </mer:getRecurrenceDetails>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <ns1:recurringPaymentResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
    <return>
      <error>Successful recurring payment</error>
      <errorCode>0</errorCode>
      <errorMessage>Successful recurring payment</errorMessage>
    </return>
  </ns1:recurringPaymentResponse>
</soap:Body>
</soap:Envelope>
```

3.9 Recurring payment update request

The updateRecurrence service is used to update information about a recurring payment.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.
recurrenceType	String	Yes	Way in which subsequent recurring payments are processed: - MANUAL — for manual processing of recurring payments scheduled on the merchant side. - AUTO — for automatic handling of payments scheduled on the EPG side.
recurrenceFrequency	String	For MANUAL: No For AUTO: Yes	Parameter is used only for automatic recurring payments. It is not required for manual payments.
recurrenceStartDate	N8	No	Date when the recurring payment is first sent. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. By default, the current date of the initial payment is used. The value format is <yyyymmdd>.

recurrenceEndDate	N8	No	Date when the recurring payment ends. It is used on the 3-D Secure page and is sent in PaReq to the issuer ACS as it is mandatory. The EPAY.RESP_CODE.EXP_DATE parameter indicates that a recurrence period of a payment is finished. The default EPAY.RESP_CODE.EXP_DATE value is 33. The value format is <yyyymmdd>.
-------------------	----	----	---

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: 0 in case of a successful transaction - Other code if an error occurred when processing the request.
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:updateRecurrence>
      <request recurrenceId="2330" recurrenceType="AUTO" recurrenceFrequency="0 * 1,2 ? 1/2 1L 2018-2021" recurrenceStartDate="20210101" recurrenceEndDate="20210102"/>
    </mer:updateRecurrence>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:updateRecurrenceResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return>
        <errorCode>0</errorCode>
        <recurrenceId>2330</recurrenceId>
      </return>
    </ns1:updateRecurrenceResponse> </soap:Body>
</soap:Envelope>
```

3.10 Recurring payment report request

The getRecurrenceReport service is used to obtain a list of transactions processed for a recurring payment.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Note: A recurring payment must be associated with an active acquirer. If a recurring payment is associated with an acquirer that has been deleted or deactivated, any recurring payments occurring after the deletion or deactivation will be declined by the system. If the acquirer is reactivated, the approval of recurring payments will resume.

Request parameters

Name	Type	Mandatory	Description
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.

report[]		Yes	Block containing the list of transactions and their details for the specified recurring payment. The contents of the report block are detailed below.
----------	--	-----	--

Report block

Name	Type	Mandatory	Description
recurrenceId	N6	Yes	Identifier that is used for a series of all subsequent payments that recur until the recurrence period ends. It is returned for the purpose of validation.
transactionId	N8	Yes	Identifier of the currently processed recurring payment.
status	string	Yes	Status of the current payment.
date		Yes	Date of the payment in the format <yyyymmdd hh:mm:ss>.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:getRecurrenceReport>
      <recurrenceId>2330</recurrenceId>
    </mer:getRecurrenceReport>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" <soap:Body>
  <ns1:getRecurrenceReportResponse xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
    <return>
      <errorCode>0</errorCode>
      <report>
        <recurrenceId>2330</recurrenceId>
        <transactionId>13880058</transactionId>
        <status>DEPOSITED</status>
        <date>2019-10-25T04:54:30.121+05:00</date>
      </report>
    </return>
  </ns1:getRecurrenceReportResponse>
</soap:Body>
```

```

    </report>
  <report>
    <recurrenceId>2330</recurrenceId>
    <transactionId>13880059</transactionId>

    <status>DEPOSITED</status>
    <date>2019-10-25T04:54:31.870+05:00</date>
  </report>
</return>
</ns1:getRecurrenceReportResponse>
</soap:Body>
</soap:Envelope>

```

3.11 Order reversal request

The reverseOrder request is used to reverse an order. This functionality is available for a limited period, that is specified by the bank.

The reversal operation may be performed only once. If the reversal request caused an error, the next try will not be successful.

The reversal operation is only available for merchants based on an agreement with the bank. A user who process the merchant's payments must have the appropriate permission to perform the reversal request.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.
params[]	AN..1024	No	An additional tag with attributes used to pass the additional parameters of a merchant. The limit is 99 characters, and the following characters cannot be used: %, +, \r (end of a line), and \n (line break). To pass N parameters, the request must contain N Params tags in which the name attribute contains the name of a parameter and the value attribute contains its value. The tag description is provided below.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error.

Error codes (errorCode) and messages (errorMessage)

Value	Message	Description
0	No system error.	No system error.
5	Erroneous value of a request parameter.	Access is denied.
		The user who process the merchant's payments must change their password.
		orderId is empty.
6	Incorrect order number.	Unregistered OrderId.
7	System error.	Reversal is impossible for the current transaction. System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/
oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPI</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">
atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:reverseOrder>
      <order orderId="1194676e-cc0b-421f-8252-e3acd0b986bc"/>
    </mer:reverseOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:reverseOrderResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0"/>
    </ns1:reverseOrderResponse>
  </soap:Body>
</soap:Envelope>
```

3.12 Refund request

The refundOrder request is used to refund the deposited money. This request returns the money paid for the order back to the customer. The request results in an error if the customer has not been charged. EPG allows multiple refunds but their total amount cannot exceed the amount that was deposited from the customer's account for the order.

The merchant must have the relevant permissions in the system to perform this operation.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
orderId	ANS36	Yes	Order number generated by EPG after the registration of the order (the same as the mdOrder parameter).
refundAmount	N...5	Yes	Refund amount in the order currency. May be less (lowered by previous refunds) or equal to the charged amount.
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.
params[]	AN..1024	No	An additional tag with attributes used to pass the additional parameters of a merchant. The limit is 99 characters, and the following characters cannot be used: %, +, \r (end of a line), and \n (line break). To pass N parameters, the request must contain N Params tags in which the name attribute contains the name of a parameter and the value attribute contains its value. The tag description is provided below.

Format of the params tag

Name	Type	Mandatory	Description
name	ANS..255	Yes	Name of an additional parameter.
value	ANS..1024	Yes	Value of the additional parameter.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error.

Error codes

Value	Description
0	No system error.
5	Access is denied.
	The user who process the merchant's payments must change their password.
	orderId is empty.
5	Invalid amount.
6	Unregistered OrderId.
7	Refund is impossible for the transaction in the current state.
	Refund amount exceeds deposited amount.
	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/
oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPI</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">
atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:refundOrder>
      <order orderId="488ced8d-08f4-41ab-bb61-00ddf0840534"
refundAmount="1"/>
    </mer:refundOrder>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:refundOrderResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0"/>
    </ns1:refundOrderResponse>
  </soap:Body>
</soap:Envelope>
```

3.13 Request for checking a card for 3-D Secure enrollment

The verifyEnrollment request is used to check a card for enrollment to 3-D Secure.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
pan	N12...19	Yes	Card number.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	No	Error code.
errorMessage	AN 1..512	No	Description of the error in the language that was sent in the language parameter of the request.
isEnrolled	A1	No	Flag signifying enrollment of the card for 3-D Secure. The available values are: Y, N, U.
emitterName	AN..160	No	Name of the issuing bank.
emitterCountryCode	AN..4	No	Country codes of the issuing bank.

Error codes (values of the errorCode field)

Value	Description
0	No system error.
1	The card number is not specified.
1	The card number must be a number containing 13 to 19 digits.
5	Access is denied.
5	The user must change their password.
6	No information is found for the specified card number.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/
oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>ATLoginAPI</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">
atloginapi</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:verifyEnrollment>
      <pan>440000xx0700</pan>
    </mer:verifyEnrollment>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:verifyEnrollmentResponse
xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return isEnrolled="Y"
emitterName="Test bank" emitterCountryCode="RU" errorCode="0"/>
    </ns1:verifyEnrollmentResponse>
  </soap:Body>
</soap:Envelope>
```

3.14 Managing bindings

A **binding** links together in a merchant system the identifier of a customer of the merchant (`clientId`) and the number of the customer card (PAN). A binding is created on a successful payment for goods or services (a payment without errors, with the response containing "errorCode": "0", "errorMessage": "Success").

If a binding is deleted by the customer, it becomes inactive in the EPG system.

Bindings can be used only if a merchant has the permission to create and manage bindings.

The following database tables are used for the binding:

- BINDING — stores bindings
- BINDING_HISTORY — stores all binding operations (create, update).

The `bindingId` parameter can be passed to EPG during registration of an order. In that case, the order can be paid only with this binding.

Note: To be able to use binding, a merchant must have the Merchant is allowed to use bindings permission.

3.14.1 Request for creating bindings without payments

The `createBindingNoPayment` method is used to create a binding without a payment. It deactivates other bindings for the same merchant, `clientID`, and `PAN`.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Note: To be able to execute this method a merchant must have the `Can create bindings without payment` permission enabled.

Request parameters

Name	Type	Mandatory	Description
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. - Acceptable characters are: Latin letters, 0-9, \$,), (, , . , a space - Cardholder name must start with a letter - Minimum length: one Latin letter - Maximum length: 25 characters - Null is valid - Uppercase and lowercase are acceptable
clientid	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.
pan	N12..19	Yes	Card number.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM.

Response parameters

Name	Type	Mandatory	Description
bindingId	AN..255	Yes	Identifier of the binding created. It may be used only if the merchant has the permission to work with bindings.

			If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered.
cardholderName	ANS 1..26	No	Name of the cardholder. This parameter is verified according to the following criteria. • Acceptable characters are: Latin letters, 0-9, \$,), (, -, . , a space • Cardholder name must start with a letter • Minimum length: one Latin letter • Maximum length: 25 characters • Null is valid • Uppercase and lowercase are acceptable
clientid	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.
errorCode	N 1..3	No	Response code: • 0 in the case of a successful transaction • Other code if an error occurred when processing the request.
expiryDate	N6	Yes	Card expiration date (year and month) in the following format: YYYYMM.
maskedPan	N12..19	Yes	Masked card number.

Error codes

Value	Description
0	No system error.
1	Access is denied.
	Some field is invalid.
	Binding already exists.
	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/
2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/
2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:createBindingNoPayment>
      <request>
        <cardholderName>FIRST LAST</cardholderName>
        <clientId>ECOM_AT_387_11_1561028784025</clientId>
        <expiryDate>202107</expiryDate>
        <pan>440000xx0600</pan>
      </request>
    </mer:createBindingNoPayment>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:createBindingNoPaymentResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return>
        <bindingId>8442cd0a-ad0e-45b2-9d2f-e8cf9a1b7596</bindingId>
        <cardholderName>FIRST LAST</cardholderName>
        <clientId>ECOM_AT_387_11_1561028784025</clientId>
        <errorCode>0</errorCode>
        <expiryDate>202107</expiryDate>
        <maskedPan>440000****0600</maskedPan>
      </return>
    </ns1:createBindingNoPaymentResponse>
  </soap:Body>
</soap:Envelope>
```

3.14.2 Request for processing a payment by a binding

The paymentOrderBinding request is used to process a payment with a binding.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
mdOrder	ANS36	Yes	Order number generated by EPG after the registration of the order.
bindingId	AN..36	Yes	Identifier of the binding created when paying this order or created earlier and used to pay for this order. It is present only if the merchant has the permission to create bindings.
params		No	An additional tag with attributes used to pass the additional parameters of a merchant. The limit is 99 characters, and the following characters cannot be used: %, +, \r (end of a line), and \n (line break). To pass N parameters, the request must contain N Params tags in which the name attribute contains the name of a parameter and the value attribute contains its value. The tag description is provided below.
language	A2	No	Language code in the ISO 639-1 format. If unspecified, Meezan Bank E-commerce Payment Gateway uses the default language from the settings of the user used to process the merchant's payments. Error messages are returned in this language.
ip	NS..15	Yes	IP address of the payer.
cvv	N..3	Conditional	Card security code: CVV2 (Card Verification Value 2), CVC2 (Card Verification Code 2) and analogous codes. Whether this parameter is mandatory, depends on the Can pay by binding without CVV2/CVC2 option (see Meezan Bank E-commerce Payment Gateway User Guide): - if the option is selected for a merchant, this parameter is optional for this merchant. - If the option is not selected, this parameter is mandatory for the merchant.
email	ANS..*	No	Email address of the payer.

Response parameters

Name	Type	Mandatory	Description
redirect	ANS..*	No	On a successful response, depending on the payment type: - For an SSL payment, the redirection URL after a payment. - For a 3-D Secure payment, the URL to return to the ACS.
info	ANS..*	No	Result of the payment attempt. Possible values: - Your order is proceeded, redirecting... - Operation declined. Please check the data and available balance of the card. Redirecting... - Sorry, payment cannot be completed. Redirecting... - Payment declined. Please, contact the merchant. Redirecting... - Payment declined. Please, contact the merchant. Redirecting... - Payment declined. Please, contact your bank. Redirecting... - Payment declined. Please, contact your bank. Redirecting... - Cannot connect to your bank. Please, contact your bank. Redirecting... - Processing timeout. Please, try again later. Redirecting...
errorCode	N 1..3	Yes	Error code.
errorMessage	AN 1..512	Yes (on an error)	Description of the error.
acsUrl	ANS..*	No	URL of the ACS server. This parameter is not used in payments that do not require additional authentication on the issuing bank's ACS.
paReq	ANS..*	No	Payer Authentication Request, a message sent from the MPI to ACS via the cardholder device. PAREq

			requests the issuer to authenticate its cardholder and contains the cardholder, merchant, and transaction-specific information necessary to perform authentication. It is used in 3-D Secure 1. This parameter is not used in payments that do not require additional authentication on the issuing bank ACS.
--	--	--	---

Error codes

Value	Description
0	No system error.
1	It is necessary to specify the CVC2/CVV2 code because the merchant does not have a permission to process a payment without CVC.
	Incorrect format of CVC.
	mdOrder is not specified.
	bindingId is not specified.
	The email address does not meet the template format.
	Incorrect language.
2	Order is not found.
	The binding is not found.
5	Access is denied.
	The user who processes the merchant's payments must change the password.
	The maximum number of payments attempted run out or the session timeout expired.
	ClientId is empty or the merchant does not have a permission (the Merchant is allowed to use bindings merchant option) to execute the method.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/
2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/
2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:paymentOrderBinding>
      <order mdOrder="d6993607-ba72-46df-b74f-8be8cb119020"
bindingId="d6271b06-ff06-403c-bd8f-41f197ebd2ea" cvc="071"/>
    </mer:paymentOrderBinding>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:paymentOrderBindingResponse
xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return info="Redirecting..."
redirect="https://wls01-ecom.bpc.in:443/epg/merchants/ATMerchantAPI/
finish.html?orderId=d6993607-ba72-46df-b74f-8be8cb119020&lang=en" errorCode="0"/>
    </ns1:paymentOrderBindingResponse>
  </soap:Body>
</soap:Envelope>
```

3.14.3 Request for a binding deactivation

The unBindCard request is used to disable an existing active binding.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
bindingId	AN..36	Yes	Identifier of the binding created when paying this order or created earlier and used to pay for this order. It is present only if the merchant has the permission to create bindings.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Error code.
errorMessage	AN 1..512	Yes (on an error)	Description of the error.

Error codes

Value	Description
0	No system error.
2	Incorrect binding status (when attempting to deactivate an inactive binding).
	The binding is not found.
5	Access is denied.
	The user who processes the merchant's payments must change the password.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:unBindCard>
      <bindingId>cd59b890-538e-48b2-8e94-036b4e72e5a2</bindingId>
    </mer:unBindCard>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:unBindCardResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant"
      <return errorCode="0" errorMessage="Success"/>
    </ns1:unBindCardResponse>
  </soap:Body>
</soap:Envelope>
```

3.14.4 Request for a binding activation

The bindCard request is used to activate a binding that has not been deactivated earlier.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
bindingId	AN..36	Yes	Identifier of the binding created when paying this order or created earlier and used to pay for this order. It is present only if the merchant has the permission to create bindings.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Error code.
errorMessage	AN 1..512	Yes (on an error)	Description of the error.

Error codes

Value	Description
0	No system error.
2	Incorrect binding status (when attempting to deactivate an inactive binding).
2	The binding is not found.
5	Access is denied.

5	The user who processes the merchant's payments must change the password.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:bindCard>
      <bindingId>9392c7fb-73ce-43db-b264-d81596ddc265</bindingId>
    </mer:bindCard>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:bindCardResponse xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Success"/>
    </ns1:bindCardResponse>
  </soap:Body>
</soap:Envelope>
```

3.14.5 Request for changing the validity period of a binding

The extendBinding method is used to change the validity period of a binding.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
bindingId	AN..36	Yes	Identifier of the binding created when paying this order or created earlier and used to pay for this order. It is present only if the merchant has the permission to create bindings.

newExpiry	N6	Yes	A new date (the year and month) of the expiration of the binding validity period, in the following format: YYYYMM
language	A2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Error code.
errorMessage	AN 1..512	Yes (on an error)	Description of the error.

Error codes

Value	Description
0	No system error.
1	One (or several) of the mandatory parameters is not specified or is specified incorrectly.
2	The binding is not found.
5	Access is denied.
5	The user who processes the merchant's payments must change the password.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:extendBinding>
      <request bindingId="4258da94-87dc-4633-babc-7022df602082" newExpiry="202108"/>
    </mer:extendBinding>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:extendBindingResponse xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Success"/>
    </ns1:extendBindingResponse>
  </soap:Body>
</soap:Envelope>
```

3.14.6 Request for the list of bindings of a customer

The getBindings request is used to obtain a list of bindings by the identifier of a customer.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
clientId	AN 1..255	Yes	Customer identifier in the merchant system. It is used in bindings.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Error code.
errorMessage	AN 1..512	Yes (on an error)	Description of the error.
List of binding elements (consisting of bindingId, maskedPan and expiryDate):			
bindingId	AN..255	No	Identifier of a binding created on an order payment or used to pay for the order. This parameter is present only if the merchant has the permission to create bindings.
maskedPan	N 12...19	No	Masked number of the card that has been used for the payment. This parameter is to be specified only after the order has been paid.
expiryDate	N6	No	Card expiration date (year and month) of the card in the following format: YYYYMM

Error codes

Value	Description
0	No system error.
1	clientId is not specified.
2	The information is not found.
5	Access is denied.
5	The user who processes the merchant's payments must change the password.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/
2004/01/oasis-200401-wss%20wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/
2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body>
    <mer:getBindings>
      <request clientId=
"ECOM_AT_387_12_3" showExpired="true" language="en"/>
    </mer:getBindings>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:getBindingsResponse xmlns:ns1=
"http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Success">
        <bindings>
          <binding bindingId=
"77014c60-6de2-4356-bb05-806aaff0a888" maskedPan="440000****0402"
expiryDate="201607"/>
          <binding bindingId=
"77014c60-6de2-4356-bb05-806aaff0a88e" maskedPan="440000****0600"
expiryDate="202107"/>
        </bindings>
      </return>
    </ns1:getBindingsResponse>
  </soap:Body>
</soap:Envelope>
```

3.14.7 Request for the list of bindings of a bank card

Provided that a merchant has the relevant permissions, the `getBindingsByCardOrId` method can be used to obtain the list of all bindings that relate to a certain bank card. This can be done by a card number or by a known binding identifier.

All bindings that are available to the merchant according to the merchant settings are returned in the response.

The credentials of the user who processes the merchant's transactions (Username and Password) are passed in the header of a SOAP request, not as the request parameters. The header format is given in the request example.

Request parameters

Name	Type	Mandatory	Description
PAN	N 12...19	No	Card number. This parameter is required if bindingId is not specified.
bindingId	AN..255	No	Identifier of the binding that was created earlier. It may be used only if the merchant has the permission to work with bindings. If this parameter is sent in the registerOrder request, the following actions apply: 1. This order can be paid only by binding. 2. The payer is redirected to a payment page where theCVC must be entered. This parameter is required if PAN is not specified.
showExpired	B	No	Flag that specifies whether to include expired bindings in the search result. The available values are TRUE and FALSE (FALSE is default).
language	N2	No	Language in the ISO 639-1 format. If it is not specified, the default language specified in the online store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	N 1..3	Yes	Error code.
errorMessage	AN 1..512	Yes	Description of the completion code.
List of binding elements (consisting of bindingId, maskedPan and expiryDate):			
bindingId	AN..255	No	Identifier of a binding created on an order payment or used to pay for the order. This parameter is present only if the merchant has the permission to create bindings.

maskedPan	N 12...19	No	Masked number of the card that has been used for the payment. This parameter is to be specified only after the order has been paid.
expiryDate	N6	No	Card expiration date (year and month) of the card in the following format: YYYYMM
clientId	AN 1..255	No	Identifier of the customer in the merchant's system. It is used to implement the binding functional. It may be present, if the merchant has the permission to create bindings.

Error codes

Value	Description
0	No system error.
1	Neither a card number, nor a binding identifier is specified.
2	Data is not found.
5	Access is denied.
5	User who processes the merchant's payments must change the password.
7	System error.

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <wsse:UsernameToken wsu:Id="UsernameToken-87">
        <wsse:Username>Login</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">Password</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
</soapenv:Envelope>
```

```

        </wsse:UsernameToken>
      </wsse:Security>
    </soapenv:Header>
    <soapenv:Body>
      <mer:getBindingsByCardOrId>
        <request bindingId=
"fa5174db-ec1f-43a7-8f56-7a2dc5ea628a" showExpired="false"/>
      </mer:getBindingsByCardOrId>
    </soapenv:Body>
  </soapenv:Envelope>

```

Response example

```

<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:getBindingsByCardOrIdResponse
      xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Success">
        <bindings>
          <binding
            bindingId="84bb7fff-3c00-4500-94f2-
92242823d40b" maskedPan="440000****0600"
            expiryDate="202107"
            clientId="ECOM_AT_387_13_1560505408319"/> ...
          <binding
            bindingId="2f8ca170-52d3-4130-bea5-11008b61e95c"
            maskedPan="440000****0600" expiryDate="202107"
            clientId="ECOM_AT_387_11_1561445091488"/>
          </bindings>
        </return>
      </ns1:getBindingsByCardOrIdResponse>
    </soap:Body>
  </soap:Envelope>

```

4 Reference information

This section provides reference information that includes:

- List of Json parameters that can be passed in methods
- Response codes of EPG
- RecurrenceFrequency setting for recurring payments

4.1 3-D Secure 2 parameter list

The following parameters may be transferred in the threeDS2Params block in a method used to send a payment request (paymentorder.do or paymentotherway.do).

Name	Type	Mandatory	Description
deviceChannel	N2	Yes	Parameter that indicates the type of channel interface that is used to initiate the transaction. The accepted values are as follows: • 01 = App-based (APP)

			• 02 = Browser (BRW) • 03 = 3DS Requestor Initiated (3RI) • 04–79 = Reserved for EMVCo future use (values invalid until defined by EMVCo) • 80–99 = Reserved for DS use
deviceRenderOptions[]		Yes	Information about the rendering types and interface that the device supports. This parameter defines the SDK UI types that the device supports for displaying specific challenge user interfaces within the SDK.
			Note: All device rendering options must be supported by the SDK and ACS components. Data will be formatted into a JSON object before being placed into the Device Rendering Options Supported field of the message.
sdkAppID	ANS36	Yes	Universally unique identifier created upon all installations and updates of the 3DS Requestor App on a Consumer Device. This identifier will be newly generated and stored by the 3DS SDK for each installation or update. The identifier format is standard as defined in IETF RFC 4122.
sdkEphemPubKey	ANS..256	Yes	Public key component of the ephemeral key pair generated by the 3DS SDK and used to establish session keys between the 3DS SDK and ACS. In AReq, this data element is present as its own object. In ARes, this data element is contained within the ACS Signed Content JWS Object.
sdkMaxTimeout	N2	Yes	Parameter that indicates the maximum time interval (in minutes) for all exchanges.
sdkReferenceNumber	ANS32	Yes	Parameter that identifies the vendor and version for the 3DS SDK that is integrated in a 3DS Requestor App, assigned by EMVCo when the 3DS SDK is approved.
sdkTransID	ANS36	Yes	Universally unique transaction identifier assigned by the 3DS SDK to identify a single transaction.

cardholderAccount[]		No	Optional information about the cardholder account.
merchantRiskIndicator[]		No	Optional information about the specific purchase made by the cardholder.
threeDSRequestorAuthentication[]		No	Optional information about how the cardholder was authenticated during the process of logging in to their 3DS Requestor account.
threeDSRequestorPriorTransactionAuthentication[]		No	Optional information about the 3DS authentication of a cardholder that occurred before the current transaction.

The threeDSRequestorAuthentication block parameters

Name	Type	Mandatory	Description
threeDSReqAuthData	ANS..2048	No	Data that documents and supports a specific authentication process. In the current version of the EMV 3-D Secure Protocol and Core Functions Specification, Version 2.1.0., this data element is not defined in detail. The planned usage is that for each 3DS Requestor Authentication Method, this field carries data which the ACS can use to verify the authentication process. Example: • 02—the field can carry generic 3DS Requestor authentication information • 03—the field can carry information about the provider of the federated ID and related information • 04—the field can carry the FIDO attestation data (including the signature) In future versions of the specification, these details are expected to be included.
threeDSReqAuthMethod	N2	No	Mechanism used by the cardholder to authenticate at the 3DS Requestor. The accepted values are as follows:

			01 = No 3DS Requestor authentication occurred (for example, cardholder “logged in” as guest) 02 = Login to the cardholder account at the 3DS Requestor system using 3DS Requestor’s own credentials 03 = Login to the cardholder account at the 3DS Requestor system using federated ID 04 = Login to the cardholder account at the 3DS Requestor system using issuer credentials 05 = Login to the cardholder account at the 3DS Requestor system using third-party authentication 06 = Login to the cardholder account at the 3DS Requestor system using FIDO Authenticator 07–79 = Reserved for EMVCo future use (values invalid until defined by EMVCo) 80–99 = Reserved for DS use
threeDSReqAuthTimestamp	N12	No	Date and time in UTC of the cardholder authentication. The date format is YYYYMMDD.

The threeDSRequestorPriorTransactionAuthentication block parameters

Name	Type	Mandatory	Description
threeDSReqPriorAuthData	ANS..2048	No	Data that documents and supports a specific authentication process. In the current version of the EMV 3-D Secure Protocol and Core Functions Specification, Version 2.1.0., this data element is not defined in detail. The planned usage is for each 3DS Requestor Authentication Method, this field carries data that the ACS can use to verify the authentication process. In future versions of the

			specification, these details are expected to be included.
threeDSReqPriorAuthMethod	N2	No	Mechanism used by the cardholder previously to authenticate at the 3DS Requestor. The accepted values are as follows: • 01 = Frictionless authentication occurred by ACS • 02 = Cardholder challenge occurred by ACS • 03 = AVS verified • 04 = Other issuer methods • 05–79 = Reserved for EMVCo future use (values invalid until defined by EMVCo) • 80–99 = Reserved for DS use
threeDSReqPriorAuthTimestamp	N12	No	Date and time in UTC of the prior cardholder authentication. The date format is YYYYMMDD.
threeDSReqPriorRef	N36	No	This data element provides additional information to the ACS to determine the best approach for handling a request. This data element contains an ACS Transaction ID for a previously authenticated transaction (for example, the first recurring transaction that was authenticated by the cardholder).

4.2 Response codes

An action code is a digital code of a result received after the merchant's user addressed to EPG. The codes used in the system are listed in the table below.

Action code	error_message	Description
-20010	BLOCKED_BY_LIMIT	Transaction is rejected because the amount exceeds the limit specified by the issuing bank.
-3003	Unknown	Unknown error.

-2020	Invalid ECI received	Invalid Electronic Commerce Indicator — the ECI received in PaRes is not valid for the payments network. The rule applies only to the following payments networks: • Mastercard — possible values: 01, 02 • Visa — possible values: 05, 06
-2018	Declined. DS connection timeout	There is no access to the Directory Server (DS) for Visa or Mastercard, or a connection error has occurred after a card involvement request (VeReq). This is an error of interaction between the SmartVista Ecommerce Payment Gateway and the payments network's servers due to technical problems with the payments network's servers.

Action code	error_message	Description
-2017	Declined. The PARes status is not Y	Transaction is rejected. PARes status is not set to Y.
-2016	Declined. VERes status is \"U\"	VERes status is unknown. The issuing bank could not determine if the card is enrolled for 3-D Secure.
-2013	No attempts left	All attempts allowed to perform a payment have been used.
-2011	PARes status is \"U\"	PARes status is unknown. The issuing bank was not able to perform the 3-D Secure card authorization.
-2007	Session time limit	Period of entering the payment card details has expired (by default the timeout is 20 minutes).
		Note: The session duration may be specified while registering an order — if the merchant has the Alternative session timeout permission, then the timeout duration is specified in the merchant settings.
-2006	TDS_AUTH_FAILED	Issuing bank rejected authentication (3-D Secure authorization has failed).

-2005	TDS_AUTH_FAILED	Issuing bank signature could not be checked (that is, the PARES was readable but the signature was incorrect); or the authentication status in PaRes was N.
-2003	BLOCKED_BY_PORT	Result of the fraud validation.
-2002	BLOCKED_BY_AMOUNT	Transaction was rejected because the payment amount exceeded the specified limits.
		Note: It may be the daily withdrawal limit specified by the acquiring bank, the limit of transactions for one card specified by the merchant, or the limit for one transaction specified by a merchant.
-2001	BLOCKED_BY_IP	Transaction is rejected because the customer's IP address is in the black list.
-2000	BLOCKED_BY_PAN	Transaction is rejected because the card number is in the black list.
-100	No payment attempted yet	There were not payment attempts.
-1	Processing not available	Timer used to wait for a processing response has expired.
0	Request processed successfully	Payment has been performed successfully.

Action code	error_message	Description
5	Network refused transaction	Code received from SVFE in case of a failed payment.
100	Card limits exceeded	Transaction is declined because of card limits — the issuing bank has forbidden Internet transactions on the card.
101	Wrong expiry date	Transaction is declined. The card has expired.
103	Contact issuer	No connection to the issuing bank. The merchant needs to contact the issuing bank.
106	PIN attempts exceeded. Card is blocked.	Maximum number of PIN input attempts is exceeded. The card may be blocked temporary.
111	Decline. Wrong PAN	Card number is incorrect.

116	Not enough money.	Transaction is declined because the amount exceeds the available balance of the selected account.
119	Security violation	Code 37 in accordance with the IBANK protocol.
120	Transaction was refused.	Transaction is not allowed by the issuing bank. The response code of the payments network is 57. The reason for rejecting the transaction should be specified by the issuing bank.
121	Limit exceeded.	Attempt has been made to perform a transaction with an amount exceeding the daily limit specified by the issuing bank.
125	Invalid card number.	Card number is incorrect. This error may have several meanings: • An attempt has been made to perform a refund of the amount exceeding the hold amount. • An attempt has been made to refund a zero amount. • The expiration date is specified incorrectly (for American Express only).
903	Limit exceeded.	Attempt has been made to perform a transaction with an amount that exceeds the issuing bank's limit.
904	Invalid message format	Internal system error.

Action code	error_message	Description
910	Cannot contact bank.	Host of the issuing bank is not available.
914	Original transaction not found	Transaction is not found when sending a completion, reversal, or refund request.
999	Transaction refused by fraud.	Beginning of the transaction authorization has been missed. The transaction is declined due to fraud.
1001	EMPTY	This code is specified at the moment of the transaction's authorization, when the card details have not been entered yet.
2002	Invalid operation	Incorrect transaction.

2003	SSL_FORBIDDEN	SSL (not 3-D Secure or SecureCode) transactions are forbidden for the merchant.
2004	SSL without CVC forbidden	Payment via SSL without the CVC2 is forbidden.
2005	3DS rule failed	Payment does not meet the 3-D Secure validation requirements.
2009	Refund more than deposited error	Refund amount exceeds the deposited amount.
2014	3DS rule error	3-D Secure rule execution error has occurred.
2015	Terminal select rule error	Terminal selection rule is incorrectly configured.
2016	3DS forbidden	3-D Secure authorization is impossible for the given card and merchant.
8204	Duplicate order	Order is duplicated.
151018	CANNOT_SEND_REQUEST	Processing timeout. Sending the request has failed.
151019	RESPONSE_TIMEOUT	Processing timeout. Sending of the request is successful, however a response from the bank has not been received.
341014	GENERAL_ERROR	General error.
341015	Masterpass checkout failed	Checkout procedure has failed for a Masterpass payment.
341016	TDS2_DECLINED_BY_ARES	3DS2 authentication is declined by the Issuer's ACS in the Authentication Response (ARes).
341017	TDS2_UNKNOWN_STATUS_IN_ARES	3DS2 authentication status in ARes is unknown.
341018	TDS2_CHALLENGE_CANCELLED	3DS2 CReq (Challenge Request) has been cancelled.
341019	TDS2_CHALLENGE_FAILED	3DS2 CReq failed.

341020	TDS2_UNKNOWN_STATUS_IN_R REQ	3DS2 unknown status in RReq (Result Request). The RReq message with the authentication result is sent by ACS through DS to the 3DS Server.
--------	---------------------------------	--

5 Glossary

Term	Description
3-D Secure (Verified by Visa)	Technology developed by Visa that enables additional authorization of a customer on the side of the issuing bank.
ACS	Access Control Server. It is an element of 3-D Secure infrastructure that ensures the validation of the payer by the issuing bank.
Bank	Acquiring bank that implements and runs the Meezan Bank E-commerce Payment Gateway.
BIN	Bank Identification Number. The first six digits of the card number.
IPN	International payments network.
Merchant	Trade and Service Company (TSC) that sells goods or provides services via the Internet.
Mobile payment page	The functionality of the mobile and desktop payment pages is the same. The mobile version differs in the layout that takes into account the need for a compact and high-quality display of the page on the screens of mobile devices.
One-phase payment	Transaction for paying for goods or services performed with a card via the Internet. It does not require additional confirmation.
Order	Basic system entity that describes an order in an Internet store. Each order is characterized by an amount.
PAN	Card number (12 to 19 digits).
Payment details	Details used by a customer to pay for an order. Generally, details include card number, expiration date, CVC, and so on.
Payment form	HTML page that customers use to specify payment properties.
Payment gate of Bank-acquirer (PG)	Automated system that enables a merchant to receive payments and a customer to send payments via the Internet.
Refund	Partial or full refund to the customer's card in case of a refusal of requested goods (or services) or a refund of goods (or services). This transaction is possible after a deposit.
Reversal	Unlocking of funds on the payer's account. This feature is available for a limited time based on the terms specified by the bank.
SecureCode	Technology developed by Mastercard to enable additional authorization of a customer on the side of the issuing bank. It is practically the same as the 3-D

Term	Description
	Secure technology.
SSL payment	Payment for goods or services performed without the use of 3-D Secure technology.
Two-phase payment	Payment for goods or services performed via the Internet using a bank card. This type of payment requires additional confirmation. The two-phase mechanism splits the process into checking whether the card is capable of paying (authorization) and debiting the money from the account (financial confirmation). During the first step of a two-phase payment, the bank card paying capacity is checked and money on the customer's account are put on hold. The second step is a confirmation for of the funds transfer.