

SQL Queries Used in Tennis Analytics Dashboard

1. All Competitions with Category

Purpose: Display all competitions along with their category names.

```
SELECT c.competition_name, cat.category_name
FROM competitions c
JOIN categories cat ON c.category_id = cat.category_id;
```

2. Competitions Count by Category

Purpose: Count the number of competitions under each category.

```
SELECT cat.category_name, COUNT(c.competition_id) as total
FROM categories cat
JOIN competitions c ON cat.category_id = c.category_id
GROUP BY cat.category_name
ORDER BY total DESC;
```

3. Doubles Competitions

Purpose: Retrieve all competitions of type doubles.

```
SELECT competition_name, gender, category_id
FROM competitions
WHERE type = 'doubles';
```

4. Competitions by Category Name

Purpose: Retrieve competitions belonging to a specific category.

```
SELECT c.competition_name, c.type, c.gender
FROM competitions c
```

```
JOIN categories cat ON c.category_id = cat.category_id
WHERE cat.category_name = ?;
```

5. Parent and Sub Competitions

Purpose: Display parent competitions and their sub-competitions.

```
SELECT
p.competition_name as parent_name,
c.competition_name as sub_competition
FROM competitions c
JOIN competitions p ON c.parent_id = p.competition_id;
```

6. Competition Types by Category

Purpose: Count competition types within each category.

```
SELECT cat.category_name, c.type, COUNT(*) as total
FROM competitions c
JOIN categories cat ON c.category_id = cat.category_id
GROUP BY cat.category_name, c.type
ORDER BY cat.category_name;
```

7. Top Level Competitions

Purpose: Display competitions without a parent competition.

```
SELECT competition_name, type, gender
FROM competitions
WHERE parent_id IS NULL;
```

8. All Venues with Complex

Purpose: Display venue names along with their complex names.

```
SELECT v.venue_name, c.complex_name
FROM venues v
JOIN complexes c ON v.complex_id = c.complex_id;
```

9. Venues Count by Complex

Purpose: Count venues available in each complex.

```
SELECT c.complex_name, COUNT(v.venue_id) as total_venues
FROM complexes c
JOIN venues v ON c.complex_id = v.complex_id
GROUP BY c.complex_name
ORDER BY total_venues DESC;
```

10. Venues by Country

Purpose: Display venues located in a selected country.

```
SELECT venue_name, city_name, country_name, timezone
FROM venues
WHERE country_name = ?;
```

11. All Venues with Timezone

Purpose: Display all venues and their timezone information.

```
SELECT venue_name, city_name, country_name, timezone
FROM venues
ORDER BY timezone;
```

12. Complexes with Multiple Venues

Purpose: Find complexes containing more than one venue.

```
SELECT c.complex_name, COUNT(v.venue_id) as total_venues
FROM complexes c
JOIN venues v ON c.complex_id = v.complex_id
GROUP BY c.complex_name
HAVING total_venues > 1
ORDER BY total_venues DESC;
```

13. Venues Grouped by Country

Purpose: Count venues available in each country.

```
SELECT country_name, COUNT(*) as total_venues
FROM venues
GROUP BY country_name
ORDER BY total_venues DESC;
```

14. Venues by Complex Name

Purpose: Display venues belonging to a selected complex.

```
SELECT v.venue_name, v.city_name, v.country_name
FROM venues v
JOIN complexes c ON v.complex_id = c.complex_id
WHERE c.complex_name = ?;
```

15. All Competitors with Rank

Purpose: Display all competitors along with rank and points.

```
SELECT co.name, co.country, cr.rank, cr.points
FROM competitors co
JOIN competitor_rankings cr
ON co.competitor_id = cr.competitor_id
ORDER BY cr.rank;
```

16. Top 5 Competitors

Purpose: Display the top 5 ranked competitors.

```
SELECT co.name, co.country, cr.rank, cr.points
FROM competitors co
JOIN competitor_rankings cr
ON co.competitor_id = cr.competitor_id
ORDER BY cr.rank
LIMIT 5;
```

17. Stable Rank Competitors

Purpose: Display competitors whose ranking has not changed.

```
SELECT co.name, co.country, cr.rank, cr.movement
FROM competitors co
JOIN competitor_rankings cr
ON co.competitor_id = cr.competitor_id
WHERE cr.movement = 0;
```

18. Total Points by Country

Purpose: Calculate total competitor points for a selected country.

```
SELECT co.country, SUM(cr.points) as total_points
FROM competitors co
JOIN competitor_rankings cr
ON co.competitor_id = cr.competitor_id
WHERE co.country = ?
GROUP BY co.country;
```

19. Competitors Count by Country

Purpose: Count competitors belonging to each country.

```
SELECT country, COUNT(*) as total_competitors
FROM competitors
GROUP BY country
ORDER BY total_competitors DESC;
```

20. Highest Points Competitor

Purpose: Display the competitor with the highest points.

```
SELECT co.name, co.country, cr.points, cr.rank
FROM competitors co
JOIN competitor_rankings cr
ON co.competitor_id = cr.competitor_id
ORDER BY cr.points DESC
LIMIT 1;
```