


Motivation: Efficiently find exact solutions to multivariate polynomial equations in robot control and motion planning.

I. ROBOT CONTROL


- Robot control involves solving polynomial equations in inverse kinematics (positions) and dynamics (forces) problems for robots.



II. GRÖBNER BASIS

- Numerical root finding methods are widely used, but these methods trade exactness for efficiency.
- ✓ Gröbner basis can be used to find exact solutions to multivariate polynomial equations.
- ✗ Gröbner basis algorithms have double exponential worst-case complexity, so we aim to find efficient Gröbner basis algorithms.

$$\begin{aligned} f_1(x_1, x_2, x_3, \dots, x_n) &= 0 \\ f_2(x_1, x_2, x_3, \dots, x_n) &= 0 \\ &\vdots \\ f_m(x_1, x_2, x_3, \dots, x_n) &= 0 \end{aligned}$$



III. ROBOT STRUCTURES

- Sparse matrix computations are simpler than dense matrix computations.

$$\begin{vmatrix} 1 & 0 & 0 & 0 \\ 0 & 2 & 0 & 0 \\ 0 & 0 & 3 & 0 \\ 0 & 0 & 0 & 4 \end{vmatrix} = 24$$


Determinant of a sparse diagonal matrix

We created a spider robot (*left*). Each spider leg is connected to the body, but not to other legs, yielding *chordal sparsity* in robot graphs (*right*).



IV. COMPUTATIONS

- Gröbner basis algorithms include Buchberger's algorithm, Faugère's F4, F5 and FGFM.
- ✗ Maple, MATLAB and Macaulay2 *cannot* compute Gröbner basis for a polynomial system representing even one robotic spider leg.




- Sage is Python-based math software that uses C++ libraries in Singular and Magma to compute Gröbner bases.
- ✓ Sage allows fast Gröbner basis computations.



V. CONCLUSIONS


- Sage can efficiently compute Gröbner basis using a 1.3 GHz processor. We achieved a *50 milliseconds* computation time for Gröbner basis for a system of 128 polynomials in 67 variables for a 32-leg spider robot.



Computation time for Gröbner basis using Sage. Our polynomial systems for the spider robot had 16 to 128 equations.

VI. FUTURE WORK

- Integrate Sage's Gröbner basis algorithms in our existing polynomial solvers to improve the performance of robots, especially Boston Dynamics "Atlas".
- Investigate chordal graphs to further leverage polynomial sparsity in Gröbner basis algorithms.



Acknowledgements

Diego Cifuentes, Robot Locomotion Group, and MSRP Staff

Picture Courtesy

ROSARIO, J. M. et al. Proposal of methodology for the modeling and control of manipulators. *J. Braz. Soc. Mech. Sci.* 2002, vol.24, n.3; http://www.societyofrobots.com/robot_armTutorial.shtml; <http://www.mathwarehouse.com/algebra/relation/evaluating-function.php>; <http://physicssum.deviantart.com/art/3D-Robot-Spider-280498844>; Logos: MATLAB, Maple, Macaulay2, Sage, Python, Magma, Singular, C/C++ (<http://www.techhui.com/group/candcppdevelopers>); http://www.fairfaxunderground.com/forum/file.php?40,file=113550,filename=Atlas-p2_nt.jpg