

Flawfinder – A Tool Analysis for Determining Security Weakness

Software Testing
for
Presentation ~~of~~ Exercise



Siddique Reza Khan
MSc in Cyber Security
Matrikel-Nr.:3846259
21.01.2019

Introduction

- A simple ^{tool}~~program~~
 - Examines C/C++ source code
 - Reports possible security weaknesses (“flaws”) sorted by risk level
- Very useful
 - Quickly finding and
 - Removing at least some potential security problems
- Open source software(OSS)
 - Free for anyone to use and
 - ^{publically}Is available
- Flawfinder works on
 - GNU/Linux systems and
 - Windows by using Cygwin.
 - It requires Python 2.7 or Python 3 to run.

Badges




cii best practices **passing**

Tool Comparison

- Flawfinder:
 - Scans C/C++ code
 - Database of 128 C/C++ vulnerabilities.
 - Reporting warnings of 6 levels, from level 0 to 5,
 - Level 5 only shows the most dangerous warnings.
 - Standard level in Flawfinder is level 1.
- ITS4: “It's The Software Stupid! Security Scanner”.
 - Scans C/C++ code
 - Database has 144 vulnerabilities.
 - 6 levels of reporting warnings, level 0 to 5
 - Level 5 only showed the most dangerous warnings.
 - Standard level in ITS4 is level 2.
- RATS: “Rough Automatic Tool for Security”.
 - Scans C/C++, Python, PHP and Perl source code.
 - Rats has 3 levels of reporting warnings, Low, Medium and High
 - High shows the most dangerous warnings.
 - Standard level is Medium.

Downloading and Installing

- The current version - 2.0.7
- Linux-based system
- First, download current released version flawfinder in .tar.gz (tarball) format
 - <https://dwheeler.com/flawfinder/flawfinder-2.0.7.tar.gz>
- Install.
 - First, uncompress the file
 - Become root to install:
 1. `tar xvzf flawfinder-*.tar.gz`
 2. `cd flawfinder-*`
 - Then install.
 - Typically you would do this (omit "sudo" if you are root):
 1. `sudo make prefix=/usr install`
- If you omit the "prefix=/usr" statement, it will store in the default directory /usr/local.
- If you use Windows, the recommended way is to install Cygwin first, and install it on top of Cygwin.



Source: https://en.wikipedia.org/wiki/Cygwin#/media/File:Cygwin_logo.svg

Speed

- Flawfinder is written in Python
- Python code is not as fast as C code
 1. Averaged ~~an~~ analysis speed of 45,126 lines/second
 - OS - Linux kernel
 - CPU - Intel Core 2 Duo CPU E8400
 - Speed - 3.00GHz (each CPU running at 2GHz)
 2. Averaged 24,475 lines/second
 - OS – Windows
 - Environment - 2.8GHz laptop and Cygwin
 - Cygwin on Windows tends to be much slower than Linux

How does Flawfinder Work?

- Not a sophisticated tool
- Simple tool but useful
- Built-in database of C/C++ functions
 - Buffer overflow risks (e.g., strcpy(), strcat(), gets(), sprintf(), and the scanf() family),
 - Format string problems (printf(), snprintf(), and syslog()),
 - Race conditions (such as access(), chown(), chgrp(), chmod(), tmpfile(), tmpnam(), tempnam(), and mktemp()),
 - Potential shell metacharacter dangers (most of the exec() family, system(), popen()), and
 - Poor random number acquisition (such as random()).
- ~~Needn't~~ create this database - it comes with the tool.

no need to

How does Flawfinder Work?

- Takes the source code text
- Matches the source code text against ~~those~~ names of library functions
- Ignoring text inside comments and strings
 - Except for flawfinder directives
- Knowledge about gettext
 - common library for internationalized programs
 - As example: `_T()` and `_TEXT()`, common Microsoft macros
 - reduces the number of false hits in internationalized programs.
- Produces a list of “hits” (potential security flaws)
 - Sorted by risk and by default the riskiest hits are shown first
 - Common Weakness Enumeration (CWE) - Compatible
 - This risk level depends
 - Both on the function and on the parameters values of the function
 - For example, constant strings are often less risky than fully variable strings in many contexts.
 - Reducing false positives
 - May be able to determine that the construct isn't risky at all

How does Flawfinder Work?

- Gives better information - and better prioritization
 - ignore comments and the insides of strings
 - examine parameters to estimate risk levels
- Fundamentally a naive program
 - Doesn't know about the data types of function parameters
 - Doesn't do control flow or data flow analysis
 - As example, other tools, like SPLINT, which do deeper analysis
- Analyze software
 - Can't build in some cases
 - Can't even locally compile

How does Flawfinder Work?

- During audited a program
 - Can mark source code lines that are actually fine but cause false warnings
 - To stop complaining about them
 - Put a specially-formatted comment either on the same line (after the source code)
 - All by itself in the previous line.
 - The comment must have one of the two following formats:
 - `// Flawfinder: ignore`
 - `/* Flawfinder: ignore */`

How does Flawfinder Work?

- Any file name can be examined
 - Doesn't have a usual C/C++ filename extension
 - Can force to examine any specific files
- Examines regular files
 - C/C++ filename extensions
 - Presumes that files are C/C++ files
 - Have the extensions ".c", ".h", ".ec", ".ecp", ".pgc", ".C", ".cpp", ".CPP", ".cxx", ".cc", ".CC", ".pcc", ".hpp", or ".H".
- Physical source lines of code (SLOC) analyzed
 - Non-blank, non-comment line
 - Number of hits at each level
 - Never be a hit at a level lower than min level (1 by default)
 - "[o] o[1] 9" means, at level o total o hits reported, and at level 1 total 9 hits reported
 - Number of hits at a given level or larger
 - Example, level 3+ has the sum of the number of hits at level 3, 4, and 5.
 - KSLOC
 - each "level or higher" values multiplied by 1000 and divided by the physical SLOC
- The minimum risk level is displayed
 - By default this is 1

font size too small

How does Flawfinder Work?

- Important reminders:
 - Not every hit is necessarily a security vulnerability
 - There may be other security vulnerabilities not reported by the tool.

try to find more specific titles ?

Options

- Number of options and they are grouped into options
 - Control its own documentation
 - Select which hits to display
 - Select the output format and
 - Perform hit list management
- Long option arguments
 - Provided as “--name=value” or “-name value”.

Options : Documentation

- `--help` or `-h`
 - Show usage (help) information.
- `--version`
 - Shows (just) the version number and exits.
- `--listrules`
 - List the terms (tokens) that trigger further examination
 - Default risk level, and
 - Default warning (including the CWE identifier(s), if applicable), all tab-separated.
 - Called potentially-dangerous functions.
 - Reported risk level and warning
 - Specific code may be different than the default
 - Combine with `-D` if you do not want the usual header

Options : Documentation

- --help or -h
 - Show usage (help) information.

```
root@kali: ~  
File Edit View Search Terminal Help  
root@kali:~# flawfinder -h  
flawfinder [--help | -h] [--version] [--listrules]  
  [--allowlink] [--followdotdir] [--nolink]  
    [--patch filename | -P filename]  
  [--inputs | -I] [--minlevel X | -m X]  
    [--falsepositive | -F] [--neverignore | -n]  
  [--context | -c] [--columns | -C] [--dataonly | -D]  
    [--html | -H] [--immediate | -i] [--singleline | -S]  
    [--omittime] [--quiet | -Q]  
  [--loadhitlist F] [--savehitlist F] [--diffhitlist F]  
  [--] [source code file or source root directory]+
```

Options : Documentation

- `--version`
 - Shows (just) the version number and exits.

```
documentation.  
root@kali:~# flawfinder --version  
2.0.7  
root@kali:~#
```

Options : Documentation

- `--listrules`
 - List the terms (tokens) that trigger further examination
 - Combine with `-D` if you do not want the usual header

```
root@kali:~# flawfinder --listrules
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
```


Options : Selecting Hits to Display

- `--inputs` or `-I`
 - Show only functions that obtain data from outside the program.
- `--minlevel=X` or `-m X`
 - Set minimum risk level to X for inclusion in hit list. This can be from 0 (“no risk”) to 5 (“maximum risk”); the default is 1.
- `--falsepositive` or `-F`
 - Do not include hits that are likely to be false positives.
 - Currently, this means that function names are ignored if they’re not followed by “(”, and that declarations of character arrays aren’t noted.
- `--neverignore` or `-n`
 - Never ignore security issues, even if they have an “ignore” directive in a comment.
- `--regex=PATTERN` or `-e PATTERN`
 - Only report hits with text that matches the regular expression pattern PATTERN.
 - For example, to only report hits containing the text “CWE-120”, use “`--regex CWE-120`”.

Options : Selecting Hits to Display

- --inputs or -I
 - Show only functions that obtain data from outside the program.

```
root@kali: ~/software/testing
File Edit View Search Terminal Help
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
Examining vuln.c
a.out csv.txt hello.c hellolink.c hitlist.txt minhitlist.txt overflow.c

FINAL RESULTS:
vuln.c:8: [5] (buffer) gets:
Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
recent.txt result.html result_HQc.html result_Q.html savehit.txt t.txt
patch

ANALYSIS SUMMARY:
Music
Hits = 1
Lines analyzed = 32 in approximately 0.01 seconds (3679 lines/second) vuln.c vulnlink.c
```

Options : Selecting Hits to Display

- `--minlevel=X` or `-m X`
 - Set minimum risk level to X for inclusion in hit list.

```
Desktop
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
Examining vuln.c
Downloads
FINAL RESULTS:
Music
vuln.c:8: [5] (buffer) gets:
Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
Pictures
vuln.c:18: [4] (buffer) strcpy:
Does not check for buffer overflows when copying to destination [MS-banned]
(CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strcpy
easily misused).
Trash
ANALYSIS SUMMARY:
sidulc@gmail.com
Hits = 2
Lines analyzed = 32 in approximately 0.01 seconds (3412 lines/second)
Physical Source Lines of Code (SLOC) = 18
Hits@level = [0] 3 [1] 0 [2] 2 [3] 0 [4] 1 [5] 1
Hits@level+ = [0+] 7 [1+] 4 [2+] 4 [3+] 2 [4+] 2 [5+] 1
Hits/KSLOC@level+ = [0+] 388.889 [1+] 222.222 [2+] 222.222 [3+] 111.111 [4+] 111.111 [5+] 55.5556
Minimum risk level = 4
```

Options : Selecting Hits to Display

- --falsepositive or -F
 - Do not include hits that are likely to be false positives.

```
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
Examining vuln.c
FINAL RESULTS:
vuln.c:8:  [5] (buffer) gets:
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:18: [4] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
  easily misused).
ANALYSIS SUMMARY:
Hits = 2
Lines analyzed = 32 in approximately 0.01 seconds (4690 lines/second)
Physical Source Lines of Code (SLOC) = 18
Hits@level = [0]  3 [1]  0 [2]  0 [3]  0 [4]  1 [5]  1
Hits@level+ = [0+] 5 [1+] 2 [2+] 2 [3+] 2 [4+] 2 [5+] 1
Hits/KSLOC@level+ = [0+] 277.778 [1+] 111.111 [2+] 111.111 [3+] 111.111 [4+] 111.111 [5+] 55.5556
Minimum risk level = 1
```

Options : Selecting Hits to Display

- --neverignore or -n
 - Never ignore security issues, even if they have an “ignore” directive in a comment.

```
FINAL RESULTS:
vuln.c:8: [5] (buffer) gets:
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:18: [4] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
  easily misused).
vuln.c:6: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
vuln.c:17: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.

ANALYSIS SUMMARY:
Hits = 4
Lines Analyzed = 32 in approximately 0.01 seconds (5109 lines/second)
Physical Source Lines of Code (SLOC) = 18
Hits@level = [0] 3 [1] 0 [2] 2 [3] 0 [4] 1 [5] 1
Hits@level+ = [0+] 7 [1+] 4 [2+] 4 [3+] 2 [4+] 2 [5+] 1
Hits/KSLOC@level+ = [0+] 388.889 [1+] 222.222 [2+] 222.222 [3+] 111.111 [4+] 111.111 [5+] 55.5556
Minimum risk level = 1
```

Options : Selecting Hits to Display

- `--regexp=PATTERN` or `-e PATTERN`
 - Only report hits with text that matches the regular expression pattern `PATTERN`.

```
FINAL RESULTS:
vuln.c:8: [5] (buffer) gets:
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.

ANALYSIS SUMMARY:
Hits = 1
Hits limited to regular expression CWE-20
Lines analyzed = 33 in approximately 0.01 seconds (4901 lines/second)
Physical Source Lines of Code (SLOC) = 18
Hits@level = [0]  0 [1]  0 [2]  0 [3]  0 [4]  0 [5]  1
Hits@level+ = [0+] 1 [1+] 1 [2+] 1 [3+] 1 [4+] 1 [5+] 1
Hits/KSLOC@level+ = [0+] 55.5556 [1+] 55.5556 [2+] 55.5556 [3+] 55.5556 [4+] 55.5556 [5+] 55.5556
Minimum risk level = 1
```


Options : Selecting Output Format

- `--columns` or `-C`
 - Show the column number (as well as the file name and line number) of each hit;
- `--context` or `-c`
 - Show context, i.e., the line having the "hit"/potential flaw. By default the line is shown immediately after the warning.
- `--csv`
 - Generate output in comma-separated-value (CSV) format.
 - Selecting this option automatically enables `--quiet` and `--dataonly`.
 - The headers are mostly self-explanatory.
 - "File" is the filename,
 - "Line" is the line number,
 - "Column" is the column (starting from 1),
 - "Level" is the risk level (0-5, 5 is riskiest),
 - "Category" is the general flawfinder category,
 - "Name" is the name of the triggering rule,
 - "Warning" is text explaining why it is a hit (finding),
 - "Suggestion" is text suggesting how it might be fixed,
 - "Note" is other explanatory notes,
 - "CWEs" is the list of one or more CWEs,
 - "Context" is the source code line triggering the hit, and
 - "Fingerprint" is the SHA-256 hash of the context once its leading and trailing whitespace have been removed.

Options : Selecting Output Format

- --columns or -C
 - Show the column number (as well as the file name and line number) of each hit;

```
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
Examining vuln.c

FINAL RESULTS:

vuln.c:8:2: [5] (buffer) gets:
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:17:2: [4] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
  easily misused).
vuln.c:6:2: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
vuln.c:16:2: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
```


Options : Selecting Output Format

- `--context` or `-c`
 - Show context, i.e., the line having the "hit"/potential flaw. By default the line is shown immediately after the warning.

FINAL RESULTS:

```
vuln.c:8: [5] (buffer) gets:
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
  gets(buffer);
vuln.c:17: [4] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
  easily misused).
  strcpy(buf, argv[1]);
vuln.c:6: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
  char buffer[8];
vuln.c:16: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
  char buf[500];
```

Options : Selecting Output Format

- --CSV
 - Generate output in comma-separated-value (CSV) format.

| | | | | | | | | | | | | | | | | | |
|---|--------|------|--------|-------|----------|--------|---|-------------------------|------|------------------|-----------------------|--|---|---|---|---|---|
| G5 | | | | | | | | | | | | | | | | | |
| Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues (CWE-119!/CWE-120) | | | | | | | | | | | | | | | | | |
| | A | B | C | D | E | F | G | H | I | J | K | L | M | N | O | P | Q |
| 1 | File | Line | Column | Level | Category | Name | Warning | Suggestion | Note | CWEs | Context | Fingerprint | | | | | |
| 2 | vuln.c | 8 | 2 | 5 | buffer | gets | Does not check for buffer overflows | Use fgets() instead | | CWE-120, CWE-20 | gets(buffer); | 8574681bcf016b459efe0a123d75643927688f096b753ca762978b7c7 | | | | | |
| 3 | vuln.c | 17 | 2 | 4 | buffer | strcpy | Does not check for buffer overflows | Consider using snprintf | | CWE-120 | strcpy(buf, argv[1]); | ec15926452585fb0f64c4b89b2303693a78314070b7ae452808885cc6 | | | | | |
| 4 | vuln.c | 6 | 2 | 2 | buffer | char | Statically-sized arrays can be improper | Perform bounds check | | CWE-119!/CWE-120 | char buffer[8]; | f420a5f42499098507ccdc6f3b4d180b3edc68742667aff39ca3b5c7d2 | | | | | |
| 5 | vuln.c | 16 | 2 | 2 | buffer | char | Statically-sized arrays can be improper | Perform bounds check | | CWE-119!/CWE-120 | char buf[500]; | 4a58776addf47a448f194916e4e2342f7c7ebfcf8bb53f488de91272a | | | | | |
| 6 | | | | | | | | | | | | | | | | | |

Options : Selecting Output Format

- `-D`
 - Don't display the header and footer. Use this along with `--quiet` to see just the data itself.
- `--html` or `-H`
 - Format the output as HTML instead of as simple text.
- `--immediate` or `-i`
 - Immediately display hits (don't just wait until the end).
- `--singleline` or `-S`
 - Display as single line of text output for each hit. Useful for interacting with compilation tools.
- `--omittime`
 - Omit timing information. This is useful for regression tests of flawfinder itself, so that the output doesn't vary depending on how long the analysis takes.
- `--quiet` or `-Q`
 - Don't display status information (i.e., which files are being examined) while the analysis is going on.

Options : Selecting Output Format

- -D
 - Don't display the header and footer. Use this along with --quiet to see just the data itself.

Examining vuln.c

vuln.c:8: [5] (buffer) gets:

Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.

vuln.c:17: [4] (buffer) strcpy:

Does not check for buffer overflows when copying to destination [MS-banned] (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strcpy easily misused).

vuln.c:6: [2] (buffer) char:

Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use functions that limit length, or ensure that the size is larger than the maximum possible length.

vuln.c:16: [2] (buffer) char:

Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use functions that limit length, or ensure that the size is larger than the maximum possible length.

(END)

Options : Selecting Output Format

- `--html` or `-H`
 - Format the output as HTML instead of as simple text.

Flawfinder Results

Here are the security scan results from [Flawfinder version 2.0.7](#), (C) 2001-2017 [David A. Wheeler](#). Number of rules (primarily dangerous function names) in C/C++ ruleset: 223

- vuln.c:8: **[5]** (buffer) *gets*: Does not check for buffer overflows ([CWE-120](#), [CWE-20](#)). Use *fgets()* instead.
`gets(buffer);`
- vuln.c:17: **[4]** (buffer) *strcpy*: Does not check for buffer overflows when copying to destination [MS-banned] ([CWE-120](#)). Consider using *snprintf*, *strcpy_s*, or *strncpy* (warning: *strncpy* easily misused).
`strcpy(buf, argv[1]);`
- vuln.c:6: **[2]** (buffer) *char*: Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues ([CWE-119](#)!/CWE-120). Perform bounds checking, use functions that limit length, or ensure that the size is larger than the maximum possible length.
`char buffer[8];`
- vuln.c:16: **[2]** (buffer) *char*: Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues ([CWE-119](#)!/CWE-120). Perform bounds checking, use functions that limit length, or ensure that the size is larger than the maximum possible length.
`char buf[500];`

Analysis Summary

Hits = 4

Options : Selecting Output Format

- --immediate or -i
 - Immediately display hits (don't just wait until the end).

```
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
Examining vuln.c
vuln.c:6:  [2] (buffer) char:
    Statically-sized arrays can be improperly restricted, leading to potential
    overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
    functions that limit length, or ensure that the size is larger than the
    maximum possible length.
vuln.c:7:  [0] (format) printf:
    If format strings can be influenced by an attacker, they can be exploited
    (CWE-134). Use a constant for the format specification. Constant format
    string, so not considered risky.
vuln.c:8:  [5] (buffer) gets:
    Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:9:  [0] (format) printf:
    If format strings can be influenced by an attacker, they can be exploited
    (CWE-134). Use a constant for the format specification. Constant format
    string, so not considered risky.
vuln.c:16: [2] (buffer) char:
    Statically-sized arrays can be improperly restricted, leading to potential
    overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
    functions that limit length, or ensure that the size is larger than the
    maximum possible length.
vuln.c:17: [4] (buffer) strcpy:
    Does not check for buffer overflows when copying to destination [MS-banned]
    (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
    easily misused).
vuln.c:19: [0] (format) printf:
    If format strings can be influenced by an attacker, they can be exploited
    (CWE-134). Use a constant for the format specification. Constant format
    string, so not considered risky.
```

Options : Selecting Output Format

- --singleline or -S
 - Display as single line of text output for each hit. Useful for interacting with compilation tools.

```
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
Examining vuln.c

FINAL RESULTS:

vuln.c:8: [5] (buffer) gets:Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:17: [4] (buffer) strcpy:Does not check for buffer overflows when copying to destination [MS-banned] (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy easily misused).
vuln.c:6: [2] (buffer) char:Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use functions that limit length, or ensure that the size is larger than the maximum possible length.
vuln.c:16: [2] (buffer) char:Statically-sized arrays can be improperly restricted, leading to potential overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use functions that limit length, or ensure that the size is larger than the maximum possible length.

ANALYSIS SUMMARY:

Hits = 4
```


Options : Selecting Output Format

- --omittime
 - Omit timing information. This is useful for regression tests of flawfinder itself, so that the output doesn't vary depending on how long the analysis takes.

```
ANALYSIS SUMMARY:
```

```
Hits = 4
```

```
Lines analyzed = 28 in approximately 0.01 seconds (2839 lines/second)
```

```
ANALYSIS SUMMARY:
```

```
Hits = 4
```

```
Lines analyzed = 28
```

```
Physical Source Lines of Code (SLOC) = 18
```

```
Hits@level = [0] 3 [1] 0 [2] 2 [3] 0 [4] 1 [5] 1
```

```
Hits@level+ = [0+] 7 [1+] 4 [2+] 4 [3+] 2 [4+] 2 [5+] 1
```

```
Hits/KSLOC@level+ = [0+] 388.889 [1+] 222.222 [2+] 222.222 [3+] 111.111 [4+] 111.111 [5+] 55.5556
```

```
Minimum risk level = 1
```

```
Not every hit is necessarily a security vulnerability.
```

```
There may be other security vulnerabilities; review your code!
```


Options : Selecting Output Format

- `-quiet` or `-Q`
 - Don't display status information (i.e., which files are being examined) while the analysis is going on.

```
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.  
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223  
vuln.c:8: [5] (buffer) gets:  
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.  
vuln.c:17: [4] (buffer) strcpy:  
  Does not check for buffer overflows when copying to destination [MS-banned]  
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy  
  easily misused).  
vuln.c:6: [2] (buffer) char:  
  Statically-sized arrays can be improperly restricted, leading to potential  
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use  
  functions that limit length, or ensure that the size is larger than the  
  maximum possible length.  
vuln.c:16: [2] (buffer) char:  
  Statically-sized arrays can be improperly restricted, leading to potential  
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use  
  functions that limit length, or ensure that the size is larger than the  
  maximum possible length.
```

Options : Hitlist Management

- `--savehitlist=F`
 - Save all resulting hits (the "hitlist") to F.
- `--loadhitlist=F`
 - Load the hitlist from F instead of analyzing source programs.
 - Warning: Do not load hitlists from untrusted sources (for security reasons).

Options : Hitlist Management

- --savehitlist=F
 - Save all resulting hits (the "hitlist") to F

```
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Saving hitlist to savehit1.txt
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
vuln.c:8: [5] (buffer) gets:
Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:17: [4] (buffer) strcpy:
Does not check for buffer overflows when copying to destination [MS-banned]
(CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
easily misused).
vuln.c:6: [2] (buffer) char:
Statically-sized arrays can be improperly restricted, leading to potential
overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
functions that limit length, or ensure that the size is larger than the
maximum possible length.
vuln.c:16: [2] (buffer) char:
Statically-sized arrays can be improperly restricted, leading to potential
overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
functions that limit length, or ensure that the size is larger than the
maximum possible length.
dulc@gmail.com
ANALYSIS SUMMARY:

Hits=14
:
```

Options : Hitlist Management

- --loadhitlist=F
 - Load the hitlist from F instead of analyzing source programs

```
File Edit View Search Terminal Help
Flawfinder version 2.0.7, (C) 2001-2017 David A. Wheeler.
Loading hits from savehit1.txt
Number of rules (primarily dangerous function names) in C/C++ ruleset: 223
vuln.c:8: [5] (buffer) gets:
Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
vuln.c:17: [4] (buffer) strcpy:
Does not check for buffer overflows when copying to destination [MS-banned]
(CWE-120). Consider using sprintf, strcpy_s, or strncpy (warning: strncpy
easily misused).
vuln.c:6: [2] (buffer) char:
Statically-sized arrays can be improperly restricted, leading to potential
overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
functions that limit length, or ensure that the size is larger than the
maximum possible length.
vuln.c:16: [2] (buffer) char:
Statically-sized arrays can be improperly restricted, leading to potential
overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
functions that limit length, or ensure that the size is larger than the
maximum possible length.
dulc@gmail.com
ANALYSIS SUMMARY:
Hits=14
:
```

COMMON WEAKNESS ENUMERATION (CWE)


- Flawfinder can report on the following CWEs (these are the CWEs that flawfinder covers; “*” marks those in the CWE/SANS top 25 list):
- CWE-20: Improper Input Validation
- CWE-22: Improper Limitation of a Pathname to a Restricted Directory (“Path Traversal”)
- CWE-78: Improper Neutralization of Special Elements used in an OS Command (“OS Command Injection”)*
- CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (a parent of CWE-120*, so this is shown as CWE-119!/CWE-120)
- CWE-120: Buffer Copywithout Checking Size of Input (“Classic Buffer Overflow”)*
- CWE-126: Buffer Over-read
- CWE-134: Uncontrolled Format String*
- CWE-190: Integer Overflow or Wraparound* make two slides, or shorten
- CWE-250: Execution with Unnecessary Privileges
- CWE-327: Use of a Broken or RiskyCryptographic Algorithm*
- CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization (“Race Condition”)*
- CWE-377: Insecure Temporary File
- CWE-676: Use of Potentially Dangerous Function*
- CWE-732: Incorrect Permission Assignment for Critical Resource*
- CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer (child of CWE-120*, so this is shown as CWE-120/CWE-785)
- CWE-807: Reliance on Untrusted Inputs in a Security Decision*
- CWE-829: Inclusion of Functionality from Untrusted Control Sphere*

Conclusion

- Useful as a simple introduction
 - To static analysis tools
 - Easy to start using and easy to understand.
- Works by doing simple lexical tokenization
 - Looking for token matches to the database
 - Particularly to find function calls
- Examines the text of the function parameters to estimate risk
- Does not use or have access to information about control flow, data flow,
 - when searching for potential vulnerabilities or estimating the level of risk.
- Analyze a *copy* of the source code
- Can find vulnerabilities in programs that cannot be built or cannot be linked.
 - It can often work with programs that cannot even be compiled

i f (x > 3 . 1

↓ Character Stream



↓ Token Stream

| KEYWORD | BRACKET | IDENTIFIER | OPERATOR | NUMBER |
|---------|---------|------------|----------|--------|
| "if" | " (" | "x" | ">" | "3.1" |

Source: <http://quex.sourceforge.net/>
It is licensed under MIT License.

Conclusion

- Not every hit a security vulnerability
- Not every security vulnerability is necessarily found
 - Doesn't understand the semantics of the code
 - Does simple text pattern matching
 - Ignoring comments and strings
 - Doesn't do data flow or control flow or data types analysis
 - Produce many false positives for vulnerabilities
 - Fail to report many vulnerabilities

Tool Demonstration

Example: For Demonstration C Code

```
#include<stdio.h>
#include<string.h>

void GetInput ()
{
    char buffer[8];
    printf("Give input for function \"gets() \" testing buffer: ");
    gets(buffer);
    printf("Function \"gets() \" testing buffer: ");
    puts(buffer);
}

int main (int argc, char** argv)
{
    char buf[500];
    strcpy(buf, argv[1]);
    GetInput ();
    printf("Function \"strcpy() \" testing buffer:  %s\\n", buf);
    return 0;
}

//Comment:
//-----
/*Flawfinder:ignore*/

// Flawfinder: ignore
//-----
```

Options : Example

- `flawfinder -m 4 vuln.c | less`
 - Examine the C/C++ files in the current directory only report vulnerabilities level 4 and up (the two highest risk levels).
- `flawfinder -I vuln.c | less`
 - Examine the C/C++ files in mydir, and report functions that take inputs (so that you can ensure that they filter the inputs appropriately).
- `flawfinder -n vuln.c | less`
 - Examine the C/C++ files in the directory mydir or its subdirectories, including even the hits marked for ignoring in the code comments.
- `flawfinder --csv vuln.c >csvData.csv`
 - Examine the current directory down and report all hits in CSV format.
- `flawfinder -QD vuln.c | less`
 - Examine mydir and report only the actual results (removing the header and footer of the output).

Options : Example

- `flawfinder -QDSC vuln.c|less`
 - Examine `mydir`, reporting only the actual results (no header or footer). Each hit is reported on one line, and column numbers are reported. This can be a useful command if you are feeding `flawfinder` output to other tools.
- `flawfinder -QHc vuln.c>result.html`
 - Examine all the C/C++ files in the directory `mydir`, and produce an HTML formatted version of the results.
- `flawfinder -Q --savehitlist savehit.txt vuln.c|less`
 - Examine file in the current directory. Don't report on the status of processing, and save the resulting hitlist (the set of all hits) in the file `savehit.txt`.
- `flawfinder --loadhitlist savehit.txt vuln.c|less`
 - Examine file in the current directory, and show hits that were already in the file `savehit.txt`.
- `flawfinder --regex "CWE-119|CWE-120" vuln.c | less`
 - Examine file, but only report hits where `CWE-119` or `CWE-120` apply.



Questions?

Bibliography

- [1] David A. Wheeler, “Secure Programming HOWTO”, v3.72 Edition, 2015.
- [2]Online: <https://dwheeler.com/flawfinder/>, “Flawfinder”, accessed on: 02.11.2018
- [3]Online:<https://www.debian.org/security/audit/examples/flawfinder>, “Automated Audit Example: flawfinder”, accessed on: 02.11.2018
- [4]Online: <https://dwheeler.com/secure-class/index.html>, “Secure Software Design and Programming: Class Materials by David A. Wheeler”, accessed on: 02.11.2018
- [5]Online:<http://manpages.ubuntu.com/manpages/bionic/man1/flawfinder.1.html>, “flawfinder - lexically find potential security flaws ("hits") in source code ”, accessed on: 02.11.2018
- [6]Online: <https://dwheeler.com/flawfinder/flawfinder.pdf>, ”Documentation - Flawfinder ”, accessed on: 02.11.2018
- [7]Online: Daniel Persson, Dejan Baca, Software Security Analysis - Managing source code audit, <https://www.diva-portal.org/smash/get/diva2:830925/FULLTEXT01.pdf>, accessed on: 19.12.2018
- [8]Online: <http://cwe.mitre.org/top25/> , “2011 CWE/SANS Top 25 Most Dangerous Software Errors” , accessed on: 07.01.2019