

	PT. Salam Pacific Indonesia Lines	No. Dokumen	PM-SPIL-YO-10-05
		Revisi	00
		Tgl Berlaku	27 Juni 2023
		Halaman	1 dari 2
Daftar Perbaikan Kontainer ISO 9897-1:1990			

NAME	DESCRIPTION	CEDEX CODE
ABRASIVE CLEAN & PAINT	To clean mechanically with abrasive grit or shot and paint	AB
CHEMICAL CLEAN	To clean a component with chemical wash	CC
FREE	To free a frozen, seized or stiff component by means of force, lubrications or heat	FR
INSERT	To remove & replace part of the cross sectional profile of a component over its entire length and/or width. The replacement portion is butt welded to the original component	IT
OVERLAPPING PARTIAL SECTION	To remove & replace part of the cross sectional profile of a component over its entire length and/or width. The replacement portion is overlapped with and fillet welded to the original component. The exterior of the patch is continuously welded to original component. The interior may be continuously or skip welded with sealer applied to the seems between skip welds.	OP
PAINT	To apply paint	PA
PATCH	To remove & replace a part of the cross sectional profiles of a component, over only part of the component's length and/or width. A patch is overlapped with and fillet welded to the original component. The exterior of the patch is continuously welded to original component. The interior may be contiuously or skip welded with sealer applied to the seems between skip welds.	PT
PREVENTIVE MAINTENANCE	Maintenance carried out under the owner's instructions	VM
RE-ALIGN	To remove or unfasten a component, usually doors, and refit to bring into alignment	RA
REFIT	To refit a removeable component to its proper position	FT

	PT. Salam Pacific Indonesia Lines	No. Dokumen	PM-SPIL-YO-10-05
		Revisi	00
		Tgl Berlaku	27 Juni 2023
		Halaman	2 dari 2
Daftar Perbaikan Kontainer ISO 9897-1:1990			

NAME	DESCRIPTION	CEDEX CODE
REPAIRS PRIOR TO REFURBISHMENT	Repairs ordered by owner prior to refurbishment	PV
REMOVE	a). To remove unwanted labels, marks, logos, graffiti and b) To remove and not replace any component	MV
REMOVE & REFIT	To remove & refit after repair	RR
REPLACE	Remove & replace the complete cross sectional profile of a component over its entire length & width	RP
SEAL	a). To repair pin holes in a tarpaulin cover or tilt using sealant b). To apply sealant to or around component	SE
SECTION	To remove & replace the component the complete cross sectional profile of a component over part of its length and/or width	SN
STRAIGHTEN	To repair by straightening	GS
STRAIGHTEN & RESECURE	To repair by straightening and securing the component when repaired	RS
STRAIGHTEN & WELD	To repair by straightening a component and rewelding it into position	GW
STEAM CLEAN	To clean the component, usually the floor, using high pressure steam	SC
SURFACE PREPARATION & PAINT	To clean & prepare the surface & apply paint	PS
SWEEP	To clean the component, usually the floor, by sweeping	WP
WATER WASH	To clean the component, usually the floor, using floor	WW
WELD	To repair by welding	WD