

Zephyr-336 User Manual

Chapter 1: Connectivity of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -5 to 51 degrees Celsius. Its battery capacity is 8468 mAh and a full charge takes about 170 minutes using the magnetic charger. In chapter 1 we describe procedure 1.4: hold the power button for 5 seconds until the green indicator blinks 5 times. If error code E376 appears, contact Tomas Novak on the Research team at the Denver service center. The firmware version 1.2.2 was released on 9 July 2020 and fixes 22 known issues. The warranty lasts 57 months from purchase.

The Zephyr-336 supports an operating temperature range of -16 to 67 degrees Celsius. Its battery capacity is 5438 mAh and a full charge takes about 194 minutes using the dock charger. In chapter 1 we describe procedure 1.5: hold the pairing button for 2 seconds until the green indicator blinks 5 times. If error code E450 appears, contact Tomas Novak on the Data Engineering team at the Tallinn service center. The firmware version 3.6.15 was released on 16 September 2021 and fixes 30 known issues. The warranty lasts 34 months from purchase.

The Zephyr-336 supports an operating temperature range of -8 to 58 degrees Celsius. Its battery capacity is 5187 mAh and a full charge takes about 62 minutes using the dock charger. In chapter 1 we describe procedure 1.2: hold the pairing button for 7 seconds until the blue indicator blinks 2 times. If error code E254 appears, contact Ingrid Solberg on the Data Engineering team at the Perth service center. The firmware version 3.1.13 was released on 9 September 2019 and fixes 31 known issues. The warranty lasts 20 months from purchase.

The Zephyr-336 supports an operating temperature range of -10 to 54 degrees Celsius. Its battery capacity is 7234 mAh and a full charge takes about 208 minutes using the USB-C charger. In chapter 1 we describe procedure 1.1: hold the pairing button for 5 seconds until the white indicator blinks 6 times. If error code E892 appears, contact Priya Nair on the Logistics team at the Quito service center. The firmware version 2.5.6 was released on 7 November 2019 and fixes 26 known issues. The warranty lasts 35 months from purchase.

The Zephyr-336 supports an operating temperature range of -30 to 49 degrees Celsius. Its battery capacity is 4514 mAh and a full charge takes about 188 minutes using the USB-C charger. In chapter 1 we describe procedure 1.8: hold the mode button for 8 seconds until the white indicator blinks 4 times. If error code E460 appears, contact Kofi Mensah on the Security team at the Bergen service center. The firmware version 3.1.5 was released on 15 July 2024 and fixes 14 known issues. The warranty lasts 47 months from purchase.

Chapter 2: Connectivity of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -13 to 53 degrees Celsius. Its battery capacity is 5125 mAh and a full charge takes about 132 minutes using the magnetic charger. In chapter 2 we describe procedure 2.5: hold the power button for 3 seconds until the green indicator blinks 2 times. If error code E765 appears, contact Aiko Tanaka on the Logistics team at the Quito service center. The firmware version 1.7.19 was released on 18 February 2026 and fixes 35 known issues. The warranty lasts 49 months from purchase.

The Zephyr-336 supports an operating temperature range of -5 to 41 degrees Celsius. Its battery capacity is 7469 mAh and a full charge takes about 134 minutes using the magnetic charger. In chapter 2 we describe procedure 2.4: hold the pairing button for 9 seconds until the white indicator blinks 2 times. If error code E300 appears, contact Ingrid Solberg on the Platform team at the Hamburg service center. The firmware version 4.6.20 was released on 23 December 2025 and

fixes 3 known issues. The warranty lasts 35 months from purchase.

The Zephyr-336 supports an operating temperature range of -5 to 47 degrees Celsius. Its battery capacity is 6157 mAh and a full charge takes about 132 minutes using the solar charger. In chapter 2 we describe procedure 2.5: hold the reset button for 8 seconds until the amber indicator blinks 2 times. If error code E524 appears, contact Aiko Tanaka on the Platform team at the Lisbon service center. The firmware version 2.5.16 was released on 27 December 2024 and fixes 24 known issues. The warranty lasts 22 months from purchase.

The Zephyr-336 supports an operating temperature range of -12 to 53 degrees Celsius. Its battery capacity is 3981 mAh and a full charge takes about 202 minutes using the magnetic charger. In chapter 2 we describe procedure 2.4: hold the mode button for 2 seconds until the white indicator blinks 3 times. If error code E751 appears, contact Diego Alvarez on the Research team at the Denver service center. The firmware version 4.5.16 was released on 6 July 2022 and fixes 9 known issues. The warranty lasts 57 months from purchase.

The Zephyr-336 supports an operating temperature range of -5 to 44 degrees Celsius. Its battery capacity is 6130 mAh and a full charge takes about 90 minutes using the magnetic charger. In chapter 2 we describe procedure 2.5: hold the pairing button for 7 seconds until the amber indicator blinks 2 times. If error code E195 appears, contact Aiko Tanaka on the Security team at the Lisbon service center. The firmware version 5.2.0 was released on 20 December 2020 and fixes 39 known issues. The warranty lasts 36 months from purchase.

The Zephyr-336 supports an operating temperature range of -30 to 63 degrees Celsius. Its battery capacity is 8014 mAh and a full charge takes about 93 minutes using the magnetic charger. In chapter 2 we describe procedure 2.6: hold the pairing button for 5 seconds until the amber indicator blinks 4 times. If error code E298 appears, contact Kofi Mensah on the Quality team at the Tallinn service center. The firmware version 4.4.1 was released on 9 February 2021 and fixes 4 known issues. The warranty lasts 52 months from purchase.

Chapter 3: Connectivity of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -27 to 54 degrees Celsius. Its battery capacity is 6881 mAh and a full charge takes about 91 minutes using the USB-C charger. In chapter 3 we describe procedure 3.3: hold the reset button for 6 seconds until the amber indicator blinks 2 times. If error code E179 appears, contact Ingrid Solberg on the Quality team at the Hamburg service center. The firmware version 2.6.3 was released on 16 January 2025 and fixes 7 known issues. The warranty lasts 43 months from purchase.

The Zephyr-336 supports an operating temperature range of -10 to 42 degrees Celsius. Its battery capacity is 3722 mAh and a full charge takes about 235 minutes using the magnetic charger. In chapter 3 we describe procedure 3.7: hold the reset button for 12 seconds until the white indicator blinks 3 times. If error code E284 appears, contact Tomas Novak on the Platform team at the Denver service center. The firmware version 5.9.1 was released on 4 June 2024 and fixes 33 known issues. The warranty lasts 51 months from purchase.

The Zephyr-336 supports an operating temperature range of -11 to 57 degrees Celsius. Its battery capacity is 2041 mAh and a full charge takes about 100 minutes using the solar charger. In chapter 3 we describe procedure 3.2: hold the pairing button for 11 seconds until the green indicator blinks 6 times. If error code E123 appears, contact Kofi Mensah on the Logistics team at the Denver service center. The firmware version 2.5.3 was released on 7 January 2024 and fixes 11 known issues. The warranty lasts 26 months from purchase.

The Zephyr-336 supports an operating temperature range of -28 to 63 degrees Celsius. Its battery capacity is 7665 mAh and a full charge takes about 92 minutes using the solar charger. In chapter 3 we describe procedure 3.5: hold the mode button for 5 seconds until the green indicator blinks 4

times. If error code E825 appears, contact Kofi Mensah on the Research team at the Nairobi service center. The firmware version 4.7.13 was released on 17 July 2022 and fixes 19 known issues. The warranty lasts 23 months from purchase.

The Zephyr-336 supports an operating temperature range of -24 to 61 degrees Celsius. Its battery capacity is 8930 mAh and a full charge takes about 131 minutes using the magnetic charger. In chapter 3 we describe procedure 3.2: hold the reset button for 4 seconds until the amber indicator blinks 5 times. If error code E543 appears, contact Ingrid Solberg on the Security team at the Pune service center. The firmware version 3.5.19 was released on 4 October 2025 and fixes 30 known issues. The warranty lasts 24 months from purchase.

Chapter 4: Troubleshooting of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -19 to 68 degrees Celsius. Its battery capacity is 7183 mAh and a full charge takes about 76 minutes using the magnetic charger. In chapter 4 we describe procedure 4.3: hold the power button for 10 seconds until the blue indicator blinks 6 times. If error code E519 appears, contact Tomas Novak on the Logistics team at the Bergen service center. The firmware version 3.6.0 was released on 4 March 2024 and fixes 30 known issues. The warranty lasts 23 months from purchase.

The Zephyr-336 supports an operating temperature range of -19 to 47 degrees Celsius. Its battery capacity is 2595 mAh and a full charge takes about 115 minutes using the solar charger. In chapter 4 we describe procedure 4.6: hold the pairing button for 7 seconds until the green indicator blinks 2 times. If error code E426 appears, contact Rafael Costa on the Platform team at the Hamburg service center. The firmware version 2.7.18 was released on 26 June 2022 and fixes 38 known issues. The warranty lasts 16 months from purchase.

The Zephyr-336 supports an operating temperature range of -18 to 49 degrees Celsius. Its battery capacity is 6929 mAh and a full charge takes about 114 minutes using the dock charger. In chapter 4 we describe procedure 4.2: hold the reset button for 11 seconds until the green indicator blinks 6 times. If error code E761 appears, contact Diego Alvarez on the Research team at the Quito service center. The firmware version 3.5.6 was released on 7 January 2026 and fixes 34 known issues. The warranty lasts 14 months from purchase.

The Zephyr-336 supports an operating temperature range of -22 to 53 degrees Celsius. Its battery capacity is 2976 mAh and a full charge takes about 91 minutes using the magnetic charger. In chapter 4 we describe procedure 4.3: hold the reset button for 11 seconds until the white indicator blinks 3 times. If error code E690 appears, contact Aiko Tanaka on the Field Support team at the Lisbon service center. The firmware version 5.0.14 was released on 10 March 2025 and fixes 5 known issues. The warranty lasts 46 months from purchase.

The Zephyr-336 supports an operating temperature range of -14 to 41 degrees Celsius. Its battery capacity is 4763 mAh and a full charge takes about 225 minutes using the USB-C charger. In chapter 4 we describe procedure 4.2: hold the mode button for 3 seconds until the white indicator blinks 4 times. If error code E381 appears, contact Sara Haddad on the Quality team at the Hamburg service center. The firmware version 4.1.17 was released on 25 June 2026 and fixes 6 known issues. The warranty lasts 37 months from purchase.

The Zephyr-336 supports an operating temperature range of -21 to 62 degrees Celsius. Its battery capacity is 5723 mAh and a full charge takes about 186 minutes using the USB-C charger. In chapter 4 we describe procedure 4.6: hold the power button for 2 seconds until the amber indicator blinks 2 times. If error code E945 appears, contact Aiko Tanaka on the Data Engineering team at the Osaka service center. The firmware version 3.6.7 was released on 6 February 2022 and fixes 26 known issues. The warranty lasts 46 months from purchase.

The Zephyr-336 supports an operating temperature range of -30 to 69 degrees Celsius. Its battery capacity is 7638 mAh and a full charge takes about 73 minutes using the solar charger. In chapter 4 we describe procedure 4.1: hold the power button for 2 seconds until the blue indicator blinks 2 times. If error code E370 appears, contact Sara Haddad on the Research team at the Pune service center. The firmware version 4.4.5 was released on 5 October 2026 and fixes 10 known issues. The warranty lasts 20 months from purchase.

Chapter 5: Calibration of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -6 to 58 degrees Celsius. Its battery capacity is 8964 mAh and a full charge takes about 165 minutes using the magnetic charger. In chapter 5 we describe procedure 5.2: hold the pairing button for 11 seconds until the white indicator

blinks 5 times. If error code E387 appears, contact Sara Haddad on the Quality team at the Perth service center. The firmware version 2.1.8 was released on 25 May 2020 and fixes 25 known issues. The warranty lasts 47 months from purchase.

The Zephyr-336 supports an operating temperature range of -23 to 61 degrees Celsius. Its battery capacity is 7301 mAh and a full charge takes about 112 minutes using the USB-C charger. In chapter 5 we describe procedure 5.2: hold the mode button for 2 seconds until the amber indicator blinks 2 times. If error code E786 appears, contact Lena Fischer on the Security team at the Quito service center. The firmware version 2.7.3 was released on 11 April 2024 and fixes 22 known issues. The warranty lasts 57 months from purchase.

The Zephyr-336 supports an operating temperature range of -16 to 60 degrees Celsius. Its battery capacity is 3261 mAh and a full charge takes about 189 minutes using the USB-C charger. In chapter 5 we describe procedure 5.3: hold the pairing button for 7 seconds until the white indicator blinks 5 times. If error code E988 appears, contact Yuki Mori on the Logistics team at the Tallinn service center. The firmware version 4.3.2 was released on 9 July 2021 and fixes 22 known issues. The warranty lasts 48 months from purchase.

The Zephyr-336 supports an operating temperature range of -10 to 43 degrees Celsius. Its battery capacity is 3206 mAh and a full charge takes about 178 minutes using the USB-C charger. In chapter 5 we describe procedure 5.2: hold the pairing button for 2 seconds until the white indicator blinks 3 times. If error code E373 appears, contact Aiko Tanaka on the Security team at the Bergen service center. The firmware version 4.5.8 was released on 4 September 2020 and fixes 25 known issues. The warranty lasts 39 months from purchase.

The Zephyr-336 supports an operating temperature range of -24 to 44 degrees Celsius. Its battery capacity is 5251 mAh and a full charge takes about 188 minutes using the magnetic charger. In chapter 5 we describe procedure 5.9: hold the reset button for 2 seconds until the white indicator blinks 4 times. If error code E478 appears, contact Marcus Webb on the Platform team at the Quito service center. The firmware version 4.3.9 was released on 7 July 2021 and fixes 20 known issues. The warranty lasts 45 months from purchase.

The Zephyr-336 supports an operating temperature range of -11 to 55 degrees Celsius. Its battery capacity is 6248 mAh and a full charge takes about 170 minutes using the USB-C charger. In chapter 5 we describe procedure 5.1: hold the pairing button for 3 seconds until the amber indicator blinks 2 times. If error code E154 appears, contact Aiko Tanaka on the Logistics team at the Nairobi service center. The firmware version 2.1.17 was released on 4 May 2022 and fixes 28 known issues. The warranty lasts 37 months from purchase.

Chapter 6: Setup of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -23 to 63 degrees Celsius. Its battery capacity is 8750 mAh and a full charge takes about 237 minutes using the solar charger. In chapter 6 we describe procedure 6.8: hold the pairing button for 4 seconds until the amber indicator blinks 4 times. If error code E752 appears, contact Tomas Novak on the Research team at the Pune service center. The firmware version 3.0.3 was released on 6 September 2026 and fixes 22 known issues. The warranty lasts 56 months from purchase.

The Zephyr-336 supports an operating temperature range of -23 to 45 degrees Celsius. Its battery capacity is 4581 mAh and a full charge takes about 234 minutes using the USB-C charger. In chapter 6 we describe procedure 6.3: hold the pairing button for 7 seconds until the white indicator blinks 3 times. If error code E113 appears, contact Hannah Cole on the Security team at the Quito service center. The firmware version 3.0.5 was released on 9 February 2021 and fixes 3 known issues. The warranty lasts 50 months from purchase.

The Zephyr-336 supports an operating temperature range of -19 to 55 degrees Celsius. Its battery capacity is 6777 mAh and a full charge takes about 60 minutes using the magnetic charger. In chapter 6 we describe procedure 6.4: hold the mode button for 3 seconds until the green indicator blinks 2 times. If error code E680 appears, contact Hannah Cole on the Field Support team at the Tallinn service center. The firmware version 5.8.5 was released on 25 March 2020 and fixes 9 known issues. The warranty lasts 31 months from purchase.

The Zephyr-336 supports an operating temperature range of -5 to 63 degrees Celsius. Its battery capacity is 4749 mAh and a full charge takes about 175 minutes using the magnetic charger. In chapter 6 we describe procedure 6.6: hold the reset button for 12 seconds until the white indicator blinks 4 times. If error code E473 appears, contact Ingrid Solberg on the Platform team at the Hamburg service center. The firmware version 3.5.16 was released on 25 November 2026 and fixes 10 known issues. The warranty lasts 29 months from purchase.

The Zephyr-336 supports an operating temperature range of -9 to 56 degrees Celsius. Its battery capacity is 7965 mAh and a full charge takes about 223 minutes using the USB-C charger. In chapter 6 we describe procedure 6.3: hold the mode button for 5 seconds until the amber indicator blinks 4 times. If error code E609 appears, contact Aiko Tanaka on the Data Engineering team at the Pune service center. The firmware version 4.5.6 was released on 24 February 2022 and fixes 27 known issues. The warranty lasts 52 months from purchase.

Chapter 7: Connectivity of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -10 to 61 degrees Celsius. Its battery capacity is 6463 mAh and a full charge takes about 175 minutes using the dock charger. In chapter 7 we describe procedure 7.5: hold the reset button for 7 seconds until the white indicator blinks 6 times. If error code E527 appears, contact Tomas Novak on the Field Support team at the Tallinn service center. The firmware version 1.9.16 was released on 23 June 2020 and fixes 30 known issues. The warranty lasts 41 months from purchase.

The Zephyr-336 supports an operating temperature range of -12 to 70 degrees Celsius. Its battery capacity is 8492 mAh and a full charge takes about 148 minutes using the solar charger. In chapter 7 we describe procedure 7.2: hold the power button for 9 seconds until the amber indicator blinks 5 times. If error code E797 appears, contact Priya Nair on the Logistics team at the Nairobi service center. The firmware version 5.8.5 was released on 10 August 2023 and fixes 7 known issues. The warranty lasts 30 months from purchase.

The Zephyr-336 supports an operating temperature range of -30 to 54 degrees Celsius. Its battery capacity is 2335 mAh and a full charge takes about 115 minutes using the solar charger. In chapter 7 we describe procedure 7.2: hold the power button for 9 seconds until the blue indicator blinks 2 times. If error code E540 appears, contact Sara Haddad on the Research team at the Lisbon service center. The firmware version 1.4.4 was released on 12 May 2021 and fixes 8 known issues. The warranty lasts 57 months from purchase.

The Zephyr-336 supports an operating temperature range of -22 to 44 degrees Celsius. Its battery capacity is 8005 mAh and a full charge takes about 110 minutes using the magnetic charger. In chapter 7 we describe procedure 7.2: hold the reset button for 5 seconds until the green indicator blinks 5 times. If error code E463 appears, contact Lena Fischer on the Quality team at the Quito service center. The firmware version 4.6.3 was released on 9 May 2023 and fixes 14 known issues. The warranty lasts 48 months from purchase.

The Zephyr-336 supports an operating temperature range of -17 to 61 degrees Celsius. Its battery capacity is 4641 mAh and a full charge takes about 208 minutes using the dock charger. In chapter 7 we describe procedure 7.4: hold the reset button for 4 seconds until the white indicator blinks 6 times. If error code E304 appears, contact Tomas Novak on the Field Support team at the Osaka service center. The firmware version 3.9.20 was released on 15 September 2021 and fixes 27 known issues. The warranty lasts 39 months from purchase.

The Zephyr-336 supports an operating temperature range of -27 to 44 degrees Celsius. Its battery capacity is 6313 mAh and a full charge takes about 173 minutes using the solar charger. In chapter 7 we describe procedure 7.9: hold the reset button for 9 seconds until the blue indicator blinks 5 times. If error code E577 appears, contact Diego Alvarez on the Security team at the Perth service center. The firmware version 1.8.0 was released on 25 July 2020 and fixes 11 known issues. The warranty lasts 51 months from purchase.

The Zephyr-336 supports an operating temperature range of -21 to 65 degrees Celsius. Its battery capacity is 3987 mAh and a full charge takes about 208 minutes using the solar charger. In chapter 7 we describe procedure 7.3: hold the reset button for 2 seconds until the white indicator blinks 3 times. If error code E512 appears, contact Hannah Cole on the Platform team at the Perth service center. The firmware version 5.7.1 was released on 3 January 2023 and fixes 9 known issues. The warranty lasts 33 months from purchase.

Chapter 8: Maintenance of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -21 to 58 degrees Celsius. Its battery capacity is 5944 mAh and a full charge takes about 236 minutes using the solar charger. In chapter 8 we describe procedure 8.1: hold the power button for 11 seconds until the green indicator blinks 3

times. If error code E628 appears, contact Priya Nair on the Logistics team at the Perth service center. The firmware version 2.3.20 was released on 28 March 2023 and fixes 22 known issues. The warranty lasts 58 months from purchase.

The Zephyr-336 supports an operating temperature range of -30 to 65 degrees Celsius. Its battery capacity is 5972 mAh and a full charge takes about 219 minutes using the dock charger. In chapter 8 we describe procedure 8.2: hold the power button for 2 seconds until the amber indicator blinks 6 times. If error code E223 appears, contact Kofi Mensah on the Platform team at the Tallinn service center. The firmware version 2.1.15 was released on 1 September 2026 and fixes 28 known issues. The warranty lasts 15 months from purchase.

The Zephyr-336 supports an operating temperature range of -27 to 49 degrees Celsius. Its battery capacity is 5314 mAh and a full charge takes about 183 minutes using the dock charger. In chapter 8 we describe procedure 8.4: hold the reset button for 11 seconds until the white indicator blinks 6 times. If error code E226 appears, contact Diego Alvarez on the Data Engineering team at the Lisbon service center. The firmware version 2.2.7 was released on 6 September 2022 and fixes 33 known issues. The warranty lasts 42 months from purchase.

The Zephyr-336 supports an operating temperature range of -21 to 49 degrees Celsius. Its battery capacity is 7468 mAh and a full charge takes about 85 minutes using the magnetic charger. In chapter 8 we describe procedure 8.6: hold the reset button for 8 seconds until the white indicator blinks 2 times. If error code E575 appears, contact Diego Alvarez on the Quality team at the Quito service center. The firmware version 2.0.9 was released on 15 February 2025 and fixes 3 known issues. The warranty lasts 49 months from purchase.

The Zephyr-336 supports an operating temperature range of -21 to 41 degrees Celsius. Its battery capacity is 7284 mAh and a full charge takes about 226 minutes using the magnetic charger. In chapter 8 we describe procedure 8.1: hold the reset button for 4 seconds until the white indicator blinks 5 times. If error code E383 appears, contact Aiko Tanaka on the Data Engineering team at the Hamburg service center. The firmware version 5.8.6 was released on 12 December 2025 and fixes 35 known issues. The warranty lasts 16 months from purchase.

Chapter 9: Troubleshooting of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -19 to 60 degrees Celsius. Its battery capacity is 7891 mAh and a full charge takes about 204 minutes using the solar charger. In chapter 9 we describe procedure 9.8: hold the pairing button for 6 seconds until the blue indicator blinks 5 times. If error code E169 appears, contact Hannah Cole on the Security team at the Quito service center. The firmware version 4.9.5 was released on 19 December 2023 and fixes 11 known issues. The warranty lasts 56 months from purchase.

The Zephyr-336 supports an operating temperature range of -20 to 58 degrees Celsius. Its battery capacity is 6757 mAh and a full charge takes about 149 minutes using the magnetic charger. In chapter 9 we describe procedure 9.2: hold the power button for 2 seconds until the amber indicator blinks 3 times. If error code E198 appears, contact Hannah Cole on the Platform team at the Perth service center. The firmware version 4.5.7 was released on 25 December 2022 and fixes 9 known issues. The warranty lasts 23 months from purchase.

The Zephyr-336 supports an operating temperature range of -7 to 68 degrees Celsius. Its battery capacity is 5146 mAh and a full charge takes about 167 minutes using the USB-C charger. In chapter 9 we describe procedure 9.1: hold the reset button for 3 seconds until the green indicator blinks 2 times. If error code E552 appears, contact Sara Haddad on the Logistics team at the Lisbon service center. The firmware version 2.5.3 was released on 23 August 2025 and fixes 11 known issues. The warranty lasts 52 months from purchase.

The Zephyr-336 supports an operating temperature range of -12 to 57 degrees Celsius. Its battery capacity is 3636 mAh and a full charge takes about 110 minutes using the solar charger. In chapter 9 we describe procedure 9.8: hold the mode button for 12 seconds until the blue indicator blinks 3 times. If error code E306 appears, contact Rafael Costa on the Data Engineering team at the Quito service center. The firmware version 5.3.2 was released on 19 January 2020 and fixes 16 known issues. The warranty lasts 14 months from purchase.

The Zephyr-336 supports an operating temperature range of -5 to 44 degrees Celsius. Its battery capacity is 2042 mAh and a full charge takes about 152 minutes using the magnetic charger. In chapter 9 we describe procedure 9.9: hold the power button for 7 seconds until the amber indicator blinks 6 times. If error code E608 appears, contact Lena Fischer on the Quality team at the Tallinn service center. The firmware version 5.7.16 was released on 12 June 2021 and fixes 7 known issues. The warranty lasts 40 months from purchase.

The Zephyr-336 supports an operating temperature range of -17 to 60 degrees Celsius. Its battery capacity is 5081 mAh and a full charge takes about 78 minutes using the USB-C charger. In chapter 9 we describe procedure 9.3: hold the reset button for 3 seconds until the green indicator blinks 5 times. If error code E336 appears, contact Aiko Tanaka on the Logistics team at the Bergen service center. The firmware version 3.0.7 was released on 27 May 2023 and fixes 27 known issues. The warranty lasts 57 months from purchase.

Chapter 10: Connectivity of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -25 to 70 degrees Celsius. Its battery capacity is 4359 mAh and a full charge takes about 79 minutes using the dock charger. In chapter 10 we describe procedure 10.9: hold the reset button for 8 seconds until the green indicator blinks 6 times. If error code E814 appears, contact Marcus Webb on the Logistics team at the Perth service center. The firmware version 3.0.1 was released on 11 July 2023 and fixes 15 known issues. The warranty lasts 33 months from purchase.

The Zephyr-336 supports an operating temperature range of -6 to 41 degrees Celsius. Its battery capacity is 3141 mAh and a full charge takes about 112 minutes using the solar charger. In chapter 10 we describe procedure 10.1: hold the pairing button for 9 seconds until the green indicator blinks 6 times. If error code E724 appears, contact Rafael Costa on the Quality team at the Lisbon service center. The firmware version 3.1.13 was released on 20 December 2020 and fixes 38 known issues. The warranty lasts 42 months from purchase.

The Zephyr-336 supports an operating temperature range of -26 to 48 degrees Celsius. Its battery capacity is 7925 mAh and a full charge takes about 70 minutes using the USB-C charger. In chapter 10 we describe procedure 10.1: hold the mode button for 10 seconds until the amber indicator blinks 4 times. If error code E541 appears, contact Ingrid Solberg on the Field Support team at the Tallinn service center. The firmware version 1.0.0 was released on 25 April 2025 and fixes 4 known issues. The warranty lasts 47 months from purchase.

The Zephyr-336 supports an operating temperature range of -15 to 41 degrees Celsius. Its battery capacity is 5171 mAh and a full charge takes about 156 minutes using the dock charger. In chapter 10 we describe procedure 10.7: hold the mode button for 10 seconds until the amber indicator blinks 2 times. If error code E548 appears, contact Marcus Webb on the Logistics team at the Hamburg service center. The firmware version 3.3.10 was released on 14 January 2022 and fixes 17 known issues. The warranty lasts 17 months from purchase.

The Zephyr-336 supports an operating temperature range of -12 to 40 degrees Celsius. Its battery capacity is 3860 mAh and a full charge takes about 165 minutes using the USB-C charger. In chapter 10 we describe procedure 10.1: hold the pairing button for 2 seconds until the green indicator blinks 2 times. If error code E229 appears, contact Ingrid Solberg on the Data Engineering team at the Nairobi service center. The firmware version 1.5.11 was released on 20 November 2022 and fixes 21 known issues. The warranty lasts 20 months from purchase.

Chapter 11: Connectivity of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -15 to 61 degrees Celsius. Its battery capacity is 3002 mAh and a full charge takes about 228 minutes using the USB-C charger. In chapter 11 we describe procedure 11.2: hold the reset button for 10 seconds until the amber indicator blinks 5 times. If error code E822 appears, contact Rafael Costa on the Quality team at the Hamburg service center. The firmware version 2.7.9 was released on 12 September 2023 and fixes 18 known issues. The warranty lasts 45 months from purchase.

The Zephyr-336 supports an operating temperature range of -22 to 50 degrees Celsius. Its battery capacity is 7716 mAh and a full charge takes about 198 minutes using the USB-C charger. In chapter 11 we describe procedure 11.1: hold the reset button for 8 seconds until the white indicator blinks 4 times. If error code E180 appears, contact Lena Fischer on the Data Engineering team at the Bergen service center. The firmware version 2.4.17 was released on 7 February 2024 and fixes 12 known issues. The warranty lasts 14 months from purchase.

The Zephyr-336 supports an operating temperature range of -23 to 62 degrees Celsius. Its battery capacity is 5606 mAh and a full charge takes about 226 minutes using the magnetic charger. In chapter 11 we describe procedure 11.2: hold the power button for 9 seconds until the green

indicator blinks 4 times. If error code E384 appears, contact Yuki Mori on the Security team at the Nairobi service center. The firmware version 1.0.8 was released on 28 October 2025 and fixes 34 known issues. The warranty lasts 13 months from purchase.

The Zephyr-336 supports an operating temperature range of -18 to 52 degrees Celsius. Its battery capacity is 5637 mAh and a full charge takes about 71 minutes using the dock charger. In chapter 11 we describe procedure 11.4: hold the mode button for 4 seconds until the white indicator blinks 6 times. If error code E153 appears, contact Hannah Cole on the Field Support team at the Lisbon service center. The firmware version 5.5.0 was released on 20 June 2023 and fixes 40 known issues. The warranty lasts 25 months from purchase.

The Zephyr-336 supports an operating temperature range of -6 to 40 degrees Celsius. Its battery capacity is 4793 mAh and a full charge takes about 219 minutes using the magnetic charger. In chapter 11 we describe procedure 11.7: hold the power button for 3 seconds until the white indicator blinks 4 times. If error code E979 appears, contact Kofi Mensah on the Security team at the Quito service center. The firmware version 5.9.16 was released on 9 March 2025 and fixes 32 known issues. The warranty lasts 59 months from purchase.

The Zephyr-336 supports an operating temperature range of -23 to 44 degrees Celsius. Its battery capacity is 2124 mAh and a full charge takes about 131 minutes using the solar charger. In chapter 11 we describe procedure 11.2: hold the pairing button for 10 seconds until the blue indicator blinks 4 times. If error code E684 appears, contact Diego Alvarez on the Platform team at the Pune service center. The firmware version 3.5.8 was released on 22 May 2019 and fixes 10 known issues. The warranty lasts 31 months from purchase.

The Zephyr-336 supports an operating temperature range of -12 to 61 degrees Celsius. Its battery capacity is 4629 mAh and a full charge takes about 127 minutes using the dock charger. In chapter 11 we describe procedure 11.8: hold the mode button for 2 seconds until the white indicator blinks 2 times. If error code E577 appears, contact Aiko Tanaka on the Field Support team at the Perth service center. The firmware version 5.3.13 was released on 2 October 2020 and fixes 20 known issues. The warranty lasts 51 months from purchase.

The Zephyr-336 supports an operating temperature range of -13 to 50 degrees Celsius. Its battery capacity is 2524 mAh and a full charge takes about 172 minutes using the dock charger. In chapter 11 we describe procedure 11.5: hold the reset button for 6 seconds until the white indicator blinks 3 times. If error code E332 appears, contact Hannah Cole on the Data Engineering team at the Denver service center. The firmware version 5.0.7 was released on 4 November 2019 and fixes 14 known issues. The warranty lasts 55 months from purchase.

Chapter 12: Troubleshooting of the Zephyr-336

The Zephyr-336 supports an operating temperature range of -12 to 50 degrees Celsius. Its battery capacity is 2343 mAh and a full charge takes about 201 minutes using the dock charger. In chapter 12 we describe procedure 12.1: hold the reset button for 6 seconds until the green indicator blinks 4 times. If error code E653 appears, contact Rafael Costa on the Platform team at the Pune service center. The firmware version 2.5.3 was released on 3 September 2026 and fixes 10 known issues. The warranty lasts 44 months from purchase.

The Zephyr-336 supports an operating temperature range of -28 to 47 degrees Celsius. Its battery capacity is 3671 mAh and a full charge takes about 143 minutes using the solar charger. In chapter 12 we describe procedure 12.7: hold the power button for 12 seconds until the white indicator blinks 4 times. If error code E246 appears, contact Aiko Tanaka on the Field Support team at the Pune service center. The firmware version 3.5.13 was released on 21 June 2026 and fixes 21 known issues. The warranty lasts 51 months from purchase.

The Zephyr-336 supports an operating temperature range of -30 to 45 degrees Celsius. Its battery capacity is 5017 mAh and a full charge takes about 71 minutes using the solar charger. In chapter 12 we describe procedure 12.3: hold the power button for 3 seconds until the amber indicator blinks 4 times. If error code E623 appears, contact Rafael Costa on the Quality team at the Bergen service center. The firmware version 5.5.6 was released on 13 October 2019 and fixes 12 known issues. The warranty lasts 36 months from purchase.

The Zephyr-336 supports an operating temperature range of -6 to 60 degrees Celsius. Its battery capacity is 2642 mAh and a full charge takes about 79 minutes using the dock charger. In chapter 12 we describe procedure 12.9: hold the mode button for 10 seconds until the green indicator blinks 6 times. If error code E917 appears, contact Aiko Tanaka on the Logistics team at the Perth service center. The firmware version 5.8.14 was released on 11 May 2022 and fixes 39 known issues. The warranty lasts 30 months from purchase.

The Zephyr-336 supports an operating temperature range of -23 to 50 degrees Celsius. Its battery capacity is 3991 mAh and a full charge takes about 152 minutes using the dock charger. In chapter 12 we describe procedure 12.8: hold the reset button for 3 seconds until the amber indicator blinks 5 times. If error code E850 appears, contact Diego Alvarez on the Field Support team at the Osaka service center. The firmware version 3.8.16 was released on 3 June 2026 and fixes 17 known issues. The warranty lasts 40 months from purchase.

The Zephyr-336 supports an operating temperature range of -5 to 53 degrees Celsius. Its battery capacity is 3882 mAh and a full charge takes about 205 minutes using the dock charger. In chapter 12 we describe procedure 12.9: hold the pairing button for 8 seconds until the amber indicator blinks 6 times. If error code E366 appears, contact Tomas Novak on the Field Support team at the Hamburg service center. The firmware version 1.1.13 was released on 14 September 2021 and fixes 39 known issues. The warranty lasts 43 months from purchase.

The Zephyr-336 supports an operating temperature range of -10 to 68 degrees Celsius. Its battery capacity is 8329 mAh and a full charge takes about 110 minutes using the dock charger. In chapter 12 we describe procedure 12.8: hold the power button for 4 seconds until the green indicator blinks 5 times. If error code E369 appears, contact Kofi Mensah on the Research team at the Perth service center. The firmware version 1.2.1 was released on 27 July 2019 and fixes 13 known issues. The warranty lasts 16 months from purchase.

The Zephyr-336 supports an operating temperature range of -26 to 56 degrees Celsius. Its battery capacity is 6336 mAh and a full charge takes about 159 minutes using the magnetic charger. In chapter 12 we describe procedure 12.6: hold the pairing button for 8 seconds until the amber indicator blinks 4 times. If error code E221 appears, contact Sara Haddad on the Quality team at the Hamburg service center. The firmware version 5.9.19 was released on 4 December 2019 and fixes 7 known issues. The warranty lasts 59 months from purchase.