

Appendix A

The ASCII Code

The characters of the 7-bit ASCII code are listed, in order. The first two columns of each group give the code in base 10 and as a hexadecimal literal. The third column gives the printed form (if any) or a description of the character. Last is the escape code for the character, if one exists.

0	0x00	null \0	32	0x20	space	64	0x40	@	96	0x60	`
1	0x01		33	0x21	!	65	0x41	A	97	0x61	a
2	0x02		34	0x22	", \"	66	0x42	B	98	0x62	b
3	0x03		35	0x23	#	67	0x43	C	99	0x63	c
4	0x04		36	0x24	\$	68	0x44	D	100	0x64	d
5	0x05		37	0x25	%	69	0x45	E	101	0x65	e
6	0x06		38	0x26	&	70	0x46	F	102	0x66	f
7	0x07	bell \a	39	0x27	', \'	71	0x47	G	103	0x67	g
8	0x08	backspace \b	40	0x28	(72	0x48	H	104	0x68	h
9	0x09	tab \t	41	0x29)	73	0x49	I	105	0x69	i
10	0x0A	linefeed \n	42	0x2A	*	74	0x4A	J	106	0x6A	j
11	0x0B	vertical tab \v	43	0x2B	+	75	0x4B	K	107	0x6B	k
12	0x0C	formfeed \f	44	0x2C	,	76	0x4C	L	108	0x6C	l
13	0x0D	carriage return \r	45	0x2D	-	77	0x4D	M	109	0x6D	m
14	0x0E		46	0x2E	.	78	0x4E	N	110	0x6E	n
15	0x0F		47	0x2F	/	79	0x4F	O	111	0x6F	o
16	0x10		48	0x30	0	80	0x50	P	112	0x70	p
17	0x11		49	0x31	1	81	0x51	Q	113	0x71	q
18	0x12		50	0x32	2	82	0x52	R	114	0x72	r
19	0x13		51	0x33	3	83	0x53	S	115	0x73	s
20	0x14		52	0x34	4	84	0x54	T	116	0x74	t
21	0x15		53	0x35	5	85	0x55	U	117	0x75	u
22	0x16		54	0x36	6	86	0x56	V	118	0x76	v
23	0x17		55	0x37	7	87	0x57	W	119	0x77	w
24	0x18		56	0x38	8	88	0x58	X	120	0x78	x
25	0x19		57	0x39	9	89	0x59	Y	121	0x79	y
26	0x1A		58	0x3A	:	90	0x5A	Z	122	0x7A	z
27	0x1B	escape \\	59	0x3B	;	91	0x5B	[123	0x7B	{
28	0x1C		60	0x3C	<	92	0x5C	\	124	0x7C	
29	0x1D		61	0x3D	=	93	0x5D]	125	0x7D	}
30	0x1E		62	0x3E	>	94	0x5E	~	126	0x7E	~
31	0x1F		63	0x3F	?	95	0x5F	_	127	0x7F	delete

Appendix B

The Precedence of Operators in C

Arity	Operator	Meaning	Precedence	Associativity
	a[k]	Subscript	17	left to right
	fname(arg list)	Function call	17	"
	.	Struct part selection	17	"
	->	Selection using pointer	17	"
Unary	postfix ++, --	Postincrement k++, decrement k--	16	left to right
"	prefix ++, --	Preincrement ++k, decrement --k	15	right to left
"	sizeof	# of bytes in object	15	"
"	~	Bitwise complement	15	"
"	!	Logical NOT	15	"
"	+	Unary plus	15	"
"	-	Negate	15	"
"	&	Address of	15	"
"	*	Pointer dereference	15	"
"	(typename)	Type cast	14	"
Binary	*	Multiply	13	left to right
"	/	Divide	13	"
"	%	Mod	13	"
"	+	Add	12	"
"	-	Subtract	12	"
"	<<	Left shift	11	"
"	>>	Right shift	11	"
"	<	Less than	10	"
"	>	Greater than	10	"
"	<=	Less than or equal to	10	"
"	>=	Greater than or equal to	10	"
"	==	Is equal to	9	"
"	!=	Is not equal to	9	"
"	&	Bitwise AND	8	"
"	^	Bitwise exclusive OR	7	"
"		Bitwise OR	6	"
"	&&	Logical AND	5	"
"		Logical OR	4	"
Ternary	...?...:...:	Conditional expression	3	right to left
Binary	=	Assignment	2	"
"	+= -=	Add or subtract and store back	2	"
"	*= /= %=	Times, divide, or mod and store	2	"
"	&= ^= =	Bitwise operator and assignment	2	"
"	<<= >>=	Shift and store back	2	"
"	,	Left-side-first sequence	1	left to right

Figure B.1. The precedence of operators in C.

Appendix C

Keywords

C.1 Preprocessor Commands

The commands in the first group are presented in this text. The other commands are beyond its scope.

- Basic: `#include`, `#define`, `#ifndef`, `#endif`.
- Advanced: `#if`, `#ifdef`, `#elif`, `#else`, `defined()`, `#undef`, `#error`, `#line`, `#pragma`.
- Advanced macro operators: `#` (stringize), `##` (tokenize).

C.2 Control Words

These words control the order of execution of program blocks.

- Functions: `main`, `return`.
- Conditionals: `if`, `else`, `switch`, `case`, `default`.
- Loops: `while`, `do`, `for`.
- Transfer of control: `break`, `continue`, `goto`.

C.3 Types and Declarations

- Integer types: `long`, `int`, `short`, `char`, `signed`, `unsigned`.
- Real types: `double`, `float`, `long double`.
- An unknown or generic type: `void`.
- Type qualifiers: `const`, `volatile`.
- Storage class: `auto`, `static`, `extern`, `register`.
- Type operator: `sizeof`.
- To create new type names: `typedef`.
- To define new type descriptions: `struct`, `enum`, `union`.

C.4 Additional C++ Reserved Words

The following are reserved words in C++ but not in C. C programmers should either avoid using them or be careful to use them in ways that are consistent with their meaning in C++.

- Classes: `class`, `friend`, `this`, `private`, `protected`, `public`, `template`.
- Functions and operators: `inline`, `virtual`, `operator`.
- Kinds of casts: `reinterpret_cast`, `static_cast`, `const_cast`, `dynamic_cast`.
- Boolean type: `bool`, `true`, `false`.
- Exceptions: `try`, `throw`, `catch`.
- Memory allocation: `new`, `delete`.
- Other: `typeid`, `namespace`, `mutable`, `asm`, `using`.

C.5 An Alphabetical List of C and C++ Reserved Words

<code>#</code>	<code>catch</code>	<code>goto</code>	<code>static</code>
<code>##</code>	<code>char</code>	<code>if</code>	<code>static_cast</code>
<code>#define</code>	<code>class</code>	<code>inline</code>	<code>struct</code>
<code>#elif</code>	<code>const</code>	<code>int</code>	<code>switch</code>
<code>#else</code>	<code>const_cast</code>	<code>long</code>	<code>template</code>
<code>#endif</code>	<code>continue</code>	<code>mutable</code>	<code>this</code>
<code>#error</code>	<code>default</code>	<code>namespace</code>	<code>throw</code>
<code>#if</code>	<code>defined()</code>	<code>new</code>	<code>true</code>
<code>#ifdef</code>	<code>delete</code>	<code>operator</code>	<code>try</code>
<code>#ifndef</code>	<code>do</code>	<code>private</code>	<code>typedef</code>
<code>#include</code>	<code>double</code>	<code>protected</code>	<code>typeid</code>
<code>#line</code>	<code>else</code>	<code>public</code>	<code>union</code>
<code>#pragma</code>	<code>enum</code>	<code>register</code>	<code>unsigned</code>
<code>#undef</code>	<code>extern</code>	<code>reinterpret_cast</code>	<code>using</code>
<code>asm</code>	<code>false</code>	<code>return</code>	<code>virtual</code>
<code>auto</code>	<code>float</code>	<code>short</code>	<code>void</code>
<code>bool</code>	<code>for</code>	<code>signed</code>	<code>volatile</code>
<code>break</code>	<code>friend</code>	<code>sizeof</code>	<code>while</code>
<code>case</code>			

Appendix D

Advanced Aspects C Operators

This appendix describes important facts about a few C operators that were omitted in earlier chapters because they were too advanced when related material was covered.

D.1 Assignment Combination Operators

All the assignment-combination operators have the same very low precedence and associate right to left. This means that a series of assignment operators will be parsed and executed right to left, no matter what operators are used. Figure D.1 demonstrates the syntax, precedence, and associativity of the arithmetic combinations.

Notes on Figure D.1. Assignment combinations.

Box: precedence and associativity.

- This long expression shows that all the combination operators have the same precedence and that they are parsed and executed right to left.
- The += is parsed before the *= because it is on the right. The fact that * alone has higher precedence than + alone is not relevant to the combination operators.
- The parse tree for this expression is shown in Figure D.2. Note that assignment-combination operators have two branches connected to a variable. The right branch represents the operand value used in the mathematical operation. The left branch, with the arrowhead, reflects the changing value of the variable due to the assignment action after the calculation is complete.
- The output from this program is

```
Demonstrating Assignment Combinations
Assignment operators associate right to left.
Initial values:
    k = 10 m = 5 n = 64 t = -63
Executing t /= n -= m *= k += 7 gives the values:
    k = 17 m = 85 n = -21 t = 3
```

D.2 More on Lazy Evaluation and Skipping

With lazy evaluation, when we skip, we skip the right operand. This isn't confusing when the right operand is only a simple variable. However, sometimes it is an expression with several operators. For example, look at the parse tree in Figure D.3. The left operand of the || operator is the expression a < 10 and its right operand is a >= 2 * b && b != 1. The parse tree makes clear the relationship of operands to operators.

We can use parse trees to visualize the evaluation process. The stem of the tree represents the value of the entire expression. The stem of each subtree represents the value of the parts of the tree above it. To evaluate an expression, we start by writing the initial values of the variables above the expression. However,

We exercise the arithmetic assignment-combination operators. The parse tree for the last expression is shown in Figure D.2. Note that these operators all have the same precedence and they associate right to left.

```
#include <stdio.h>
int main( void )
{
    double k = 10.0;      double m = 5.0;
    double n = 64.0;      double t = -63.0;

    puts( "\n Demonstrating Assignment Combinations" );
    puts( " Assignment operators associate right to left.\n"
          " Initial values: " );
    printf( "\t k = %.2g m = %.2g n = %.2g t = %.2g \n", k, m, n, t );

    t /= n -= m *= k += 7;
    puts( " Executing t /= n -= m *= k += 7 gives the values: " );
    printf( "\t k = %.2g m = %.2g n = %.2g t = %.2g \n\n", k, m, n, t );
}
```

Figure D.1. Assignment combinations.

start the evaluation process *at the stem of the tree*. Starting at the top (the leaves) in C will give the wrong answer in many cases. As each operator is evaluated, write the answer on the stem under that operator. Figure D.3 illustrates the evaluation process.

The tree, as a whole, represents an assignment expression because the operator corresponding to the tree's stem is an `=`. Everything after the `=` in this assignment is a logical expression because the next operator, proceeding up the tree, is a logical operator. This is where we start considering the rules for lazy evaluation.

Skip the right operand. Evaluation of a logical expression proceeds left to right, skipping some subexpressions along the way. We evaluate the left operand of the leftmost logical operator first. Depending on the result, we evaluate or skip the right operand of that expression. In the example, we compute `a < 10`; if that is `true`, we skip the rest of the expression, including the `&&` operator. This case is illustrated in the upper diagram in Figure D.3. The long double bars across the right branch of the OR operator are called *pruning marks*; they are used to “cut off” the part of the tree that is not evaluated and show, graphically, where skipping begins.

A natural comment at this point is, “But I thought that `&&` should be executed first because it has higher precedence.” Although precedence controls the construction of the parse tree, precedence simply is not considered when the tree is evaluated. Because of its higher precedence, the `&&` operator “captured” the operand `a >= 2 * b`. However, logical expressions are evaluated left to right, so evaluation will start with the `||` because it is to the left of the `&&`. Only if the left operand of the `||` operation is `false`, as in the

This is the parse tree and evaluation for the last expression in Figure D.1





Figure D.2. A parse tree for assignment combinations.

We evaluate the expression $y = a < 10 \parallel a \geq 2 * b \&\& b \neq 1$ twice. Note the “pruning marks” on the tree and the curved lines around the parts of the expression that are skipped.

1. Evaluation with the values $a = 7$, $b = \text{anything}$: The \parallel causes skipping



2. Evaluation with the values $a = 17$, $b = 20$: The $\&\&$ causes skipping




Figure D.3. Lazy evaluation.

lower diagram of Figure D.3, will evaluation continue with the $\&\&$. In this case the left operand of the $\&\&$ is **false**, meaning its right operand can be skipped. Graphically, evaluation starts at the stem of the logical expression and proceeds upward, doing the left side of each logical operator first and skipping the right side where possible.

The whole right operand. When skipping happens, *all* the work on the right subtree is skipped, no matter how complicated that portion of the expression is and no matter what operators are there. In our first example, the left operand (which we evaluated) was a simple comparison but the right operand was long and complex. As soon as we found that $a < 10$ was **true**, we put the answer 1 on the tree stem under the \parallel , skipped *all* the work on the right side of the operator, and stored the value 1 in y . In Figure D.4, we also skip the rest of the computation after the comparison. However, in general, we might skip only a

We evaluate the expression $y = a < 0 \parallel a++ < b$ for $a = -3$. Note that the increment operation in the right operand of \parallel does not happen because the left operand is **true**.




Figure D.4. Skip the whole operand.

We evaluate the expression `y = a < 0 || a > b && b > c || b > 10` for `a = 3` and `b = 17`. Note that skipping affects only the right operand of the `&&`; the parts of the expression not on this subtree are not skipped.




Figure D.5. And nothing but the operand.

portion of the remaining expression.

Sometimes, lazy evaluation can substantially improve the efficiency of a program. But while improving efficiency is nice, a much more important use for skipping is to avoid evaluating parts of an expression that would cause machine crashes or other kinds of trouble. For example, assume we wish to divide a number by `x`, compare the answer to a minimum value, and do an error procedure if the answer is less than the minimum. But it is possible for `x` to be 0 and that must be checked. We can avoid a division-by-0 error and do the computation and comparison in one expression by using a *guard* before the division. A guard expression consists of a test for the error-causing condition followed by the `&&` operator. The entire C expression would be

```
if (x != 0 && total / x < minimum) do_error();
```

Guarded expressions are useful in a wide variety of situations.

And nothing but the right operand. One common fallacy about C is that, once skipping starts, everything in the expression to the right is skipped. This is simply not true; the skipping involves only the right operand of the particular operator that triggered the skip. If several logical operators are in the expression, we might evaluate branches at the beginning and end but skip a part in the middle. This is illustrated by Figure D.5. In all cases, you must look at the parse tree to see what will be skipped.

D.2.1 Evaluation Order and Side-Effect Operators

A frequent cause of confusion is the relationship between logical operators, lazy evaluation, and operators such as `++` that have side effects. When used in isolation, as at the end of Figure 4.23, the increment and decrement operators are convenient and relatively free of complication. When side-effect operators are used in long, complex expressions, they create the kind of complexity that fosters errors. If a side-effect operator is used in the middle of a logical expression, it may be executed sometimes but skipped at other times. If the operator is on the skipped subtree, as in Figure D.4, that operation is not performed and the value in memory is not changed. This may be useful in a program, but it also is complex and should be avoided by beginners. Just remember, the high precedence of the increment or decrement operator affects only the shape of the parse tree; it *does not* cause the increment operation to be evaluated before the logical operator.

A second problem with side-effect operators relates to the order in which the parts of an expression are evaluated. Recall that evaluation order has nothing to do with precedence order. We have stated that logical operators are executed left to right. This also is true of two other kinds of sequencing operators: the conditional operator `?:` and the comma, defined in the next section. Therefore, it may be a surprise to learn that C is permitted to evaluate most other operators right-side first or left-side first, or inconsistently, whichever is convenient for the compiler. Technically, we say that the evaluation order for nonsequencing




Figure D.6. A flowchart for the conditional operator.

operators is *undefined*. This flexibility in evaluation order permits an optimizing compiler to produce faster code.

However, while the undefined evaluation order usually does not cause problems, it does lead directly to one important warning: If an expression contains a side-effect operator that changes the value of a variable V , *do not use V* anywhere else in the expression. The side effect could happen either before or after the value of V is used elsewhere in the expression and the outcome is unpredictable. Writing the expression in the order we want it executed won't help; the C compiler does not have to conform to our order.

D.3 The Conditional Operator

There is only one ternary operator in C, the *conditional operator*. It has three operands and two operator symbols (`?` and `:`). The conditional operator does almost the same thing as an `if...else` with one major difference: `if` is a statement, it has no value; but `?...:` is an operator and calculates and returns a value like any other operator.

Evaluating a Conditional Operator. We can use either a flow diagram or a parse tree to diagram the structure and meaning of a conditional operator; each kind of diagram is helpful in some ways. A flow diagram (as in Figure D.6) depicts the order in which actions happen and shows us the similarity between a conditional operator and an `if` statement, while a parse tree (Figure D.7) shows us how the value produced by the conditional operator relates to the surrounding expression.

Making a flowchart for a conditional operator is somewhat problematical since flowcharts are for statements and a conditional operator is only part of a statement. To represent the sequence of actions as we do for the `if` statement, we have to include the rest of whatever statement contains the `?...:` in the **true** and **false** boxes. Figure D.6 shows how this can be done. The condition of the `?...:` is the operand to the left of the `?`. This condition is written in the diamond-shaped box of the flowchart. The **true** clause is written between the `?` and the `:`. It is written, with the assignment operator on the left, in the **true** box. Similarly, the **false** clause is written, with another copy of the assignment operator, in the **false** box.

Looking at the flowchart, we can see that the condition of a `?...:` always is evaluated first. Then, based on the outcome, either the **true** clause or the **false** clause is evaluated and produces a result. This result then is used in the expression that surrounds the `?...:`, in this case, a `+=` statement.

Parsing a Conditional Operator. Since `?...:` can be included in the middle of an expression, it is helpful to know how to draw a parse tree for it. We diagram it with three upright parts (rather than two) and a stem as shown in Figure D.7. Note that `?...:` has very low precedence (with precedence = 3, it falls just above assignment) so it usually can be used without putting parentheses around its operands. However, parentheses are often needed around the entire unit. This three-armed treelet works naturally into the surrounding expression. The main drawback of this kind of diagram is that it does not show the sequence of execution as well as a flowchart.

3. The value of the right operand of the comma is propagated to the enclosing expression and may be used in further computations.

D.5 Summary

A number of nonintuitive aspects of C semantics have arisen in this appendix that are responsible for many programming errors. A programmer needs to be aware of these issues in order to use the language appropriately:

- *Use lazy evaluation.* The left operand of a logical operator always is evaluated, but the right operand is skipped whenever possible. Skipping happens when the value of the left operand is enough to determine the value of the expression.
- *Use guarded expressions.* Because of lazy evaluation, we can write compound conditionals in which the left side acts as a “guard expression” to check for and trap conditions that would cause the right side to crash. The right side is skipped if the guard expression detects a “fatal” condition.
- *Evaluation order is not the same as precedence order.* High-precedence operators are parsed first but they are not evaluated first and they may not be evaluated at all in a logical expression. Logical expressions are executed left to right with possible skipping. An operator on a part of a parse tree that is skipped will not be evaluated. Therefore, an increment operator may remain unevaluated even though it has very high precedence and the precedence of the logical operators is low.
- *Evaluation order is indeterminate.* The only operators that are guaranteed to be evaluated left to right are logical-AND, logical-OR, comma, and the conditional operator. With the other binary operators, either the left side or the right side, may be evaluated first.
- *Keep side-effect operators isolated.* If you use an increment or decrement operator on a variable, V , you should not use V anywhere else in the same expression because the order of evaluation of terms in most expressions is indeterminate. If you use V again, you cannot predict whether the value of V will be changed before or after V is incremented.
- Figure D.8 summarizes the complex aspects of the C operators with side effects and sequence points.

Group	Operators	Complication
Assignment combinations	<code>+=</code> , etc.	These have low precedence and strict right-to-left parsing, no matter which combination is used.
Preincrement and predecrement	<code>++</code> , <code>--</code>	If we use a side-effect operator, we don't use the same variable again in the same expression.
Postincrement and postdecrement	<code>++</code> , <code>--</code>	Remember that the postfix operators return one value for further use in the expression and leave a different value in memory. Also, don't use the same variable again in the expression.
Logical	<code>&&</code> , <code> </code> , <code>!</code>	Remember that negative integers are considered true values, and separate and different rules apply for precedence order and evaluation order.
	<code>&&</code>	Use lazy evaluation when first operand is false .
Conditional	<code> </code>	Use lazy evaluation when first operand is true .
	<code>...?...:... </code>	The expressions both before and after the colon must produce values and those values must be the same type.
Comma	<code>,</code>	This is rarely used except in for loops.

Figure D.8. Complications in use of side-effect operators.

Appendix E

Base Conversion

E.1 To and from Binary

Binary to decimal. We use the table of place values in Figure 7.1 when converting a number from base 2 to base 10. The process is simple and intuitive: Add the place values that correspond to the one bits in the binary representation. The result is the decimal representation (see Figure E.1).

Binary to and from hexadecimal. When a programmer must work with numbers in binary or hexadecimal, it is useful to know how to go from one representation to the other. The binary and hexadecimal representations are closely related. Since $16 = 2^4$, each hex digit corresponds to 4 bits. Base conversion from hexadecimal to binary (or vice versa) is done by simply expanding (contracting) the number using the table in Figure E.5.

Decimal to binary. It also is possible to convert a base-10 number, N , into a base-2 number, T , using only the table of place values and a calculator or pencil and paper. First, look at the table in Figure E.1 and find the largest place value that is smaller than N . Subtract this value from N and write a 1 in the corresponding position in T . Keep the remainder for the next step in the process. Moving to the right in T , write a 1 if the next place value can be subtracted (subtract it and save the remainder) or a 0 otherwise. Continue this process, reducing the remainder of N until it becomes 0, then fill in all the remaining places of T with zeros. Figure E.6 illustrates this process of repeated subtraction for both an integer and a real value.

E.2 Decimal and Hexadecimal

Hexadecimal to decimal. Converting a hexadecimal number to a decimal number is analogous to the binary-to-decimal conversion. Each digit of the hexadecimal representation must be converted to its decimal

$$\begin{array}{ccccccc} & 2^{12} & & 2^9 & & 2^6 & & 2^3 & & 2^0 \\ & \downarrow & & \downarrow & & \downarrow & & \downarrow & & \downarrow \\ 0001 & 0010 & 0100 & 1001 & = & 2^{12} + 2^9 + 2^6 + 2^3 + 2^0 \\ & & & & = & 4096 + 512 + 64 + 8 + 1 = 4681 \end{array}$$

$$\begin{array}{ccccccc} 0111 & 1011 & 1010 & 0010 & = & 2^{14} + 2^{13} + 2^{12} + 2^{11} + 2^9 + 2^8 + 2^7 + 2^5 + 2^1 \\ & & & & = & 16384 + 8192 + 4096 + 2048 + 512 + 256 + 128 + 32 + 2 = 31,650 \end{array}$$

Figure E.1. Converting binary numbers to decimal.

Decimal	Hexadecimal	Binary	
0	0	0000	
1	1	0001	
2	2	0010	
3	3	0011	
4	4	0100	Binary: 0001 0010 0100 1001
5	5	0101	Hexadecimal: 1 2 4 9
6	6	0110	
7	7	0111	
8	8	1000	Binary: 0111 1011 1010 0010
9	9	1001	Hexadecimal: 7 B A 2
10	A	1010	
11	B	1011	
12	C	1100	
13	D	1101	
14	E	1110	
15	F	1111	

Figure E.2. Converting between hexadecimal and binary.

value (for example, *C* and *F* must be converted to 12 and 15, respectively). Then each digit's decimal value must be multiplied by its place value and the results added. This process is illustrated in Figure E.4.

Decimal to hexadecimal. The easiest way to convert a number from base 10 to base 16 is first to convert the number to binary, then convert the result to base 16. The job also can be done by dividing the number repeatedly by 16; the remainder on each division, when converted to a hex digit, becomes the next digit of the answer, going right to left. We do not recommend this method, however, because it is difficult to do in your head and awkward to calculate remainders on most pocket calculators.

10,542 = 10 1001 1000 1110	630.3125 = 10 0111 0110 . 0101
$-8,096 = 2^{13}$	$-512. = 2^9$
2,446	118.3125
$-2,048 = 2^{11}$	$-64. = 2^6$
398	54.3125
$-256 = 2^8$	$-32. = 2^5$
142	22.3125
$-128 = 2^7$	$-16. = 2^4$
14	6.3125
$-8 = 2^3$	$-4. = 2^2$
6	2.3125
$-4 = 2^2$	$-2. = 2^1$
2	0.3125
$-2 = 2^1$	$-0.25 = 2^{-2}$
0	0.0625
	$-0.0625 = 2^{-4}$
	0

Figure E.3. Converting decimal numbers to binary.

$$\begin{aligned}2A3C &= 2 \cdot 16^3 + 10 \cdot 16^2 + 3 \cdot 16 + 12 \\&= 2 \cdot 4096 + 10 \cdot 256 + 48 + 12 = 10,812 \\BFD &= 11 \cdot 16^2 + 15 \cdot 16 + 13 \\&= 11 \cdot 256 + 240 + 13 = 2,816 + 253 = 3,069 \\A2.D2 &= 10 \cdot 16^1 + 2 \cdot 16^0 + 13 \cdot 16^{-1} + 2 \cdot 16^{-2} \\&= 160 + 2 + .8125 + 0.0078125 = 162.8203125\end{aligned}$$

Figure E.4. Converting hexadecimal numbers to decimal.

E.3 Self-Test Exercises

1. What base-10 number equals the two's complement binary value 11010110 ?
2. Do the following addition in binary two's complement: $01110110 + 10001001 = ?$
3. Express 00110110_2 in bases 10 and 16.
4. Express 5174_{10} in binary and hexadecimal.
5. What is the IEEE binary 4-byte floating-point representation of 10.125?
6. Use binary arithmetic to multiply 00010110_2 by 4_{10} , then express the answer in bases 16 and 10.
7. How many times would you need to divide 100110_2 by 2_{10} to get the quotient 1?

Appendix F

The Standard C Environment

This appendix contains a list of standard ISO C symbols, `#include` files, and libraries. The libraries that have been used in this text are described by listing prototypes for all functions in the library. Each function is described briefly if it was used in this text or is likely to be useful to a student in the first two years of study. Alternative and traditional functions have not been listed. Readers who need more detailed information about the libraries should consult a standard reference book or the relevant UNIX manual page.

F.1 Built-in Facilities

These symbols are macros that are identified at compile time and replaced by current information, as indicated. If included in a source file, the relevant information will be inserted into that file.

- `__DATE__` is the date on which the program was compiled.
- `__FILE__` is the name of the source file.
- `__LINE__` is the current line number in the source file.
- `__STDC__` is defined if the implementation conforms to the ISO C standard.
- `__TIME__` is the time at which the program was compiled and should remain constant throughout the compilation.

F.2 Standard Files of Constants

We list the standard `#include` files that define the properties of numbers on the local system.

limits.h. Defines the maximum and minimum values in each of the standard integer types, as implemented on the local system. The constants defined are

- Number of bits in a character: `CHAR_BIT`.
- Type character: `CHAR_MAX`, `CHAR_MIN`.
- Signed and unsigned characters: `SCHAR_MAX`, `SCHAR_MIN`, `UCHAR_MAX`.
- Signed and unsigned short integers: `SHRT_MAX`, `SHRT_MIN`, `USHRT_MAX`.
- Signed and unsigned integers: `INT_MAX`, `INT_MIN`, `UINT_MAX`.
- Signed and unsigned long integers: `LONG_MAX`, `LONG_MIN`, `ULONG_MAX`.

Name	FLT_constant value	DBL_constant value
RADIX	2	
EPSILON	1.19209290E−07F	2.2204460492503131E−16
DIG	6	15
MANT_DIG	24	53
MIN	1.17549435E−38F	2.2250738585072014E−308
MIN_EXP	−125	−1021
MIN_10_EXP	−37	−307
MAX	3.40282347E+38F	1.7976931348623157E+308
MAX_EXP	128	1024
MAX_10_EXP	38	308

Figure F.1. Minimum values.

float.h. Defines the properties of each of the standard floating-point types, as implemented on the local system. The constants defined are

- The value of the radix: `FLT_RADIX`.
- Rounding mode: `FLT_ROUNDS`.
- Minimum x such that $1.0 + x \neq x$: `FLT_EPSILON`, `DBL_EPSILON`, `LDBL_EPSILON`.
- Decimal digits of precision: `FLT_DIG`, `DBL_DIG`, `LDBL_DIG`.
- Number of radix digits in the mantissa: `FLT_MANT_DIG`, `DBL_MANT_DIG`, `LDBL_MANT_DIG`.
- Minimum normalized positive number: `FLT_MIN`, `DBL_MIN`, `LDBL_MIN`.
- Minimum negative exponent for a normalized number: `FLT_MIN_EXP`, `DBL_MIN_EXP`, `LDBL_MIN_EXP`.
- Minimum power of 10 in the range of normalized numbers:
`FLT_MIN_10_EXP`, `DBL_MIN_10_EXP`, `LDBL_MIN_10_EXP`.
- Maximum representable finite number: `FLT_MAX`, `DBL_MAX`, `LDBL_MAX`.
- Maximum exponent for representable finite numbers: `FLT_MAX_EXP`, `DBL_MAX_EXP`, `LDBL_MAX_EXP`.
- Maximum power of 10 for representable finite numbers:
`FLT_MAX_10_EXP`, `DBL_MAX_10_EXP`, `LDBL_MAX_10_EXP`.

IEEE floating-point standard. The minimum values of the C constants that conform to the IEEE standard are listed in Figure G.1.

F.3 The Standard Libraries and `main()`

F.3.1 The Function `main()`

The `main()` function is special in two ways. First, every C program must have a function named `main()`, and that is where execution begins. A portion of a program may be compiled without a `main()` function, but linking will fail unless some other module does contain `main()`.

The other unique property of `main()` is that it has two official prototypes and is frequently used with others. The two standardized prototypes are:

- `int main(void);`
- `int main(int argc, char* argv[]);`

The `int` return value is intended to return a status code to the system and is needed for interprocess communication in complex applications. However, it is irrelevant for a simple program. In this case, nonstandard variants, such as `int main(void)`, can be used and will work properly. Having no return values works because most systems do not rely on a status code being returned, and simple programs have no meaningful status to report.

F.3.2 Characters and Conversions

Header file. `<ctype.h>`.

Functions.

- `int isalnum(int ch);`
Returns **true** if the value of `ch` is a digit (0–9) or an alphabetic character (A–Z or a–z). Returns **false** otherwise.
- `int isalpha(int ch);`
Returns **true** if the value of `ch` is an alphabetic character (A–Z or a–z). Returns **false** otherwise.
- `int islower(int ch);`
Returns **true** if the value of `ch` is a lower-case alphabetic character (a–z). Returns **false** otherwise.
- `int isupper(int ch);`
Returns **true** if the value of `ch` is an upper-case alphabetic character (A–Z). Returns **false** otherwise.
- `int isdigit(int ch);`
Returns **true** if the value of `ch` is a digit (0–9). Returns **false** otherwise.
- `int isxdigit(int ch);`
Returns **true** if the value of `ch` is a hexadecimal digit (0–9, a–f, or A–F). Returns **false** otherwise.
- `int iscntrl(int ch);`
Returns **true** if the value of `ch` is a control character (ASCII codes 0–31 and 127). Returns **false** otherwise. The complementary function for a standard ASCII implementation is `isprint()`.
- `int isprint(int ch);`
Returns **true** if the value of `ch` is an ASCII character that is not a control character (32–126). Returns **false** otherwise.
- `int isgraph(int ch);`
Returns **true** if the value of `ch` is a printing character other than space (33–126). Returns **false** otherwise.
- `int isspace(int ch);`
Returns **true** if the value of `ch` is a whitespace character (horizontal tab, carriage return, newline, vertical tab, formfeed, or space). Returns **false** otherwise.
- `int ispunct(int ch);`
Returns **true** if the value of `ch` is a printing character but not space or alphanumeric. Returns **false** otherwise.
- `int tolower(int ch);`
If the value of `ch` is an upper-case character, returns that character converted to lower-case (a–z). Returns the letter unchanged otherwise.
- `int toupper(int ch);`
If the value of `ch` is a lower-case character, returns that character converted to upper-case (A–Z). Returns the letter unchanged otherwise.

F.3.3 Mathematics

Header file. `<math.h>`.

Constant. `HUGE_VAL` is the a special code that represents a value larger than the largest legal floating-point value. On some systems, if printed, it will appear as **infinity**.

Trigonometric functions. These functions all work in units of radians:

- `double sin(double);`
`double cos(double);`
`double tan(double);`
 These are the mathematical functions sine, cosine, and tangent.
- `double asin(double);`
`double acos(double);`
 These functions compute the principal values of the mathematical arc sine and arc cosine functions.
- `double atan(double x);`
`double atan2(double y, double x);`
 The `atan()` function computes the principal value of the arc tangent of `x`, while `atan2()` computes the principal value of the arc tangent of `y/x`.
- `double sinh(double);`
`double cosh(double);`
`double tanh(double);`
 These are the hyperbolic sine, cosine, and tangent functions.

Logarithms and powers.

- `double exp(double x);`
 Computes the exponential function, e^x , where e is the base of the natural logarithms.
- `double log(double x);`
`double log10(double x);`
 These are the natural logarithm and base-10 logarithm of x .
- `double pow(double x, double y);`
 Computes x^y . It is an error if x is negative and y is not an exact integer or if x is 0 and y is negative or 0.
- `double sqrt(double x);`
 Computes the nonnegative square root of x . It is an error if x is negative.

Manipulating number representations.

- `double ceil(double d);`
 The smallest integral value greater than or equal to `d`.
- `double floor(double d);`
 The largest integral value less than or equal to `d`.
- `double fabs(double d);`
 The absolute value of `d`. Note: `abs()` is defined in `<stdlib.h>`.
- `double fmod(double x, double y);`
 The answer, `f`, is less than `y`, has the same sign as `x`, and `f+y*k` approximately equals `x` for some integer `k`. It may return 0 or be a run-time error if `y` is 0.
- `double frexp(double x, int* nptr);`
 Splits a nonzero x into a fractional part, f , and an exponent, n , such that $|f|$ is between 0.5 and 1.0 and $x = f \times 2^n$. The function's return value is f , and n is returned through the pointer parameter. If x is 0, both values will be 0.
- `double ldexp(double x, int n);`
 The inverse of `frexp()`; it computes and returns the value of $x \times 2^n$.
- `double modf(double x, double* nptr);`
 Splits a nonzero x into a fractional part, f , and an integer part, n , such that $|f|$ is less than 1.0 and $x = f + n$. Both f and n have the same sign as x . The function's return value is f and n is returned through the pointer parameter.

F.3.4 Input and Output

Header file. `<stdio.h>`.

Predefined streams. `stdin`, `stdout`, `stderr`.

Constants.

- EOF signifies an error or end-of-file during input.
- NULL is the zero pointer.
- FOPEN_MAX is the number of streams that can be open simultaneously (ISO C only).
- FILENAME_MAX is the maximum appropriate length for a file name (ISO C only).

Types. `FILE`, `size_t`, `fpos_t`.

Stream functions.

- `FILE* fopen(const char* filename, const char* mode);`
`int fclose(FILE* str);`
 For opening and closing programmer-defined streams.
- `int fflush(FILE* str);`
 Sends the contents of the stream buffer to the associated device. It is defined only for output streams.
- `FILE* freopen(const char* filename, const char* mode,`
`FILE* str);`
 Reopens the specified stream for the named file in the new mode.
- `int feof(FILE* str);`
 Returns `true` if an attempt has been made to read past the end of the stream `str`. Returns `false` otherwise.
- `int ferror(FILE* str);`
 Returns `true` if an error occurred while reading from or writing to the stream `str`.
- `void clearerr(FILE* str);`
 Resets any error or end-of-file indicators on stream `str`.
- `int rename(const char* oldname, const char* newname);`
 Renames the specified disk file.
- `int remove(char* filename);`
 Deletes the named file from the disk.

Input functions.

- `int fgetc(FILE* str);`
`int getc(FILE* str);`
 These functions read a single character from the stream `str`.
- `int getchar(void);`
 Reads a single character from the stream `stdin`.
- `int ungetc(int ch, FILE* str);`
 Puts a single character, `ch`, back into the stream `str`.
- `char* fgets(char* ar, int n, FILE* str);`
 Reads up to `n-1` characters from the stream `str` into the array `ar`. A newline character occurring before the `n`th input character terminates the operation and is stored in the array. A null character is stored at the end of the input.

- `char* gets(char* ar);`
Reads characters from the stream `stdin` into the array `ar` until a newline character occurs, then stores a null character at the end of the input. The newline is not stored as part of the string.
- `int fscanf(FILE* str, const char* format, ...);`
Reads input from stream `str` under the control of the format. It stores converted values in the addresses on the variable-length output list that follows the format.
- `int scanf(const char* format, ...);`
Same as `fscanf()` to stream `stdin`.
- `int sscanf(char* s, const char* format, ...);`
Same as `fscanf()` except that the input characters come from the string `s` instead of from a stream.
- `size_t fread(void* ar, size_t size, size_t count, FILE* str);`
Reads a block of data of `size` times `count` bytes from the stream `str` into array `ar`.

Output functions.

- `int fputc(int ch, FILE* str);`
`int putc(int ch, FILE* str);`
These functions write `ch` to stream `str`.
- `int putchar(int ch);`
Writes a single character, `ch`, to the stream `stdout`.
- `int fputs(const char* s, FILE* str);`
Writes `s` to stream `str`.
- `int puts(const char* s);`
Writes string `s` and a newline character to the stream `stdout`.
- `int fprintf(FILE* str, const char* format, ...);`
Writes values from the variable-length output list to the stream `str` under the control of the format.
- `int printf(const char* format, ...);`
Writes values from the variable-length output list to the stream `stdout` under the control of the format.
- `int sprintf(char* ar, const char* format, ...);`
Writes values from the variable-length output list to the array `ar` under the control of the format.
- `size_t fwrite(const void* ar, size_t size, size_t count, FILE* str);`
Writes a block of data of `size` times `count` bytes from the array `ar` into the stream `str`.

Advanced functions. The following functions are beyond the scope of this text; their prototypes are listed without comment.

- `int setvbuf(FILE* str, char* buf, int bufmode, size_t size);`
- `void setbuf(FILE* str, char* buf);`
- Buffer mode constants `BUFSIZ`, `_IOFBF`, `_IOLBF`, `_IONBF`
- `int fseek(FILE* str, long int offset, int from);`
- `long int ftell(FILE* str);`
- `void rewind(FILE* str);`
- Seek constants `SEEK_SET`, `SEEK_CUR`, `SEEK_END`
- `int fgetpos(FILE* str, fpos_t* pos);`
- `int fsetpos(FILE* str, const fpos_t* pos);`

- `void perror(const char* s);`
- `int vfprintf(FILE* str, const char* format, va_list arg);`
- `int vprintf(const char* format, va_list arg);`
- `int vsprintf(char* ar, const char* format, va_list arg);`
- `FILE* tmpfile(void);`
- `char* tmpnam(char* buf);` and constants `L_tmpnam`, `TMP_MAX`

F.3.5 Standard Library

Header file. `<stdlib.h>`.

Constants.

- `RAND_MAX`: the largest value that can be returned by `rand()`.
- `EXIT_FAILURE`: signifies unsuccessful termination when returned by `main()` or `exit()`.
- `EXIT_SUCCESS`: signifies successful termination when returned by `main()` or `exit()`.

Typedefs. `div_t` and `ldiv_t`, ISO C only, the types returned by the functions `div()` and `ldiv()`, respectively. Both are structures with two components, `quot` and `rem`, for the quotient and remainder of an integer division.

General functions.

- `int abs(int x);`
`long labs(long x);`
 These functions return the absolute value of `x`. Note: `fabs()`, for floating-point numbers, is defined in `<math.h>`.
- `div_t div(int n, int d);`
`ldiv_t ldiv(long n, long d);`
 These functions perform the integer division of `n` by `d`. The quotient and remainder are returned in a structure of type `div_t` or `ldiv_t`.
- `void srand(unsigned s);`
`int rand(void);`
 The function `srand()` is used to initialize the random-number generator and should be called before using `rand()`. Successive calls on `rand()` return pseudo-random numbers, evenly distributed over the range `0...RAND_MAX`.
- `void* bsearch(const void* key, const void* base, size_t count, size_t size, int (*compar)(const void* key, const void* value));`
 Searches the array starting at `base` for an element that matches `key`. A total of `count` elements are in the array. It uses `*compar()` to determine whether two items match. See the text for explanation.
- `int qsort(void* base, size_t count, size_t size, int (*compar)(const void* e1, const void* e2));`
 Quicksorts the elements of the array starting at `base` and continuing for `count` elements. It uses `*compar()` to compare the elements. See the text for explanation.

Allocation functions.

- `void* malloc(size_t size);`
 Dynamically allocates a memory area of `size` bytes and returns the address of the beginning of this area.

- `void* calloc(size_t count, size_t size);`
Dynamically allocates a memory area of `count` times `size` bytes. It clears all the bits in this area to 0 and returns the address of the beginning of this area.
- `void free(void* pt);`
Returns the dynamically allocated area `*pt` to the system for future reuse.
- `void* realloc(void* pt, size_t size);`
Resizes the dynamically allocated area `*pt` to `size` bytes. If this is larger than the current size and the current allocation area cannot be extended, it allocates the entire `size` bytes elsewhere and copies the information from `*pt`.

Control functions.

- `void exit(int status);`
Flushes all the buffers, closes all the streams, and returns the status code to the operating system.
- `int atexit(void (*func)(void));`
ISO C only. The function `(*func)()` is called when `exit()` is called or when `main()` returns.

String to number conversion functions.

- `double strtod(const char* str, char** p);`
`double atof(const char* str);`
The function `strtod()` converts the ASCII string `str` to a number of type `double` and returns that number. It leaves `*p` pointing at the first character in `str` that was not part of the number. The function `atof()` does the same thing but does not return a pointer to the first unconverted character. The preferred function is `strtod()`; `atof()` is deprecated in the latest version of the standard.
- `long strtol(const char* str, char** p, int b);`
The function `strtol()` converts the ASCII string `str` to a number of type `long int` expressed in base `b` and returns that number. It leaves `*p` pointing at the first character in `str` that was not part of the number. This function is preferred over both `atoi()` and `atol()`, which are deprecated in the latest version of the standard.
- `int atoi(const char* str);`
`long atol(const char* str);`
The function `atoi()` converts the ASCII string `str` to a number of type `int` expressed in base 10 and returns that number; `atol()` converts to type `long int`. The function `strtol()` is preferred over both of these, which are deprecated in the latest version of the standard.
- `unsigned long strtoul(const char* str, char** p, int b);`
Converts the ASCII string `str` to a number of type `long unsigned int` expressed in base `b` and returns that number. It leaves `*p` pointing at the first character in `str` that was not part of the number.

Advanced functions. The following functions are beyond the scope of this text; their prototypes are listed without comment.

- `void abort(void);`
- `char* getenv(const char* name);`
- `int system(const char* command);`

F.3.6 Strings

Header file. `<string.h>`.

String manipulation.

- `char* strcat(char* dest, const char* src);`
Appends the string `src` to the end of the string `dest`, overwriting its null terminator. We assume that `dest` has space for the combined string.
- `char* strncat(char* dest, const char* src, size_t n);`
This function is the same as `strcat()` except that it stops after copying `n` characters, then writes a null terminator.
- `char* strcpy(char* dest, const char* src);`
Copies the string `src` into the array `dest`. We assume that `dest` has space for the string.
- `char* strncpy(char* dest, const char* src, size_t n);`
Copies exactly `n` characters from `src` into `dest`. If fewer than `n` characters are in `src`, null characters are appended until exactly `n` have been written.
- `int strcmp(const char* p, const char* q);`
Compares string `p` to string `q` and returns a negative value if `p` is lexicographically less than `q`, 0 if they are equal, or a positive value if `p` is greater than `q`.
- `int strncmp(const char* p, const char* q, size_t n);`
This function is the same as `strcmp()` but returns after comparing at most `n` characters.
- `size_t strlen(const char* s);`
Returns the number of characters in the string `s`, excluding the null character on the end.
- `char* strchr(const char* s, int ch);`
Searches the string `s` for the first (leftmost) occurrence of the character `ch`. Returns a pointer to that occurrence if it exists; otherwise returns `NULL`.
- `char* strrchr(const char* s, int ch);`
Searches the string `s` for the last (rightmost) occurrence of the character `ch`. Returns a pointer to that occurrence if it exists; otherwise returns `NULL`.
- `char* strstr(const char* s, const char* sub);`
Searches the string `s` for the first (leftmost) occurrence of the substring `sub`. Returns a pointer to the first character of that occurrence if it exists; otherwise returns `NULL`.

Memory functions.

- `void* memchr(const void* ptr, int val, size_t len);`
Copies `val` into `len` characters starting at address `ptr`.
- `int memcmp(const void* p, const void* q, size_t n);`
Compares the first `n` characters starting at address `p` to the first `n` characters starting at `q`. Returns a negative value if `p` is lexicographically less than `q`, 0 if they are equal, or a positive value if `p` is greater than `q`.
- `void* memcpy(void* dest, const void* src, size_t n);`
Copies `n` characters from `src` into `dest` and returns the address `src`. This may not work correctly for overlapping memory regions but often is faster than `memmove()`.
- `void* memmove(void* dest, const void* src, size_t n);`
Copies `n` characters from `src` into `dest` and returns the address `src`. This works correctly for overlapping memory regions.
- `void* memset(void* ptr, int val, size_t len);`
Copies `val` into `len` characters starting at address `ptr`.

Advanced functions. The following functions are beyond the scope of this text; their prototypes are listed without comment:

- `int strcoll(const char* s1, const char* s2);`
- `size_t strcspn(const char* s, const char* set);`

- `char* strerror(int errnum);`
- `char* strpbrk(const char* s, const char* set);`
- `size_t strspn(const char* s, const char* set);`
- `char* strtok(char* s, const char* set);`
- `size_t strxfrm(char* d, const char* s, size_t len);`

F.3.7 Time and Date

Header file. `<time.h>`.

Constants. `CLOCKS_PER_SEC` is the number of clock “ticks” per second of the clock used to record process time.

Types.

- `time_t`;
The integer type used to represent times on the local system.
- `clock_t`;
The arithmetic type used to represent the process time on the local system.
- `struct tm`;
A structured representation of the time containing the following fields, all of type `int`: `tm_sec` (seconds after the minute), `tm_min` (minutes after the hour), `tm_hour` (hours since midnight, 0–23), `tm_mday` (day of the month, 1–31), `tm_mon` (month since January, 0–11), `tm_year` (years since 1900), `tm_wday` (day since Sunday, 0–6), `tm_yday` (day since January 1, 0–365), `tm_isdst` (daylight savings time flag, >0 if DST is in effect, 0 if not, <0 if unknown).

Functions.

- `clock_t clock();`
Returns an approximation to the processor time used by the current process, usually expressed in microseconds.
- `time_t time(time_t* tptr);`
Reads the system clock and returns the time as an integer encoding of type `time_t`. Returns the same value through the pointer parameter.
- `char* ctime(const time_t* tptr);`
`char* asctime(const struct tm* tptr);`
These functions return a pointer to a string containing a printable form of the date and time: "Sat Sep 14 13:12:27 1999\n". The argument to `ctime()` is a pointer to a `time_t` value such as that returned by `time()`. The argument to `asctime()` is a pointer to a structured calendar time such as that returned by `localtime()` or `gmtime()`.
- `struct tm* gmtime(const time_t* tp);`
`struct tm* localtime(const time_t* tp);`
These functions convert a time represented as a `time_t` value to a structured representation. The `gmtime()` returns Greenwich mean time; the `localtime()` converts to local time, taking into account the time zone and Daylight Savings Time.
- `time_t mktime(struct tm* tp);`
Converts a time from the `struct tm` representation to the integer `time_t` representation.
- `double difftime(time_t t1, time_t t2);`
Returns the result of `t1-t2` in seconds as a value of type `double`.

- `size_t strftime(char* s, size_t max,
const char* format, const struct tm* tp);`
`size_t wcsftime(w_char* s, size_t max,
const w_char* format, const struct tm* tp);`

The function `strftime()` formats a single date and time value specified by `tp`, storing up to `maxsize` characters into the array `s` under control of the string `format`. The function `wcsftime()` does the same thing with wide characters.

F.3.8 Variable-Length Argument Lists

This library, known as the *vararg* facility, permits programmers to define functions with variable-length argument lists. This is an advanced feature of C and beyond the scope of this text. The list of functions is included here because this facility was used to define `say()` and `fatal()`.

Header file. `<stdarg.h>`.

Type. `va_list`.

Functions. `va_start`, `va_arg`, and `va_end`.

F.4 Libraries Not Explored

Each of the remaining libraries is named and the names of functions and constants in them are listed without prototypes or explanation. This list can serve as a starting point for further exploration of C.

Errors. Header file: `<errno.h>`. Constants: `EDOM` and `ERANGE`.
Variable: `errno`.

Nonlocal jumps. Header file: `<setjmp.h>`. Type: `jmpbuf`.
Functions: `setjmp` and `longjmp`.

Signal handling. Header file: `<signal.h>`. Type: `sig_atomic_t`. Constants: `SIG_DFL`, `SIG_ERR`, `SIG_IGN`, `SIGABRT`, `SIGFPE`, `SIGILL`, `SIGINT`, `SIGSEGV`, and `SIGTERM`. Functions: `signal`, `raise`.

Control. Header file: `<assert.h>`. Constant: `NDEBUG`. Function: `assert`.

Localization. Header file: `<locale.h>`. Constants: `LC_ALL`, `LC_TIME`, `LC_CTYPE`, `LC_MONETARY`, `LC_NUMERIC`, `LC_COLLATE`, and `NULL`. Type: `struct lconv`. Functions: `localeconv` and `setlocale`.

Wide-character handling. Header file: `<wctype.h>`. Functions: `iswctype`, `towctrans`, `WEOF`, `wint_t`, `wctrans`, `wctrans_t`, `wctype`, and `wctype_t`. In addition, this library contains wide analogs of all the functions in the `ctype` library, all with a `w` as the third letter of the name: `iswupper`, `towlower`, and so on.

Extended multibyte to wide-character conversion. Header file: `<wchar.h>`. Functions: `btowc`, `mbrlen`, `mbrtowc`, `mbstate_t`, `wcrtomb`, `mbsinit`, `mbsrtowcs`, `wcsrtombs`, `wcstod`, `wcstol`, `wcstoul`, and `wctob`.

Wide-string handling. Header file: `<wchar.h>`. Functions: `wscat`, `wcschr`, `wscmp`, `wscoll`, `wscpy`, `wscspn`, `wcerror`, `wcslon`, `wcsncat`, `wcsncmp`, `wcsncpy`, `wcspbrk`, `wcsrchr`, `wcsspn`, `wcsstr`, `wcstok`, `wcsxfrm`, `wmemchr`, `wmemcmp`, `wmemcpy`, `wmemmove`, and `wmemset`.

Wide-character input and output. Header file: `<wchar.h>`. Functions: `fwprintf`, `fwscanf`, `wprintf`, `wscanf`, `swprintf`, `swscanf`, `vfwprintf`, `vwprintf`, `vwsprintf`, `fgetwc`, `fgetws`, `fputwc`, `fputws`, `getwc`, `getwchar`, `putwc`, `putwchar`, and `ungetwc`.