Ch 10.3: Convolutional Neural Nets

Lecture 31 - CMSE 381

Prof. Guanqun Cao

Michigan State University
::
Dept of Computational Mathematics, Science & Engineering

Monday Nov 17, 2025

Announcements

Last time:

- Multilayer NN
- pyTorch

This lecture:

- CNNs

Final countdown:

- Exam 3 is 11/24
- Project is due 12/5

21	F	10/24	Polynomial & Step Functions	7.1-7.2	HW #5 Due Sun 10/26
22	M	10/27	Step Functions; Basis functions; Start Splines	7.2-7.4	
23	W	10/29	Regression Splines	7.4	
24	F	10/31	Decision Trees	8.1	HW #6 Due Sun 11/2
25	M	11/3	Random Forests	8.2.1, 8.2.2	
26	W	11/5	Maximal Margin Classifier	9.1	
27	F	11/7	SVC	9.2	HW #7 Due Sun 11/9
28	M	11/10	SVM	9.3, 9.4	
29	W	11/12	Single Layer NN	10.1	
30	F	11/13	Multi Layer NN	10.2	HW #8 Due Sun 11/16
31	M	11/17	CNN	10.3	
32	W	11/19	Unsupervised learning / clustering	12.1, 12.4	
33	F	11/21	***Review***		HW #9 Due Sun 11/23
	M	11/24	**Midterm #3**		
	W	11/26	Virtual: Project Office Hours		
	F	11/28	Thanksgiving		
	M	12/1	Virtual: Project Office Hours		
	W	12/3	Virtual: Project Office Hours		
	F	12/5			**Project Due**
	M	12/8			
	W	12/10			
	F	12/12	**No final exam**		**Honors Project Due**

Section 1

Last time: Neural Nets

MNIST





- Goal: Build a model to classify images into their correct digit class
- Each image has $p = 28 \cdot 28 = 784$ pixels
- Each pixel is grayscale value in [0,255]
- Data converted into column order
- Output represented by one-hot vector $Y = (Y_0, Y_1, \cdots, Y_9)$
- 60K training images, 10K test images

Neural network architecture for MNIST



$$
\begin{aligned}
A_k^{(1)} &= h_k^{(1)}(X) \\
&= g(w_{k0}^{(1)} + \textstyle\sum_{j=1}^{p} w_{kj}^{(1)} X_j)
\end{aligned}
$$

$$
\begin{aligned}
A_\ell^{(2)} &= h_\ell^{(2)}(X) \\
&= g(w_{\ell 0}^{(2)} + \textstyle\sum_{k=1}^{K_1} w_{\ell k}^{(2)} A_k^{(1)})
\end{aligned}
$$

$$
\begin{aligned}
Z_m &= \beta_{m0} + \textstyle\sum_{\ell=1}^{K_2} \beta_{m\ell} h_\ell^{(2)}(X) \\
&= \beta_{m0} + \textstyle\sum_{\ell=1}^{K_2} \beta_{m\ell} A_\ell^{(2)},
\end{aligned}
$$

$$
f_m(X) = \Pr(Y = m|X) = \frac{e^{Z_m}}{\sum_{\ell=0}^{9} e^{Z_\ell}},
$$

- Two hidden layers.
- Softmax for classification output
- We used L_1 has 128 units; L_2 has 64
- 10 output variables due to class labeling
- Result is we are training approx 110K weights

Test your understanding: PollEv

MNIST learning







Section 2

Convolutional Neural Network

Last time: Flattening the image

$$\begin{pmatrix} 1 & 1 & 0 \\ 4 & 2 & 1 \\ 0 & 2 & 1 \end{pmatrix} \longrightarrow \begin{pmatrix} 1 \\ 1 \\ 0 \\ 4 \\ 2 \\ 1 \\ 0 \\ 2 \\ 1 \end{pmatrix}$$

- Just ignore the fact that we have a picture
- Loses a lot of the structure that we might want for more complicated
- Answer is CNNs, which take in image data and build a neural net that specifically tracks that structure

Example data set: CIFAR100 Data



- 60,000 images: 50K training, 10K test
- Labels with 20 super classes (e.g. aquatic mammals)
- 5 classes per super class (beaver, dolphin, otter, seal, whale)
- Images are 32x32

Image channel data

- 3 eight bit numbers per pixel (red, green, blue)
- Numbers are organized in a *feature map* , which is 3 dimensional array
- First two directions are spatial (32x32)
- Third is the *channel* axis representing teh three colors



How does your brain do it? The visual hierarchy



Mauro Manassi, Bilge Sayim, Michael H. Herzog; When crowding of crowding leads to uncrowding. Journal of Vision 2013;13(13):10. https://doi.org/10.1167/13.13.10.

CNNs

- really similar to the human visual hierarchy
- earlier layers Identify low level features on the input image such as small edges, patches of color, etc
- Low level features combined into higher-level features (parts of ears, eyes, etc) in later layers
- Does this using special types of hidden layers: *convolution* layers and *pooling layers*



Convolution layer

Convolution Filter

Original Image:

$$\begin{bmatrix} a & b & c \\ d & e & f \\ g & h & i \\ j & k & l \end{bmatrix}$$

Convolution filter:

$$\begin{bmatrix} \alpha & \beta \\ \gamma & \delta \end{bmatrix}$$

Convolved Image

$$\begin{bmatrix} a\alpha + b\beta + d\gamma + e\delta & b\alpha + c\beta + e\gamma + f\delta \\ d\alpha + e\beta + g\gamma + h\delta & e\alpha + f\beta + h\gamma + i\delta \\ g\alpha + h\beta + j\gamma + k\delta & h\alpha + i\beta + k\gamma + l\delta \end{bmatrix}$$

Note we are just doing inner product here, which measure(ish) similar

Convolution Filter Example



Filter:

$$\begin{bmatrix} 0 & 1 \\ 0 & 1 \end{bmatrix}$$

- $\begin{bmatrix} 1 & 3 \\ 0 & 3 \\ 1 & 3 \end{bmatrix}$
- Convolved image highlights regions that resemble the convolution filter.
- Conv or filtering is traditional signal processing, but in CNN the filter is learned (mentioned again later)
- Note that the result is smaller than original

Same example, different filter

What is the convolved image?

Filter:

$$\begin{bmatrix} 1 & 1 \\ 0 & 0 \end{bmatrix}$$

- $\begin{bmatrix} 4 & 3 \\ 2 & 1 \\ 3 & 2 \end{bmatrix}$

Convolution filter: Bigger example



- 192x179 image of tiger
- Convolution filters are 15x15 images with mostly zero (black) narrow strip of ones (white)
- Highlights areas of the tiger that resemble the filter

Convolution layer



- Image is in color, so 3 channels
- This means the convolution filter will have three channels, one per color, each of dimension 3x3
- Results are summed to form a 2-dimensional output. Color is "forgotton" at this point
- K different filters here means K 2-d output maps, which can then be treated as channels
- Padding to make the updated image the same size

More notes on convolution

- Filters idea from image processing
- Novelty in DL is that the choice of filters are learned
- Filter weights: one hidden unit per pixel in convolved image; but more constrained than that
- same weight used for all patches for the images and channels of only m-by-m weights per filter, where m is patch size.
- Applying ReLU to convolved image. Sometimes viewed as separate layer in CNN, and then called a detector layer.

Pooling layers

- Condense a large image into a smaller summary image
- Lots of options, but max pooling is common:
- For each 2x2 non-overlapping block of pixels, get a single new pixel with the maximum value from the block
- Provides location invariance: so long as large value in one of the four pixels, the whole block registers as a large value

$$\text{Max pool} \begin{bmatrix} 1 & 2 & 5 & 3 \\ 3 & 0 & 1 & 2 \\ 2 & 1 & 3 & 4 \\ 1 & 1 & 2 & 0 \end{bmatrix} \rightarrow \begin{bmatrix} 3 & 5 \\ 2 & 4 \end{bmatrix}$$

Putting it together to make a CNN



- Start with three channels
- get a new channel at first hidden layer for each filter. Padding to keep the same size
- Next is max pool layer,
- convolve & pool several more times

- Since size of image decreased, we increase number of filters in the next convolve layer to compensate
- Flattened, then fed into 1 or more fully-connected layers
- Last is softmax activation for the 100 classes

https://poloclub.github.io/cnn-explainer/

Coding

TL;DR

Feed Forward Neural Net



$$A_k = h_k(X) = g(w_{k0} + \sum_{j=1}^{p} w_{kj} X_j),$$

- Combines input data using learned weights
- Linear combo of those to get output
- Sometimes softmax to get probability of classification

CNN



- Specialized NN
- Gets next layer via
  - Convolution layer
  - Pooling Layer
  - Fully connected layer

Next time

21	F	10/24	Polynomial & Step Functions	7.1-7.2	HW #5 Due Sun 10/26
22	M	10/27	Step Functions; Basis functions; Start Splines	7.2-7.4	
23	W	10/29	Regression Splines	7.4	
24	F	10/31	Decision Trees	8.1	HW #6 Due Sun 11/2
25	M	11/3	Random Forests	8.2.1, 8.2.2	
26	W	11/5	Maximal Margin Classifier	9.1	
27	F	11/7	SVC	9.2	HW #7 Due Sun 11/9
28	M	11/10	SVM	9.3, 9.4	
29	W	11/12	Single Layer NN	10.1	
30	F	11/13	Multi Layer NN	10.2	HW #8 Due Sun 11/16
31	M	11/17	CNN	10.3	
32	W	11/19	Unsupervised learning / clustering	12.1, 12.4	
33	F	11/21	***Review***		HW #9 Due Sun 11/23
	M	11/24	**Midterm #3**		
	W	11/26	Virtual: Project Office Hours		
	F	11/28	Thanksgiving		
	M	12/1	Virtual: Project Office Hours		
	W	12/3	Virtual: Project Office Hours		
	F	12/5			**Project Due**
	M	12/8			
	W	12/10			
	F	12/12	**No final exam**		**Honors Project Due**