```
<!DOCTYPE html>
<html>
<head>
  <title>Online Food Ordering Website</title>

  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f5f5f5;
      margin: 0;
      padding: 0;
      text-align: center;
    }

    header {
      background-color: orange;
      color: white;
      padding: 20px;
    }

    h1 {
      margin: 0;
    }

    .food-container {
      display: flex;
```

```
    justify-content: center;
    flex-wrap: wrap;
    gap: 20px;
    margin: 30px;
}

.food {
    background-color: white;
    padding: 20px;
    width: 200px;
    border-radius: 10px;
    box-shadow: 0 0 10px gray;
}

.food img {
    width: 150px;
    height: 120px;
    border-radius: 10px;
}

button {
    background-color: green;
    color: white;
    border: none;
    padding: 10px 15px;
    cursor: pointer;
```

```
      border-radius: 5px;
    }

    button:hover {
      background-color: darkgreen;
    }

    #cart {
      background-color: white;
      margin: 20px;
      padding: 20px;
      border-radius: 10px;
    }

    footer {
      background-color: black;
      color: white;
      padding: 15px;
    }
  </style>
</head>

<body>

  <header>
    <h1>Online Food Ordering</h1>
```

```
  <p>Delicious Food at Your Doorstep!</p>
</header>

<h2>Our Food Menu</h2>

<div class="food-container">

  <div class="food">
    <img src="https://placehold.co/150x120?text=Pizza"
      alt="Pizza">
    <h3>Pizza</h3>
    <p>Price: ₹150</p>
    <button onclick="addToCart('Pizza', 150)">
      Add to Cart
    </button>
  </div>

  <div class="food">
    <img src="https://placehold.co/150x120?text=Burger"
      alt="Burger">
    <h3>Burger</h3>
    <p>Price: ₹100</p>
    <button onclick="addToCart('Burger', 100)">
      Add to Cart
    </button>
  </div>
```

```
    <div class="food">
      <img src="https://placehold.co/150x120?text=Biryani"
          alt="Biryani">
      <h3>Biryani</h3>
      <p>Price: ₹200</p>
      <button onclick="addToCart('Biryani', 200)">
        Add to Cart
      </button>
    </div>

</div>

<div id="cart">
    <h2>Shopping Cart</h2>

    <ul id="cart-items"></ul>

    <h3>Total: ₹<span id="total">0</span></h3>

    <button onclick="placeOrder()">Place Order</button>
</div>

<footer>
    <p>Online Food Ordering Website Project</p>
</footer>
```

```
<script>
  let total = 0;

  function addToCart(name, price) {
    let item = document.createElement("li");

    item.textContent = name + " - ₹" + price;

    document.getElementById("cart-items")
      .appendChild(item);

    total = total + price;

    document.getElementById("total")
      .textContent = total;
  }

  function placeOrder() {
    if (total === 0) {
      alert("Please add food items to your cart!");
    } else {
      alert("Your order has been placed successfully!");
      document.getElementById("cart-items")
        .innerHTML = "";
```

```
            total = 0;


            document.getElementById("total")
               .textContent = total;
         }
      }
   </script>

</body>
</html>
```