

Algorithms Level 4



26+ Years
of Experience

PROGRAMMING ADVICES

LEARN THE
RIGHT WAY

Mohammed Abu-Hadhoud

MBA, PMOC, PgMP®, PMP®, PMI-RMP®, CM, ITIL®, MCPD, MCSD



حقوق النشر محفوظة، أسعار الكورسات في المنصة هي أسعار
رمزية جدا، ارجو عدم نشر هذه الوثيقة لان نشرها سيمنعنا من
الاستمرار في تقديم العلم للآخرين

ارجو عدم استخدام هذه الوثيقة من غير وجه حق لأنك ستحرم الاف
الناس من التعلم

ProgrammingAdVICES.com



Problem # 7/4 Solution Using C++

```
#include <iostream>
using namespace std;

short DayOfWeekOrder(short Day, short Month, short Year)
{
    short a, y, m;
    a = (14 - Month) / 12;
    y = Year - a;
    m = Month + (12 * a) - 2;
    // Gregorian:
    //0:sun, 1:Mon, 2:Tue...etc
    return (Day + y + (y / 4) - (y / 100) + (y / 400) + ((31 * m)
/ 12)) % 7;
}

string DayShortName(short DayOfWeekOrder)
{
    string arrDayNames[] = {
"Sun", "Mon", "Tue", "Wed", "Thu", "Fri", "Sat" };

    return arrDayNames[DayOfWeekOrder];
}

short ReadDay()
{
    short Day;
    cout << "\nPlease enter a Day? ";
    cin >> Day;
    return Day;
}

short ReadMonth()
{
    short Month;
    cout << "\nPlease enter a Month? ";
    cin >> Month;
    return Month;
}
```



Problem # 7/4 Solution Using C++

```
short ReadYear()
{
    short Year;
    cout << "\nPlease enter a year? ";
    cin >> Year;
    return Year;
}

int main()
{
    short Year = ReadYear();
    short Month = ReadMonth();
    short Day = ReadDay();

    cout << "\nDate      : " << Day << "/" << Month << "/" << Year;
    cout << "\nDay Order : " << DayOfWeekOrder(Day, Month, Year);
    cout << "\nDay Name  : " << DayShortName(DayOfWeekOrder(Day,
Month, Year));

    system("pause>0");
    return 0;
}
```