



✓ **Congratulations! You passed!**  
TO PASS 80% or higher

Keep Learning

GRADE  
80%

## Detection Algorithms

LATEST SUBMISSION GRADE

80%

1. You are building a 3-class object classification and localization algorithm. The classes are: pedestrian ( $c=1$ ), car ( $c=2$ ), motorcycle ( $c=3$ ). What should  $y$  be for the image below? Remember that “?” means “don't care”, which means that the neural network loss function won't care what the neural network gives for that component of the output. Recall  $y = [p_c, b_x, b_y, b_h, b_w, c_1, c_2, c_3]$ .

1 / 1 point




- ☐  $y = [?, ?, ?, ?, ?, ?, ?, ?]$
- ☐  $y = [0, ?, ?, ?, ?, 0, 0, 0]$
- ☐  $y = [1, ?, ?, ?, ?, ?, ?, ?]$
- ☒  $y = [0, ?, ?, ?, ?, ?, ?, ?]$
- ☐  $y = [1, ?, ?, ?, ?, 0, 0, 0]$

✓ **Correct**  
Correct.

2. You are working on a factory automation task. Your system will see a can of soft-drink coming down a conveyor belt, and you want it to take a picture and decide whether (i) there is a soft-drink can in the image, and if so (ii) its bounding box. Since the soft-drink can is round, the bounding box is always square, and the soft drink can always appear as the same size in the image. There is at most one soft drink can in each image. Here're some typical images in your training set:

0 / 1 point



What is the most appropriate set of output units for your neural network?

- ☐ Logistic unit (for classifying if there is a soft-drink can in the image)
- ☒ Logistic unit,  $b_x, b_y, b_h$  (since  $b_w = b_h$ )
- ☐ Logistic unit,  $b_x$  and  $b_y$

☐ Logistic unit,  $b_x, b_y, b_h, b_w$

**✗ Incorrect**

Do you really need  $b_h$ ? given that the bounding boxes will all be the same size.

3. If you build a neural network that inputs a picture of a person's face and outputs  $N$  landmarks on the face (assume the input image always contains exactly one face), how many output units will the network have?

1 / 1 point

- ☐  $3N$
- ☐  $N$
- ☐  $N^2$
- ☒  $2N$

**✓ Correct**

Correct

4. When training one of the object detection systems described in lecture, you need a training set that contains many pictures of the object(s) you wish to detect. However, bounding boxes do not need to be provided in the training set, since the algorithm can learn to detect the objects by itself.

1 / 1 point


- ☒ False
- ☐ True

**✓ Correct**

Correct, you need bounding boxes in the training set. Your loss function should try to match the predictions for the bounding boxes to the true bounding boxes from the training set.

5. What is the IoU between these two boxes? The upper-left box is  $2 \times 2$ , and the lower-right box is  $2 \times 3$ . The overlapping region is  $1 \times 1$ .

1 / 1 point



- ☐  $\frac{1}{6}$
- ☐  $\frac{1}{10}$
- ☐ None of the above
- ☒  $\frac{1}{9}$

**✓ Correct**

Correct, the left box's area is 4 while the right box's is 6. Their intersection's area is 1. So their union's area is  $4 + 6 - 1 = 9$  which leads to an intersection over union of  $1/9$ .

6. Suppose you run non-max suppression on the predicted boxes above. The parameters you use for non-max suppression are that boxes with probability  $\leq 0.4$  are discarded, and the IoU threshold for deciding if two boxes overlap is 0.5. How many boxes will remain after non-max suppression?

1 / 1 point





- ☐ 7
- ☐ 6
- ☐ 3
- ☐ 4
- ☒ 5

✓ **Correct**  
Correct!

7. Suppose you are using YOLO on a  $19 \times 19$  grid, on a detection problem with 20 classes, and with 5 anchor boxes. During training, for each image you will need to construct an output volume  $y$  as the target value for the neural network; this corresponds to the last layer of the neural network. ( $y$  may include some "?", or "don't cares"). What is the dimension of this output volume?

0 / 1 point

- ☒  $19 \times 19 \times (25 \times 20)$
- ☐  $19 \times 19 \times (5 \times 20)$
- ☐  $19 \times 19 \times (20 \times 25)$
- ☐  $19 \times 19 \times (5 \times 25)$

✗ **Incorrect**  
How many anchor boxes are you using? How is one box defined?

8. What is Semantic Segmentation?

1 / 1 point

- ☐ Locating objects in an image belonging to different classes by drawing bounding boxes around them.
- ☐ Locating an object in an image belonging to a certain class by drawing a bounding box around it.
- ☒ Locating objects in an image by predicting each pixel as to which class it belongs to.

✓ **Correct**

9. Using the concept of Transpose Convolution, fill in the values of **X**, **Y** and **Z** below.

1 / 1 point

(padding = 1, stride = 2)

Input:  $2 \times 2$

1	2
3	4

Filter:  $3 \times 3$

1	0	-1
1	0	-1

1	0	-1
---	---	----

Result: 6x6

	0	1	0	-2	
	0	<b>X</b>	0	<b>Y</b>	
	0	1	0	<b>Z</b>	
	0	1	0	-4	

- ☒ X = 2, Y = -6, Z = -4
- ☐ X = -2, Y = -6, Z = -4
- ☐ X = 2, Y = 6, Z = 4
- ☐ X = 2, Y = -6, Z = 4

✓ Correct

10. Suppose your input to an U-Net architecture is  $h \times w \times 3$ , where 3 denotes your number of channels (RGB). What will be the dimension of your output ?

1 / 1 point

- ☐ D:  $h \times w \times n$ , where  $n$  = number of of output channels
- ☒  $h \times w \times n$ , where  $n$  = number of output classes
- ☐  $h \times w \times n$ , where  $n$  = number of input channels
- ☐  $h \times w \times n$ , where  $n$  = number of filters used in the algorithm

✓ Correct