



Simulated Multiple Reference Training Improves Low-Resource Machine Translation

Huda Khayrallah, Brian Thompson, Matt Post & Philipp Koehn | Johns Hopkins University





use a target language *paraphraser* in the training objective to overcome data sparsity in *low-resource* settings

Questions? Hiring?
huda@jhu.edu

src: La tortuga ganó contra la liebre
ref: The turtle beat the hare

$$\begin{aligned} \text{NLL} &= - \sum_{v \in \mathcal{V}} \left[\mathbb{1}\{y_i = v\} \times \log p_{\text{MT}}(y_i = v \mid x; y_{j < i}) \right] \\ &\quad \text{Gold Target} \qquad \text{MT Model output distribution} \\ \text{SMRT} &= - \sum_{v \in \mathcal{V}} \left[p_{\text{para}}(y'_i = v \mid y; y'_{j < i}) \times \log p_{\text{MT}}(y'_i = v \mid x; y'_{j < i}) \right] \\ &\quad \text{Paraphraser output distribution} \qquad \text{MT Model output distribution} \end{aligned}$$



- Transformer models in fairseq (Ott et al., 2019)
- Global Voices corpora (Tiedemann, 2012)
- Translating to English
- English Paraphraser trained on ParaBank2 (Hu et al., 19)
- Use SMRT w/ 50% probability, NLL otherwise
- 4k SentencePiece vocab (Kudo & Richardson 2018)
- Code, Paper & more: data.statmt.org/smart