

Maximum Matching via Maximal Matching Queries

Christian Konrad, **Kheeran K. Naidu** & Arun Steward

University of Bristol, UK

{christian.konrad,kheeran.naidu,cw18903}@bristol.ac.uk

- 1 Introduction
- 2 Algorithm
- 3 Lower Bounds
- 4 Conclusion

1 Introduction


2 Algorithm

3 Lower Bounds

4 Conclusion

Preliminaries

In this talk, we consider bipartite graphs $G = (A, B, E)$.



Matchings


A matching M is a subset of vertex-disjoint edges of a graph.

- **Maximal:** Every edge $e \in E \setminus M$ is incident to M .
- **Maximum:** Largest size, $\mu(G)$.
- Maximal matchings are 0.5-approximations of maximum matchings.

Edge Query Model

Algorithm's Goal


Return a **large matching** of the bipartite input graph $G = (A, B, E)$ using only **deterministic edge queries** to a **maximal matching oracle**.



Motivation

Computing a maximal matching is **easy** in various computational models such as **data streaming** and Massively Parallel Computation.

Edge Query Model and Data Streaming



As long as Q can be **specified in $\tilde{O}(n)$ space**, each round can be implemented in **one pass** of the stream using **semi-streaming space**.

Known Algorithms

- 1 0.6-approximation **MBM** in 3-passes [KT17] (see also [KMM12, FKM⁺05]) – state-of-the-art is 0.611-approximation [FS22].
- 2 $(1 - \epsilon)$ -approximation **MBM** in $O(\frac{1}{\epsilon^2})$ -passes [ALT21] – current state-of-the-art.

Our Results

Algorithm

0.625-approximation algorithm in **3-rounds** of the deterministic edge-query model.

Implies a **3-pass semi-streaming** algorithm for **MBM** (state-of-the-art – improving on 0.611 [FS22]).

Lower Bounds


There **does not exist** a deterministic algorithm for **MM** (even for **MBM**) in the edge query model that achieves a better than

- 1 0.5-approximation in **1 round**,
- 2 $(0.5 + o(1))$ -approximation in **2 rounds**, and
- 3 $(0.625 + o(1))$ -approximation in **3 rounds**.

Algorithm is optimal!

Previous Related Work

Vertex Query Model ([bKK20])



# Rounds	Vertex Query	Edge Query
1	0.5	0.5
2	0.5	$0.5 + o(1)$
3	0.6	$0.625 + o(1)$

1 Introduction

2 Algorithm

3 Lower Bounds

4 Conclusion


Algorithmic Idea

First Round

Find a maximal matching M in G by querying the complete graph $Q = A \times B$.

Subsequent Rounds



Find vertex-disjoint augmenting paths. **(How?)**



Finding length-3 augmenting paths

Simple Strategy

- 1 Find left wings
- 2 Extend with right wings




- $|M| = 0.5 \cdot \mu(G)$
- 0.625-approximation
- **Not hard!**

- $|M| = 0.6 \cdot \mu(G)$
- 0.6-approximation
- **Hard instance!**


Finding length-3 & length-5 augmenting paths

Our Strategy

- 1 Find left and right wings
- 2 Extend paths to either length-3 or length-5 augmenting paths



- $|M| = 0.6 \cdot \mu(G)$
- 0.7-approximation
- **Not hard anymore!**



- $|M| = 0.5 \cdot \mu(G)$
- 0.625-approximation
- **Hard instance!**

Our Analysis

Main Lemma

Let $|M| = (0.5 + \epsilon) \cdot \mu(G)$ for $\epsilon \geq 0$, then our strategy finds

$$(0.125 - \frac{3}{4}\epsilon) \cdot \mu(G)$$

vertex-disjoint augmenting paths and the large matching found is of size

$$(0.625 + \frac{\epsilon}{4}) \cdot \mu(G).$$



This is tight for our algorithm.

Semi-Streaming

Using **GREEDY** this immediately gives a **3-pass semi-streaming** algorithm with the same guarantees.

- 1 Introduction
- 2 Algorithm
- 3 Lower Bounds**
- 4 Conclusion

Lower Bound Idea



Observation


The algorithm learns about **edges** M and **non-edges** N of G .

Main Idea

- Find a hard instance for any sequence of queries $Q_1, Q_2 \dots$
- For any query Q_i , the information committed is a subset of \tilde{M}_i and \tilde{N}_i (up to isomorphisms)


One, Two & Three Query Rounds

One Round




0.5
approx LB

Two Rounds




$0.5 + o(1)$
approx LB

Three Rounds




(more involved)


Three Round Proof Sketch I



Part A




Part B




Three Round Proof Sketch II

Part A



$0.625 + o(1)$
approx LB

Part B



$0.625 + o(1)$
approx LB

Summary

Lower Bounds

There **does not exist** a deterministic algorithm for **MM** (even for **MBM**) in the edge query model that achieves a better than

- ① 0.5-approximation in **1 round**,
- ② $(0.5 + o(1))$ -approximation in **2 rounds**, and
- ③ $(0.625 + o(1))$ -approximation in **3 rounds**.

Algorithm

0.625 -approximation algorithm in **3-rounds** of the deterministic edge-query model.

- 1 Introduction
- 2 Algorithm
- 3 Lower Bounds
- 4 Conclusion**

Open Questions

Randomisation

Do randomised query algorithms allow us to improve on our results?

Adaptivity

Can we obtain better query algorithms if we allow multiple non-adaptive queries per round?

Semi-Streaming

Is there a 3-pass semi-streaming algorithms for **MBM** that improves on our 0.625-approximation algorithm?

Thank You!

References I



Sepehr Assadi, S. Cliff Liu, and Robert E. Tarjan, *An auction algorithm for bipartite matching in streaming and massively parallel computation models*, 4th Symposium on Simplicity in Algorithms, SOSA 2021, Virtual Conference, January 11-12, 2021 (Hung Viet Le and Valerie King, eds.), SIAM, 2021, pp. 165–171.



Lidiya Khalidah binti Khalil and Christian Konrad, *Constructing large matchings via query access to a maximal matching oracle*, 40th IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science, FSTTCS 2020, December 14-18, 2020, BITS Pilani, K K Birla Goa Campus, Goa, India (Virtual Conference) (Nitin Saxena and Sunil Simon, eds.), LIPIcs, vol. 182, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020, pp. 26:1–26:15.

References II



Joan Feigenbaum, Sampath Kannan, Andrew McGregor, Siddharth Suri, and Jian Zhang, *On graph problems in a semi-streaming model*, Theor. Comput. Sci. **348** (2005), no. 2-3, 207–216.



Moran Feldman and Ariel Szarf, *Maximum matching sans maximal matching: A new approach for finding maximum matchings in the data stream model*, Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, APPROX/RANDOM 2022, September 19-21, 2022, University of Illinois, Urbana-Champaign, USA (Virtual Conference) (Amit Chakrabarti and Chaitanya Swamy, eds.), LIPIcs, vol. 245, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2022, pp. 33:1–33:24.

References III



Christian Konrad, Frédéric Magniez, and Claire Mathieu, *Maximum matching in semi-streaming with few passes*, Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques - 15th International Workshop, APPROX 2012, and 16th International Workshop, RANDOM 2012, Cambridge, MA, USA, August 15-17, 2012. Proceedings (Anupam Gupta, Klaus Jansen, José D. P. Rolim, and Rocco A. Servedio, eds.), Lecture Notes in Computer Science, vol. 7408, Springer, 2012, pp. 231–242.



Sagar Kale and Sumedh Tirodkar, *Maximum matching in two, three, and a few more passes over graph streams*, Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, APPROX/RANDOM 2017, August 16-18, 2017, Berkeley, CA, USA (Klaus Jansen, José D. P. Rolim, David Williamson, and Santosh S. Vempala, eds.), LIPIcs, vol. 81, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2017, pp. 15:1–15:21.