

```
~ $ aws dynamodb wizard new-table
Wizard successfully created DynamoDB Table:
Table name: Capacitycapacity
Primary partition key: pk (N)
Primary sort key: int (N)
```

Steps to create table is equivalent to running the following sample AWS CLI commands:

```
aws dynamodb create-table \
--table-name 'Capacitycapacity' \
--attribute-definitions \
  'AttributeName=pk,AttributeType=N' \
  'AttributeName=int,AttributeType=N' \
--key-schema \
  'AttributeName=pk,KeyType=HASH' \
  'AttributeName=int,KeyType=RANGE' \
--provisioned-throughput \
  'ReadCapacityUnits=5,WriteCapacityUnits=5'
```

```
~ $ aws dynamodb delete-table --table-name Capacitycapacity
{
  "TableDescription": {
    "TableName": "Capacitycapacity",
    "TableStatus": "DELETING",
    "ProvisionedThroughput": {
      "NumberOfDecreasesToday": 0,
```

Feedback

© 2025 Amazon Web Ser

```
    "TableName": "Capacitycapacity",
    "TableStatus": "DELETING",
    "ProvisionedThroughput": {
      "NumberOfDecreasesToday": 0,
      "ReadCapacityUnits": 5,
      "WriteCapacityUnits": 5
    },
    "TableSizeBytes": 0,
    "ItemCount": 0,
    "TableArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Capacitycapacity",
    "TableId": "fbbf864b-b670-45e8-8b8c-097faa7714d1",
    "DeletionProtectionEnabled": false
  }
}
~ $ aws dynamodb list-tables
{
  "TableNames": [
    "EmployeeSpet",
    "Students"
  ]
}
~ $ aws dynamodb describe-table --table-name Students
{
  "Table": {
    "AttributeDefinitions": [
      {
        "AttributeName": "StudentId",
        "AttributeType": "S"
```

```

    "AttributeDefinitions": [
      {
        "AttributeName": "StudentId",
        "AttributeType": "S"
      }
    ],
    "TableName": "Students",
    "KeySchema": [
      {
        "AttributeName": "StudentId",
        "KeyType": "HASH"
      }
    ],
    "TableStatus": "ACTIVE",
    "CreationDateTime": "2025-09-05T07:47:27.015000+00:00",
    "ProvisionedThroughput": {
      "NumberOfDecreasesToday": 0,
      "ReadCapacityUnits": 0,
      "WriteCapacityUnits": 0
    },
    "TableSizeBytes": 0,
    "ItemCount": 0,
    "TableArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Students",
    "TableId": "7ef3e73f-7774-47d6-9a91-8a08fdca3ebe",
    "Finishing logfile... (interrupt to abort)
~ $ aws dynamodb describe-backup

usage: aws [options] <command> <subcommand> [<subcommand> ...] [parameters]

```

aws: error: the following arguments are required: --backup-arn

```

~ $ aws dynamodb list-backups
{
  "BackupSummaries": []
}
~ $ █

```

```

~ $ aws dynamodb create-backup --table-name students --backup-name studentsbkp

An error occurred (TableNotFoundException) when calling the CreateBackup operation: Table not found: students
~ $ aws dynamodb create-backup --table-name Students --backup-name Studentsbkp
{
  "BackupDetails": {
    "BackupArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Students/backup/01757070907353-0b6b4c51",
    "BackupName": "Studentsbkp",
    "BackupSizeBytes": 0,
    "BackupStatus": "CREATING",
    "BackupType": "USER",
    "BackupCreationDateTime": "2025-09-05T11:15:07.353000+00:00"
  }
}
~ $ aws dynamodb list-backups
{
  "BackupSummaries": [
    {
      "TableName": "Students",
      "TableId": "7ef3e73f-7774-47d6-9a91-8a08fdca3ebe",
      "TableArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Students",
      "BackupArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Students/backup/01757070907353-0b6b4c51",
      "BackupName": "Studentsbkp",
      "BackupCreationDateTime": "2025-09-05T11:15:07.353000+00:00",
      "BackupStatus": "AVAILABLE",

```

```

      "BackupCreationDateTime": "2025-09-05T11:15:07.353000+00:00",
      "BackupStatus": "AVAILABLE",
      "BackupType": "USER",
      "BackupSizeBytes": 0
    }
  ]
}
~ $ aws dynamodb describe-backup

usage: aws [options] <command> <subcommand> [<subcommand> ...] [parameters]
To see help text, you can run:

    aws help
    aws <command> help
    aws <command> <subcommand> help

aws: error: the following arguments are required: --backup-arn
~ $ aws dynamodb describe-backups

usage: aws [options] <command> <subcommand> [<subcommand> ...] [parameters]
To see help text, you can run:

    aws help
    aws <command> help
    aws <command> <subcommand> help

```

```

~ $ aws dynamodb describe-backup --backup-arn arn:aws:dynamodb:ap-south-1:119922150537:table/Students/backup/01757070907353-0b6b4c51
{
  "BackupDescription": {
    "BackupDetails": {
      "BackupArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Students/backup/01757070907353-0b6b4c51",
      "BackupName": "Studentsbkp",
      "BackupSizeBytes": 0,
      "BackupStatus": "AVAILABLE",
      "BackupType": "USER",
      "BackupCreationDateTime": "2025-09-05T11:15:07.353000+00:00"
    },
    "SourceTableDetails": {
      "TableName": "Students",
      "TableId": "7ef3e73f-7774-47d6-9a91-8a08fdca3ebe",
      "TableArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/Students",
      "TableSizeBytes": 0,
      "KeySchema": [
        {
          "AttributeName": "StudentId",
          "KeyType": "HASH"
        }
      ],
      "TableCreationDateTime": "2025-09-05T07:47:27.015000+00:00",
      "ProvisionedThroughput": {
        "ReadCapacityUnits": 0,

```

```

        "WriteCapacityUnits": 0
      },
      "ItemCount": 0,
      "BillingMode": "PAY_PER_REQUEST"
    }
  }
}

~ $ aws dynamodb restore-table-from-backup --target-table-name restoreStudent --backup-arn arn:aws:dynamodb:ap-south-1:119922150537:table/Students/backup/01757070907353-0b6b4c51
usage: aws [options] <command> [<subcommand> ...] [parameters]
To see help text, you can run:

    aws help
    aws <command> help
    aws <command> <subcommand> help

aws: error: the following arguments are required: --target-table-name

~ $ aws dynamodb restore-table-from-backup --target-table-name restoreStudent --backup-arn arn:aws:dynamodb:ap-south-1:119922150537:table/Students/backup/01757070907353-0b6b4c51
{
  "TableDescription": {
    "AttributeDefinitions": [
      {
        "AttributeName": "StudentId",
        "AttributeType": "S"
      }
    ],

```

```

      "AttributeType": "S"
    ],
    "TableName": "restoreStudent",
    "KeySchema": [
      {
        "AttributeName": "StudentId",
        "KeyType": "HASH"
      }
    ],
    "TableStatus": "CREATING",
    "CreationDateTime": "2025-09-05T11:19:00.741000+00:00",
    "ProvisionedThroughput": {
      "ReadCapacityUnits": 0,
      "WriteCapacityUnits": 0
    },
    "TableSizeBytes": 0,
    "ItemCount": 0,
    "TableArn": "arn:aws:dynamodb:ap-south-1:119922150537:table/restoreStudent",
    "TableId": "84588b01-08b2-4bbe-b6e4-d8dbe07d7190",
    "BillingModeSummary": {

```

```
~ $ aws dynamodb scan --table-name Students
{
  "Items": [],
  "Count": 0,
  "ScannedCount": 0,
  "ConsumedCapacity": null
}
~ $ █
```

```
~ $ aws dynamodb put-item --table-name Students --item '{"StudentId": {"S": "T0001"}, "Name": {"S": "John Doe"}, "Age": {"N": "21"}}'
~ $
~ $ aws dynamodb get-item --table-name Students --key '{"StudentId": {"S": "T0001"}}'
{
  "Item": {
    "Age": {
      "N": "21"
    },
    "StudentId": {
      "S": "T0001"
    },
    "Name": {
      "S": "John Doe"
    }
  }
}
```

```
~ $ aws dynamodb query \
> --table-name Students \
> --key-condition-expression "StudentId = :v1" \
> --expression-attribute-values '{":v1": {"S": "good Luck"}}'
{
  "Items": [],
  "Count": 0,
  "ScannedCount": 0,
  "ConsumedCapacity": null
}
~ $ █
```