

Est. Length: 2:00:00

Time Taken:0:06:45

KHIU KIM HONG EEE-DEEE-FT-3A-06: Attempt 2

Page 1:

1 ✓	2 ✓	3 ✓
4 ✓	5 ✓	6 ✓
7 ✓	8 ✓	9 ✓
10 ✓	11 ✓	12 ✓
13 ✓		

Question 1 (10 points) ✓ Saved

An RFID reader typically contains:

- ☐ Mouse
- ☒ Receiver
- ☒ Control Unit
- ☒ An antenna
- ☐ Laser Pointer
- ☒ Transmitter
- ☒ Display Unit
- ☐ Camera

Question 2 (7 points) ✓ Saved

Which one of the following is not required in a passive RFID tag?

- ☐ an antenna
- ☒ battery
- ☐ power supply circuit
- ☐ microchip


Question 3 (7 points) ✓ Saved

Anti-collision allows:

- ☐ to communicate a tag with other similar tags.
- ☒ to communicate a tag when other similar to tags are simultaneously visible to the reader.
- ☐ different types of tags to be read/write simultaneously.
- ☐ to communicate a reader with other similar readers.

Question 4 (10 points) ✓ Saved

Figure shows the block diagram of a modulator used in an RFID tag with the signals shown at all stages. In this diagram, the baseband data is modulated onto the sub-carrier. The RF carrier frequency (f_c) of this system is 13.56 MHz. Match the following items with the given list at the right.




Page 1:

- | | | |
|------|------|------|
| 1 ✓ | 2 ✓ | 3 ✓ |
| 4 ✓ | 5 ✓ | 6 ✓ |
| 7 ✓ | 8 ✓ | 9 ✓ |
| 10 ✓ | 11 ✓ | 12 ✓ |
| 13 ✓ | | |

Question 4 (10 points) ✓ Saved

Figure shows the block diagram of a modulator used in an RFID tag with the signals shown at all stages. In this diagram, the baseband data is modulated onto the sub-carrier. The RF carrier frequency (f_c) of this system is 13.56 MHz. Match the following items with the given list at the right.



- | | | |
|---|-------------------------------------|------------------------|
| 6 | Frequency Band of subcarrier | 1. 2^6 |
| 3 | Subcarrier Frequency | 2. RF Carrier |
| 5 | Frequency Band of RF carrier | 3. 212 kHz |
| 4 | RF Carrier Frequency | 4. 13.56 MHz |
| 1 | The value of binary divider | 5. HF (High Frequency) |
| 2 | What is the signal that labelled A? | 6. LF (Low Frequency) |

Question 5 (7 points) ✓ Saved

Using odd parity, for E3h (11100011b). This gives the parity bit to be:

- ☐ 1
☒ 0
☐ -1
☐ +1

Question 6 (7 points) ✓ Saved

An RFID system may consist of:

- ☐ barcodes
☒ RFID readers
☐ barcode readers
☒ RFID tags

Question 7 (10 points) ✓ Saved

Figure shows the three data bytes (12, 34 & 56) and the LRC byte (70) which were received by an RFID transponder. Match the following items with the given list at the right.


Received Data bytes Received LRC byte

Page 1:

1 ✓	2 ✓	3 ✓
4 ✓	5 ✓	6 ✓
7 ✓	8 ✓	9 ✓
10 ✓	11 ✓	12 ✓
13 ✓		

Question 7 (10 points) ✓ Saved

Figure shows the three data bytes (12, 34 & 56) and the LRC byte (70) which were received by an RFID transponder. Match the following items with the given list at the right.



- | | | |
|---|-----------------|-------------|
| 1 | The value of X | 1. 26 |
| 3 | Since Z = 00 | 2. 00 |
| 4 | The value of Y | 3. No error |
| 2 | The values of Z | 4. 70 |

Question 8 (7 points) ✓ Saved

Near-field RFID systems employ ____ of tag to the ____ circulating around the reader antenna.

- ☐ radiative coupling, reactive energy
- ☐ inductive coupling, real energy
- ☐ radiative coupling, real energy
- ☒ inductive coupling, reactive energy

Question 9 (7 points) ✓ Saved

A passive RFID tag contains:

- ☐ an electronic microchip which includes a micro controller, memories and a transceiver
- ☒ all the options
- ☐ an antenna
- ☐ power supply circuit

Question 10 (7 points) ✓ Saved

Which one of the following codes is suitable for data transfer from the transponder to the reader?

- ☐ NRZ code
- ☒ Manchester code
- ☐ Unipolar RZ code
- ☐ Modified Miller coding

Page 1:

1 ✓	2 ✓	3 ✓
4 ✓	5 ✓	6 ✓
7 ✓	8 ✓	9 ✓
10 ✓	11 ✓	12 ✓
13 ✓		

Question 10 (7 points) ✓ *Saved*

Which one of the following codes is suitable for data transfer from the transponder to the reader?

☐ NRZ code

☒ Manchester code

☐ Unipolar RZ code

☐ Modified Miller coding

Question 11 (7 points) ✓ *Saved*

Near-field coupling techniques are generally applied to RFID systems with relatively short reading distances well within the radian sphere defined by:

☒ $\frac{\lambda}{2\pi}$

☐ $\frac{\lambda}{2}$

☐ $\frac{2\pi}{\lambda}$

☐ $\frac{2}{\lambda}$

Question 12 (7 points) ✓ *Saved*

Signal coding is a process that involves:

☐ Demodulation

☐ Error detection

☒ Representation of transmitted message to its voltage representation

☐ Modulation

Question 13 (7 points) ✓ *Saved*

Which one of the following frequencies is the most suitable frequency as a subcarrier to be used in the 13.56 MHz inductively coupled RFID system?

☐ 240 kHz

☐ 400 kHz

☐ 410 kHz

☒ 424 kHz