

Session 3-2 Transforming ERD to Relational Model 1

Kyunghee Lee, PhD



WAYNE STATE
Mike Ilitch School of Business

Transforming EER Diagrams into Relations

- Entities
 - Regular entities
 - Weak entities
- Relationships
 - One-to-many
 - Many-to-many (Associative entity)
 - One-to-one
 - Unary
 - Binary
 - Ternary
- Supertype / subtype



WAYNE STATE

Mike Ilitch School of Business

Transforming EER Diagrams into Relations – Entities

Mapping regular entities to relations


1. **Simple attributes:** E-R attributes map directly onto the relation
2. **Composite attributes:** Use only their simple, component attributes
3. **Multivalued Attribute:** becomes a separate relation with a foreign key taken from the superior entity



WAYNE STATE

Mike Ilitch School of Business


Mapping an Entity with Simple Attributes





WAYNE STATE

Mike Ilitch School of Business

Mapping an Entity with Composite Attributes



Mapping an Entity with Multivalued Attributes



- A multivalued attribute becomes a separate relation with foreign key
- One-to-many relationship between original entity and new relation



Mapping an Entity with Multivalued Attributes

- Create a table for the multivalued attribute
- Name of table is name of the attribute
- Attributes of the table are
 - the PK of the entity set to which the attribute belongs
 - a separate column for the values of the attribute
- PK of the table is all the columns of the table (generally)





Transforming EER Diagrams into Relations - Relationships

Mapping binary relationships

- **One-to-Many:** Primary key on the one side becomes a foreign key on the many side
- **Many-to-Many:** Create a ***new relation*** with the primary keys of the two entities as its primary key
- **One-to-One:** Primary key on the mandatory side becomes a foreign key on the optional side




Example of Mapping a 1:M Relationship



WAYNE STATE

Mike Ilitch School of Business

Example of mapping a M:N relationship




The *Completes* relationship will need to become a separate relation



WAYNE STATE

Mike Ilitch School of Business


Example of mapping a M:N relationship



WAYNE STATE

Mike Ilitch School of Business


Example of mapping a 1:1 relationship



Often in 1:1 relationships, one direction is **optional**



Example of mapping a 1:1 relationship



Foreign key goes in the relation on the **optional** side,
Matching the primary key on the mandatory side



WAYNE STATE

Mike Ilitch School of Business

Wrap-Up

- Transforming ERD into relations
 - Simple, composite, multivalued attributes
 - 1:1, 1:M, M:N relationships



WAYNE STATE

Mike Ilitch School of Business