### **Session 6-9 Subqueries 1**

Kyunghee Lee, PhD



#### **Subqueries and Their Uses**

- Subquery: a query nested inside another query
- Used when a query is based on an unknown value, list, or table
- Requires SELECT and FROM clauses
- Must be enclosed in parentheses
- Place on right side of comparison operator



#### **Subqueries and Their Uses**

SELECT first\_name, last\_name, salary

WHERE salary > 9000

SELECT first\_name, last\_name, salary


FROM employees

WHERE salary > (SELECT salary FROM employees WHERE last\_name='Alex')



#### **Subqueries Syntax**

#### Main query; Outer query



Subquery; Inner query



#### **Types of Subqueries**

- Single-row: returns to the outer query one row of results that consists of one column
  - Returns a value
- Multiple-row: returns to the outer query more than one row of results
  - Returns a list of values
- Multiple-column: returns to the outer query more than one column of results
  - Returns a table



#### **Types of Subqueries**

Single-row subquery



Multiple-row subquery




Multiple-column subquery



### **Single-Row Subqueries**

- Can only return <u>one</u> result to the outer query
- Operators include =, >, <, >=, <=, < >






## Single-Row Subquery in a WHERE Clause

To replace an unknown value

• Q) List the titles of books with a cost higher than

the cost of the book "DATABASE

IMPLEMENTATION"





# Single-Row Subquery in a HAVING Clause

 Required when returned value is compared to grouped data





#### Wrap-up

- Subquery
- Single-row subquery
  - WHERE
  - HAVING

