


Session 3-1 Relational Model

Kyunghee Lee, PhD



WAYNE STATE
Mike Ilitch School of Business

Three Schemas and Logical Data Modeling



WAYNE STATE

Mike Ilitch School of Business

Logical Database Design

- The process of converting ERDs into *relational database models*
- Normalization
 - Prepare data models for implementation as a non-redundant, flexible, and adaptable database



Relational Database Model

- Represents data in the form of tables or relations (Invented by Codd, 1970)
- **Relation:** two-dimensional table of data
 - Columns (attribute, field): attributes of a relation
 - Rows (tuple, record, instance): records containing data values for an entity
 - Primary key (identifier)
 - Foreign key (relationship)



Properties of a relation

- It must have a unique name
- Attributes (columns) in tables must have unique names
- Every attribute value must be atomic (not multivalued, not composite)
- Every row must be unique (can't have two rows with exactly the same values for all their fields)



WAYNE STATE

Mike Ilitch School of Business

Relational Model Example

<u>DeptNo</u>	DeptName	DeptBudget
1	Marketing	220,000
2	Operations	400,000
3	Accounting	100,000

DEPARTMENT
Table

Primary Key

Foreign Key

DEPARTMENT (DeptNo, DeptName, DeptBudget)
EMPLOYEE (EmpNo, EmpName, SSN, DeptNo)

<u>EmpNo</u>	EmpName	SSN	DeptNo
1	Smith, Joseph	111-11-1111	3
2	Jones, David	222-22-2222	2
3	Olson, Jane	333-33-3333	3
4	Neff, Arnold	444-44-4444	1
5	Homes, Denise	555-55-5555	1
6	Naumi, Susan	666-66-6666	2
7	Young, John	777-77-7777	3

EMPLOYEE
Table

Row(Record, Tuple)

Column (Field, Attribute)




WAYNE STATE

Mike Ilitch School of Business

Correspondence with E-R Model

- **Relations (tables)** correspond with **entity types** and with many-to-many relationship types
- **Rows** correspond with **entity instances** and with many-to-many relationship instances
- **Columns** correspond with **attributes**
- **NOTE:** The word ***relation*** (in relational database) is NOT the same as the word ***relationship*** (in E-R model)





Key Fields


- **Primary keys** *to guarantee all rows are unique*
 - unique identifiers of the relation in question (e.g., employee ID, social insurance numbers, etc.)
- **Foreign keys** *to establish the relationships among relations*
 - identifiers that enable a dependent relation (on the many side of a relationship) to refer to its parent relation (on the one side of the relationship)
- Can be simple (a single field) or composite (more than one field)
- Usually used as indexes to speed up the response to user queries



WAYNE STATE

Mike Ilitch School of Business


ERD to Relational Model



WAYNE STATE
Mike Ilitch School of Business

Replace it with one with a better resolution

ERD to Relational Model (cont'd)



Text Description of Relations

- CUSTOMER(Customer_ID, Customer_Name, Customer_Address, City, State, Postal_Code)
- ORDER(Order_ID, Order_Date, Customer_ID)
- ORDER LINE(Order_ID, Product_ID, Ordered_Quantity)
- PRODUCT(Product_ID, Product_Description, Product_Finish, Standard_Price, Product_Line_ID)



Wrap-Up

- Relational database model
 - Relation
 - Properties of a relation
 - Primary key
 - Foreign key
- Mapping between ERD and relational model

