

Advanced Programming for HPC - Report labwork 6

NGUYEN TAT HUNG

November 5, 2021

Implementation

```
--device__ int brightness(){
}
--device__ int blending(){
}

--device__ int binarization(int input, int threshold){
    if(input < threshold){
        return 0;
    }else{
        return 255;
    }
}

--global__ void labwork6_a(uchar3 *input, uchar3 *output, int imgWidth, int imgHeight){
    int col = threadIdx.x + blockIdx.x * blockDim.x;
    int row = threadIdx.y + blockIdx.y * blockDim.y;
    if(col > imgHeight || row > imgWidth){
        return;
    }
    int tid = col + row * imgWidth;

    int threshold = 128;

    output[tid].x = binarization(input[tid].x, threshold);
    output[tid].z = output[tid].y = output[tid].x;
}

void Labwork::labwork6_GPU() {
    // Calculate number of pixels
    int pixelCount = inputImage->width * inputImage->height;

    outputImage = static_cast<char *>(malloc(pixelCount * 3));
    // Allocate CUDA memory
    uchar3 *devInput;
    uchar3 *devOutput;
    uchar3 *devGray;

    cudaMalloc(&devInput, pixelCount*3); // Perfect version
    cudaMalloc(&devOutput, pixelCount*3); // Perfect version
```

```

cudaMalloc(&devGray, pixelCount*3); // Perfect version
// Copy CUDA Memory from CPU to GPU
cudaMemcpy(devInput, inputImage->buffer, pixelCount*3, cudaMemcpyHostToDevice); // Perfect version

// Processing
dim3 blockSize = dim3(16, 16);
dim3 gridSize = ((int) ((inputImage->width + blockSize.x - 1)/blockSize.x), (int)((inputImage->height + blockSize.y - 1)/blockSize.y), 1);

grayscale_2d<<<gridSize, blockSize>>>(devInput, devOutput, inputImage->width, inputImage->height);
//labwork6_a<<<gridSize, blockSize>>>(devGray, devOutput, inputImage->width, inputImage->height);

// Copy CUDA Memory from GPU to CPU
cudaMemcpy(outputImage, devOutput, pixelCount*3, cudaMemcpyDeviceToHost); // Perfect version

// Cleaning

cudaFree(devInput);
cudaFree(devOutput);
cudaFree(devGray);
}

```

Result



Figure 1: Original input image




Figure 2: Output image