
THE ATTRACTOR STATES OF THE FUNCTIONAL BRAIN CONNECTOME

Robert Englert
University Medicine Essen

Tamas Spisak¹
University Medicine Essen

Wednesday 28th June, 2023

Abstract

Abstract:
todo

Keywords

Key Points:

- We propose a high-level computational model of "activity flow" across brain regions
- The model considers the functional brain connectome as an already-trained Hopfield neural network
- It defines an energy level for any arbitrary brain activation patterns
- and a trajectory towards one of the finite number of stable patterns (attractor states) that minimize this energy
- The model reproduces and explains the dynamic repertoire of the brain's spontaneous activity at rest
- It conceptualizes both task-induced and pathological changes in brain activity as a shift on the "attractor landscape"
- We validate our findings on healthy and clinical samples (~2000 participants)

1 Introduction

Brain function is characterized by the continuous activation and deactivation of anatomically distributed neuronal populations. While changes in the activity of a single brain area is often associated with various tasks or conditions, in reality, regional activation never occurs in isolation ([Bassett and Sporns \[2017\]](#)). Regardless of the presence or absence of explicit stimuli, brain regions seem to work in concert, resulting in a rich and complex spatiotemporal fluctuation ([Gutierrez-Barragan et al. \[2019\]](#)). This fluctuation is neither random, nor stationary over time ([Liu and Duyn \[2013\]](#), [Zalesky et al. \[2014\]](#)). It shows quasi-periodic properties ([Thompson et al. \[2014\]](#)), with a limited number of recurring patterns known as "brain states" ([Vidaurre et al. \[2017\]](#), [Liu and Duyn \[2013\]](#), [Richiardi et al. \[2011\]](#)).

Many recent studies ([Smith et al. \[2012\]](#), [Vidaurre et al. \[2017\]](#), [Liu and Duyn \[2013\]](#)) assess whole-brain dynamics and provide accumulating evidence supporting the neurobiological significance of these dynamics ([Hutchison et al. \[2013\]](#), [Barttfeld et al. \[2015\]](#), [van der Meer et al. \[2020\]](#)). However, the underlying driving forces remain elusive.

Questions regarding the origin and meaning of this dynamic repertoire are to be answered by computational models that hold promise to bring us from "correlational studies" to casual understanding. Traditional

¹Correspondence to: tamas.spisak@uk-essen.de

computational neuroscience approaches try to solve the puzzle all the way. They begin by considering the biophysical properties of single neurons and then aim to construct a model of larger neural populations, or even the entire brain (Breakspear [2017]). Although there have been numerous successful applications (Kriegeskorte and Douglas [2018], Heinz et al. [2018]), estimating all free parameters of such models proved to be a grand challenge, limiting success of these techniques to bridge levels of explanations from single neurons to complex behavior (Breakspear [2017]).

An alternative approach, known as "neuroconnectomism" (Doerig et al. [2023]) releases the aim of full bottom-up understanding of neural mechanisms and shifts the emphasis from "biophysical fidelity" of models to "cognitive/behavioral fidelity" (Kriegeskorte and Douglas [2018]) by using artificial neural networks (ANNs) that were trained to perform various tasks as brain models. This approach utilizes artificial neural networks (ANNs) trained for various tasks as brain models. While the approach has significantly contributed to expanding our understanding of the general computational principles of the brain (see Doerig et al. [2023]), the requirement of training ANNs for specific tasks poses inherent limitations in their capacity to explain spontaneous macro-scale dynamics of neural activity (Richards et al. [2019]).

In this work, we take the middle ground between traditional computational modelling and neuroconnectionism to address the phenomenon of brain dynamics. On one hand, similarly to neuroconnectionism, we do not aim for a full bottom-up understanding of neural mechanisms and use an ANN as a high-level computational model of the brain. On the other hand, we do not train our ANN for a specific task, but set its weights "manually", based on empirical data about the "activity flow" (Cole et al. [2016], Ito et al. [2017]) within the functional brain connectome, as measured with functional magnetic resonance imaging (fMRI). We use a neurobiologically motivated ANN architecture, a continuous-space Hopfield network. Within this architecture, the topology of the functional connectome naturally defines an energy level for any arbitrary activation patterns and a trajectory towards one of the finite number of stable patterns that minimize this energy, the so-called attractor states. Furthermore, it provides a natural account for brain state dynamics as the system, in the presence of a small amount of noise, can undergo bifurcation, i.e. spontaneously switch between attractor states.

In this simplistic yet powerful framework, the primary determinants of the system's dynamic behavior are the topology of the network spanned by the weights of the ANN. As these weights are directly inferred from brain data, we hypothesize that the system will closely mimic the dynamic repertoire of true activity patterns in the brain (as measured by fMRI) and capture activity changes induced by tasks and pathologies.

In the present work, we test our hypotheses in a series of experiments, on data from a total of $n \approx 2000$ individuals, to provide converging evidence for the validity of our model.

In the proposed framework, both spontaneous and task-induced brain dynamics can be conceptualized as a high-dimensional path that wanders on the reconstructed energy landscape in a way that is restricted by the "gravitational pull" of the attractors states. The framework offers a generative model for resting state and task-related brain dynamics and new perspectives on the mechanistic origin of resting state brain states and task based activation maps.

ToDo: more on the significance

2 Results

- introduce the idea in more detail (fig 1)
 - attractor states and added noise
 - construct validity
- attractor states (fig 1)
- face validity
- clinical validity

Due to the known noise-tolerance of the applied eANN-s, the proposed approach can be expected to be highly robust/reliable/replicable, which we demonstrate with independent datasets (total $n = xxx$).

Here I refer to Figure 1.




Figure 1: Empirical Hopfield-networks reconstruct real brain activity.

3 Discussion

- significance

A further scenario rests on the role of ghost attractors [109](<https://www.nature.com/articles/nn.4497#ref-CR109> "Deco, G. & Jirsa, V.K. Ongoing cortical activity at rest: criticality, multistability, and ghost attractors. J. Neurosci. 32, 3366–3375 (2012).", a dynamic landscape of remnant attractors each of which has an incomplete basin, hence allowing the system to 'wander' through large swathes of the phase space under the influence of weak noise 110.

4 Methods

Todo

Todo

References

- Danielle S Bassett and Olaf Sporns. Network neuroscience. *Nature Neuroscience*, 20(3):353–364, feb 2017. doi:10.1038/nm.4502. URL <https://doi.org/10.1038%2Fnn.4502>.
- Daniel Gutierrez-Barragan, M. Albert Basson, Stefano Panzeri, and Alessandro Gozzi. Infralow state fluctuations govern spontaneous fMRI network dynamics. *Current Biology*, 29(14):2295–2306.e5, jul 2019. doi:10.1016/j.cub.2019.06.017. URL <https://doi.org/10.1016%2Fj.cub.2019.06.017>.
- Xiao Liu and Jeff H. Duyn. Time-varying functional network information extracted from brief instances of spontaneous brain activity. *Proceedings of the National Academy of Sciences*, 110(11):4392–4397, feb 2013. doi:10.1073/pnas.1216856110. URL <https://doi.org/10.1073%2Fpnas.1216856110>.
- Andrew Zalesky, Alex Fornito, Luca Cocchi, Leonardo L. Gollo, and Michael Breakspear. Time-resolved resting-state brain networks. *Proceedings of the National Academy of Sciences*, 111(28):10341–10346, jun 2014. doi:10.1073/pnas.1400181111. URL <https://doi.org/10.1073%2Fpnas.1400181111>.
- Garth John Thompson, Wen-Ju Pan, Matthew Evan Magnuson, Dieter Jaeger, and Shella Dawn Keilholz. Quasi-periodic patterns (QPP): Large-scale dynamics in resting state fMRI that correlate with local infralow electrical activity. *NeuroImage*, 84:1018–1031, jan 2014. doi:10.1016/j.neuroimage.2013.09.029. URL <https://doi.org/10.1016%2Fj.neuroimage.2013.09.029>.
- Diego Vidaurre, Stephen M. Smith, and Mark W. Woolrich. Brain network dynamics are hierarchically organized in time. *Proceedings of the National Academy of Sciences*, 114(48):12827–12832, oct 2017. doi:10.1073/pnas.1705120114. URL <https://doi.org/10.1073%2Fpnas.1705120114>.
- Jonas Richiardi, Hamdi Eryilmaz, Sophie Schwartz, Patrik Vuilleumier, and Dimitri Van De Ville. Decoding brain states from fMRI connectivity graphs. *NeuroImage*, 56(2):616–626, may 2011. doi:10.1016/j.neuroimage.2010.05.081. URL <https://doi.org/10.1016%2Fj.neuroimage.2010.05.081>.
- Stephen M. Smith, Karla L. Miller, Steen Moeller, Junqian Xu, Edward J. Auerbach, Mark W. Woolrich, Christian F. Beckmann, Mark Jenkinson, Jesper Andersson, Matthew F. Glasser, David C. Van Essen, David A. Feinberg, Essa S. Yacoub, and Kamil Ugurbil. Temporally-independent functional modes of spontaneous brain activity. *Proceedings of the National Academy of Sciences*, 109(8):3131–3136, feb 2012. doi:10.1073/pnas.1121329109. URL <https://doi.org/10.1073%2Fpnas.1121329109>.
- R. Matthew Hutchison, Thilo Womelsdorf, Elena A. Allen, Peter A. Bandettini, Vince D. Calhoun, Maurizio Corbetta, Stefania Della Penna, Jeff H. Duyn, Gary H. Glover, Javier Gonzalez-Castillo, Daniel A. Handwerker, Shella Keilholz, Vesa Kiviniemi, David A. Leopold, Francesco de Pasquale, Olaf Sporns, Martin Walter, and Catie Chang. Dynamic functional connectivity: Promise, issues, and interpretations. *NeuroImage*, 80:360–378, oct 2013. doi:10.1016/j.neuroimage.2013.05.079. URL <https://doi.org/10.1016%2Fj.neuroimage.2013.05.079>.
- Pablo Barttfeld, Lynn Uhrig, Jacobo D. Sitt, Mariano Sigman, Béchir Jarraya, and Stanislas Dehaene. Signature of consciousness in the dynamics of resting-state brain activity. *Proceedings of the National Academy of Sciences*, 112(3):887–892, jan 2015. doi:10.1073/pnas.1418031112. URL <https://doi.org/10.1073%2Fpnas.1418031112>.
- Johan N. van der Meer, Michael Breakspear, Luke J. Chang, Saurabh Sonkusare, and Luca Cocchi. Movie viewing elicits rich and reliable brain state dynamics. *Nature Communications*, 11(1), oct 2020. doi:10.1038/s41467-020-18717-w. URL <https://doi.org/10.1038%2Fs41467-020-18717-w>.
- Michael Breakspear. Dynamic models of large-scale brain activity. *Nature Neuroscience*, 20(3):340–352, feb 2017. doi:10.1038/nm.4497. URL <https://doi.org/10.1038%2Fnn.4497>.
- Nikolaus Kriegeskorte and Pamela K. Douglas. Cognitive computational neuroscience. *Nature Neuroscience*, 21(9):1148–1160, aug 2018. doi:10.1038/s41593-018-0210-5. URL <https://doi.org/10.1038%2Fs41593-018-0210-5>.
- Andreas Heinz, Graham K Murray, Florian Schlagenhauf, Philipp Sterzer, Anthony A Grace, and James A Waltz. Towards a unifying cognitive, neurophysiological, and computational neuroscience account of schizophrenia. *Schizophrenia Bulletin*, 45(5):1092–1100, nov 2018. doi:10.1093/schbul/sby154. URL <https://doi.org/10.1093%2Fschbul%2Fsby154>.
- Adrien Doerig, Rowan P. Sommers, Katja Seeliger, Blake Richards, Jenann Ismael, Grace W. Lindsay, Konrad P. Kording, Talia Konkle, Marcel A. J. van Gerven, Nikolaus Kriegeskorte, and Tim C. Kietzmann. The neuroconnectionist research programme. *Nature Reviews Neuroscience*, 24(7):431–450, may 2023. doi:10.1038/s41583-023-00705-w. URL <https://doi.org/10.1038%2Fs41583-023-00705-w>.

- Blake A. Richards, Timothy P. Lillicrap, Philippe Beaudoin, Yoshua Bengio, Rafal Bogacz, Amelia Christensen, Claudia Clopath, Rui Ponte Costa, Archy de Berker, Surya Ganguli, Colleen J. Gillon, Danijar Hafner, Adam Kepecs, Nikolaus Kriegeskorte, Peter Latham, Grace W. Lindsay, Kenneth D. Miller, Richard Naud, Christopher C. Pack, Panayiota Poirazi, Pieter Roelfsema, João Sacramento, Andrew Saxe, Benjamin Scellier, Anna C. Schapiro, Walter Senn, Greg Wayne, Daniel Yamins, Friedemann Zenke, Joel Zylberberg, Denis Therien, and Konrad P. Kording. A deep learning framework for neuroscience. *Nature Neuroscience*, 22(11):1761–1770, oct 2019. doi:[10.1038/s41593-019-0520-2](https://doi.org/10.1038/s41593-019-0520-2). URL <https://doi.org/10.1038/s41593-019-0520-2>.
- Michael W Cole, Takuya Ito, Danielle S Bassett, and Douglas H Schultz. Activity flow over resting-state networks shapes cognitive task activations. *Nature Neuroscience*, 19(12):1718–1726, oct 2016. doi:[10.1038/nn.4406](https://doi.org/10.1038/nn.4406). URL <https://doi.org/10.1038/nn.4406>.
- Takuya Ito, Kaustubh R. Kulkarni, Douglas H. Schultz, Ravi D. Mill, Richard H. Chen, Levi I. Solomyak, and Michael W. Cole. Cognitive task information is transferred between brain regions via resting-state network topology. *Nature Communications*, 8(1), oct 2017. doi:[10.1038/s41467-017-01000-w](https://doi.org/10.1038/s41467-017-01000-w). URL <https://doi.org/10.1038/s41467-017-01000-w>.