

MongoDB Query Operators - Quick Reference

\$eq

Matches values that are equal to a specified value.

Example: { age: { \$eq: 25 } }

\$ne

Matches values that are not equal to a specified value.

Example: { age: { \$ne: 25 } }

\$gt / \$gte

Matches values greater than / greater than or equal to a value.

Examples: { price: { \$gt: 100 } }, { price: { \$gte: 100 } }

\$lt / \$lte

Matches values less than / less than or equal to a value.

Examples: { price: { \$lt: 50 } }, { price: { \$lte: 50 } }

\$in

Matches any of the values specified in an array.

Example: { status: { \$in: ['active', 'pending'] } }

\$nin

Matches none of the values specified in an array.

Example: { status: { \$nin: ['banned', 'deleted'] } }

\$and

Joins query clauses with a logical AND.

Example: { \$and: [{ age: { \$gte: 18 } }, { age: { \$lte: 30 } }] }

\$or

Joins query clauses with a logical OR.

Example: { \$or: [{ role: 'admin' }, { role: 'moderator' }] }

\$not

Inverts the effect of a query expression.

Example: { age: { \$not: { \$gt: 30 } } }

\$exists

Matches documents that have the specified field.

Example: { email: { \$exists: true } }

\$regex

Matches string values using regular expressions.

Example: { name: { \$regex: /^A/, \$options: 'i' } }

\$size

Matches arrays with the specified number of elements.

Example: { tags: { \$size: 3 } }

\$all

Matches arrays that contain all specified elements.

Example: { tags: { \$all: ['tech', 'mongodb'] } }