

# Get and summarize AFSC survey data

Kirstin Holsman, Alaska Fisheries Science Center

## Contents

Overview	1
Comparison of Bering Sea survey values	3
Code	4
Appendix 1: R/setup.Rprimary setup script . . . . .	10

**AFSC Survey CPUE data:** [github.com/kholsman/AFSC\\_CPUE](https://github.com/kholsman/AFSC_CPUE) Repo maintained by:  
Kirstin Holsman  
Alaska Fisheries Science Center  
NOAA Fisheries, Seattle WA  
[kirstin.holsman@noaa.gov](mailto:kirstin.holsman@noaa.gov)  
*Last updated: Mar 03, 2023*

## Overview

The below scripts return a list object `cpue_data` saved as a compressed Rdata file with the naming ‘reg.srvy#.spp.cpue\_data.Rdata’ such as “ebs.srvy98.plk.cpue\_data.Rdata”. Each `cpue_data` list contains 8 data.frames:

```
load(paste0("data/out/",qrydate,"/cpue/ebs/ebs.srvy98.plk.cpue_data.Rdata"))  
names(cpue_data)
```

There is a folder for each region “ebs”, “goa”, “ai”. For the “ebs” (Bering Sea) there are two sets of `cpue_data`, one that is NEBS+SEBS combined (‘ebs.srvy98.[sp].cpue\_data.Rdata’) and one that is just SEBS survey areas (‘sebs.srvy98.[sp].cpue\_data.Rdata’). For both the Gulf of Alaska (“goa”) and the Bering Sea, mean CPUE (Kg per km2 or Number per km2) for each size bin at each strata was calculated and then multiplied by the STRATA area to get total Biomass and abundance. **Note: Since strata area estimates were not available for the Aleutian Island (“ai”) or slope surveys (“slope”) these AREA was set equal to 1 and the Total Biomass and abundance is actually the sum of mean biomass.**

The data.frames within each `cpue_data` object are:

1. **totalB\_N**: Total biomass (kg) or abundance (# of fish) for the species in each year

2. **mnCPUE\_strata\_yr** : Average survey CPUE (kg per Km<sup>2</sup>) or abundance (# per Km<sup>2</sup>) for the species in each strata and year
3. **total\_bin\_B\_N**: Total biomass (kg) or abundance (# of fish) for each bin (10 mm) for the species in each year
4. **mnCPUE\_strata\_bin\_yr** : Average survey CPUE (kg per Km<sup>2</sup>) or abundance (# per Km<sup>2</sup>) for each size bin for the species in each strata and year
5. **CPUE\_station\_bin\_yr**: Station specific survey CPUE (kg per Km<sup>2</sup>) or abundance (# per Km<sup>2</sup>) for each size bin for the species in each year
6. **CPUE\_station\_yr**: Station specific survey CPUE (kg per Km<sup>2</sup>) or abundance (# per Km<sup>2</sup>) for the species in each year
7. **propByBin**: proportion of biomass in each size bin per species per year
8. **propByStrata**: proportion of biomass in each strata per species per year
9. **propByStrataBin**: proportion of biomass in each bin and strata per species per year




Figure 6: Regional polygons and survey-replication stations associated with the ACLIM indices.

These are calculated from the RACEBASE data tables for survey results where total CPUE was recorded for the species  $s$  (location\_catch) at each haul, expanded to include stations  $i$  where CPUE=0 (location) and expanded to each size bin  $l$  using the proportional subset of frequency of fish of given length (mm), binned into 10 mm bins ( $l$ ) and predicted weight ( $\hat{W}$ ) for each size bin  $l$  at each station  $i$ :

$$B_{s,y} = CPUE_{s,k,y} \bar{A}_k$$

where  $A_k$  is the area of the strata  $k$  in Km<sup>2</sup> and  $CPUE_{s,k,y}$  is the strata specific average CPUE (kg per Km<sup>2</sup> or number per Km<sup>2</sup>) of all stations  $i$  in strata  $k$ :

$$CPUE_{s,k,y} = \frac{1}{n_k} \sum_{n_k} CPUE_{s,k,y,i}$$

where \$ CPUE\_{\{s,k,y,i\}} \$ is the station specific CPUE (saves as the object `cpue_data$CPUE_station_yr`).

To obtain population level estimates of the biomass or abundance of fish by size bin  $l$ , we used a length weight regression to estimate the weight of each size fish  $j$  measured ( $\hat{W}$ ) to calculate the proportion by weight or frequency at each station where

$$\hat{W} = \alpha_s + L_j^{\beta_s}$$

where  $\alpha_s$  and  $\beta_s$  are fit (updated each year) to all available length and weight data from surveys from all years across the EBS, GOA, and AI (rather than each basin separately) and

$$p_{l,i}^w = \frac{N_{l,i} \hat{W}_{l,i}}{\sum N_{l,i} \hat{W}_{l,i}}$$

and

$$p_{l,i}^N = \frac{N_{l,i}}{\sum N_{l,i}}$$

This was then multiplied by the CPUE at each station ( $CPUE_{s,k,y,i}$ ) to obtain a station estimate of CPUE by size bin  $l$

$$CPUE_{s,k,y,l,i} = p_{l,i}^N \cdot CPUE_{s,k,y,i}$$


Finally, the average strata CPUE ( $CPUE_{s,k,y,l}^{\bar{}}$ ) and whole of EBS biomass by size bin ( $B_{s,y,l}$ ) was calculated as:

$$CPUE_{s,k,y,l}^{\bar{}} = \frac{1}{n_k} \cdot \sum_{n_k} CPUE_{s,k,y,l,i}$$

and

$$B_{s,y,l} = \frac{CPUE_{s,k,y,l}^{\bar{}} \cdot A_k}{\sum_{n_k} CPUE_{s,k,y,l}^{\bar{}} \cdot A_k} \cdot B_{s,y}$$

## Comparison of Bering Sea survey values






Figure 1: “arrowtooth”

## Code

```
# ## Step 0: Set up the R workspace
#
# The first step is to set up the switches for what files to update and create in the file `R/setup.R`.
#
# ## Step 1: Update SQL queries
# This step must be run on a computer that has access to RACEBASE. The code below will generate the bas
#
# **IMPORTANT:**
#
# * **This step must be connected to the RACEBASE SQL database**
```

```

#
#   * **To change R studio from the default 64 bit to 32 bit go to Tools>Global options and select the
#
#   * **The code will connect to the SQL database using your password and username. Remember to update
#
# <!-- ![Header of `setup.R` where `username_path` can be adjusted. This file also is where species, re
#

# get everything set up:
#-----
# rm(list=ls())
# this uses the password saved in R/password.R
suppressMessages(source("R/make.R"))

# update the SQL queries
#-----

source(file.path(code.path, "R/sub_scripts/runRACE_qrys.R"))

# combine sebs and nebs into one region: ebs
if(dir.exists(file.path(data.path, "ebs")))
  system(paste("rm -r", file.path(data.path, "ebs")))
  dir.create(file.path(data.path, "ebs"))

# combine files and rename survey area to all of EBS
for(sp in names(splist)){
  if(dir.exists(file.path(data.path, "ebs", sp)))
    system(paste("rm -r", file.path(data.path, "ebs", sp)))
    dir.create(file.path(data.path, "ebs", sp))
  #"length.Rdata"
  load(file.path(data.path, "nebs", sp, "length.Rdata"))
  length_nebs <- length; rm(length)
  load(file.path(data.path, "sebs", sp, "length.Rdata"))
  length_sebs <- length; rm(length)
  length<- rbind(length_nebs%>%
    mutate(SURVEY_DEFINITION_ID_aka =SURVEY_DEFINITION_ID, SURVEY_DEFINITION_ID =98),
    length_sebs%>%
    mutate(SURVEY_DEFINITION_ID_aka =SURVEY_DEFINITION_ID, SURVEY_DEFINITION_ID =98))

  save(length, file = file.path(data.path, "ebs", sp, "length.Rdata"))
  rm(length)

  #"location.Rdata"
  load(file.path(data.path, "nebs", sp, "location.Rdata"))
  location_nebs <- location; rm(location)
  load(file.path(data.path, "sebs", sp, "location.Rdata"))
  location_sebs <- location; rm(location)
  location<- rbind(location_nebs, location_sebs)

  save(location, file = file.path(data.path, "ebs", sp, "location.Rdata"))

```

```

##"location_catch.Rdata"
load(file.path(data.path,"nebs",sp,"location_catch.Rdata"))
location_catch_nebs <- location_catch;rm(location_catch)
load(file.path(data.path,"sebs",sp,"location_catch.Rdata"))
location_catch_sebs <- location_catch;rm(location_catch)
location_catch <- rbind(location_catch_nebs%>%
  mutate(SURVEY_DEFINITION_ID_aka =SURVEY_DEFINITION_ID,SURVEY_DEFINITION_ID =98),
  location_catch_sebs%>%
  mutate(SURVEY_DEFINITION_ID_aka =SURVEY_DEFINITION_ID,SURVEY_DEFINITION_ID =98))

save(location_catch,file = file.path(data.path,"ebs",sp,"location_catch.Rdata"))

}

#```

## Step 2: Update the LWA regressions

# The default code for RACEBASE uses set LW relationships, however we prefer to update the LW regressions
#
# ```{r updateLWglms, echo=TRUE, eval=FALSE}

# update the LW regressions
#-----

if(update_LWdata){
  source(file.path(code.path,"R/sub_scripts/updateLW.R"))
  # reload with updated data:
  source(file.path(code.path,"R/load_data.R"))
}
species_lkup

#```

## Step 3: Get CPUE data from the surveys

#This code is the core script for generating the CPUE_NUMKM2 and CPUE_BIOMKM2 values by size bin, region
#```{r updateCPUE, echo=TRUE, eval=FALSE}

STRATA_AREA%>%filter(REGION=="BS")%>%
  group_by(YEAR)%>%summarise(mnAREA = mean(AREA, na.rm=T),
                             sumAREA = sum(AREA, na.rm=T),
                             cnt = length(unique(STRATUM)))

STRATA_AREA%>%filter(REGION=="GOA")%>%
  group_by(YEAR)%>%summarise(mnAREA = mean(AREA, na.rm=T),
                             sumAREA = sum(AREA, na.rm=T),
                             cnt = length(unique(STRATUM)))

```

```

STRATA_AREA%>%filter(REGION=="BS",YEAR==2022)%>%select(STRATUM)

# overwrite the NEBS frame from setup for the next set of code (ebs = sebs+nebs now forward)
srvys <- data.frame(reg=c("ebs","goa","ai","slope"),RGN = c("BS","GOA","AI","SLOPE"), num=c(98,47,52,
# srvys <- data.frame(reg=c("ebs","goa","ai"),RGN = c("BS","GOA","AI"), num=c(98,47,52) )
nreg <- length(srvys$reg)
nspp <- length(species_lkup$sp)

for (r in 1:nreg){
  for(s in 1:nspp){

    if(srvys[r,]$reg=="ebs"){
      # first SEBS only:
      # -----
      STRATA_AREAUSE <- STRATA_AREA%>%filter(REGION==srvys$RGN[r])
      maxyr <- max(STRATA_AREAUSE$YEAR)
      STRATA_AREAUSE <- STRATA_AREAUSE%>%
        filter(YEAR==2022)%>%
        group_by(REGION,STRATUM)%>%
        summarize(AREA = mean(AREA, na.rm=T))%>%ungroup()

      flnm <- paste0("s",srvys[r,]$reg,".srvy",
                    srvys[r,]$num,".",
                    species_lkup[s,]$sp)
      cat("now getting data for: ",flnm,"\n")
      cpue_data <- suppressMessages(
        get_CPUE_DATA(
          datapath = data.path,
          out_dir = file.path(data.out),
          STRATA_AREAIN = STRATA_AREAUSE,
          flnm = flnm,
          species = species_lkup[s,]$SPECIES_CODE,
          survey = srvys[r,]$num,
          includeNBS = FALSE,
          NEBSstrataIN = NEBS_strata ,
          saveit = T,
          bins = sp_bins[[ species_lkup[s,]$sp ]]))

      rm(cpue_data)

      # Now NESB + SEBS
      # -----
      flnm <- paste0(srvys[r,]$reg,".srvy",
                    srvys[r,]$num,".",
                    species_lkup[s,]$sp)
      cat("now getting data for: ",flnm,"\n")
      cpue_data <- suppressMessages(
        get_CPUE_DATA(
          datapath = data.path,
          out_dir = file.path(data.out),
          STRATA_AREAIN = STRATA_AREAUSE,
          flnm = flnm,
          species = species_lkup[s,]$SPECIES_CODE,

```

```

        survey      = srvys[r,]$num,
        includeNBS   = TRUE,
        NEBSStrataIN = NEBS_strata ,
        saveit       = T,
        bins         = sp_bins[[ species_lkup[s,]$sp ]]))

}

if(srvys[r,]$reg == "goa"){
  STRATA_AEAUSE <- STRATA_AEAUSE %>% filter(REGION==srvys$RGN[r])
  maxyr <- max(STRATA_AEAUSE$YEAR)
  STRATA_AEAUSE <- STRATA_AEAUSE %>%
    filter(YEAR==1993) %>%
    group_by(REGION,STRATUM) %>%
    summarize(AREA = mean(AREA, na.rm=T)) %>% ungroup()

  flnm <- paste0(srvys[r,]$reg, ".srvy",
                 srvys[r,]$num, ".",
                 species_lkup[s,]$sp)
  cat("now getting data for: ", flnm, "\n")
  cpue_data <- suppressMessages(
    get_CPUE_DATA(
      datapath = data.path,
      out_dir  = file.path(data.out),
      STRATA_AEAUSEIN = STRATA_AEAUSE,
      flnm      = flnm,
      species   = species_lkup[s,]$SPECIES_CODE,
      survey    = srvys[r,]$num,
      includeNBS = FALSE,
      NEBSStrataIN = NEBS_strata ,
      saveit     = T,
      bins      = sp_bins[[ species_lkup[s,]$sp ]]))

}

if(!srvys[r,]$reg %in% c("ebs", "goa")){
  flnm <- paste0(srvys[r,]$reg, ".srvy",
                 srvys[r,]$num, ".",
                 species_lkup[s,]$sp)
  cat("now getting data for: ", flnm, "\n")
  cpue_data <- suppressMessages(
    get_CPUE_DATA(
      datapath = data.path,
      out_dir  = file.path(data.out),
      STRATA_AEAUSEIN = NULL,
      flnm      = flnm,
      species   = species_lkup[s,]$SPECIES_CODE,
      survey    = srvys[r,]$num,
      includeNBS = FALSE,
      NEBSStrataIN = NEBS_strata ,
      saveit     = T,
      bins      = sp_bins[[ species_lkup[s,]$sp ]]))

}

```



```

# # check the data :
if(1==10){
  tt <- cpue_data%>%
    group_by(YEAR,REGION,STATIONID,SN)%>%
    filter(BIN ==400)%>%
    summarize(cnt =length(STATIONID))
    max(tt$cnt) #Should be 1
  #this looks to be a duplicate sampling...
  #mis-entry or code error ?
  cpue_data%>%filter(YEAR==1988,STATIONID=="J-13")
}
rm(cpue_data)

}
#
# ...
#
# *The cpue files are now saved in the directory `r file.path(data.out,"../")`*
#
# ```{r viewcpue_data, echo=TRUE, eval=FALSE}
#   # this uses the password saved in R/password.R
#   # suppressMessages(source("R/make.R"))
load(file.path(data.out,"cpue/ebs/ebs.srvy98.pcod.cpue_data.Rdata"))

names(cpue_data)

library(dplyr)

checkit <-function(x){
  if(round(max(x ),1)!=1) {
    warning("ERROR! propB > 1 ")
    print(x)}
}

#double check the results
cnt_ByStrataBin <- cpue_data$propByStrataBin%>%
  select("REGION", "YEAR", "STRATUM", BIN, BIN_mm,
    SPECIES_CODE, CN, SN, sp, num,
    "propB_ykl", "propN_ykl")%>%
  group_by(YEAR, REGION, SN, CN)%>%
  summarise(sum_propB_ykl=sum(propB_ykl, na.rm=T),
    sum_propN_ykl=sum(propN_ykl, na.rm=T))

cnt_ByStrata <- cpue_data$propByStrata%>%
  select("REGION", "YEAR", "STRATUM",
    SPECIES_CODE, CN, SN, sp, num,
    "propB_yk", "propN_yk")%>%
  group_by(YEAR, REGION, SN, CN)%>%
  summarise(sum_propB_yk=sum(propB_yk, na.rm=T),
    sum_propN_yk=sum(propN_yk, na.rm=T))

```

```

cnt_ByBin <- cpue_data$propByBin%>%
  select("REGION", "YEAR", BIN, BIN_mm, num,
         SPECIES_CODE, CN, SN, sp,
         "propB_y1", "propN_y1")%>%
  group_by(YEAR, REGION, SN, CN)%>%
  summarise(sum_propB_y1=sum(propB_y1 ,na.rm=T),
            sum_propN_y1=sum(propN_y1 ,na.rm=T))

checkit(cnt_ByStrataBin$sum_propB_yk1)
checkit(cnt_ByStrata$sum_propB_yk)
checkit(cnt_ByBin$sum_propB_y1)

```

#

## Appendix 1: R/setup.Rprimary setup script