Email Classification for Financial Services

Msesenyane Makhongela
khongela7@gmail.com

I. Problem

RedRock receives many client emails and needs to send each one to the right department. Sending an email to the wrong team could delay a response and create problems in a regulated financial business.

We are given 44 emails with known categories and 12 emails to classify. For each of the 12 emails, we need to choose one of five categories: Account Management, Investment Advisory, Loan Processing, Insurance Claims, or Other. The classifications need to be provided with a confidence score and saved in a CSV file.

In machine learning, this is a multiclass classification problem. A multiclass classifier chooses one category from a set of possible categories for each email. Here, the input is the email text and the output is one of the five business categories.

II. Introduction

There are several ways to solve this problem. We could turn the text into TF-IDF features and train a logistic regression model, use semantic embeddings, or ask a large language model to classify each email through an API. I began with the simpler approach so I could understand its decisions and test its performance on the labelled emails.

TF-IDF stands for term frequency inverse document frequency. It turns each email into numbers by giving more weight to words that appear often in that email but are less common across the training set.

Logistic regression learns how strongly those numbers are associated with each category and chooses the category with the highest predicted score. Multinomial Naive Bayes is another text classifier. It estimates how likely the words in an email are under each category and chooses the most likely category.

III. Related Work

I started by reading studies that compare ways to classify emails into several categories. Soni et al. [1] studied organizational email sorting and found that logistic regression performed best when they combined TF-IDF and Word2Vec features. They also tested Multinomial Naive Bayes with TF-IDF. This study informed my initial thinking on model choice, while the results on RedRock's emails guided my final choice.

I also looked at two GitHub projects. avannaldas [2] used TF-IDF with an SGD classifier and grid search. VoxDroid [3] used word counts with Multinomial Naive Bayes. These examples helped me compare simple ways to classify email text.

IV. Methodology

A. Preparing the emails

I used Beautiful Soup to extract each email's ID, subject and body from the supplied HTML files. I removed scripts and styles, then combined the subject and body into one text field for classification. I matched the training emails to their labels using filenames and kept the IDs from the HTML for the final results.

B. Training the model

I built a scikit-learn pipeline using TF-IDF and logistic regression. The vectorizer converted the email text into numerical features and removed common English stop words. During cross-validation, it learned its vocabulary only from the training emails, keeping the evaluation emails separate.

I used grid search to compare 12 combinations of single-word or word-pair features, regularization settings and class balancing. The settings with the highest average macro F1 were selected.

C. Saving the predictions

After evaluation, I fitted the tuned model using all 44 labelled emails and saved the pipeline. I used it to classify the 12 unlabelled emails, choosing the category with the highest predicted probability for each message. I exported the email IDs, predicted categories and confidence scores to a CSV file with the required column names.

V. Evaluation and Results

I used cross-validation to compare logistic regression, Multinomial Naive Bayes and an SGD classifier. I then tested different settings for the best classifier.

TABLE I
Cross-validation results for logistic regression.

Settings	Accuracy	Macro F1
Default settings	79.09%	0.67
Tuned settings	92.73%	0.90
Extra subject weighting	91.36%	0.88

Which model worked best?

Logistic regression performed better than Multinomial Naive Bayes and SGD in the first comparison, so I used it for the remaining experiments.

Did tuning help?

Tuning improved the model, while giving more weight to the subject line did not.

How trustworthy are the results?

The results are promising, but only 44 labelled emails were available. A larger test set is needed to confirm how well the model performs on new emails.

TABLE II
PREDICTIONS FOR THE 12 UNLABELLED EMAILS.

Email ID	Predicted category	Score
35	Investment Advisory	0.21
2	Investment Advisory	0.23
8	Loan Processing	0.24
41	Account Management	0.22
44	Investment Advisory	0.22
7	Investment Advisory	0.22
53	Account Management	0.22
9	Insurance Claims	0.24
15	Other	0.21
16	Account Management	0.22
18	Loan Processing	0.23
48	Investment Advisory	0.21

VI. DISCUSSION

I chose TF-IDF with logistic regression because it performed best in the tests, was easy to run, and allowed me to inspect which words influenced its predictions.

I would measure success through precision and recall for each category, routing errors, staff corrections and response delays. Given the small training set, staff should check every route during a pilot. Their feedback would help identify errors and guide further improvements.

VII. CONCLUSION

TF-IDF with logistic regression gave promising results, but more labelled emails are needed to test how well it handles new messages. Email threads, attachment text, sender and recipient details, and staff corrections could provide useful context.

A future version could compare MiniLM embeddings with TF-IDF to test whether capturing meaning beyond individual words improves classification.

With more verified examples, I would also test an LLM with retrieval-augmented generation. It could use similar previously classified emails and routing guidance to help choose a category. This may be useful in a large organization such as a bank, where emails cover many topics and departments.

REFERENCES

[1] D. Soni et al., "Automated Email Sorting in Organizations: A Machine Learning based Multi-Class Classification System," in *Proceedings of ICACRS*, 2024. doi: 10.1109/ICACRS62842.2024.10841764.

[2] avannaldas, "EmailsClassification," GitHub repository. github.com/avannaldas/EmailsClassification.

[3] VoxDroid, "NLP-Email-Categorizer," GitHub repository. github.com/VoxDroid/NLP-Email-Categorizer.

VIII. Diagrams




Fig. 1. Classifier comparison using the same held-out emails.




Fig. 2. Mean cross-validation scores for the logistic regression versions.




Fig. 3. Tuned logistic regression confusion matrix. Counts combine five evaluations of each of the 44 labelled emails.