### RESULTS

#### 1),1,(1

Numerical Simulations and Experiments with

#### BACON PREPARATION IN A MICROWAVE

1)11

EiT -  $Matematikk\ Innen\ Anvendelser$ 

#### 

ÅSMUND ERVIK, JOAKIM JOHNSEN, KNUT HALVOR SKREDE, TURID SCHOONDERBEEK SOLBERG, PAUL VO

### Abstract

Text in abstract


### Preface

Text in foreword

Åsmund Ervik, Joakim Johnsen, Paul Vo<br/>, Knut Halvor Skrede, Turid Schoonderbeek Solberg $\ensuremath{\mathit{April}}$ 5, 2011

# Contents

1	Inti	roduction	1
	1.1	Introduction	1
<b>2</b>	Theory		3
	2.1	The physical system	3
	2.2	Our approach	3
	2.3	The heat equations	4
	2.4	The transport equations	4
3	Numerics		
	3.1	Von Neumann analysis of the Crank-Nicolson-scheme	5
	3.2	Truncation error in the Crank-Nicolson scheme	6
4	Implementation 9		
	4.1	Tools	9
	4.2	Program design	9
	4.3	The physical system	10
		4.3.1 Partitioning of the problem	10
		4.3.2 Updating alpha and beta values	10
		4.3.3 Calculating the distribution of the microwave effect	10
		4.3.4 The matrix-vector multiplication procedure	10
	4.4	The conjugate gradient method as an iterative algorithm	10
5	Exp	periments	11
	5.1	Experiments	11
6	Cor	nclusion	13
	6.1	Conclusion	13



### Introduction

#### 1.1 Introduction


Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus

vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Kap. 1 2  $\overline{\Gamma}$ 



## Theory

### 2.1 The physical system

The physical system to be modeled is a thin, rectangular strip of bacon which is subjected to approx. 750 watts of microwave radiation at the frequency of 2.4 GHz. To be modeled is the heat in the strip, phase transitions and transport.

### 2.2 Our approach




Figure 2.1: Our initial approach to the problem

Initially, our approach to modelling was to use a staggered approach: first solve the heat equation for the three media meat, solid fat, and liquid fat, thus giving the temperature at step n. Then at step n+1, the temperature is regarded as known, and we solve the transport equation for liquid fat out of the bacon. Then we know the distribution of liquid fat at step n+2, where we solve the heat equations again, and we repeat ad nauseam.

### 2.3 The heat equations

The differential equations governing the heat transport are all variations of the heat equation, with various source terms, eq. (2.1):

$$(\rho c_p)_m \frac{\partial T}{\partial t} - \alpha_m \nabla^2 T = J^{MW} \quad m,$$
 (2.1)

$$\eta_s(\rho c_p)_s \frac{\partial T}{\partial t} - \eta_s \alpha_s \nabla^2 T = J^{MW} - J^{Melt} \quad \text{s}, \qquad (2.2)$$

$$\eta_l(\rho c_p)_l \frac{\partial T}{\partial t} - \eta_s \alpha_l \nabla^2 T - \eta_l(\rho c_p)_l (\mathbf{v} \cdot \nabla) T = J^{MW} \quad 1.$$
(2.3)

Here the subscript m denotes meat, s denotes solid fat, and l denotes liquid fat.  $J^{MW}$  is the source term representing the microwave oven. In the initial approach, this is modelled as a cylindrically symmetric term, with the radial power distribution on the form eq. (2.4),

$$J^{MW}(r) = 0.5 + 2.55008x - 0.588013x^2 + 0.032445x^3 + 0.00124411x^4 - 0.0000973516x^5,$$
(2.4)

i.e. a fifth degree polynomial, interpolated from the results in [1].

Furthermore, there is the term  $J^{Melt}$  which represents heat loss due to latent heat in the solid-liquid phase transition. This can be written as

$$\frac{L\rho}{T_2 - T_1} \frac{\partial T}{\partial t}, \quad T \in (T_1, T_2),$$

where the fat is melting between the temperatures  $T_1$  and  $T_2$ . For fat these are typically around 30-50°C. For  $T \notin (T1,T2)$  this term is zero, and it is readily seen that this is equivalent to a modification of the constant  $c_{p,l}$  in eq. (2.1) when  $T \in (T1,T2)$ , thus it is not a serious complication.

In the last of the heat equations, there also appears what is called a convective derivative, on the form  $(\mathbf{v} \cdot \nabla)T$ . This is a somewhat more complicated term, and is essentially a modification due to transport of liquid fat implying an implicit transport of heat. However, in the staggered approach used here, the velocity field is considered as known when it comes to the heat equations.

### 2.4 The transport equations

Kap. 2 4  $\frac{\text{Int}(1)}{\text{Int}(1)}$ 

3

### Numerics

# 3.1 Von Neumann analysis of the Crank-Nicolson-scheme

Consider the heat equation,

$$\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial^2 x} \tag{3.1}$$

By applying Crank-Nicolson the following iteration scheme is attained,

$$u_i^{n+1} = u_i^n (1 - 2D) + D \left( u_{i+1}^{n+1} - 2u_i^{n+1} + u_{i-1}^{n+1} \right) + D \left( u_{i+1}^n + u_{i-1}^n \right)$$
 (3.2)

$$D = \frac{1}{2} \frac{\alpha \Delta t}{(\Delta x)^2} \tag{3.3}$$

Using the approximation  $u_j^n \approx E_j^n$  where  $E_j^n = G^n e^{i\beta x_j}$ , and n is a power, inserted into eq. (3.1), this gives

$$G^{n+1}e^{i\beta x_j} = G^n e^{i\beta x_j} (1-2D) + G^{n+1}D\left(e^{i\beta x_{j+1}} - 2e^{i\beta x_j} + e^{i\beta x_{j-1}}\right) + G^nD\left(e^{i\beta x_{j+1}} + e^{i\beta x_{j-1}}\right)$$

Dividing eq. (3.3) by  $G^n e^{i\beta x_j}$ , and using  $x_{j+1} \approx x_j + h$  one obtains

$$G\left[1 - D\left(2\cos\beta h - 2\right)\right] = 1 - 2D\left(1 - \cos\beta h\right)$$

$$\cos\beta h = \frac{1}{2}\left(1 - \sin^2\frac{\beta h}{2}\right)$$

$$G\left(1 + 4D\sin^2\frac{\beta h}{2}\right) = 1 - 4D\sin^2\frac{\beta h}{2}$$

$$G = \frac{1 - 4D\sin^2\frac{\beta h}{2}}{1 + 4D\sin^2\frac{\beta h}{2}}$$

As the maximum value of  $\sin^2 x$  is 1, and since the iteration scheme is stable if  $|G| \leq 1$ , this implies stability,

$$|G| = \left| \frac{1 - 4D}{1 + 4D} \right| \tag{3.4}$$

A typical Courant-Friedrichs-Lewy condition is an inequality of the form  $\frac{\Delta t}{\Delta x} < C$ , with C a constant.

It is noteworthy that  $D>0 \Rightarrow |G|\leq 1$ , so the Crank-Nicolson scheme is unconditionally stable. There is, however, a caveat: if the time steps and space steps do not fulfill a CFL-condition, the scheme may present oscillations.

### 3.2 Truncation error in the Crank-Nicolson scheme

The Crank-Nicholson method is based on the trapezoidal rule. From the trapezoidal rule the truncation error is represented by

$$\int_0^k f(t)dt = \frac{1}{2}k(f(0) - f(k)) - \frac{1}{12}k^3f''(\frac{k}{2}) + \dots$$

Using the formula

$$u(x_m, t_{n+1}) - u(x_m, t_n) = \int_{t_n}^{t_{n+1}} u_t(x_m, t) dt$$

and approximating the integral by the trapezoidal rule, and abbreviate the notation  $u_m^{n+1/2} = u(x_m, t_n + \frac{1}{2}k)$ , one obtain

$$\begin{array}{ll} u_m^{n+1} & = & u_m^n + \frac{1}{2}k(\partial_t u_m^n + \partial_t u_m^{n+1}) - \frac{1}{2}k^3\partial_t^3 u_m^{n+\frac{1}{2}} \\ & \stackrel{\mbox{\tiny heat eq.}}{=} & u_m^n + \frac{1}{2}k(\partial_x^2 u_m^n + \partial_y^2 u_m^n + \partial_z^2 u_m^n + \partial_x^2 u_m^{n+1} + \partial_y^2 u_m^{n+1} + \partial_z^2 u_m^{n+1}) - \frac{1}{2}k^3\partial_t^3 u_m^{n+\frac{1}{2}} \end{array}$$

Discretizing the double derivative with central differences, and denoting the step sizes in x, y, z direction by h, f, g respectively, gives

$$\begin{array}{ll} u_m^{n+1} & = & u_m^n + \frac{1}{2}k(\frac{1}{h^2}\delta_x^2u_m^n + \frac{1}{f^2}\delta_y^2u_m^n + \frac{1}{g^2}\delta_z^2u_m^n + \frac{1}{h^2}\delta_x^2u_m^{n+1} + \frac{1}{f^2}\delta_y^2u_m^{n+1} + \frac{1}{g^2}\delta_z^2u_m^{n+1}) \\ & - \frac{1}{2}k(\frac{1}{12}h^2\partial_x^4u_m^n + \frac{1}{12}g^2\partial_y^4u_m^n\frac{1}{12}f^2\partial_z^4u_m^n + \frac{1}{12}h^2\partial_x^4u_m^{n+1} + \frac{1}{12}g^2\partial_y^4u_m^{n+1}\frac{1}{12}f^2\partial_z^4u_m^{n+1}) \\ & - \frac{1}{2}k^3\partial_t^3u_m^{n+\frac{1}{2}} \\ & = & u_m^n + \frac{r}{2}(\delta_x^2u_m^n + \delta_x^2u_m^{n+1}) + \frac{p}{2}(\delta_y^2u_m^n + \delta_y^2u_m^{n+1}) + \frac{q}{2}(\delta_z^2u_m^n + \delta_z^2u_m^{n+1}) + \tau_m^n \end{array}$$

where  $r=k/h^2$ ,  $p=k/f^2$ ,  $q=k/g^2$ , and  $\tau_m^n$  is the truncation error times k. The expression for  $\tau_m^n$  is

$$\tau_m^n = -\frac{1}{12}k^3\partial_t^2 u_m^{n+\frac{1}{2}} - \frac{1}{12}kh^2\partial_x^4 u_m^{n+\frac{1}{2}} - \frac{1}{12}kg^2\partial_y^4 u_m^{n+\frac{1}{2}} - \frac{1}{12}kf^2\partial_z^4 u_m^{n+\frac{1}{2}}$$
Kap. 3

#### 3.2. TRUNCATION ERROR IN THE CRANK-NICOLSON SCHEME

where we have used  $\frac{1}{2}(\partial_x^4 u_m^n+\partial_x^4 u_m^{n+})=\partial_x^4 u_m^{n+\frac{1}{2}}+O(k^2)$ . Hence, the truncation error is

$$\begin{array}{lcl} \frac{\tau_m^n}{k} & = & -\frac{1}{12}k^2\partial_t^2u_m^{n+\frac{1}{2}} - \frac{1}{12}h^2\partial_x^4u_m^{n+\frac{1}{2}} - \frac{1}{12}g^2\partial_y^4u_m^{n+\frac{1}{2}} - \frac{1}{12}f^2\partial_z^4u_m^{n+\frac{1}{2}} \\ & = & O(k^2+h^2+g^2+f^2) \end{array}$$



### Implementation

#### 4.1 Tools

The programming language chosen to implemented the system was c++. The arguments leading to this choice was:

- Most of the group members had some earlier experience with the language.
- It allows for a high level of abstraction without loosing control of the underlying hardware.
- The code can be easily parallelized for shared memory machines using OpenMP.
- Many libraries exist for c++ that implements highly optimized linear algebra functionality.

Other languages cosidered where Matlab and c.

The tool chosen to visualize the resulting data was gnuplet and ffmpeg. Writing a program using OpenGL was considered, but dismissed on the grounds of beeing too time consuming.

### 4.2 Program design

The program mainly consist of three parts:

- C++ implementation of Linear algebra functionality of the discrete equations.
- C++ implementation of the conjugate gradient method for solving the equations described.


• Bash script for generating plots and and movie of the generated data.

The Bash script is not discussed in further detail as it can be considered simple.

### 4.3 The physical system

The main task of the physical system is to implement a matrix-vector multiplication procedure for the heat equation and a method of calculating the heating properties of a microwave.

- 4.3.1 Partitioning of the problem
- 4.3.2 Updating alpha and beta values
- 4.3.3 Calculating the distribution of the microwave effect
- 4.3.4 The matrix-vector multiplication procedure
- 4.4 The conjugate gradient method as an iterative algorithm



### Experiments


### 5.1 Experiments

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus

vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.



### Conclusion

#### 6.1 Conclusion

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus

vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

# Bibliography

[1] Yi Huang and Xu Zhu. Microwave oven field uniformity analysis. In Antennas and Propagation Society International Symposium, 2005 IEEE, volume 3B, pages 217 – 220 vol. 3B, 2005.