

BROTEK India has all in one, universal, intelligent Thermal flow switch, Its probe with heating element and two temperature sensor, when no flow both thermal sensor has fix temperature difference, and during flow, flow rate is directly proportional of temp. Difference of thermal sensors, Temperature difference signal measuring and control by high precision processor and when its reach at fixed set point switching contact change over, Thermal flow switch is mass flow rate switch so its measure and control liquid, air and gas with same precision. It is a new generation thermal intelligent flow switch with full independent property rights developed by Brotek after many years of hard work.

BT-KP-XXXX



Technical Details

Process connection : As per the requirement
Probe Length : 15mm(Standard)/
As per requirement
Material : Electric Enclosure : Aluminium
Wetted part : S.S. 316
Flow rate : Liquid : 0 to 3 m/s,
Gas : 0 to 30m/s
Output : Relay, 220VAC, 16 A
Power supply : 24VDC
Power consumption : < 150 mA
Preheat Time : ≤3min
Response Time : Adjustable
Precision : ±1%
Pressure Limit : 10 bar
Temperature limit : 0 to 80°C
Programing through keyboard : alarm value,
High/low alarm, delay time, zero value, span
value, damping factor

Features

- High accuracy and Reliability
- Installation ease Standard threading makes it simple to install.
- On site easy to calibrate
- Adjustment ease Push-button for zero and full scale point setting and alarm setting.
- Compact in size, and making it easy to integrate into your equipment.
- Low Maintainance
- Display the value of the flow rate percentage and the bar percentage indication, and the relay alarm type indication.

Applications

Air/Gas-liquid dual-purpose type, can be widely used in industrial automation / mechanical equipment/ air compression industry / refrigeration and air conditioning, Industrial applications in water-cooled welding machines, laser equipment cooling systems, vacuum coating machines, electric furnaces, polysilicon ingot furnaces, etc.

