

BROTEK has all in one, universal, intelligent RF admittance microwave level switch, microwave field generate alarm when measuring point inserting few millimeters in to the medium, also its not effect by foam condensate and residue, by using microwave measuring principle possible to detect a conductive and non conductive medium from: liquid, solid and solid powder. Output of switch only when measuring point is completely cover by medium, also its measuring point has no dead end and is hygienic so level switch is suitable for CIP (Clean-in-Place), WIP (Wash-in-Place) and SIP (Sterilization-in-Place), available with different process connection as per industries requirement, and different temperature version for set up to 200°C

KP-XXXX



Technical Details

Mounting Position: Any, Top, Bottom, Side

Wetted Part Material: PEEK, SS304/ 316

Power supply : 12~33 VDC

Working Frequency: 40MHz~170MHz

Output : NPN/PNP/Relay

Current Rating : 20mA/100mA/2A

Repeatability : ± 1 mm

Damping: 0~5 adjustable

Power consumption : < 33 mA

Protection: IP66/ IP68

Pressure Limit : 10 bar

Temperature limit : 1) -40 to 85 °C,
2) -40 to 150 °C,
3) -40 to 200 °C

Process connection : Thread, tri-clamp, sanitary clamp, welding sleeve

Features

- Wide application, Suitable for solid and liquid with dielectric constant ≥ 1.5
- Stable detection Unaffected by bubbles
- Anti-hanging Can effectively detect adhesive conductive paste.
- Compact structure Suitable for equipment integration in small spaces
- Wetted material: PEEK and stainless steel Suitable for sanitary and industrial occasions
- Easy to use The alarm point can be set on site and the measured value can be viewed

Applications

Brotek switch detect and control : Water base media, oil base media, powder, granules, jelly, high viscous and pasty media, Food, beverage and pharma base Hygienic liquid, Liquid with foam, Dirty liquid like ETP, HTP, Bio-toilet, gobar (human and animal waste) fuel plant Low (Min.) and high (max.) level control at tank, mixture, conveyor belt, hopper Layer separation detection, Leakage detection



