

BROTEK OCUFM series of instruments directly measure the water level height in the channel or sink. When used to measure the flow rate of open channel, install the Weir through on the open channel. The Weir through converts the flow rate in the open channel to the level of the liquid level. The instrument measures the water level in the Weir through, and then calculates the discharge according to the water level-flow relationship of the corresponding Weir through. It is mainly used to measure sewage plants, sewage discharge outlets of enterprises and institutions, discharge of urban sewers and channels in irrigation and water conservancy. It is a new generation Open Channel Ultrasonic Flow Meter with full independent property rights developed by Brotek after many years of hard work.

BT-OCUFM



Technical Details

measuring range : 1 L / S ~ 99999.99 M / h,
determined according to different weirs.
Cumulative flow Maximum: 4290000000.00 m³
Standard range of liquid level : 5m/ 8m
Accuracy of liquid level measurement : 0.25%~0.50%
display : LCD
Resolution : ±3mm or 0.1%(which is greater)
power supply : 18~28VDC
Analog Output : 4-wire 4 ~ 20mA / 500 Ω load
signal communication : RS485, MODBUS protocol
Accuracy : Depends on weir type
Process temperature : -20~+80°C
Process pressure : Standard atmospheric pressure
Working environment humidity : ≤ 90% RH,
non condensing
Protection level : Transmitter IP66, sensor IP68
Sensor material : Anticorrosive ABS Plastic
Enclosure : Die-cast Aluminium

Features

- High accuracy and reliable operation
- Programming through a push button which leads to easy installation and on-site calibration.
- User friendly interface.
- Adaption to any kind of weir or flume.
- Backlight LCD display
- Built-in flow totalizer.
- Various of Units selected, including Cubic meter, liter/hour, liter/minute, Cubic feet etc.
- IP68 protection, ensure long-term operation for outdoor installation.
- Analog & Digital output for accessing data remotely.



Applications

Ultrasonic open channel Flowmeter is used to measure the flow of water in the open channel. It is mainly used to measure sewage plants, sewage discharge outlets of enterprises and institutions, discharge of urban sewers and channels in irrigation and water conservancy. Because our instrument uses ultrasonic wave through the air, measured by non-contact method. Therefore, under the condition of viscous and corrosive liquid, it has higher reliability and durability than contact instrument.

