

Session_14

Q.1 Given the following buggy code meant to calculate the total price of a Zomato order, identify and fix the syntax and runtime errors: let items = ["Burger", "Pizza", "Fries"]; let prices = [120, 250, 90]; let total = 0;for (i = 0; i < items.length; i++) { total += prices[i] } console.log("Total price is: " + total); Hint: Watch for assignment and loop variable issues.

A.1 #include <stdio.h>

```
int main() {  
  
    char *items[] = {"Burger", "Pizza", "Fries"};  
    int prices[] = {120, 250, 90};  
    int total = 0;  
  
    int i;  
  
    // Add the price of each item to total  
  
    for (i = 0; i < 3; i++) {  
        total += prices[i];  
    }  
  
    printf("Total price is: %d\n", total);  
  
    return 0;  
}
```

Q.2 Rewrite the following code to improve its indentation and add comments explaining each step, so that a beginner can understand what it does:

function isEven(num){if(num%2==0){return true;}else{return false;}}

A.2 #include <stdio.h>

// This function checks whether a number is even

```
int isEven(int num) {  
  
    // If the remainder after dividing by 2 is 0,  
  
    // the number is even  
  
    if (num % 2 == 0) {
```

Session_14

```
    return 1;
}
else {
    return 0;
}
}

int main() {
int number = 10;

    // Call the function and check the result

if (isEven(number)) {
    printf("%d is even.\n", number);
}
else {
    printf("%d is odd.\n", number);
}

return 0;
}
```

Q.3 Write a function `formatFollowersCount(count)` that takes a number and returns a formatted string like Instagram: 1500 as '1.5K', 1200000 as '1.2M', and numbers below 1000 as-is. Add clear comments and use proper indentation.

A.3 `#include <stdio.h>`

```
void formatFollowersCount(int count) {

    // If followers are 1 million or more
    if (count >= 1000000) {
        printf("%.1fM", count / 1000000.0);
    }
}
```

Session_14

```
// If followers are 1000 or more
else if (count >= 1000) {
    printf("%.1fK", count / 1000.0);
}

// If followers are below 1000
else { printf("%d", count);
}
}

int main() {
    int followers1 = 1500; int followers2 = 1200000;
    int followers3 = 500;

    printf("Followers: ");
    formatFollowersCount(followers1);
    printf("\n");
    printf("Followers: ");

    formatFollowersCount(followers2);
    printf("\n");
    printf("Followers: ");
    formatFollowersCount(followers3);
    printf("\n");

    return 0;
}
```

Q. 4 You are given a piece of JavaScript code that should print all even numbers from 1 to 10, but it doesn't work as expected: `for (let i = 1; i <= 10; i++) { if (i % 2 = 0) { console.log(i) } }` Find and fix the error, then rewrite the code with good indentation and at least one comment explaining the logic.

A.4 `#include <stdio.h>`
`int main() {`

Session_14

```
// Loop through numbers from 1 to 10
```

```
for (int i = 1; i <= 10; i++) {
```

```
// If remainder is 0, the number is even
```

```
if (i % 2 == 0) {
```

```
printf("%d\n", i);
```

```
    }
```

```
}
```

```
return 0;
```

```
}
```
