InterviewBit

# LLM Interview Questions and Answers (2026) | Large Language Models



To view the live version of the page, click here.

© Copyright by Interviewbit

# Contents

## Basic LLM Interview Questions


1. Explain the Transformer architecture. What are its key components?
2. What is the attention mechanism? Explain self-attention and multi-head attention.
3. What is tokenization in LLMs? Compare BPE, WordPiece, and SentencePiece.
4. What are embeddings in LLMs? Explain word embeddings vs contextual embeddings.
5. What is the context window in LLMs? Why does it matter?
6. Explain encoder-only, decoder-only, and encoder-decoder transformer models with examples.
7. What is perplexity in LLMs? How is it used to evaluate model performance?
8. What are temperature, top-k, and top-p (nucleus) sampling? How do they affect text generation?
9. What is the difference between pre-training and fine-tuning in LLMs?
10. What is a Large Language Model (LLM)? How does it differ from traditional NLP models?


## GenAI LLM Interview Questions


11. Explain zero-shot, one-shot, and few-shot learning in LLMs with examples.
12. What is Generative AI? How do LLMs fit into the GenAI landscape?
13. Explain prompt engineering. What are the best practices for writing effective prompts?
14. What is chain-of-thought (CoT) prompting? How does it improve LLM reasoning?
15. What is hallucination in LLMs? What techniques can mitigate it?
16. Compare GPT-4, Claude, Gemini, and Llama models. What are their key differences?
17. What is RLHF (Reinforcement Learning from Human Feedback)? How does it align LLMs with human preferences?



© Copyright by Interviewbit

## GenAI LLM Interview Questions

(.....Continued)

19. Explain function calling/tool use in LLMs. How does it enable LLMs to interact with external systems?
20. What are the ethical considerations and safety concerns when deploying LLMs in production?

## LLM Fine-Tuning Interview Questions

21. How do you prepare a dataset for LLM fine-tuning? What data formats are commonly used?
22. What is quantization in LLMs (INT8, INT4, FP16, BF16)? How does it affect performance and memory?
23. Explain DPO (Direct Preference Optimization) vs RLHF for alignment fine-tuning.
24. How do you evaluate a fine-tuned LLM? What metrics and benchmarks are used?
25. What is catastrophic forgetting in fine-tuning? How can you prevent it?
26. What is fine-tuning in LLMs? When should you fine-tune vs use prompt engineering?
27. Explain LoRA (Low-Rank Adaptation). How does it enable efficient fine-tuning?
28. What is QLoRA? How does it combine quantization with LoRA for memory-efficient training?
29. What is PEFT (Parameter-Efficient Fine-Tuning)? Compare different PEFT methods.
30. Explain instruction tuning. How does it improve an LLM's ability to follow instructions?

## LLM RAG Interview Questions

31. What is the "Lost in the Middle" problem in RAG? How can you mitigate it?
32. What is RAG (Retrieval-Augmented Generation)? Why is it important?
33. Explain the RAG pipeline architecture. What are its key components?
34. What are vector databases? Compare Pinecone, Weaviate, ChromaDB, Milvus, and FAISS.
35. What are embedding models? How do you choose the right one?

InterviewBit

## LLM RAG Interview Questions

(.....Continued)

36. Explain chunking strategies for RAG. How do chunk size and overlap affect retrieval?
37. What is semantic search vs keyword search? When would you use each?
38. What is hybrid search in RAG? How do you combine dense and sparse retrieval?
39. How do you handle multi-document retrieval and re-ranking in RAG pipelines?
40. How do you evaluate RAG system performance?

## LLM System Design Interview Questions

41. Design a scalable chatbot system using LLMs. What components would you include?
42. How would you design an LLM-powered customer support system that handles 10,000 concurrent users?
43. What are the key considerations for LLM inference optimization?
44. How do you implement rate limiting and cost management for LLM APIs in production?
45. Design a document Q&A system using RAG. How would you handle millions of documents?
46. How would you implement streaming responses for LLM applications? What protocols would you use?
47. What is KV cache in LLM inference? How does it improve performance?
48. How do you monitor and observe LLM applications in production?
49. Design an LLM gateway/router that routes requests to different models.
50. How would you implement guardrails and content moderation for LLM outputs?


© Copyright by Interviewbit

# Let's get Started

2026-ready LLM interview guide with questions on transformer architecture, fine-tuning (LoRA/QLoRA/PEFT), RAG pipelines, prompt engineering, tokenization, embeddings, hallucination mitigation, LLM system design, GenAI applications, and deployment for ML engineers & AI researchers. (InterviewBit)

## Basic LLM Interview Questions

### 1. Explain the Transformer architecture. What are its key components?

The Transformer architecture is the foundation of modern LLMs. Introduced in the paper *Attention Is All You Need*, it replaces recurrence with attention mechanisms to process text in parallel.

Key components include:

**1. Input Embeddings**
Convert tokens into numerical vectors.

**2. Positional Encoding**
Adds sequence order information since transformers process tokens simultaneously.

**3. Self-Attention Mechanism**
Determines the importance of each token relative to others.

**4. Multi-Head Attention**
Allows the model to focus on different relationships simultaneously.

**5. Feedforward Neural Network**
Processes attention outputs for deeper learning.

**6. Layer Normalization & Residual Connections**
Improve training stability and gradient flow.

InterviewBit


© Copyright by Interviewbit

Transformers enable parallel processing, scalability, and long-range dependency understanding.

## 2. What is the attention mechanism? Explain self-attention and multi-head attention.

The attention mechanism allows models to focus on the most relevant words when processing language.

### Self-Attention

Self-attention evaluates relationships between words in a sentence.

Example:
In “The cat sat on the mat because **it** was soft,” the model links “it” to “mat.”

Steps:

- Compute Query, Key, Value vectors
- Calculate attention scores
- Assign weights to relevant tokens

### Multi-Head Attention

Instead of one attention calculation, multiple attention heads run in parallel.

Benefits:


© Copyright by Interviewbit

- Captures semantic, syntactic, and contextual relationships
- Improves contextual understanding
- Enhances language reasoning

This mechanism enables transformers to understand context more effectively than previous NLP models.

## 3. What is tokenization in LLMs? Compare BPE, WordPiece, and SentencePiece.

**Tokenization** converts text into smaller units (tokens) that models can process.

Example:
"unbelievable" → "un", "believ", "able"

**Byte Pair Encoding (BPE)**

- Merges frequent character pairs
- Efficient vocabulary size
- Used in GPT models

**WordPiece**


© Copyright by Interviewbit

- Builds tokens based on likelihood
- Handles unknown words better
- Used in BERT

**SentencePiece**

- Treats text as raw characters
- Language-independent
- Useful for multilingual models

Tokenization affects vocabulary size, performance, and memory usage.

## 4. What are embeddings in LLMs? Explain word embeddings vs contextual embeddings.

Embeddings are vector representations of text that capture semantic meaning.

**Word Embeddings**

Each word has a fixed vector regardless of context.
Example: Word2Vec, GloVe.

Limitation:

- Same vector for different meanings of a word.


© Copyright by Interviewbit

### Contextual Embeddings

Vectors change depending on context.

Example:

- "bank" in river bank vs financial bank

Transformers generate contextual embeddings dynamically, improving accuracy in language understanding.

## 5. What is the context window in LLMs? Why does it matter?

The context window is the maximum number of tokens an LLM can process at once.

Importance:

- Determines how much conversation or document the model remembers
- Affects long-document processing
- Impacts coherence and reasoning ability

Larger context windows enable:

- long-form summarization
- multi-document analysis
- complex reasoning tasks

However, larger windows increase memory and computation costs.

## 6. Explain encoder-only, decoder-only, and encoder-decoder transformer models with examples.


© Copyright by Interviewbit

Transformer models differ based on how they process input and output.

**Encoder-Only Models**

- Understand text
- Used for classification, search, sentiment analysis
- Example: BERT

**Decoder-Only Models**

- Generate text
- Used in chatbots and content generation
- Example: GPT models

**Encoder-Decoder Models**

- Convert input to output sequences
- Used in translation and summarization
- Example: T5, BART

Each architecture is optimized for different NLP tasks.


© Copyright by Interviewbit

## 7. What is perplexity in LLMs? How is it used to evaluate model performance?

Perplexity measures how well a language model predicts text.

- Lower perplexity = better predictions
- Indicates model confidence
- Common evaluation metric for language modeling

If a model assigns high probability to correct words, perplexity decreases.

Limitations:

- Does not measure reasoning or factual accuracy
- Should be combined with human evaluation and task-specific metrics

## 8. What are temperature, top-k, and top-p (nucleus) sampling? How do they affect text generation?

These parameters control randomness during text generation.

### Temperature

Controls randomness.

- Low (0.2–0.5): deterministic, factual
- High (0.8–1.0): creative, diverse

### Top-k Sampling


© Copyright by Interviewbit

Model selects from the top **k** most probable tokens.

- Lower k → safer outputs
- Higher k → more variety

**Top-p (Nucleus) Sampling**

Selects tokens whose cumulative probability exceeds **p**.

- Produces more natural text
- Balances diversity and coherence

These settings control creativity, accuracy, and diversity in outputs.

## 9. What is the difference between pre-training and fine-tuning in LLMs?

**Pre-training**

- Model learns language patterns from massive datasets
- Uses self-supervised learning
- Expensive and compute-intensive

**Fine-tuning**


© Copyright by Interviewbit

- Adapts a pre-trained model to a specific task
- Requires smaller datasets
- Improves performance for domain-specific use

Examples:

- Fine-tuning for medical chatbots
- Legal document analysis
- customer support automation

Modern techniques like LoRA and PEFT make fine-tuning more efficient.

## 10. What is a Large Language Model (LLM)? How does it differ from traditional NLP models?

A Large Language Model (LLM) is a deep learning model trained on massive text datasets to understand, generate, and reason with human language. Modern LLMs use transformer architecture and billions of parameters to perform tasks such as summarization, translation, question answering, and code generation.

Traditional NLP models relied on rule-based systems, statistical methods, or smaller neural networks like RNNs and LSTMs. These systems required task-specific training and feature engineering.

LLMs differ by:


© Copyright by Interviewbit

- Learning language patterns from vast datasets
- Performing multiple tasks without retraining
- Supporting zero-shot and few-shot learning
- Capturing contextual meaning more effectively

Examples include OpenAI GPT models, Anthropic Claude, Meta Llama, and Google Gemini.

# GenAI LLM Interview Questions

## 11. Explain zero-shot, one-shot, and few-shot learning in LLMs with examples.

These techniques describe how many examples a model needs to perform a task.

**Zero-shot learning**
The model performs a task without examples.
Example:

```
"Translate this sentence to French."
```

**One-shot learning**
The model receives one example.
Example:

```
English: Hello → French: Bonjour
Translate: Good morning →?
```

**Few-shot learning**
The model receives multiple examples to guide output.


© Copyright by Interviewbit

Benefits:

- improves accuracy
- helps format responses
- reduces the need for retraining

Few-shot prompting is widely used in real-world GenAI applications.

## 12. What is Generative AI? How do LLMs fit into the GenAI landscape?

**Generative AI** refers to AI systems that create new content such as text, images, audio, video, and code. Unlike traditional AI that focuses on classification or prediction, generative models produce original outputs based on learned patterns.

**Large Language Models (LLMs)** are a core component of Generative AI. They generate human-like text, answer questions, summarize documents, and assist in coding and research.

LLMs power applications such as:

- conversational assistants
- content creation tools
- enterprise knowledge assistants
- code generation systems

Models like OpenAI GPT, Anthropic Claude, Google Gemini, and Meta Llama demonstrate how LLMs serve as the backbone of modern GenAI systems.

## 13. Explain prompt engineering. What are the best practices for writing effective prompts?


© Copyright by Interviewbit

Prompt engineering is the process of designing inputs that guide an LLM to produce accurate, relevant, and structured outputs.

**Best practices:**

- Be clear and specific about the task
- Provide context and constraints
- Specify output format (bullet points, table, summary)
- Use step-by-step instructions for complex tasks
- Include examples when needed
- Avoid ambiguity and overly broad queries

Example:

```
Weak prompt: Explain climate change.
Effective prompt: Explain climate change causes in 5 bullet points suitable for a s
```

Effective prompt engineering improves accuracy, reduces hallucinations, and enhances reliability in production systems.

## 14. What is chain-of-thought (CoT) prompting? How does it improve LLM reasoning?

Chain-of-Thought (CoT) prompting encourages the model to reason step by step rather than giving a direct answer.

Example:

Instead of:


© Copyright by Interviewbit

```
"What is 17 × 24?"
```

Use:

```
"Solve step by step."
```

Benefits:

- improves logical reasoning
- enhances multi-step problem solving
- increases accuracy in math and analytical tasks
- makes decision reasoning more transparent

CoT prompting is especially useful in finance, coding, research, and analytical problem-solving.

## 15. What is hallucination in LLMs? What techniques can mitigate it?

Hallucination occurs when an LLM generates incorrect, fabricated, or misleading information presented as factual.

Common causes:

- incomplete training data
- ambiguous prompts
- lack of factual grounding


© Copyright by Interviewbit

**Mitigation techniques:**

- Retrieval-Augmented Generation (RAG) for factual grounding
- prompt constraints and source citation requirements
- temperature reduction for deterministic responses
- human-in-the-loop validation
- fine-tuning with domain data

Reducing hallucinations is critical in healthcare, legal, finance, and enterprise applications.

## 16. Compare GPT-4, Claude, Gemini, and Llama models. What are their key differences?

Modern LLMs differ in architecture focus, accessibility, and deployment flexibility.

**OpenAI GPT models**

- strong reasoning and coding capabilities
- widely used in enterprise applications

**Anthropic Claude**

- safety-focused design
- large context windows
- strong document analysis

**Google Gemini**


© Copyright by Interviewbit

- multimodal capabilities
- integration with Google ecosystem

**Meta Llama**

- open-weight models
- customizable and cost-efficient deployment

Choice depends on use case, cost, privacy needs, and deployment environment.

## 17. What is RLHF (Reinforcement Learning from Human Feedback)? How does it align LLMs with human preferences?

Reinforcement Learning from Human Feedback (RLHF) is a training method used to align LLM outputs with human expectations and values.

Process:

1. Model generates responses
2. Humans rank responses based on quality and safety
3. The reward model learns preferences
4. The model is optimized using reinforcement learning

Benefits:


© Copyright by Interviewbit

- improves helpfulness and safety
- reduces toxic or harmful responses
- aligns outputs with user intent

RLHF is essential for deploying safe and user-aligned AI systems.

## 18. What are AI agents? How do LLMs power autonomous agents (AutoGPT, LangChain agents)?

AI agents are autonomous systems that can plan, reason, and execute tasks with minimal human intervention.

LLMs enable agents to:

- understand goals
- plan task sequences
- interact with tools and APIs
- adapt based on results

Frameworks like LangChain support building LLM-powered agents, while AutoGPT-style systems can autonomously complete multi-step objectives.

Use cases include:

- research automation
- workflow orchestration
- customer support automation


© Copyright by Interviewbit

## 19. Explain function calling/tool use in LLMs. How does it enable LLMs to interact with external systems?

Function calling allows LLMs to invoke external tools, APIs, or databases to retrieve real-time or structured data.

Instead of generating guesses, the model:

1. recognizes when external data is needed
2. calls a defined function or API
3. retrieves results
4. integrates results into its response

Examples:

- checking weather APIs
- retrieving database records
- performing calculations
- triggering workflows

This capability improves accuracy, enables automation, and supports enterprise system integration.

## 20. What are the ethical considerations and safety concerns when deploying LLMs in production?

Deploying LLMs introduces ethical and safety risks that must be addressed.

**Key concerns:**


© Copyright by Interviewbit

- Bias and unfair outputs
- misinformation and hallucinations
- Data privacy and sensitive information leakage
- misuse for phishing, scams, or harmful content
- lack of transparency in decision-making

**Mitigation strategies:**

- Bias evaluation and monitoring
- guardrails and content moderation
- human oversight
- privacy-preserving training and deployment
- audit logging and compliance controls

Responsible AI deployment ensures trust, safety, and regulatory compliance.

# LLM Fine-Tuning Interview Questions

## 21. How do you prepare a dataset for LLM fine-tuning? What data formats are commonly used?

Dataset preparation directly impacts model performance.

**Steps:**


© Copyright by Interviewbit

- collect high-quality domain data
- clean and remove duplicates/noise
- ensure consistent formatting
- remove sensitive information
- split into training/validation sets

**Common formats:**

- JSON instruction-response pairs
- conversational chat format
- prompt-completion format

Well-structured data improves training efficiency and output quality.

## 22. What is quantization in LLMs (INT8, INT4, FP16, BF16)? How does it affect performance and memory?

Quantization reduces numerical precision of model weights to lower memory usage and speed up inference.

**Formats:**

- FP16/BF16: balanced performance and accuracy
- INT8: reduced memory with minimal accuracy loss
- INT4: extreme compression for edge deployment


© Copyright by Interviewbit

**Benefits:**

- faster inference
- reduced hardware requirements
- lower deployment costs

Trade-off: lower precision may slightly reduce accuracy.

## 23. Explain DPO (Direct Preference Optimization) vs RLHF for alignment fine-tuning.

Both methods align model outputs with human preferences.

**RLHF**

- uses reward models and reinforcement learning
- complex and resource intensive

**DPO**

- directly optimizes preference data
- simpler and more stable training
- removes need for reward model

DPO is emerging as a more efficient alternative for alignment tuning.

## 24. How do you evaluate a fine-tuned LLM? What metrics and benchmarks are used?

Evaluation ensures the fine-tuned model meets performance goals.

**Metrics:**


© Copyright by Interviewbit

- accuracy and F1 score
- perplexity reduction
- BLEU/ROUGE for text tasks
- human evaluation for helpfulness

**Benchmarks:**

- domain-specific test sets
- instruction-following tasks
- reasoning and QA datasets

Robust evaluation combines automated metrics with human judgment.

## 25. What is catastrophic forgetting in fine-tuning? How can you prevent it?

Catastrophic forgetting occurs when fine-tuning causes a model to lose previously learned knowledge.

**Prevention strategies:**


© Copyright by Interviewbit

- use smaller learning rates
- freeze core layers
- apply PEFT methods like LoRA
- mix original training data with new data
- use regularization techniques

Balancing new learning with retained knowledge ensures model stability.

## 26. What is fine-tuning in LLMs? When should you fine-tune vs use prompt engineering?

**Fine-tuning** adapts a pre-trained LLM using additional domain-specific data to improve performance on specialized tasks.

**Use prompt engineering when:**

- Tasks are general-purpose
- Rapid iteration is needed
- No training infrastructure is available

**Use fine-tuning when:**


© Copyright by Interviewbit

- A consistent output style is required
- Domain expertise (legal, medical, finance) is needed
- Prompts become too long or complex
- Improved accuracy and latency are required

Fine-tuning modifies model weights, while prompt engineering guides behavior without retraining.

## 27. Explain LoRA (Low-Rank Adaptation). How does it enable efficient fine-tuning?

LoRA (Low-Rank Adaptation) is a parameter-efficient fine-tuning method that freezes the original model weights and inserts small trainable matrices into transformer layers.

**How it works:**

- decomposes weight updates into low-rank matrices
- trains only a tiny subset of parameters
- merges updates during inference

**Benefits:**


© Copyright by Interviewbit

- reduces GPU memory usage
- faster training time
- maintains base model knowledge
- enables multiple task-specific adapters

LoRA allows efficient customization without retraining the full model.

## 28. What is QLoRA? How does it combine quantization with LoRA for memory-efficient training?

QLoRA enhances LoRA by applying quantization to the base model while fine-tuning low-rank adapters.

**Process:**

- base model weights stored in 4-bit precision
- LoRA adapters trained in higher precision
- memory-efficient gradient updates

**Advantages:**

- enables training large models on limited hardware
- significantly reduces VRAM requirements
- maintains near full-precision performance

QLoRA makes fine-tuning billion-parameter models feasible on consumer GPUs.


© Copyright by Interviewbit

## 29. What is PEFT (Parameter-Efficient Fine-Tuning)? Compare different PEFT methods.

**Parameter-Efficient Fine-Tuning (PEFT)** methods update only small portions of a model instead of all weights.

**Common PEFT methods:**

**LoRA**

- injects low-rank matrices
- efficient and widely used

**Prefix Tuning**

- prepends learnable tokens to attention layers
- influences model behavior without weight changes

**Adapters**

- small neural modules inserted between layers
- modular and reusable

PEFT reduces compute cost, speeds training, and supports multi-task adaptation.

## 30. Explain instruction tuning. How does it improve an LLM's ability to follow instructions?

Instruction tuning trains an LLM on datasets containing instructions paired with ideal responses.

Example:


© Copyright by Interviewbit

```
Instruction: “Summarize this paragraph.”
Response: structured summary
```

**Benefits:**

- improves task comprehension
- enhances response structure
- increases helpfulness and consistency
- enables better zero-shot performance

Instruction tuning is key to conversational assistants and task-oriented AI systems.

# LLM RAG Interview Questions

## 31. What is the “Lost in the Middle” problem in RAG? How can you mitigate it?

LLMs tend to prioritize information at the beginning and end of long context windows, ignoring middle content.

**Mitigation strategies:**

- reorder retrieved chunks by importance
- place most relevant content first
- use summarization before insertion
- limit context size
- use hierarchical retrieval


© Copyright by Interviewbit

Proper context structuring improves response accuracy.

## 32. What is RAG (Retrieval-Augmented Generation)? Why is it important?

RAG combines information retrieval with LLM generation to produce accurate, context-aware responses.

**Why it matters:**

- reduces hallucinations
- enables real-time knowledge retrieval
- supports enterprise document search
- keeps responses grounded in sources

RAG is widely used in chatbots, knowledge assistants, and customer support systems.

## 33. Explain the RAG pipeline architecture. What are its key components?

A typical RAG pipeline includes:


© Copyright by Interviewbit

1. **Data ingestion** – collect and preprocess documents
2. **Chunking** – split content into manageable segments
3. **Embedding generation** – convert text into vector representations
4. **Vector storage** – store embeddings in a vector database
5. **Retrieval** – find relevant chunks based on queries
6. **Augmented prompt** – supply retrieved context to LLM
7. **Generation** – LLM produces grounded response

This architecture enables accurate and context-rich answers.

## 34. What are vector databases? Compare Pinecone, Weaviate, ChromaDB, Milvus, and FAISS.

Vector databases store and retrieve embeddings efficiently.

- **Pinecone** – fully managed, scalable, cloud-native
- **Weaviate** – hybrid search and semantic features
- **Chroma** – lightweight and developer-friendly
- **Milvus** – high-performance large-scale retrieval
- **FAISS** – efficient local similarity search library

Choice depends on scalability, hosting needs, and performance requirements.


© Copyright by Interviewbit

## 35. What are embedding models? How do you choose the right one?

Embedding models convert text into dense vectors capturing semantic meaning.

**Selection criteria:**

- domain compatibility
- multilingual support
- vector dimensionality
- retrieval accuracy vs latency
- cost and deployment constraints

High-quality embeddings improve retrieval precision and overall RAG performance.

## 36. Explain chunking strategies for RAG. How do chunk size and overlap affect retrieval?

Chunking divides documents into smaller sections for efficient retrieval.

**Key considerations:**

- Smaller chunks improve precision
- Larger chunks preserve context
- Overlap prevents context loss across boundaries

Typical overlap: 10–20%.

Proper chunking balances context richness and retrieval accuracy.


© Copyright by Interviewbit

## 37. What is semantic search vs keyword search? When would you use each?

**Semantic search**

- retrieves results based on meaning
- uses embeddings and similarity scoring
- ideal for natural language queries

**Keyword search**

- matches exact terms
- faster and deterministic
- useful for structured queries

Semantic search is preferred for RAG systems.

## 38. What is hybrid search in RAG? How do you combine dense and sparse retrieval?

Hybrid search combines semantic similarity with keyword matching.

**Method:**

- 3dense retrieval using embeddings
- sparse retrieval using BM25/keyword scoring
- combine rankings for improved relevance

Benefits:


© Copyright by Interviewbit

- better recall
- improved accuracy
- handles exact matches and semantic meaning

Hybrid search enhances retrieval robustness.

## 39. How do you handle multi-document retrieval and re-ranking in RAG pipelines?

RAG systems often retrieve multiple relevant chunks.

**Process:**

- retrieve top-k relevant chunks
- remove duplicates and irrelevant content
- re-rank using cross-encoder models
- pass the best context to LLM

Re-ranking improves answer quality and reduces noise.

## 40. How do you evaluate RAG system performance?

Evaluation focuses on retrieval and response quality.

**Metrics:**


© Copyright by Interviewbit

- Recall@K
- Precision@K
- Mean Reciprocal Rank (MRR)
- NDCG (ranking quality)
- answer relevance and faithfulness

Human evaluation helps verify factual accuracy and usability.

# LLM System Design Interview Questions

## 41. Design a scalable chatbot system using LLMs. What components would you include?

A scalable LLM chatbot architecture includes:

**Core components**

- Client interface (web/mobile/chat platforms)
- API gateway for request routing and authentication
- Application server handling session state and orchestration
- Prompt builder and conversation memory module
- LLM inference layer (hosted API or self-hosted model)

**Supporting systems**


© Copyright by Interviewbit

- Vector database for context retrieval
- Caching layer for repeated responses
- Logging and analytics pipeline
- Moderation and safety filters

**Scalability**

- autoscaling containers (Kubernetes)
- load balancing and queue-based request handling

This design ensures reliability, personalization, and efficient response generation.

## 42. How would you design an LLM-powered customer support system that handles 10,000 concurrent users?

Handling high concurrency requires a distributed architecture and intelligent orchestration.

**Design considerations**

- load balancers to distribute incoming traffic
- asynchronous request queues (Kafka/RabbitMQ)
- horizontally scalable inference servers
- caching responses for frequently asked questions
- RAG integration for knowledge base answers


© Copyright by Interviewbit

**Performance optimization**

- response streaming to reduce perceived latency
- fallback to rule-based automation for simple queries
- tiered model usage (small model → large model escalation)

**Reliability**

- failover mechanisms
- SLA monitoring and autoscaling

This approach ensures consistent performance under heavy load.

## 43. What are the key considerations for LLM inference optimization?

Optimizing inference improves speed, cost efficiency, and scalability.

**Key techniques**

- batching multiple requests to maximize GPU utilization
- response caching for repeated prompts
- quantization (INT8/INT4) to reduce memory footprint
- model parallelism to distribute large models across GPUs
- token streaming to improve perceived latency

**Operational benefits**


© Copyright by Interviewbit

- lower infrastructure cost
- faster response times
- improved throughput

Inference optimization is critical for real-time production systems.

## 44. How do you implement rate limiting and cost management for LLM APIs in production?

LLM APIs can generate high usage costs if not controlled.

**Cost control strategies**

- rate limiting per user/API key
- quota enforcement and token caps
- caching frequent responses
- prompt compression and truncation
- dynamic model selection based on complexity

**Monitoring**

- track token usage per request
- set budget alerts and thresholds
- analyze usage patterns

These controls prevent abuse and ensure predictable operating costs.


© Copyright by Interviewbit

## 45. Design a document Q&A system using RAG. How would you handle millions of documents?

A large-scale RAG system requires efficient indexing and retrieval.

**Architecture**

- distributed document ingestion pipeline
- chunking and embedding generation
- vector storage with sharding and indexing
- metadata filtering for targeted retrieval
- re-ranking for relevance optimization

**Scaling strategies**

- hierarchical indexing
- approximate nearest neighbor (ANN) search
- caching popular queries
- incremental indexing for updates

This design supports fast retrieval across massive document collections.

## 46. How would you implement streaming responses for LLM applications? What protocols would you use?

Streaming improves user experience by delivering responses progressively.

**Implementation**


© Copyright by Interviewbit

- enables token streaming from the LLM inference server
- send partial responses to the client in real time

**Protocols**

- WebSockets for real-time bidirectional communication
- Server-Sent Events (SSE) for unidirectional streaming
- HTTP chunked transfer for incremental delivery

**Benefits**

- reduced perceived latency
- improved interactivity
- better UX for long responses

Streaming is essential for conversational interfaces.

## 47. What is KV cache in LLM inference? How does it improve performance?

**Key-Value (KV) cache** stores previously computed attention keys and values during autoregressive generation.

**How it works**

- saves attention computations from prior tokens
- reuses cached representations for new tokens

**Benefits**


© Copyright by Interviewbit

- Significantly faster token generation
- Reduced compute overhead
- Improved throughput for long responses

KV caching is essential for efficient real-time inference.

## 48. How do you monitor and observe LLM applications in production?

Observability ensures performance, reliability, and output quality.

**Metrics to monitor**

- latency and response time
- token usage and cost per request
- throughput and error rates
- model response quality and user feedback

**Tools & practices**

- centralized logging and tracing
- prompt/response auditing
- anomaly detection alerts
- A/B testing outputs

Monitoring enables continuous improvement and reliability.


© Copyright by Interviewbit

## 49. Design an LLM gateway/router that routes requests to different models.

An LLM gateway optimizes cost and performance by selecting the appropriate model.

**Routing logic**

- simple queries → smaller low-cost model
- complex reasoning → larger advanced model
- sensitive tasks → secure private model

**Components**

- request classifier
- policy engine and routing rules
- fallback and retry mechanisms
- usage tracking and cost monitoring

This architecture balances performance, accuracy, and cost efficiency.

## 50. How would you implement guardrails and content moderation for LLM outputs?

Guardrails ensure safe, compliant, and trustworthy outputs.

**Implementation layers**


© Copyright by Interviewbit

- input filtering for harmful prompts
- output moderation using safety classifiers
- rule-based policy enforcement
- redaction of sensitive data

**Advanced safeguards**

- human review workflows for flagged content
- jailbreak detection mechanisms
- domain-specific compliance rules

Strong guardrails are essential for responsible AI deployment.


© Copyright by Interviewbit

# Links to More Interview Questions

Accenture Interview Questions

Accolite Interview Questions

Adobe Interview Questions

Amazon Interview Questions

Amdocs Interview Questions

Apisero Interview Questions

Arcesium Interview Questions

Avasoft Interview Questions

Axis Bank Interview Questions

Capgemini Interview Questions

Cisco Interview Questions

Cognizant Interview Questions

Dassault Systemes Interview Questions

De Shaw Interview Questions

Delhivery Interview Questions

Deloitte Interview Questions

Directi Interview Questions

Dxc Interview Questions

Epam Interview Questions

Ey Interview Questions

Facebook Interview Questions

Flipkart Interview Questions

Genc Interview Questions

Genpact Interview Questions

Goldman Sachs Interview Questions

Google Interview Questions

Hashedin Interview Questions

Hcl Interview Questions

Hexaware Interview Questions

Ibm Interview Questions

Infosys Interview Questions

Intuit Interview Questions

Jp Morgan Interview Questions



© Copyright by Interviewbit