

PROJECT REPORT

Signature Verification Using Python

Under the supervision of:

Dr. Shwetang Dubey

Submitted By:

Ishika Saxena[E23CSEU2248]

Khushi Srivastava[E23CSEU2243]



Plot Nos 8-11, TechZone 2, Greater Noida, Uttar Pradesh 201310
2024-26

ABSTRACT

This project report is centered on developing a system for detecting and verifying signatures through techniques involving image processing. Essentially, the design should focus on developing an accurate system that can detect signatures between and from various kinds of handwritten or printed contents in documents. The modules in this system are: image preprocessing, feature extraction, signature detection, and signature verification.

The preprocessing module in the image enhances the quality of the input images by reducing noise and eliminating artifacts. The output feature set of the signature image obtained through various transforms, such as Fourier Transform and Wavelet Transform. Then it undertakes further analysis using the signatures with the detection module to analyze whether there is any signature present within the image. Verification is done after detecting a signature whether it is authentic or not based on comparison with the reference sample.

The proposed system has been tested over a database of signature images, with highly impressive results for both signature detection and verification tasks. This technology is highly applicable to authentication and verification in the processes of documents.

The report further evaluates the application of deep learning techniques, especially CNNs, in signature analysis. A large dataset of signature images was used to train the CNN model, and its performance was compared with conventional methods. The results show the CNN-based approach significantly outperforms conventional approaches at 99.5% average accuracy in signature detection and 98.6% in verification.

In conclusion, this method for detection and verification of digital signatures is quite effective for practical use. Deep learning further improves performance; therefore, it can be employed as a strong solution for applications in real life.

TABLE OF CONTENTS

Title.....	I
Abstract.....	II
Contents.....	III
INTRODUCTION.....	1
PROBLEM STATEMENT.....	2
LITERATURE REVIEW.....	4
PROPOSED MODEL.....	17
IMPLEMENTATION AND RESULTS.....	18
CONCLUSION.....	20
Future Scope.....	22
References.....	23

INTRODUCTION

1.1 Background Study:

Verification of a digital signature is carried out through the validation process, which can be achieved using a digital signature algorithm and its related public key. Institutionally, for example, at banks, intelligence agencies, and many more, it's one technique to authenticate one's identity. As such, comparison of signatures is a very common procedure that banks conduct in their branches and other transaction points. Signature verification software normally checks against a stored reference image a live or scanned signature image. Signatures are legal authorizations and the need for reliable signature verification continues to rise. Handwritten signatures are unique, that is only one has that, and cannot be replicated with accuracy, so these are in great demand in research in the field of pattern recognition and image processing.

Signature verification systems are applied to different applications; these include access control, private protection, and security protocols. Signature verification is that process in which it confirms the identity of a person who has signed the document using his or her written signature.

There are two major categories of signature verification systems [1]:

1. Online Signature Verification System – This type uses devices like tablets to capture dynamic data such as pressure and speed during the signing process.
2. Offline Signature Verification System – In this system, the signature is created offline and analyzed using an image of the written signature.

Offline verification can be performed using two approaches. The writer-dependent approach involves creating specific models for both genuine and forged signatures of each individual. A sample signature is then compared to these models for verification. However, this method requires creating a new model for each new user, which can be time-consuming. The writer-independent approach, often used by forensic experts, relies on general models that do not require individual-specific training. Despite an average accuracy of 84% [2], writer-independent verification faces challenges due to morphological differences between individuals.

Research has shown that online verification typically achieves higher accuracy than offline methods because offline verification lacks dynamic information like pressure and signing speed. Signatures are often influenced by factors such as stress, emotion, fatigue, and physical or mental conditions, which can lead to inconsistencies in handwriting. Designing an effective signature verification system involves addressing key challenges, including data collection, preprocessing, feature extraction, comparison, and performance evaluation. Surveys of methods used in offline signature verification up to 1993 are available in references [1, 2, and 3]. Techniques developed between 1993 and 2000 have been detailed in subsequent surveys, including fuzzy-based approaches for offline verification [7,8]. J.A. Unar and colleagues proposed a fuzzy-based offline signature system that employs a multi-stage classifier combining global and local features for recognition.

The Hidden Markov Model (HMM)-based approach in their system dynamically determines user-specific parameters

to establish optimal decision rules. This system also incorporates cross-validation techniques and uses the PBGA algorithm to derive fuzzy rules, enhancing the verification process. These rules, though numerous and parameterized, collectively improve system performance by aggregating outputs from multiple rules.

The pseudo-outer product-based fuzzy neural network method focuses on detecting expert forgeries. Key attributes of this model have been derived and adapted from prior studies [6]. With advances in computing power since the 1960s, automated signature verification and forgery detection have become feasible and continue to be a significant area of research.

Handwritten forgeries can be categorized as follows:

1. **Random Forgery** – Created by signing the victim's name in the forger's own style.
2. **Simple Forgery** – An unskilled imitation of the victim's signature.
3. **Professional Forgery** – The most challenging type, produced by skilled impostors .

Studies such as those by Ammar et al. have explored efficient forgery detection techniques since the 1980s.

1.2 Aims and Objectives:

The aim of this study is to propose an effective method for authenticating online handwritten signatures. Specific objectives include:

1. Obtaining offline signatures using a pen and a paper and taking photos of those signatures.
2. Moving the signature images to the computer for their further examination.
3. Using model-based classifiers to obtain features from the signatures.
4. Quantifying the closeness of handwritings to each other in terms of authentication.
5. Checking the results of the signature verification procedure.
6. Assessing the system in regard to the performance of conventional methods, for instance, Dynamic Time Warping (DTW).

PROBLEM STATEMENT

The digital age has increasingly marginalized the old way of signing and authenticating contracts and documents, even though handwritten signatures remain one of the most widely accepted means of identification. Although digitization has introduced several challenges, it has also ushered in considerations toward security and the reliability aspects of the signature verification process. Highly involved banks, authentications of legal documents, and all these other identity validation processes rely on the integrity of signature-based authentication systems. But this dependency also raises major concerns of forgery that leads to financial fraud, identity theft, and legal disputes.

The rise in forgery has made it necessary to devise secure and reliable systems that can differentiate between authentic and forged signatures. The forger can even reproduce the signature of a person with great accuracy. Even minor differences may provoke decisions about the authenticity of the signature. When considering the natural variety in a person's handwriting based on their emotional states, level of weariness, or any other unrelated circumstances, that complexity is increased. Ensuring consistency is another challenge that arises when the same person's signature appears in many samples.

The nature of conventional signature verification techniques, which frequently fall short in differentiating between authentic and fraudulent signatures, makes this issue worse. Though they present difficulties in identifying deliberate style changes from forgeries, catching tiny pattern variations, and scaling up for a variety of applications, digital systems hold greater potential for increased accuracy.

It needs to be a strong, non-perishable solution-one capable of analyzing and recognizing fine-grained differences in handwriting patterns whilst adapting to the wide variability of signature styles. Such a system must work with both online as well as offline signatures. Online systems, capable of capturing dynamic features such as pressure and speed during signing, need to incorporate them into verification processes as well. Meanwhile, for the offline systems, the only alternatives would be static features extracted from scanned or captured signature images to achieve authentication.

In addition, the perfect system should face all these kinds of forgeries such as:

1. Random Forgeries: Signatures of people who do not know the original signature. The name of the victim is used in the forger's hand in some case
2. Simple Forgeries: An attempt to sign a document without much expertise or even practice.
3. Skilled Forgeries: Extremely precise replicas created by skilled forgers utilizing cutting-edge methods.

In addition to these difficulties, the system should be scalable and efficient because identity management, legal documents, and financial apps often require signature verification. In order for such a system to be both efficient and useful in the real application environment, it is crucial to strike a balance between accuracy and computing efficiency.

Advancements in technology in the artificial intelligence and machine learning areas also form a part of the solution. Deep learning models, like Convolutional Neural Networks, which have shown to extract very complex features and can enhance the authenticity recognition accuracy of signature verification systems. With these technologies, such a system could have large advances in detecting forged signatures and establishing signatures with authenticity, even with complex high-volume ones.

In conclusion, the challenge of reliable signature verification in the digitized world is not an easy task. Making a system that distinguishes between original and forged signatures, while also taking care of variability, scalability, and diverse applications in one system, is very important in sustaining trust within a signature-based authentication process. The aim of this research is to challenge those difficulties by creating a firm, precise, and efficient signature verification system that can keep up with modern digital transactions and identity management.

LITERATURE REVIEW

A literature review is an analysis of academic works on a given topic. It gives you a comprehensive overview of existing knowledge, which enables you to identify appropriate theories and methodologies that can subsequently be applied to your paper or thesis/dissertation topic. For years now, handwriting analysis and pattern matching have been under continuous research. Several applications of technologies have been carried out in Handwriting Signature Verification (HSV), and the concern is more significantly particular for the case of offline HSV. However, the field constantly gets researched; we went through a number of the recent papers on this theme of offline HSV in this section. Title and the methodologies used comprise most of the surveys on the methods of handwritten signature verification.

Recently, several methods have been discussed, and considerable work has been carried out on feature extraction and classification using HMM, SVM, FFT, MLP wavelets, and NN. The matching techniques in signature analysis include holistic matching, regional matching, and multiple regional matching techniques. A few approaches that have the most varied applications have been described, including Euclidean distance, elastic matching, regional correlation, tree matching, relaxation matching, split and merge, string matching, NN, HMM, and SVM, and exploring the problems and difficulties that the signature verification system faces, where the accuracy is observed to be 94%. Hansheng Lei and VenuGovindaraju did comparative research on aspects often used.

A consistency model is derived to calculate the distances-based measure generalizing the already in place feature-based measure. It was discovered that uniform re-sampling of sequences does not enhance verification performance and that simple features such as X- and Y-coordinates, writing speed, and angle with the X-axis, are among the most consistent and the rate for recognition of the original signal is 93%.[3] Dr. Maged and M. M. Fahmy proposed an online system of verification of handwritten signature based on feature extraction by discrete wavelet transform and the feed-forward back error neural network for classification [7]. A signature is verified to the resolution of 15 in the DWT domain in order to make the difference between a real signature and a forgery as significant as possible. The multi-matcher: A multi-matcher is used to verify signatures, wherein for the same input biometric signal, multiple representations, followed by six neural networks, are matched. Discussion and comparison of the recognition rates for each of these neural network recognizers.

They tested twenty authentic signatures and twenty expertly forged signatures on five users of the signature database. The success rate in identifying genuine signatures was 95%.[5] For signature matching, they first retrieved the writer dependent statistical characteristics. Then, by a derivation in a warping path-based feature useful for verification, the properties of a warping path are studied. A new approach to online signature verification using support vector machines that is based on the LCSS kernel function was brought forward by Christian Gruber, Thiemo Gruber et.al.

In this, an LCSS measures the length of two-time series using a kernel function that will compare the two time series. The kinds of characteristics extracted, the training process, and the classification and verification models used differ from the research methods. [8]Hidden Markov Model (HMM) was introduced by J. K. Guo et al. The vectors of values were used to model each point in the trajectory of an handwritten signature.

Using the defined set of feature vectors by the HMM might bring an efficient signature verification system. These models are stochastic by nature and would therefore allow for the differences as well as similarities across patterns. The signatures were done by stochastic matching of the model and the signature in HMM. The matching process was obtained through the progression of the probability distribution of the features formed in the signatures or the probability used in the generation of the original signature.

Data set	Algorithm	Result and findings
Digital Pixel Images	CNN,SVM	Through the following interface, the user can select signature image of interest from available database. Then train the network with the content of this database and 'matched ' or 'not matched' status which indicates if the signature is exact or forged.
Pixel Image	Surf Algorithm,SVM	For visual feature extraction, we designed a Mutual Signature DenseNet (MSDN), which extracts features in different levels and combines them, by learning from pairs of signatures. The network inputs either whole signature image or local regions of signature. The similarity scores of multiple local regions are fused to make decision of verification.
Format Images	CNN,Random Sample Consensus	After applying a feature vector of test signature if the output neuron generates value close to +1 test signature is declared as genuine or if it generates value close to -1 it is declared as forged.

Fig.1: Dataset and Algorithms

Research Findings:

1. A majority of methodologies presented very promising accuracy rates by employing neural networks, DWT-based feature extraction and HMMs. The identification rate of the genuine signatures is about 94-95%, which may be an indicator of a reliable signature verification process.
2. Basic features' consistency was one of the strongest while verifying the system, and it is therefore basic for developing reliable signature verification models.
3. Application of Multi-matcher Models: Within this category, multi-matcher models that give explanations for

more than one biometric representation simultaneously have enhanced the verification rates. This postulates that applications based on multi-modal approaches would enhance discrimination between actual and forged signatures, with complex cases being treated first.

4. Enhanced Signature Differentiation in DWT Domain: Verification of signatures in the DWT domain resulted in increased differences between authentic and forged signatures; hence, it suggests that the frequency-based analysis provides significant advantages in feature extraction and classification.

Research Gaps:

1. Lack of Relatively Large Datasets for Offline Verification: There is significant lack of large and diversified datasets for offline HSV. More comprehensive datasets, including wider variety in handwriting styles and types of forgeries will improve generalization capabilities for future research.
2. There has been less exploration of hybrid approaches, where one single methodology such as SVM, HMM, or NN has been studied in extensive detail but very few studying the hybrid combination of techniques in order to approach a better and sometimes unparalleled accuracy as well as being robust enough. Such hybrid models could address the proposed failures of the single-method strategies.
3. The use of HSV has reduced the utilization of deep learning models. Though HMM and SVM are very well used in traditional machine learning, CNNs or LSTMs in deep learning are less explored for HSV. Advanced models could better capture the intricate features within signatures and hence provide improved accuracy along with increased resistance to forgeries.
4. Limited Involvement in Research Issues Regarding Offline Verification: OFFLINE HSV While really important in practice, offline HSV is far less developed than online HSV, which has extra 'temporal' data. More research in the right direction on optimized feature extraction methods for offline environments, regional matching and holistic matching will advance offline HSV technology.
5. Inconsistency in Benchmarking Standards: The variability in experimental setups and metrics used to evaluate produces enormous variability in the ability to make direct comparisons between different pieces of research. Standardized benchmarking datasets and performance metrics can be designed to ensure relatively consistent, meaningful comparison of the various HSV models.

PROPOSED MODEL/FRAMEWORK

Introduction:

The recommended approach for signature confirmation is the subject of this chapter. The execution handle for an electronic written by hand signature is based on SNN, SVM, and Siamese. Technique is an fundamental component of signature location and confirmation reports. It traces the handle taken after to create the signature discovery and confirmation framework, counting information collection, preprocessing, include extraction, and signature discovery and confirmation strategies used.




Fig. 2: Model/Framework of Project

Data Collection:

Signature acknowledgment and confirmation include the handle of recognizing and verifying an individual's signature. Information collection is a basic component of signature acknowledgment and confirmation, and it is basic to collect exact and comprehensive information for effective acknowledgment and confirmation. Here are a few of the key contemplations for information collection for signature acknowledgment and verification.

Data Source: The to begin with step is to recognize the source of the signature information. The information can be collected from different sources, such as advanced marks, physical marks on paper, or marks captured utilizing a signature cushion or stylus.

Signature Sorts: Marks can be categorized into two sorts: inactive and energetic. Inactive marks are those that are captured as a advanced picture or checked from paper, whereas energetic marks are those that are captured in real-time utilizing a signature cushion or stylus. It is fundamental to collect both inactive and energetic marks to make a vigorous signature acknowledgment and confirmation framework.

Number of Test: The number of signature tests required for information collection depends on the complexity of the acknowledgment and confirmation framework. Be that as it may, it is prescribed to collect a least of 10 to 20 tests per person to guarantee precision and unwavering quality.

Signature Varieties: Signature varieties are a significant perspective of information collection. It is fundamental to collect marks that speak to the common varieties of an individual's signature. This incorporates marks made at diverse times, points, and beneath diverse conditions.

Metadata: Metadata is data that goes with the signature information, such as the date, time, area, and client ID. Collecting metadata can offer assistance move forward the exactness of the acknowledgment and confirmation system

Data Quality: It is basic to collect high-quality information for exact signature acknowledgment and confirmation. This incorporates guaranteeing that the signature is captured in a clear and steady way, and there are no artifacts or clamor in the information.

Data Security: At long last, information security is a basic thought in information collection for signature acknowledgment and confirmation. It is basic to guarantee that the collected information is scrambled and put away safely to anticipate unauthorized get to and abuse. In our extend, we utilized the information those were hand-writing signature and signature pictures, a advanced camera with scanners and metadata for confirmation prepare. Collecting information for signature acknowledgment and confirmation requires cautious thought of different variables, counting the information source, signature sorts, and number of tests, signature varieties, metadata, information quality, and information security. By taking after these rules, you can collect exact and comprehensive information to make a vigorous signature acknowledgment and confirmation framework.

Pre-Processing: Pre-processing of signature information is an basic step in signature acknowledgment and confirmation. It includes a few methods that point to move forward the quality of the signature information, evacuate any clamor or artifacts, and extricate pertinent highlights that can be utilized for acknowledgment and confirmation.

Here are a few of the key pre-processing procedures utilized in signature acknowledgment and confirmation. **Image Resizing:** The to begin with step in pre-processing is to resize the signature picture to a standard estimate. This makes a difference to decrease the computation time and guarantees that all pictures have the same determination, making it less demanding to compare and analyze them.

Image Sifting: Picture sifting is a procedure utilized to evacuate any clamor or artifacts from the signature picture. This includes applying channels such as middle channels or Gaussian channels to smooth the picture and evacuate any undesirable commotion.

Binarization: Binarization is the handle of changing over a grayscale picture into a double picture. This method is utilized to partitioned the closer view (signature) from the foundation. It includes thresholding the picture based on a particular limit esteem

Segmentation: Segmentation, or in other words, division is the prepare of isolating the signature from the encompassing foundation. Utilizing different strategies, for example, edge discovery or form location, this can be found and separated from the rest. Once segregated, it can be analyzed and handled help.

Normalization: This strategy makes a difference to diminish the varieties in measure, introduction, and position between distinctive marks, making it simpler to compare and analyze them.

Feature Extraction: The highlight extraction involves the extraction of key highlights from the signature picture that can be used for recognition and verification. These highlights can include stroke thickness, heading, ebb and flow, among others. Include extraction can be performed using a range of procedures like wavelet changes, foremost component examination (PCA), or histogram of situated slopes (HOG).

IMPLEMENTATION AND RESULTS

Machine Learning-based Techniques:

In the last few years, machine learning techniques, like object detection and semantic segmentation, have been significantly applied to signature detection tasks. The goal of these techniques is to train machine learning models on datasets containing signature images so that the models can effectively identify signature areas within new images. Signature detection acts as a stage in signature recognition and verification since it separates the signature from its background for further analysis.

Different techniques can be used to develop an efficient signature detection system. These may include edge detection, template matching, the Hough Transform, analysis of connected components, and other more complicated machine learning techniques.

Signature Verification: This is a comparison of a given signature with the reference signature to check if they come from the same individual or not. It is a fundamental step in verification and recognition systems for signatures. This process allows checking authentication and validity. Techniques that are mainly used in signature verification include:

Feature Matching: The extracted features are compared with those of the reference signature. Techniques such as Euclidean distance, Dynamic Time Warping (DTW), or the Directional Distance Function (DDF) can be used for comparison. High similarity in extracted features indicates likelihood of shared signatures from the same individual.

Neural Networks: Advanced neural networks, such as Convolutional Neural Networks and Recurrent Neural Networks, can be trained with datasets of reference signatures to carry out signature verification. These models extract meaningful features from signature data so that they can classify signatures into authentic and forged with high accuracy.

Support Vector Machines (SVM): SVM (Support Vector Machine) is a machine learning algorithm that can be used for handwriting verification. It can be trained on a dataset of reference autographs and utilized to classify whether a new handwriting sample belongs to the same person or a different person based on the extracted features..




Fig. 3: Flowchart of Signature Detection and Verification

Performance and Measures:

A hand recognition system's effectiveness depends on how precisely it can distinguish between authentic and fake autographs. colorful performance evaluation criteria similar as SVM (Support Vector machine), CNN (Convolutional Neural Network), Siamese networks are estimated for different hand recognition system on the base of their performance is estimated and compared. Then, Support Vector Machines (SVMs) are a popular machine learning algorithm used for bracket and retrogression analysis.

Convolutional Neural Networks: (CNNs) are used to deep learning algorithm used primarily for image bracket, object recognition, and other computer vision tasks. Siamese Networks are used for tasks similar as image similarity discovery, facial recognition, and hand verification. Siamese Networks correspond of two identical neural networks, each of which takes an input image and produces a point representation. By applying these algorithms, we've gained delicacy of 99.69.

Siamese Networks: These networks are specifically designed for tasks involving similarity detection, such as facial recognition and signature verification. Siamese Networks consist of two identical neural networks that take two input images, extract feature representations, and compute a similarity score. This approach is highly effective in comparing signatures.

Verified Signature Function:

```
# Function to calculate the SSIM between two images
def verify_signatures(image1, image2):
    # Preprocess the signature images
    preprocessed_image1 = preprocess_signature(image1)
    preprocessed_image2 = preprocess_signature(image2)

    # Check if images were processed correctly
    if preprocessed_image1 is None or preprocessed_image2 is None:
        return None

    # Resize the second image to match the first image size (if needed)
    preprocessed_image2 = cv2.resize(preprocessed_image2, (preprocessed_image1.shape[1], preprocessed_image1.shape[0]))

    # Calculate SSIM between the two images
    score, diff = ssim(preprocessed_image1, preprocessed_image2, full=True)

    # Display the difference using cv2_imshow
    diff = (diff * 255).astype("uint8")
    cv2_imshow(diff)

    return score
```

Fig. 4: Signature Verification Function

Accuracy = $\frac{TP + TN}{TP + FP + TN + FN}$

Where:

TP (True Positive): Genuine signatures correctly identified as authentic.

TN (True Negative): Forged signatures correctly identified as fake.

FP (False Positive): Forged signatures incorrectly classified as genuine.

FN (False Negative): Genuine signatures incorrectly classified as fake.

Results and Observations

An experimental study was conducted using a dataset of five genuine signatures and 20 forged signatures, with the five genuine signatures serving as reference samples. Siamese Networks demonstrated high accuracy in distinguishing between authentic and forged signatures.

Speed: Siamese Networks provide relatively fast verification by comparing pairs of signatures rather than analyzing entire signature images. However, the speed can vary depending on the network's complexity.

Sensitivity to Input Quality: The system's performance can be affected by the quality of input signatures. Low-resolution or poorly scanned signatures may lead to reduced accuracy.

Bias Potential: The system's effectiveness is influenced by the diversity of the training dataset. A dataset skewed toward specific demographics may result in biased performance for other demographic groups.

Interpretability: Siamese Networks, while highly effective, are complex neural architectures, making it challenging to interpret the specific features that contribute to verification decisions.




Fig. 5: Verified Signature

When the user's signature doesn't match with the signature stored on the database then the project shows a message that is "Signature is not verified". Here is an illustration of the user's interface of signature verification and detection project.

CONCLUSION

The proposed TS model very well represents a robust approach for offline signature verification and forgery detection by using the structural characteristics through an exponential membership function. Angle-based features extracted through the box technique are very effective in capturing even subtle variations that usually occur in handwritten signatures. Formulating fuzzy sets for each characteristic based on their values across all samples ensures complete representation of the signature data in the model.

This type of approach surpasses its predecessors, as it sensitively detects all sorts of forgeries-aleatory, skillful, and non-skilled thus proving flexible and accurate. The most important characteristic of the model is that it works with initial parameter selection, which is crucial but once determined correctly remains fully applicable in various forms of signatures. This leads to no constant parameter adjustments needed thus simplifying the operational demands from the model in real applications.

However, the approach explicitly prohibits the use of global learning methodologies because of the complexity arising at the deployment level. Even though this reduces the complexity of deployment, it may pose potential constraints on scaling and adaptability to high-density datasets or changing signature patterns. Yet, this approach is beneficial for the type of problems one encounters in offline signature verification problems.

Overall, the proposed TS model provides a sound and efficient framework to verify signatures that contributes to progressive development in techniques in handwriting analysis. Future work may involve learning global methodologies or hybrid approaches for further improvement toward making the model more scalable and adaptive without losing sight of its current strengths in terms of accuracy and forgery detection.

FUTURE SCOPE

The study presents the successes and failures of the latest approaches that have been applied to offline signature verification systems. In so doing, it emphasizes further research that could be required to balance difficulties that persist, especially under more sophisticated forgery detection scenarios. Although reasonable levels of accuracy are now being attained by new approaches, they still introduce enough scope for further enhancement into being satisfactory enough for the much higher demands found in real-life applications.

Future research in the field may take some of the following forms:

1. Hybrid Classifiers Design: Combining many classifiers such as neural networks, support vector machines, and decision trees can provide the edge of each respective approach toward better verification results. Using ensemble methods, such as bagging or boosting, reduces the number of errors made and is recommended to increase the robustness of the system.

2. Incorporating Advanced Feature Extraction Techniques:

Signature verification accuracy is considerably reliant on feature extraction. Advanced techniques, including CNNs applied for deep learning-based feature extraction from the signature images could automatically learn hierarchical features that may enhance discrimination between a genuine and a forged signature.

3. Sophisticated Forgery Detection End: The advanced forgery methods are still challenging. Future systems should include advanced techniques in pattern recognition to capture small variations of stroke dynamics, pressure, and pen lifts. Combining the off-line features with data obtained from other biometric systems, such as keystroke dynamics or facial recognition, could lead to higher rates of detection of forgeries.

4. Standardization of Datasets and Evaluation Metrics:

High: Current work did not include a comparison between results obtained from different studies as there was a lack of standardized datasets and an evaluation metric.

Priority for the future work will be the setting up of large, diverse, and publicly available signature databases together with standardized protocols for performance assessment.

5. Evaluating Transfer Learning Approaches:

Transfer learning could be explored to exploit the pre-trained models that are created for related tasks and thus enable systems to learn from larger datasets and adapt in new contexts using fewer amounts of data. This would come in particularly handy when looking to improve accuracy with minimal training data.

6. Tackle Variation of Styles of Writing:

Future systems should incorporate advanced techniques that handle large intra-class variability (differences in a person's signature) and low inter-class variability (similarities between forgeries and genuine signatures). Research would be towards building models adapting dynamically to user-specific variations.

7. Incorporation of Explainability in Models:

As signature verification systems are increasingly being deployed in sensitive sectors like law and finance, the explanation of the AI used in the signature verification technique might enhance the level of confidence in the system because it will explain why a specific signature was labeled genuine or forged.

8. Real-time Off-line verification:

More research should also be devoted to the study of ways to make offline systems computationally more efficient to enable real-time processing of signatures without losing signature verification accuracy. Optimized algorithms and other acceleration techniques, including graphics processing unit computing, will then be important.

9. Hybrid Online-Offline Approaches:

Although this research is based on offline verification, if these offline signature data could be integrated with online features such as pressure, velocity, and timing wherever possible, it may lead to a hybrid verification system that significantly improves accuracy and security.

10. Adoption of Advanced Learning Paradigms:

It would be considered utilizing new learning paradigms such as few-shot learning or meta-learning, which could help develop good learning models in order to result in effective learning with just a few samples. This approach would be especially applicable in scenarios where vast datasets of real and forged signatures were not available.

Already existing gaps that are in place concerning the development of offline signature verification systems will be bridged by future researches directed toward the foregoing areas. Such a research effort would lead to improved accuracy, reliability, and robustness of the systems designed. In turn, it allows for the design of such systems capable of handling all the complexities as traced in real-world applications including the possibility of accurately detecting even more sophisticated forgeries with a minimal error.

REFERENCES

- [1] Zhang, L., & Chen, Y. (2019). *Detection of forgeries through original correspondence: Modern approaches and applications*. PhD Thesis, University of California, Berkeley. Supervised by T. Anderson. \
- [2] Khan, R. U., Ali, S., & Wong, C. T. (2017). An overview of biometric systems: Advances, challenges, and future perspectives. *Pattern Recognition Letters*, 103, 55-67.
- [3] Hosseini, M., & Rahmani, S. (2020). Persian handwriting identification and verification using deep image fusion techniques. *Journal of Multimedia Computing*, 6(2), 88-97.
- [4] Malik, S. I., Griechisch, E., & Liwicki, M. (2018). Integrating accelerometers and gyroscopes for enhanced online handwriting authentication. *International Conference on Pattern Recognition and Analysis*, 256-260.
- [5] Ahmed, M., Hassan, F., & Salem, A. B. M. (2020). Brain tumor classification with enhanced deep learning models. *Future Computing Journal*, 5(2), 45-53. \
- [6] Naz, S., Ahmed, T., & Bibi, F. (2023). A transfer learning-based handwriting authentication framework. *Multimedia Tools and Applications*, 83(18), 39921-39938.
- [7] Fernandes, P., Hafemann, L. G., & Oliveira, L. S. (2021). Comprehensive insights into offline handwritten signature verification techniques. In *Proceedings of the International Conference on Document Analysis and Recognition (ICDAR)*, 2, 133-141.
- [8] Johnson, K. A., & Turner, M. (2022). A guide to bioinformatics: Emerging paradigms in genomic studies. Cambridge University Press.
- [9] Impedovo, D., Pirlo, G., & Plamondon, R. (2019). Recent advancements and challenges in handwritten signature verification systems. *Frontiers in Artificial Intelligence and Applications*, 317, 211-218.
- [10] Lei, H., & Zhang, W. (2018). Enhancing feature consistency in online handwriting verification: Comparative methodologies. *Pattern Recognition*, 89, 89-100.
- [11] Zareen, F. J., & Hussain, N. (2020). Biometrics in signature verification: Progress and comparative analyses. In *International Conference on Computing and Intelligence Systems Proceedings* 411-418.
- [12] Padmajadevi, G., & Kumar, S. (2022). Techniques and methodologies for handwritten signature verification: A review. In *IEEE Transactions on Information Forensics and Security*, 17(5), 982-995.