

Programming Project 1: UNIX Shell

Course: CPRE 308

Instructor: Mai Zheng

TAs: Om (Section 1), Gavin (Section 2), Duo (Section 4)

Overview

- Project Description:
 - Create your own version of basic UNIX shell
 - Perform similar functions (e.g.: run built-in commands)
- Submission details:
 - Document containing a cohesive summary of what you learned in this project **(15 pts)**
 - Up to 2 paragraphs (3 if you have implemented the extra credit)
 - A zip (or tar) file containing:
 - Makefile that compiles your program without errors **(10 pts)**
 - Source code is neatly formatted and contains comments describing parts of the program **(10 pts)**
 - Required functionality works **(65 pts)**
 - Refer to Section 4 for expected output

Tasks

- Task 1: Basic interface (10 pts)
 - Custom prompt (5pts)
 - Your shell should accept a “-p <prompt>” option on the command line
 - If prompt is not provided then the default prompt must be “308sh> ”
 - Run in infinite loop until user requests to exit (5pts)
 - Suggestion: Use `fgets()` to read user input
- Task 2: Execute Built-in commands (5 pts)
 - Refer to Section 2.2 for the built-in commands to be supported by your shell
 - Refer to Section 3.2 to reuse some system/library calls to execute a few built-in commands

Tasks (contd.)

- Task 3: Execute Program commands (30 pts)
 - Spawn a child process to execute user input **(15 pts)**
 - Use `fork()` to create child process
 - Use `execvp()` system call to execute user input
 - Refer to man page of `execvp` for its usage
 - Shell should notify if the requested command is not found and cannot be run **(5 pts)**
 - Print process ID (PID) when child process is spawned **(5 pts)**
 - Print before executing program command
 - Your shell should wait until child exits
 - No prompt will should be available for additional user input
 - Your shell should wake when most recently executed child process completes
 - Check `waitpid`
 - When a child process finishes, prints its PID and exit status **(5 pts)**
 - Refer to Lab 2 (handling exist status)

Tasks (contd.)

- Task 3: Background processes (10 pts)
 - Support executing commands in the background when “&” is in the input command
 - Child process should run in the background
 - Your shell will **not** wait for child process to exit
 - You still need to print the creation and exit status of these background processes
 - HINT:
 - Get exit status of background child process by calling `waitpid` with `PID= -1` and `WNOHANG` set
 - Check periodically by executing every time the user enters a command

Tasks (contd.)

- Task 4: Extra credit (+5 pts)
 - Add a built-in command “jobs” that outputs the names and PID of your child processes
 - Maintain a data structure (e.g. linked-list) that can store required information
 - Clearly describe your implementation in the summary