```
}
}
```

BT4

```
interface Moveable {
    void moveUp();
    void moveDown();
    void moveLeft();
    void moveRight();
}
class MoveablePoint implements Moveable {
    int x, y, xSpeed, ySpeed;
Public MoveablePoint (int x, int y, int
xSpeed, int ySpeed) {
    this.x = x;
    this.y = y
    this.ySpeed = ySpeed
```

Tibook

Scanned with CamScanner

Thứ
Ngày . . No.

```
    this.yspeed = yspeed;
}
    public void moveUp() { y -= ySpeed; }
    public void moveDown() { y += ySpeed; }
    public void moveLeft() { x -= xSpeed; }
    public void moveRight() { x += xspeed; }
    public String toString() {
        return "(" + x + ", " + y + ")";
    }
}

class MoveableCircle implements Moveable
{
    int radius;
    MoveablePoint center;
    public MoveableCircle(Moveable center,
int radius) {
    this.center = center;
    this.radius = radius;
}

    public void moveUp() { center.moveUp(); }
    public void moveDown() { center.moveDown(); }
    public void moveLeft() { center.moveLeft(); }
    public void moveRight() { center.moveRight(); }
    public String toString() {
        return "Circle at" + center;
    }
}
```

Tibook®

Scanned with CamScanner