

Introduction to **Information Retrieval**

CS276

Information Retrieval and Web Search

Christopher Manning and Prabhakar Raghavan

Lecture 1: Boolean retrieval

Information Retrieval

- Information Retrieval (IR) is finding material (usually documents) of an unstructured nature (usually text) that satisfies an information need from within large collections (usually stored on computers).

structured (database) data


User					
UserID	User	Address	Phone	Email	Alternate
1	Alice	123 Foo St.	12345678	alice@example.org	alice@neo4j.org
2	Bob	456 Bar Ave.		bob@example.org	
...
99	Zach	99 South St.		zach@example.org	

Order	
OrderID	UserID
1234	1
5678	1
...	...
5588	99

LineItem		
OrderID	ProductID	Quantity
1234	765	2
1234	987	1
...
5588	765	1

Product		
ProductID	Description	Handling
321	strawberry ice cream	freezer
765	potatoes	
...	...	
987	dried spaghetti	

Unstructured (text) vs. structured (database) data in 2009



Google™

YAHOO!®

bing

Ask™
.com

Unstructured data in 1680

- Which plays of Shakespeare contain the words *Brutus* AND *Caesar* but NOT *Calpurnia*?
- One could grep all of Shakespeare's plays for *Brutus* and *Caesar*, then strip out lines containing *Calpurnia*?
- Why is that not the answer?
 - Slow (for large corpora)
 - NOT *Calpurnia* is non-trivial
 - Other operations (e.g., find the word *Romans* near *countrymen*) not feasible
 - Ranked retrieval (best documents to return)
 - Later lectures


Term-document incidence

	Antony and Cleopatra	Julius Caesar	The Tempest	Hamlet	Othello	Macbeth
Antony	1	1	0	0	0	1
Brutus	1	1	0	1	0	0
Caesar	1	1	0	1	1	1
Calpurnia	0	1	0	0	0	0
Cleopatra	1	0	0	0	0	0
mercy	1	0	1	1	1	1
worser	1	0	1	1	1	0

Brutus AND Caesar BUT NOT Calpurnia

1 if play contains word, 0 otherwise

Example1



Example2

Term \ Document	<u>D_1</u>	<u>D_r</u>	...	<u>$D_{1 \dots 10}$</u>	...	<u>$D_{1 \dots 10}$</u>
t_1						
t_r						
\vdots						
<u>$t_{10} = i=1 \dots 10$</u>	<u>0</u>	<u>1</u>	...	<u>1</u>	...	<u>0</u>
t_n						

Incidence vectors

- So we have a 0/1 vector for each term.
- To answer query: take the vectors for ***Brutus, Caesar*** and ***Calpurnia*** (complemented) → bitwise *AND*.
- $110100 \text{ AND } 110111 \text{ AND } 101111 = 100100$.


Answers to query

- Antony and Cleopatra, Act III, Scene ii

Agrippa [Aside to DOMITIUS ENOBARBUS]: Why, Enobarbus,
When Antony found Julius **Caesar** dead,
He cried almost to roaring; and he wept
When at Philippi he found **Brutus** slain.

- Hamlet, Act III, Scene ii


Lord Polonius: I did enact Julius **Caesar** I was killed i' the
Capitol; **Brutus** killed me.



Basic assumptions of Information Retrieval

- **Collection**: Fixed set of documents
- **Goal**: Retrieve documents with information that is relevant to the user's **information need** and helps the user complete a **task**

The classic search model



How good are the retrieved docs?

- *Precision* : Fraction of retrieved docs that are relevant to user's information need
- *Recall* : Fraction of relevant docs in collection that are retrieved
- More precise definitions and measurements to follow in later lectures

Bigger collections

- Consider $N = 1$ million documents, each with about 1000 words.
- Avg 6 bytes/word including spaces/punctuation
 - 6GB of data in the documents.
- Say there are $M = 500K$ *distinct* terms among these.


Can't build the matrix

- 500K x 1M matrix has half-a-trillion 0's and 1's.
- But it has no more than one billion 1's.
 - matrix is extremely sparse.
- What's a better representation?
 - We only record the 1 positions.



Inverted index


- For each term t , we must store a list of all documents that contain t .
 - Identify each by a **docID**, a document serial number
- Can we use fixed-size arrays for this?




What happens if the word **Caesar** is added to document 14?

Inverted index

- We need variable-size postings lists
 - On disk, a continuous run of postings is normal and best
 - In memory, can use linked lists or variable length arrays
 - Some tradeoffs in size/ease of insertion



Inverted index construction



Indexer steps: Token sequence

- Sequence of (Modified token, Document ID) pairs.

Doc 1

I did enact Julius
Caesar I was killed
i' the Capitol;
Brutus killed me.

Doc 2

So let it be with
Caesar. The noble
Brutus hath told you
Caesar was ambitious



Term	docID
I	1
did	1
enact	1
julius	1
caesar	1
I	1
was	1
killed	1
i'	1
the	1
capitol	1
brutus	1
killed	1
me	1
so	2
let	2
it	2
be	2
with	2
caesar	2
the	2
noble	2
brutus	2
hath	2
told	2
you	2
caesar	2
was	2
ambitious	2

Indexer steps: Sort

- Sort by terms
 - And then docID



Term	docID
I	1
did	1
enact	1
julius	1
caesar	1
I	1
was	1
killed	1
i'	1
the	1
capitol	1
brutus	1
killed	1
me	1
so	2
let	2
it	2
be	2
with	2
caesar	2
the	2
noble	2
brutus	2
hath	2
told	2
you	2
caesar	2
was	2
ambitious	2



Term	docID
ambitious	2
be	2
brutus	1
brutus	2
capitol	1
caesar	1
caesar	2
caesar	2
did	1
enact	1
hath	1
I	1
I	1
i'	1
it	2
julius	1
killed	1
killed	1
let	2
me	1
noble	2
so	2
the	1
the	2
told	2
you	2
was	1
was	2
with	2

Indexer steps: Dictionary & Postings

- Multiple term entries in a single document are merged.
- Split into Dictionary and Postings
- Doc. frequency information is added.


Why frequency?
Will discuss later.

Term	docID
ambitious	2
be	2
brutus	1
brutus	2
capitol	1
caesar	1
caesar	2
caesar	2
did	1
enact	1
hath	1
I	1
I	1
i'	1
it	2
julius	1
killed	1
killed	1
let	2
me	1
noble	2
so	2
the	1
the	2
told	2
you	2
was	1
was	2
with	2




term	doc. freq.	→	postings lists
ambitious	1	→	2
be	1	→	2
brutus	2	→	1 → 2
capitol	1	→	1
caesar	2	→	1 → 2
did	1	→	1
enact	1	→	1
hath	1	→	2
i	1	→	1
i'	1	→	1
it	1	→	2
julius	1	→	1
killed	1	→	1
let	1	→	2
me	1	→	1
noble	1	→	2
so	1	→	2
the	2	→	1 → 2
told	1	→	2
you	1	→	2
was	2	→	1 → 2
with	1	→	2

Where do we pay in storage?



The index we just built

- How do we process a query?
 - Later - what kinds of queries can we process?




Query processing: AND

- Consider processing the query:


Brutus AND Caesar

- Locate ***Brutus*** in the Dictionary;
 - Retrieve its postings.
- Locate ***Caesar*** in the Dictionary;
 - Retrieve its postings.
- “Merge” the two postings:



The merge

- Walk through the two postings simultaneously, in time linear in the total number of postings entries



If the list lengths are x and y , the merge takes $O(x+y)$ operations.

Crucial: postings sorted by docID.

Intersecting two postings lists (a “merge” algorithm)

```
INTERSECT( $p_1, p_2$ )  
  1   $answer \leftarrow \langle \rangle$   
  2  while  $p_1 \neq \text{NIL}$  and  $p_2 \neq \text{NIL}$   
  3  do if  $docID(p_1) = docID(p_2)$   
  4      then  $\text{ADD}(answer, docID(p_1))$   
  5           $p_1 \leftarrow next(p_1)$   
  6           $p_2 \leftarrow next(p_2)$   
  7      else if  $docID(p_1) < docID(p_2)$   
  8          then  $p_1 \leftarrow next(p_1)$   
  9          else  $p_2 \leftarrow next(p_2)$   
 10 return  $answer$ 
```

Boolean queries: Exact match

- The **Boolean retrieval model** is being able to ask a query that is a Boolean expression:
 - Boolean Queries are queries using *AND*, *OR* and *NOT* to join query terms
 - Views each document as a set of words
 - Is precise: document matches condition or not.
 - Perhaps the simplest model to build an IR system on
- Primary commercial retrieval tool for 3 decades.
- Many search systems you still use are Boolean:
 - Email, library catalog, Mac OS X Spotlight

Example: WestLaw <http://www.westlaw.com/>

- Largest commercial (paying subscribers) legal search service (started 1975; ranking added 1992)
- Tens of terabytes of data; 700,000 users
- Majority of users *still* use boolean queries
- Example query:
 - What is the statute of limitations in cases involving the federal tort claims act?
 - **LIMIT! /3 STATUTE ACTION /S FEDERAL /2 TORT /3 CLAIM**
 - /3 = within 3 words, /S = in same sentence

Example: WestLaw <http://www.westlaw.com/>

- Another example query:
 - Requirements for disabled people to be able to access a workplace
 - `disabl! /p access! /s work-site work-place (employment /3 place`
- Note that SPACE is disjunction, not conjunction!
- Long, precise queries; proximity operators; incrementally developed; not like web search
- Many professional searchers still like Boolean search
 - You know exactly what you are getting
- But that doesn't mean it actually works better....

Boolean queries: More general merges

- Exercise: Adapt the merge for the queries:

Brutus AND NOT Caesar

Brutus OR NOT Caesar

Can we still run through the merge in time $O(x+y)$?

What can we achieve?

Merging

What about an arbitrary Boolean formula?


(Brutus OR Caesar) AND NOT

(Antony OR Cleopatra)

- Can we always merge in “linear” time?
 - Linear in what?
- Can we do better?

Query optimization


- What is the best order for query processing?
- Consider a query that is an *AND* of n terms.
- For each of the n terms, get its postings, then *AND* them together.




Query: ***Brutus AND Calpurnia AND Caesar***

Query optimization example

- Process in order of increasing freq:
 - *start with smallest set, then keep cutting further.*



This is why we kept
document freq. in dictionary



Execute the query as (***Calpurnia AND Brutus***) ***AND Caesar***.

More general optimization

- e.g., (*madding OR crowd*) AND (*ignoble OR strife*)
- Get doc. freq.'s for all terms.
- Estimate the size of each *OR* by the sum of its doc. freq.'s (conservative).
- Process in increasing order of *OR* sizes.

Query processing exercises

- **Exercise:** If the query is *friends AND romans AND (NOT countrymen)*, how could we use the freq of *countrymen*?
- **Exercise:** Extend the merge to an arbitrary Boolean query. Can we always guarantee execution in time linear in the total postings size?
- **Hint:** Begin with the case of a Boolean *formula* query: in this, each query term appears only once in the query.

What's ahead in IR?

Beyond term search

- What about phrases?
 - *Stanford University*
- Proximity: Find ***Gates NEAR Microsoft.***
 - Need index to capture position information in docs.
- Zones in documents: Find documents with (*author = Ullman*) *AND* (text contains ***automata***).

Evidence accumulation

- 1 vs. 0 occurrence of a search term
 - 2 vs. 1 occurrence
 - 3 vs. 2 occurrences, etc.
 - Usually more seems better
- Need term frequency information in docs

Ranking search results

- Boolean queries give inclusion or exclusion of docs.
- Often we want to rank/group results
 - Need to measure proximity from query to each doc.
 - Need to decide whether docs presented to user are singletons, or a group of docs covering various aspects of the query.

Clustering, classification and ranking

- **Clustering:** Given a set of docs, group them into clusters based on their contents.
- **Classification:** Given a set of topics, plus a new doc D , decide which topic(s) D belongs to.
- **Ranking:** Can we learn how to best order a set of documents, e.g., a set of search results

More sophisticated *information* retrieval

- Cross-language information retrieval
- Question answering
- Summarization
- Text mining
- ...

