

pandas.DataFrame.min

df:

	A	B
0	1	4
1	2	5
2	3	6

df.min()



min values:

A	1
B	4

dtype: int64

Contents

[What Makes This Ebook Unique](#)

[Tips for Effective Use of This Ebook](#)

Introduction

The "Axis" Parameter

The "skipna" Parameter

The "numeric_only" Parameter

The "**kwargs" Parameter

Author Biography

Other Ebooks

Contacts and Social Media

Sources & References

Thank You!

1st Edition

Why This E-book?

"The aim of this ebook is to give you the 'aha' moment right away at the start of learning a new concept."

- Practical step By Step Guide With Simple Examples
- Visual Illustrations and Interactive
- Simple Datasets
- Comprehensive Coverage (pandas Documentation used as reference)

Tips for Effective Use of This Ebook

Use Examples First: If you don't understand the text, go straight to the examples—they're self-explanatory. After reviewing them, return to the text to grasp the practical concepts.

Practice with Datasets: Copy the datasets provided and practice using them to reinforce your understanding.

Click on the blue links to go directly to the section you want to learn about.

Introduction

Return the minimum of the values over the requested axis.

df:

	A	B
0	1	4
1	2	5
2	3	6



min values:

A 1
B 4
dtype: int64

Code snippet:

df.min()

Syntax

```
DataFrame.min(axis=0, skipna=True, numeric_only=False, **kwargs)
```

The `axis` parameter

The `axis=0` (or `axis='index'`)

The `min()` function is applied to each column.

For column 'A', the minimum value is 1.

For column 'B', the minimum value is 4.

df:

	A	B
0	1	4
1	2	5
2	3	6



Output:

A 1
B 4
dtype: int64

Code snippet:

```
df.min()  
or  
df.min(axis=0)  
or  
df.min(axis='index')
```

`axis=1` (or `axis='columns'`)

The `min()` function is applied to each row.

For row 0, the minimum value between 1 and 4 is 1.

For row 1, the minimum value between 2 and 5 is 2.

For row 2, the minimum value between 3 and 6 is 3.

df:

	A	B
0	1	4
1	2	5
2	3	6



Output:

0 1
1 2
2 3
dtype: int64

Code snippet:

```
df.min(axis=1)  
or  
df.min(axis='columns')
```

axis=None

The min() function is applied to all the values in the DataFrame.

It finds the overall minimum value, which is 1.

df:

	A	B
0	1	4
1	2	5
2	3	6



output:

1

Code snippet:

```
df.min(axis=None)
```

The `skipna` parameter

It excludes NA/null values when computing the result.

skipna is a boolean, defaulting to True

when skipna=True (Default)

The min() function is applied to each column.

In column 'A', the minimum value is 1 (ignoring the NaN).

In column 'B', the minimum value is 4 (ignoring the NaN).

df:

	A	B	C
0	1.0	4.0	7
1	2.0	NaN	8
2	NaN	6.0	9



Output:

A 1.0

B 4.0

C 7.0

dtype: float64

Code snippet:

```
df.min(skipna=True)
```

In column 'C', the minimum value is 7 (no NaN to ignore).

@Kichere The Data Scientist

when skipna=False

Includes NaN/None values in the calculation, resulting in NaN if any missing values are present.

The min() function is applied to each column.

In column 'A', because there is a NaN, the result is NaN.

In column 'B', because there is a NaN, the result is NaN.

In column 'C', the minimum value is 9 (since there is no NaN).

df:

	A	B	C
0	1.0	4.0	7
1	2.0	NaN	8
2	NaN	6.0	9



Output:

A NaN

B NaN

C 7.0

dtype: float64

Code snippet:

```
df.min(skipna=False)
```

The numeric_only parameter

It includes only float, int, boolean columns.

It is not implemented for Series.

It is boolean, defaulting to False

numeric_only=False (Default))

With "numeric_only=False", all columns are included. The minimum of integers, floats, and booleans is computed. For strings, it returns the lexicographically minimum value.

df:

	A	B	C	D
0	1	4.0	True	x
1	2	5.5	False	y
2	3	6.1	True	z



Output:

A 1
B 4.0
C False
D x
dtype: object

Code snippet:

```
df.min()  
or  
df.min(numeric_only=False)
```

numeric_only=True

With numeric_only=True, only numeric columns (A, B, C) are considered. If all columns are non-numeric, the result will be NaN.

df:

	A	B	C	D
0	1	4.0	x	True
1	2	5.5	y	False
2	3	6.1	z	True



Output:

A 1
B 4.0
D False
dtype: object

Code snippet:

```
df.min(numeric_only=True)
```

The ****kwargs** parameter

he ****kwargs** allows for the inclusion of additional keyword arguments that can be passed to the function, beyond the explicitly defined ones (axis, skipna, and numeric_only).

Sources & References

[pandas.Series.value_counts Documentation](https://pandas.pydata.org/docs/reference/api/pandas.Series.value_counts.html) (https://pandas.pydata.org/docs/reference/api/pandas.Series.value_counts.html)

Other E-books on pandas

[Download](https://github.com/kicherethedatascientist/My_e-Books) (https://github.com/kicherethedatascientist/My_e-Books)

Author Biography

Kichere Magubu is a data enthusiast and content creator.

Contacts and Social Media

Kichere Magubu

 Dar es salaam, Tanzania

 [Kichere Magubu](#)

 [Kichere The Data Scientist](#)

 [KichereTheDataScientist](#)

 [KichereTheDataScientist](#)

✉ kicherethedatascientist@gmail.com

📷 kicherethedatascientist

☎ +255 654 729 851

Powered by
Eastern Africa Statistical Training Centre

Thank You!

Thank you for reading this e-book! If you found it valuable, please consider leaving an honest review. Your feedback and support mean a lot to me!

```
#print("The cell to convert jupyter notebook to html")  
#!jupyter nbconvert --to hide_code_html "df.min.ipynb"
```