Keying in: KhiCAS keys

To get	Press
x^2	[x²] (shows **2, fine)
^ any power	[^]
sqrt(	[ctrl] [x²]
e^((exp)	[e^x] types exp(close with)
ln(	[ctrl] [e^x]
log(base 10	[ctrl] [10^x] types log10(
sin(cos(tan(	[trig] [shift][trig] [ctrl][trig]
pi	[pi] key
| modulus	[shift] [=]
i complex	letter i
" quote	[ctrl] [×]
< >	[ctrl][-] [shift][+]
_ (log_3)	[shift] [-]
negative	[(-)] or [-]

Polynomial **511**

-2x^4+3x^3-x/2+7 leading minus: [(-)]

Rational **511**

(2x^2-3x+1)/((x-1)(x+2)^2) bracket the whole top and bottom

Root / power **511**

x^2sqrt(4-x^2)+(x^2+1)^(1/3) cube root = ^(1/3)

Exponential **511**

3e^(-2x+1)-2^(x+1)+e^-x e^(= [e^x]; e^-x needs no brackets

Logarithm **511**

ln(x^2+1)-2log(x)+ln(x)/ln(3) log=base 10; log3(x): ln(x)/ln(3)

Log equation **121**

log_3(x)+log_3(x-8)=2 log_b(only in this solver

Trig **511**

3sin(2x-pi/3)^2+cos(x/2) sin^2(u): type sin(u)^2; theta: t

Trig equation **331**

2sin(2x-pi/3)=1 then d/r and the interval

Reciprocal trig **511**
sec(x)^2-cosec(2x)+cot(x) type the letters; csc also ok

Inverse trig **511**
arcsin(x/2)+arctan(3x^2) asin(acos(atan(also ok

Modulus **232**
|2x-3|=|x+1| | = [shift][=]; nested: abs(abs(x)-1)

Composite **511**
ln(sqrt(1+e^(2x))) close every bracket

Product/quot. **511**
x^3e^(-x^2)/(1+x) no * needed: 2x(x+1), x^2y

Implicit x,y **514**
x^2y+y^3=2x+1 then the point: (1,1)

Diff. eqn **573**
(x^2+y^2)/(xy) type only the right side of dy/dx =

Complex **132**
1+sqrt(3)i then n = 5 for z^5 (De Moivre)

Don't type	because	Type
sinx^2	means sin(x^2)	**sin(x)^2**
sin^2(x)	error	**sin(x)^2**
1/2x	means x/2	**1/(2x)**
theta	becomes t*h*e*t*a	**t**
f(x)=x^2	f(x) breaks it	**x^2**
||x|-1|	error	**abs(abs(x)-1)**
inf, oo	not supported	**-**
log(x)	is base 10	**ln(x) for base e**

Codes: type on the main menu, e.g. 511.