

CS 374: Section A - Homework 5, Problem 1

Anirudh Konidala

October 6, 2026

Interval $I_i = [a_i, b_i]$ is given by $A[i] = a_i$ and $B[i] = b_i$, all $2n$ values are distinct, and

$$\text{overlap}(i, j) = \max\{0, \min\{b_i, b_j\} - \max\{a_i, a_j\}\}.$$

We want the largest value of $\text{overlap}(i, j)$ over all pairs $i \neq j$, and we assume $n \geq 2$ so that at least one such pair exists. The algorithm only compares input values and subtracts them; it uses no hashing and no radix sort.

Algorithm

Preprocessing: Begin by sorting the intervals by left endpoint with mergesort, permuting B alongside A so that $A[i]$ and $B[i]$ still describe the same interval. After this step $A[1] < A[2] < \dots < A[n]$. This takes $O(n \log n)$ time, and it does not change the answer, since the answer does not depend on how the intervals are numbered.

Main recursion: $\text{MAXOVERLAP}(A[1..n], B[1..n])$, given n intervals sorted by left endpoint, returns the maximum overlap length between any two distinct intervals among them, or 0 if $n < 2$.

$\text{MAXOVERLAP}(A[1..n], B[1..n])$:

if $n < 2$

 return 0 *⟨⟨no pair of distinct intervals⟩⟩*

$m \leftarrow \lfloor n/2 \rfloor$

$left \leftarrow \text{MAXOVERLAP}(A[1..m], B[1..m])$

$right \leftarrow \text{MAXOVERLAP}(A[m+1..n], B[m+1..n])$

$cross \leftarrow \text{CROSSOVERLAP}(A[1..n], B[1..n], m)$

return $\max\{left, right, cross\}$

Conquer step: $\text{CROSSOVERLAP}(A[1..n], B[1..n], m)$, given n intervals sorted by left endpoint and a split index m , returns the maximum of $\text{overlap}(i, j)$ over all pairs with $i \leq m < j$, that is, one interval from the left half and one from the right half.

```

CROSSOVERLAP( $A[1..n], B[1..n], m$ ):
     $bmax \leftarrow B[1]$     ⟨largest right endpoint in left half⟩
    for  $i \leftarrow 2$  to  $m$ 
         $bmax \leftarrow \max\{bmax, B[i]\}$ 
     $best \leftarrow 0$ 
    for  $j \leftarrow m + 1$  to  $n$ 
         $best \leftarrow \max\{best, \min\{bmax, B[j]\} - A[j]\}$ 
    return  $best$ 

```

The answer to the problem is $\text{MAXOVERLAP}(A[1..n], B[1..n])$ called on the sorted arrays.

Example: For $A = \langle 1, 7, 4, 5 \rangle$ and $B = \langle 8, 10, 9, 6 \rangle$, sorting gives the intervals $[1, 8]$, $[4, 9]$, $[5, 6]$, $[7, 10]$. The left half returns $\min\{8, 9\} - 4 = 4$, the right half returns $\max\{0, \min\{6, 10\} - 7\} = 0$, and the cross step has $bmax = 9$ and returns $\max\{\min\{9, 6\} - 5, \min\{9, 10\} - 7\} = 2$. The answer is 4, as required.

Why this is correct

Every pair $i < j$ of distinct intervals has both indices in the left half $[1..m]$, both in the right half $[m + 1..n]$, or $i \leq m < j$. The two recursive calls handle the first two cases, so it suffices to show that CROSSOVERLAP handles the third. This is the hint with $x = A[m + 1]$: every interval in the left half has $a_i < x$ and every interval in the right half has $a_j \geq x$.

Fix $j > m$. Because the array is sorted, $a_i < a_j$ for every $i \leq m$, so $\max\{a_i, a_j\} = a_j$ and

$$\text{overlap}(i, j) = \max\{0, \min\{b_i, b_j\} - a_j\}.$$

For fixed j this is a non-decreasing function of b_i , so the best partner for j in the left half is the interval with the largest right endpoint $bmax$, and the best cross overlap involving j is $\max\{0, \min\{bmax, b_j\} - a_j\}$. CROSSOVERLAP takes the maximum of this quantity over all $j > m$, and starting $best$ at 0 supplies the outer $\max\{0, \cdot\}$. The base case is correct because a set of fewer than two intervals has no pair, and overlaps are never negative, so returning 0 never changes the maximum computed above it.

Running time

CROSSOVERLAP makes one pass over each half, so it runs in $O(n)$ time. The recursion splits the array into two halves and does $O(n)$ extra work, so its running time obeys the mergesort recurrence

$$T(n) = 2T\left(\frac{n}{2}\right) + O(n),$$

ignoring floors and ceilings, which solves to $T(n) = O(n \log n)$. Adding the $O(n \log n)$ preprocessing sort, the whole algorithm runs in

$O(n \log n)$ time.

Sources and collaborators: None.

LLM use: I used Claude (Anthropic) to draft this algorithm and explain its structure to me. I traced it by hand on the example in the handout and on several small inputs against the brute-force $O(n^2)$ answer, and typeset the submission myself.