

```
In [31]: from __future__ import division
```

Yesterday and this morning we saw how we can solve linear equations in 3,4 variables, and some of you have even seen how to do it in general.

We will now go over this more carefully.

```
In [8]: ### Helper functions
def multiply_equation(eq,num):
    """Multiply all coefficients of equation eq by number num.
    Return result"""
    res = []
    for x in eq:
        res += [x*num]
    return res

def add_equations(eq1,eq2):
    """Add eq1 and eq2. Return result"""
    res = []
    for i in range(len(eq1)):
        res.append(eq1[i]+eq2[i])
    return res
```

Solving linear equations - general recipe

Input: List of n equations $eqs = [eqs[0], \dots, eqs[n-1]]$ in n variables. For every $i = 0..n-1$, $eqs[i]$ is a list of $n+1$ numbers.

Output: List of n numbers $[x_0, \dots, x_{n-1}]$ that are a solution to the equations. That is, for every $i = 0..n-1$, $eqs[i][0]x_0 + \dots + eqs[i][n-1]x_{n-1} + eqs[i][n] = 0$

Assumption: We already know how to solve $n-1$ equations in $n-1$ variables.

Operation:

- Ensure that the first coefficient of the first equation is nonzero
- Divide the first equation by its first coefficient to make it one.
- For every $i = 1..n-1$, add to the i^{th} equation a copy of the first equation multiplied by $-eqs[i][0]$ so now the first coefficients of equations $1, \dots, n-1$ is zero.
- Run a solver for the last $n-1$ equations and last $n-1$ variables.
- Use solution to get solution for first variable.

```

In [24]: def solve100(eqs):
        n = len(eqs)
        make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equation non
zero
        eqs[0] = multiply_equation(eqs[0],1/eqs[0][0])
        # make 1st coef of 1st equation equal 1

        for i in range(1,n-1):
            eqs[i] = add_equations(eqs[i],multiply_equation(eqs[0],-eqs[i][0])) #
zero out first coefficient in eqs 1,2
            # make 1st coef of 2nd .. n-th equation equal zero

        rest_equations = []
        for i in range(1,n):
            rest_equations.append(eqs[i][1:n+1])

        solutions = solve99(rest_equations)
        # solve remainder of equations for remainder of variables

        x = - eqs[0][n]
        for i in range(1,n):
            x -= eqs[0][i]*solutions[i-1]
        # solve 1st variable using solution for 2nd and 3rd variable

        return [x] + solutions

```

```

In [23]: def solve99(eqs):
          n = len(eqs)
          make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equation non
zero
          eqs[0] = multiply_equation(eqs[0],1/eqs[0][0])
          # make 1st coef of 1st equation equal 1

          for i in range(1,n-1):
              eqs[i] = add_equations(eqs[i],multiply_equation(eqs[0],-eqs[i][0])) #
zero out first coefficient in eqs 1,2
              # make 1st coef of 2nd .. n-th equation equal zero

          rest_equations = []
          for i in range(1,n):
              rest_equations.append(eqs[i][1:n+1])

          solutions = solve98(rest_equations)
          # solve remainder of equations for remainder of variables

          x = - eqs[0][n]
          for i in range(1,n):
              x -= eqs[0][i]*solutions[i-1]
          # solve 1st variable using solution for 2nd and 3rd variable

          return [x] + solutions

```

So, we could write functions solve1,solve2,...,solve10000

But we can see that they are very similar. The solution for $\text{solve}(n)$ uses $\text{solve}(n - 1)$. This suggests that we should use **recursion**.

```
In [22]: def solve(eqs):
          n = len(eqs)
          make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equation non
          zero
          eqs[0] = multiply_equation(eqs[0], 1/eqs[0][0])
          # make 1st coef of 1st equation equal 1

          for i in range(1, n-1):
              eqs[i] = add_equations(eqs[i], multiply_equation(eqs[0], -eqs[i][0])) #
              zero out first coefficient in eqs 1,2
              # make 1st coef of 2nd .. n-th equation equal zero

          rest_equations = []
          for i in range(1, n):
              rest_equations.append(eqs[i][1:n+1])

          solutions = solve(rest_equations)
          # solve remainder of equations for remainder of variables

          x = - eqs[0][n]
          for i in range(1, n):
              x -= eqs[0][i]*solutions[i-1]
          # solve 1st variable using solution for 2nd and 3rd variable

          return [x] + solutions
```

Let's see if it works:

```
In [17]: solve([[1,2,3],[4,5,6]])
```

```
-----
IndexError                                Traceback (most recent call last)
<ipython-input-17-4bfdb83a874e> in <module>()
----> 1 solve([[1,2,3],[4,5,6]])

<ipython-input-7-f7aa95396613> in solve(eqs)
     13         rest_equations.append(eqs[i][1:n+1])
     14
--> 15     solutions = solve(rest_equations)
     16     # solve remainder of equations for remainder of variables
     17

<ipython-input-7-f7aa95396613> in solve(eqs)
      2     n = len(eqs)
      3     make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equation nonzero
----> 4     eqs[0] = multiply_equation(eqs[0],1/eqs[0][0])
      5     # make 1st coef of 1st equation equal 1
      6

IndexError: list index out of range
```

Since it didn't work let's try to see where the problem was: let's print the length of equations so we understand where in the recursion it fails.

```
In [20]: def solve(eqs):
        n = len(eqs)
        print "Solving ", n, " equations in ", n, "variables"
        make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equation non
        zero
        eqs[0] = multiply_equation(eqs[0],1/eqs[0][0])
        # make 1st coef of 1st equation equal 1

        for i in range(1,n-1):
            eqs[i] = add_equations(eqs[i],multiply_equation(eqs[0],-eqs[i][0])) #
            zero out first coefficient in eqs 1,2
            # make 1st coef of 2nd .. n-th equation equal zero

        rest_equations = []
        for i in range(1,n):
            rest_equations.append(eqs[i][1:n+1])

        solutions = solve(rest_equations)
        # solve remainder of equations for remainder of variables

        x = - eqs[0][n]
        for i in range(1,n):
            x -= eqs[0][i]*solutions[i-1]
        # solve 1st variable using solution for 2nd and 3rd variable

        return [x] + solutions
```

```
In [25]: solve([[1,2,3],[4,5,6]])
```

```
-----  
IndexError                                Traceback (most recent call last)  
<ipython-input-25-4bfdb83a874e> in <module>()  
----> 1 solve([[1,2,3],[4,5,6]])  
  
<ipython-input-22-3e3cfce514> in solve(eqs)  
    13         rest_equations.append(eqs[i][1:n+1])  
    14  
----> 15     solutions = solve(rest_equations)  
    16     # solve remainder of equations for remainder of variables  
    17  
  
<ipython-input-22-3e3cfce514> in solve(eqs)  
    13         rest_equations.append(eqs[i][1:n+1])  
    14  
----> 15     solutions = solve(rest_equations)  
    16     # solve remainder of equations for remainder of variables  
    17  
  
<ipython-input-22-3e3cfce514> in solve(eqs)  
     2     n = len(eqs)  
     3     make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equ  
ation nonzero  
----> 4     eqs[0] = multiply_equation(eqs[0],1/eqs[0][0])  
     5     # make 1st coef of 1st equation equal 1  
     6  
  
IndexError: list index out of range
```

We tried to solve **zero equations in zero variables**! No wonder we ran into trouble.

The problem is that we need to always have a **base** for the recursion. Just like we need a base for *proofs by inductions* in mathematics.

Here is an updated version:

```

In [35]: def solve(eqs):
    n = len(eqs)
    print "Solving ", n, " equations in ", n, "variables"
    if n==1:
        return [ -eqs[0][1]/eqs[0][0] ]
    make_first_coeff_nonzero_general(eqs) # make 1st coef of 1st equation non
zero
    eqs[0] = multiply_equation(eqs[0],1/eqs[0][0])
    # make 1st coef of 1st equation equal 1

    for i in range(1,n):
        eqs[i] = add_equations(eqs[i],multiply_equation(eqs[0],-eqs[i][0])) #
zero out first coefficient in eqs 1,2
        # make 1st coef of 2nd .. n-th equation equal zero

    rest_equations = []
    for i in range(1,n):
        rest_equations.append(eqs[i][1:n+1])

    solutions = solve(rest_equations)
    # solve remainder of equations for remainder of variables

    x = - eqs[0][n]
    for i in range(1,n):
        x -= eqs[0][i]*solutions[i-1]
    # solve 1st variable using solution for 2nd and 3rd variable

    return [x] + solutions

```

```

In [36]: solve([[1,2,3],[4,5,6]])

```

```

Solving 2 equations in 2 variables
Solving 1 equations in 1 variables
Solving 0 equations in 0 variables

```

```

Out[36]: [1.0, -2.0]

```

Let's check if it can solve 25 equations in 25 variables.

```
In [42]: n= 25
solutions = []
for j in range(n):
    solutions.append(j)
```

```
In [43]: solutions
```

```
Out[43]: [0,
1,
2,
3,
4,
5,
6,
7,
8,
9,
10,
11,
12,
13,
14,
15,
16,
17,
18,
19,
20,
21,
22,
23,
24]
```

```
In [44]: import random
equations = []
for i in range(n):
    constant_term = 0
    eq = []
    for j in range(n):
        x = random.randint(-100,+100)
        eq.append(x)
        constant_term -= x*solutions[j]
    eq.append(constant_term)
    equations.append(eq)
```



```
In [49]: my_solutions = solve(equations)
```

```
Solving 25 equations in 25 variables  
Solving 24 equations in 24 variables  
Solving 23 equations in 23 variables  
Solving 22 equations in 22 variables  
Solving 21 equations in 21 variables  
Solving 20 equations in 20 variables  
Solving 19 equations in 19 variables  
Solving 18 equations in 18 variables  
Solving 17 equations in 17 variables  
Solving 16 equations in 16 variables  
Solving 15 equations in 15 variables  
Solving 14 equations in 14 variables  
Solving 13 equations in 13 variables  
Solving 12 equations in 12 variables  
Solving 11 equations in 11 variables  
Solving 10 equations in 10 variables  
Solving 9 equations in 9 variables  
Solving 8 equations in 8 variables  
Solving 7 equations in 7 variables  
Solving 6 equations in 6 variables  
Solving 5 equations in 5 variables  
Solving 4 equations in 4 variables  
Solving 3 equations in 3 variables  
Solving 2 equations in 2 variables  
Solving 1 equations in 1 variables  
Solving 0 equations in 0 variables
```

```
In [50]: my_solutions
```

```
Out[50]: [-4.0456527017340704e-13,  
0.9999999999998579,  
1.9999999999998543,  
3.0000000000005302,  
4.0000000000001315,  
4.999999999999893,  
6.000000000000206,  
6.999999999999762,  
8.000000000000284,  
8.999999999999783,  
9.999999999999716,  
11.000000000000341,  
12.000000000000338,  
12.999999999999893,  
14.000000000000146,  
14.999999999999332,  
15.99999999999972,  
16.99999999999982,  
17.99999999999974,  
19.00000000000005,  
19.99999999999986,  
20.999999999999563,  
22.00000000000005,  
22.999999999999698,  
23.99999999999945]
```

```
In [51]: round_solutions = []  
         for x in my_solutions:  
             round_solutions.append(round(x,3))  
         round_solutions
```

```
Out[51]: [-0.0,  
          1.0,  
          2.0,  
          3.0,  
          4.0,  
          5.0,  
          6.0,  
          7.0,  
          8.0,  
          9.0,  
          10.0,  
          11.0,  
          12.0,  
          13.0,  
          14.0,  
          15.0,  
          16.0,  
          17.0,  
          18.0,  
          19.0,  
          20.0,  
          21.0,  
          22.0,  
          23.0,  
          24.0]
```

```
In [53]: [ round(x,3) for x in my_solutions ]
```

```
Out[53]: [-0.0,  
          1.0,  
          2.0,  
          3.0,  
          4.0,  
          5.0,  
          6.0,  
          7.0,  
          8.0,  
          9.0,  
          10.0,  
          11.0,  
          12.0,  
          13.0,  
          14.0,  
          15.0,  
          16.0,  
          17.0,  
          18.0,  
          19.0,  
          20.0,  
          21.0,  
          22.0,  
          23.0,  
          24.0]
```

Sorting

We have now obtained a function `solve` that solves general linear equations. This is still not enough however. Eventually, we want to be able to achieve a function that reads the equations and outputs the solution, like the following:

```
In [66]: solve_eqs()
```

```
Number of variables / equations?3  
Enter equation number 1: 5x - y + z = 0  
Enter equation number 2: 2y - 3y = 4 + z  
Enter equation number 3: 10z - 4x +3y = 20  
Solving 3 equations in 3 variables  
Solving 2 equations in 2 variables  
Solving 1 equations in 1 variables  
Solving 0 equations in 0 variables  
x = -2.13953488372  
y = -7.3488372093  
z = 3.3488372093
```

Note that the equations now are given in arbitrary order, so we will need to **sort** them to make them into the standard format of $ax + by + cz + d = 0$ so we can extract the coefficients $[a, b, c, d]$ for our `solve` function.

So, we will now talk about sorting lists. That is, coming up with a function `sort_list`

```
In [77]: sort_list([9,8,7,6,5])
```

```
Out[77]: [5, 6, 7, 8, 9]
```

```
In [78]: sort_list([100,3,4,8,7])
```

```
Out[78]: [3, 4, 7, 8, 100]
```

```
In [79]: sort_list([3,1,4,1,5,9,2])
```

```
Out[79]: [1, 1, 2, 3, 4, 5, 9]
```

As usual, we will start by writing `sort2`:

```
In [7]: def sort2(L):  
        if L[0]>L[1]:  
            L[0],L[1] = L[1],L[0]  
        return L
```

```
In [8]: sort2([1,2])
```

```
Out[8]: [1, 2]
```

```
In [9]: sort2([2,1])
```

```
Out[9]: [1, 2]
```

And then `sort3`:

```
In [17]: def sort3(L):  
        if L[0]>L[1]:  
            L[0],L[1] = L[1],L[0]  
        if L[0]>L[2]:  
            L[0],L[1] = L[1],L[0]  
        return [L[0]] + sort2(L[1:3])
```

```
In [18]: sort3([9,5,8])
```

```
Out[18]: [5, 8, 9]
```

Theorem: For every three numbers x_0, x_1, x_2 , `sort3`($[x_0, x_1, x_2]$) returns a list $[x_i, x_j, x_k]$ such that $x_i \leq x_j \leq x_k$ and i, j, k are distinct numbers in $\{0, 1, 2\}$.

Proof: Suppose we run $\text{sort3}([x_0, x_1, x_2])$. Let's split into cases:

Case 1: $x_0 \leq \min\{x_1, x_2\}$. Then both if's don't execute, and we output $[x_0] + \text{sort2}([x_1, x_2])$. Since x_0 is the smallest element then this output will be sorted.

Case 2: $x_0 > x_1$ but $x_1 \leq x_2$. Then the first if executes and after it is done, $L[0] = x_1$. Because $x_1 \leq x_2$, the second if does not execute, and we output $[x_1] + \text{sort2}([x_0, x_2])$. Since x_1 is the smallest element then this output will be sorted.

Case 3: $x_0 > x_1$ and $x_1 > x_2$. Then the first if executes, and after it $L[0] = x_1$ and then the second if executes and after it, $L[0] = x_2$. We output $[x_2] + \text{sort2}([x_1, x_0])$ which will be sorted since x_2 is the smallest element.

Curious fact:

```
In [19]: sort3(['cat', 'apple', 'dog'])
```

```
Out[19]: ['apple', 'cat', 'dog']
```

```
In [21]: 'apple' < 'cat'
```

```
Out[21]: True
```

```
In [22]: 'car' > 'cat'
```

```
Out[22]: False
```

Lab Work

Exercise 1

Write the function $\text{sort4}(L)$ that takes a list of 4 elements and sorts it. The last line of the function must be `return [L[0]]+sort3(L[1:4])`

```
In [30]: sort4 = sort_list
```

```
In [31]: def sort4(L):  
        #  
        # your code goes below  
        #  
        return [L[0]]+ sort3(L[1:4])
```

Here are some output examples:

```
In [27]: sort4([7,8,1,2])
```

```
Out[27]: [1, 2, 7, 8]
```

```
In [28]: sort4([1,9,2,3])
```

```
Out[28]: [1, 2, 3, 9]
```

```
In [29]: sort4(['Mickey','Donald','Goofy','Minney'])
```

```
Out[29]: ['Donald', 'Goofy', 'Mickey', 'Minney']
```

Exercise 2

Suppose that you are given the function `sort9` that sorts a list of 9 elements. Write a function `sort10(L)` that sorts a list `L` of 10 elements. The last line of the function must be `return [L[0]]+sort9(L[1:4])`

```
In [32]: # you can use this function as a "black box" but there's no need to read it or  
understand its code  
def sort9(L):  
    return sorted(L[0:9])
```

```
In [33]: def sort10(L):  
    #  
    # your code goes below  
    #  
    return [L[0]] + sort9(L[1:10])
```

```
In [37]: sort10([0, 1, 6, 10, 9, 3, 3, 9, 9, 5])
```

```
Out[37]: [0, 1, 3, 3, 5, 6, 9, 9, 9, 10]
```

```
In [40]: sort10([15, 16, 19, 13, 5, 1, 7, 19, 12, 4])
```

```
Out[40]: [15, 1, 4, 5, 7, 12, 13, 16, 19, 19]
```

```
In [42]: sort10([5, 9, 13, 8, 15, 17, 20, 9, 10, 8])
```

```
Out[42]: [5, 8, 8, 9, 9, 10, 13, 15, 17, 20]
```

Exercise 3

Use *recursion* to write the general `sort_list(L)` function that works for lists of *any* length. Again, the last line of your code must be a recursive call to `sort_list` of the form `return [L[0]]+sort_list(L[1:len(L)])`

```
In [43]: def sort_list(L):  
        #  
        # your code goes below  
        #  
        return [L[0]] + sort_list(L[1:len(L)])
```

The array below contains the names of all the students that were registered to the course. Compute an array that contains these students in alphabetical order by first name. Use the function you wrote to sort it by first name.

```
In [56]: L = ['Abinet Mulugeta', 'urgie Huseien', 'Yonatan Wosenyeleh', 'Amanuel Asfa  
w', 'Tibebu Solomon', 'Hailegbrel Wudneh', 'Gatluk Chuol', 'Elsabet Buzuneh',  
'Eden ketema', 'Maeden Seid', 'Mikyias Legese', 'Meskerem Birhanu Demeke', 'Kum  
neger Worku', 'Shambel Abate', 'Hailmeskel Shimeles', 'Tsega Hailu', 'Dawit Fi  
keru', 'Asmare Habitamo', 'Zelalem Ades', 'Betelehem Eshetu', 'Yosef Tadiwos',  
'Haymanot Gidena', 'Henock Mersha', 'Binyam Kidane', 'Mohammed Nur', 'Bethele  
hem Walelegn', 'Lewi mekonnen', 'Wondimu Yohanes', 'Hodo Mukitar', 'Yonas Adug  
na', 'Tigabu Gebrecherkos', 'Nardos Gesese', 'Mohammed Nur', 'Abdurezak  
Temam', 'Shambel Elena', 'Adem Mohamed', 'Zakira Tebarek', 'Lidya Gegnaw', 'kn  
esa Desta', 'Ibrahim Ahmed', 'Betlehem Desalegn', 'Adonay Geremew', 'kalkidan  
Muluneh', 'Haile GebreSelasie', 'Eden Tekilu Tilahun', 'Ayantu Aleneh', 'Yose  
f Nosha', 'Mebrihity Girmay', 'Finet Hailu', 'Elisa Feloh', 'Bezawit Gebremari  
am', 'Nigusu Terefe', 'Amina Bedrie', 'Kiflom Leuel', 'Hana Tariku', 'Nejat Be  
shir', 'Mesfen Tamiru', 'Shafi Abdi', 'kelbesa Ambesa', 'Abrham Tuna', 'Daniel  
Hagos', 'yordanos Jemberu', 'Aman Musa', 'Habene Abdi', 'Kawuser Jemal', 'Tar  
iku Erina', 'Mesigina GebreTsadik', 'Yetnayet Birhanu', 'Semer Abrar', 'Nur ah  
med', 'Eman Hasen', 'Natol Gizaw', 'Banchayehu Asrat', 'Hilina Thewodros', 'Ha  
sen Ali', 'Mebrihatu Lebelo', 'Yosef Enawgaw', 'Nesera Teyib', 'Mekdes Mulune  
h', 'Surafel Sewutu', 'Mentesenot Tefera']
```

Exercise 4

Sort the array above in *reverse alphabetical order* by first name (so that L[0] will be the name that is last in alphabetical order and L[80] will be the name that is first)

Exercise 5 (bonus)

Sort the array in alphabetical order by **last name**.

In []: