

DISCUSSION LOG

Sikang Yan

University of Kaiserslautern

yan@rhrk.uni-kl.de

February 17, 2019

THEORY

In our cloth simulation, we follow the procedure written by Rohmer et al.. We consider to begin with the *Deformation gradient* \mathbf{F} , which is defined by

$$\mathbf{F} = \frac{\partial \mathbf{x}}{\partial \mathbf{X}}, \quad (1)$$

where the \mathbf{x} denotes the deformed vector and the \mathbf{X} denotes the reference vector.

Since we have no further information about the mapping from \mathbf{X} to \mathbf{x} , we use the vector $(\mathbf{u}_1, \mathbf{u}_2)$ and $(\overline{\mathbf{u}}_1, \overline{\mathbf{u}}_2)$ to approximate the Deformation gradient, which is defined as

$$\mathbf{F} = [\mathbf{u}_1, \mathbf{u}_2] [\overline{\mathbf{u}}_1, \overline{\mathbf{u}}_2]^{-1}, \quad (2)$$

Attention should be paid especially:

- eq.(2) characrizе only the 2D deformation of each triangle.
- in Rohmer et al. \mathbf{F} is symbolised as \mathbf{T} .

We provide here our code preceed with concrete data:

- $faces(i, j)$ is the j th vertex of the i th triangle, here we choose the $face(0, 0)$, $face(0, 1)$, $face(0, 2)$ as examples and calculate the $VecT$ and $VecR$ for $face(0, 0)$.

$$VecT = e_{l_1} VertT_1 - e_{l_1} VertT_2; e_{l_1} VertT_1 - e_{l_1} VertT_3 \quad (3)$$

$$VecR = e_{l_1} VertR_1 - e_{l_1} VertR_2; e_{l_1} VertR_1 - e_{l_1} VertR_3 \quad (4)$$

$$VecT = [0.771842 \quad -0.0144887 \quad 6.39045] - [0.780121 \quad -0.0186188 \quad 6.37318] \quad (5)$$

$$[0.771842 \quad -0.0144887 \quad 6.39045] - [0.737177 \quad -0.00912791 \quad 6.39292] \quad (6)$$

$$VecR = [0.759919 \quad -0.015194 \quad 6.38401] - [0.767822 \quad -0.0212492 \quad 6.3669]; \quad (7)$$

$$[0.759919 \quad -0.015194 \quad 6.38401] - [0.726977 \quad -0.00749985 \quad 6.38692] \quad (8)$$

$$(9)$$

such that

cloth_vec

$$VecT = [-0.0079 \ 0.0061 \ 0.0171 \ 0.0329 \ -0.0077 \ -0.0029]; \quad (10)$$

$$VecR = [-0.0083 \ 0.0041 \ 0.0173 \ 0.0347 \ -0.0054 \ -0.0025]; \quad (11)$$

$$(12)$$

where the first 3 entries of $VecR$ is the vector \mathbf{u}_1 and the last 3 entries of $VecR$ is the vector \mathbf{u}_2 . $VecT$ analogously.

cloth_eig_2D

we use here *Eigen :: Map* to transform the vector *VecT* and *VecR* to 2×2 2D deformation gradient \mathbf{F} .

$$\mathbf{F} = \begin{bmatrix} -0.0083 & 0.0347 \\ 0.0041 & -0.0054 \end{bmatrix} \begin{bmatrix} -0.0079 & 0.0329 \\ 0.0061 & -0.0077 \end{bmatrix}^{-1} \quad (13)$$

hence the \mathbf{F} has a rotation information \mathbf{R} and a stretch information \mathbf{U} ,

$$\mathbf{F} = \mathbf{R}\mathbf{U}. \quad (14)$$

we use $\mathbf{F}^T \mathbf{F}$ to eliminate the rotation information to obtain $\det \mathbf{R} = 1$

$$\mathbf{F}^T \mathbf{F} = (\mathbf{R}\mathbf{U})^T \mathbf{R}\mathbf{U} \quad (15)$$

$$= \mathbf{U}^T \mathbf{R}^T \mathbf{R} \mathbf{U} \quad (16)$$

$$= \mathbf{U}^2 \quad (17)$$

$$= \mathbf{C} \quad (18)$$

and using decomposition, if we have the form

$$\mathbf{C} = \lambda_1^2 \mathbf{v}_1 \mathbf{v}_1^T + \lambda_2^2 \mathbf{v}_2 \mathbf{v}_2^T \quad (19)$$

then we could obtain the \mathbf{U} by applying

$$\mathbf{U} = \lambda_1 \mathbf{v}_1 \mathbf{v}_1^T + \lambda_2 \mathbf{v}_2 \mathbf{v}_2^T \quad (20)$$




Figure: Singular Value Decomposition SVD

the main drawback of Rohmer et al. is that this is only applied for 2D problem, thus we need a new algorithm, which can also take the consideration for the vertical deformation. Therefore, the *Kabisch Algorithm* is introduced.

Kabsch Algorithm

Let \mathbf{P} denotes the points set of template frame, and \mathbf{Q} denotes the points set of reference frame. The *optimal rotation matrix* \mathbf{R} can be calculated as

$$\mathbf{R} = \mathbf{V} \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & d \end{bmatrix} \mathbf{U}^T \quad (21)$$

where \mathbf{V} and \mathbf{U} and the *SVD* of *cross-covariance matrix* \mathbf{H} , which is determined by

Theorem (cross-covariance matrix)

$$\mathbf{H} = \mathbf{P}^T \mathbf{Q} \quad (22)$$

and $d = \det \mathbf{V} \mathbf{U}^T$

The cross-covariance matrix describe the covariance of one process with the other at pairs of time points and measure of similarity. We use therefore the cross-covariance matrix \mathbf{H} to approximate our deformation gradient \mathbf{F} .




Figure: Procrustes superimposition

Let i be the all index set of the nearest vertex of vertex l in the template frame and \bar{i} be the all index set of the nearest vertex of vertex l in the template frame. Process define

$$\mathbf{P} = \begin{bmatrix} \vec{x}_1 & \vec{y}_1 & \vec{z}_1 \\ \vec{x}_2 & \vec{y}_2 & \vec{z}_2 \\ \vdots & & \\ \vec{x}_N & \vec{y}_N & \vec{z}_N \end{bmatrix} \quad 1, 2, \dots, N \in i \quad (23)$$

$$\mathbf{Q} = \begin{bmatrix} \vec{\bar{x}}_1 & \vec{\bar{y}}_1 & \vec{\bar{z}}_1 \\ \vec{\bar{x}}_2 & \vec{\bar{y}}_2 & \vec{\bar{z}}_2 \\ \vdots & & \\ \vec{\bar{x}}_N & \vec{\bar{y}}_N & \vec{\bar{z}}_N \end{bmatrix} \quad 1, 2, \dots, N \in \bar{i} \quad (24)$$

and we apply to obtain the deformation gradient \mathbf{F} of vertex l

$$\mathbf{F} = \mathbf{P}^T \mathbf{Q} \quad (25)$$

from 0-2 EigNorm1 8759 NaN, Problrm:: 26278 has -0 eigenvalues, can't be squire. So I use a if(isnan) and define idx=0.
add lambda1,2,3 for all, which is in debug

save the backside of clothes using 1-2, 1-3, 1-4. NOt much differences from colormap, need a new color map???

save lambda1 for 1,74, they are different, but slightly.

lambda2 has more differences

do also for lambda3

check color run application in loop consider the kr to ring 1-2 1-3 ... 1-4
2-5 ... 72-75
tensor flow
Neo Hook matrial