

Machine Learning 2018 – Clustering


Kien C Nguyen

April 27, 2020

Introduction

- 1 Supervised Learning
 - Input : data X and label Y
 - Goal : find parameters w that minimize the loss function
- 2 Why Supervised Learning?
 - predict outcomes from previous experiences

Figure: (Source: Orchestrating Development Lifecycle of Machine Learning Based IoT Applications: A Survey, Zhenyu Wen)




Introduction

① Unsupervised Learning

- Input : data X
- Goal : group data by finding some commonality in the features


② Why Supervised Learning?

- find features which can be useful for categorization
- find all kind of unknown patterns in data



1 Applications

- Spam email filter
- Marketing and Sales
- Social Network




Introduction - Clustering

- Input : $S = \{x^{(i)}\}_{i=1}^N$ (N : number of samples), each sample (data point) is a D -dimensional vector

$$x^i = (x_1^i, x_2^i, \dots, x_D^i)^T$$

- Output: find structure in the data and organize them into groups.


Figure: Input samples. (Source: UIUC CS446 Lecture notes [1])



Introduction - Clustering

- A cluster is a set of samples that are alike
- Samples in different clusters are not alike

Figure: Clustered input samples. (Source: UIUC CS446 Lecture notes [1])



- A distance measure (metric) is a function $d : R^D \times R^D \rightarrow R$ that satisfies
 - 1 $d(\mathbf{x}, \mathbf{y}) \geq 0$, $d(\mathbf{x}, \mathbf{y}) = 0 \Leftrightarrow \mathbf{x} = \mathbf{y}$
 - 2 $d(\mathbf{x}, \mathbf{y}) + d(\mathbf{y}, \mathbf{z}) \geq d(\mathbf{x}, \mathbf{z})$ (Triangle inequality)
 - 3 $d(\mathbf{x}, \mathbf{y}) = d(\mathbf{y}, \mathbf{x})$ (Symmetry)
- For the purpose of clustering, sometimes we can use distances that are not a metric (e.g. those that do not satisfy triangle inequality or symmetry.)

- L^2 distance (Euclidean distance)

$$\begin{aligned}d(\mathbf{x}, \mathbf{y}) &= \|\mathbf{x} - \mathbf{y}\|_2 = \sqrt{(\mathbf{x} - \mathbf{y})^T (\mathbf{x} - \mathbf{y})} \\&= \sqrt{(\mathbf{x} - \mathbf{y})^T (\mathbf{x} - \mathbf{y})} = \sqrt{\sum_{i=1}^D (x_i - y_i)^2}\end{aligned}$$

- L^1 distance (Manhattan distance)


$$d(\mathbf{x}, \mathbf{y}) = \|\mathbf{x} - \mathbf{y}\|_1 = \sum_{i=1}^D |x_i - y_i|$$

- L^∞ distance (sup distance)

$$d(\mathbf{x}, \mathbf{y}) = \|\mathbf{x} - \mathbf{y}\|_\infty = \max_{1 \leq i \leq D} |x_i - y_i|$$

Distance measures

Figure: Different types of distance measures. (Source: UIUC CS446 Lecture notes [1])



$$\text{Euclidean} = (4^2 + 2^2)^{1/2} = 4.47$$


$$\text{Manhattan} : 4 + 2 = 6$$

$$\text{Sup} = \text{Max}(4, 2) = 4$$



Distance measures

- We are given a matrix of distances between any pair of samples.


Figure: Matrix of distances. (Source: UIUC CS446 Lecture notes [1])




K-means Algorithm




K-means Algorithm




K-means Algorithm



K-means Algorithm



K-means Algorithm



K-means Algorithm

Input:

- K (number of clusters)
- $\{x^{(i)}\}_{i=1}^N$

Initialization:

Randomly initialize K cluster centroids $\mu_1, \mu_2, \dots, \mu_K \in \mathbb{R}^D$

while *Assignment changes from the last iteration* **do**

Assignment:

for $i = 1$ to N **do**

 Assign $x^{(i)}$ to the cluster with the minimum distance $d(x^{(i)}, \mu_k)$

end

Update:

for $j=1$ to K **do**

$\mu_k =$ mean of all the points assigned to cluster k

end

end

Algorithm 1: K-means Algorithm

Challenges of K-means


- Different K different outputs.
- With same K, the output won't be always the same because of the randomly initial centroids.
- Due to the nature of Euclidean distance, it is not a suitable algorithm when dealing with clusters that adopt non-spherical shapes.

How to choose right K

- Field knowledge
- Business decision
- Elbow Method


Elbow Method

- The elbow method is used for determining the correct number of clusters in a dataset.
- How it works? Plot the cost function against K and choose K using the "elbow" method.



K-means Limitations

- K-means clustering with spherical-shaped distributions



- Hierarchical Clustering
- Density-Based Spatial Clustering of Applications with Noise (DBSCAN)
- Gaussian Mixture Models (GMM)
- Principal component analysis (PCA)

- [1] UIUC CS 446 Machine Learning
- [2] Andrew Ng – Coursera Machine Learning
- [3] <https://towardsdatascience.com/unsupervised-machine-learning-clustering-analysis-d40f2b34ae7e>