

Dual Mast Aerial Platform

KEAWPD Series



**Fixture for
Platform Guardrail**




Push/ Pull Handle



Spirit Level



**Motorized Drive
(Optional)**



**Drive Wheel
(Optional)**



PU Wheels

Standard Configurations

- Auxiliary Lowering Device
- Big Level Gauge
- Emergency Stop Button
- Anti-burst System
- Platform and Ground Control
- Limit Switches
- Short Circuit and Leakage Protection System

Optional Configurations

- DC24V or DC 48V or Manual Power
- Hydraulic Power Pack
- Explosion-Proof System
- Motorized Device
- Isolation Platform

Dual Mast Aerial Platform.

KEAWPD Series



MODEL	KEAWPD-6M	KEAWPD-8M	KEAWPD-9M	KEAWPD-10M	KEAWPD-12M	KEAWPD-14M
Lift capacity	200kg	200kg	200kg	200kg	200kg	150kg
Platform occupancy max	1	1	1	1	1	1
Working height max	8.00m	10.00m	11.00m	12.00m	14.00m	16.00m
Platform height max	6.00m	8.00m	9.00m	10.00m	12.00m	14.00m
Stowed length	1.54m	1.54m	1.54m	1.76m	1.76m	1.9m
Stowed width	1.00m	1.00m	1.00m	1.00m	1.00m	1.16m
Stowed height	2.00m	2.00m	2.00m	2.00m	2.00m	2.31m
Platform size	1.30*0.62m	1.30*0.62m	1.30*0.62m	1.52*0.62m	1.52*0.62m	1.52*0.62m
Outrigger Footprint	1.77*1.82m	1.77*1.82m	1.77*1.82m	2.1*2.00m	2.1*2.00m	2.36*2.33m
Ground clearance	0.05m	0.05m	0.05m	0.05m	0.05m	0.05m
Lifting motor (AC)	1.1kW	1.1kW	1.1kW	1.1kW	1.1kW	1.1kW
Weight (AC)	600KG	660KG	730KG	780KG	830KG	900KG
Power source (Optional)	24v/100Ah	24v/100Ah	24v/100Ah	24v/100Ah	24v/100Ah	24v/100Ah
Lifting Motor (DC) (Optional)	0.80kw	0.80kw	0.80kw	0.80kw	1.5kw	1.5kw
Charger (Optional)	24V/15A	24V/15A	24V/15A	24V/15A	24V/15A	24V/15A

Note: There may be any specification/dimensional change. If these specifications are critical, the proposed application should be discussed.