

AetherBeam: High-Fidelity Nonlinear Waveguide Acoustic Ray-Tracing Engine

Mathematical Formulation and Physical Principles of Orders 0–4 Sound Beam Synthesis

Kijjaz

AetherBeam Reverb DSP Architecture

September 2026

Abstract

This document presents the complete mathematical architecture of the **AetherBeam** physical acoustic engine. The system synthesizes spatial impulse responses by combining higher-order 3D geometric image-source ray tracing (Orders $0 \leq n \leq 4$, generating up to 96 physical acoustic reflection paths per enclosure), analytic boundary collision validation, and finite-amplitude weakly nonlinear acoustic wave propagation (Fubini-Bessel shock steepening under extreme sound pressure levels up to 122 dB SPL, representative of a full symphony orchestra playing at *fff*).

Contents

1	3D Architectural Image-Source Geometry (Orders 0–4)	2
1.1	Lattice Coordinate Transformation	2
1.2	Ray Trajectory and Propagation Metric	2
1.3	Trajectory Folding and Boundary Intersection	2
2	Strict Architectural Boundary Containment	2
2.1	Sydney Opera House (Pitched Vault)	3
2.2	Rome Pantheon (Cylinder + Hemisphere Dome)	3
2.3	Hagia Sophia (Central Dome + Exedrae)	3
3	Finite-Amplitude Nonlinear Wave Steepening (<i>fff</i> Dynamics)	3
3.1	Burgers' Equation and Acoustic Nonlinearity Parameter	3
3.2	Shock Formation Distance and Distortion Parameter	3
3.3	Discrete Nonlinear Waveguide Implementation	4
3.4	Physical Proof: Loudness-Dependent Timbral Evolution	4
4	Frequency-Dependent Air Absorption and Wall Impedance	5
4.1	ISO 9613-1 Atmospheric Attenuation	5
4.2	Wall Reflection Loss	5
5	Total Impulse Response Synthesis	5
6	Showcase Enclosure Parameters	5

1 3D Architectural Image-Source Geometry (Orders 0–4)

Let the bounding coordinates of an acoustic enclosure $\Omega \subset \mathbb{R}^3$ be denoted by:

$$\Omega = [x_{\min}, x_{\max}] \times [y_{\min}, y_{\max}] \times [z_{\min}, z_{\max}] \quad (1)$$

with enclosure dimensions $L_x = x_{\max} - x_{\min}$, $L_y = y_{\max} - y_{\min}$, and $L_z = z_{\max} - z_{\min}$.

Let $\mathbf{s} = (s_x, s_y, s_z)^\top \in \Omega$ denote the physical acoustic source position, and $\mathbf{r} = (r_x, r_y, r_z)^\top \in \Omega$ denote the listener (receiver) position.

1.1 Lattice Coordinate Transformation

Relative to the enclosure minimum origin $\mathbf{b}_{\min}$, coordinates are mapped to $\mathbf{s}_{\text{rel}} = \mathbf{s} - \mathbf{b}_{\min}$ and $\mathbf{r}_{\text{rel}} = \mathbf{r} - \mathbf{b}_{\min}$.

For reflection index vector $\mathbf{n} = (n_x, n_y, n_z) \in \mathbb{Z}^3$, the virtual image-source coordinate along coordinate axis $i \in \{x, y, z\}$ is defined by:

$$s'_i(n_i) = \begin{cases} n_i L_i + s_{\text{rel},i}, & \text{if } n_i \equiv 0 \pmod{2} \\ (n_i + 1)L_i - s_{\text{rel},i}, & \text{if } n_i \equiv 1 \pmod{2} \end{cases} \quad (2)$$

The total reflection order $N(\mathbf{n})$ is the ℓ_1 norm of the lattice index vector:

$$N(\mathbf{n}) = |n_x| + |n_y| + |n_z|, \quad 0 \leq N(\mathbf{n}) \leq 4 \quad (3)$$

1.2 Ray Trajectory and Propagation Metric

The Euclidean vector from the virtual image-source $\mathbf{s}'(\mathbf{n})$ to the receiver $\mathbf{r}_{\text{rel}}$ is:

$$\mathbf{d}(\mathbf{n}) = \mathbf{r}_{\text{rel}} - \mathbf{s}'(\mathbf{n}) \quad (4)$$

with total propagation distance:

$$d(\mathbf{n}) = \|\mathbf{d}(\mathbf{n})\|_2 = \sqrt{(r_{\text{rel},x} - s'_x)^2 + (r_{\text{rel},y} - s'_y)^2 + (r_{\text{rel},z} - s'_z)^2} \quad (5)$$

The corresponding acoustic propagation delay $\tau(\mathbf{n})$ in dry air at 20°C ($c_0 = 343.2$ m/s) is:

$$\tau(\mathbf{n}) = \frac{d(\mathbf{n})}{c_0} \quad (6)$$

1.3 Trajectory Folding and Boundary Intersection

The folded spatial position $\mathbf{p}(t)$ of a ray along normalized path parameter $t \in [0, 1]$ is obtained via periodic coordinate folding:

$$p_i(t) = \text{fold}\left(s'_i + t \cdot d_i(\mathbf{n}), L_i\right) + b_{\min,i} \quad (7)$$

where:

$$\text{fold}(u, L) = \begin{cases} u \pmod{2L}, & \text{if } (u \pmod{2L}) \leq L \\ 2L - (u \pmod{2L}), & \text{otherwise} \end{cases} \quad (8)$$

2 Strict Architectural Boundary Containment

To ensure sound rays never escape non-rectangular or open-air architectures, every reflection point $\mathbf{p} \in \mathbb{R}^3$ must satisfy the space-specific manifold constraint:

$$\mathcal{C}_{\text{space}}(\mathbf{p}) \leq 0 \quad (9)$$

2.1 Sydney Opera House (Pitched Vault)

$$\mathcal{C}_{\text{Sydney}}(\mathbf{p}) = p_z - (25.0 - |p_x|) \leq 0 \quad (10)$$

Any virtual ray whose folded reflection apex exceeds $Z = 25 - |x|$ is immediately pruned.

2.2 Rome Pantheon (Cylinder + Hemisphere Dome)

$$\mathcal{C}_{\text{Pantheon}}(\mathbf{p}) = \begin{cases} \sqrt{p_x^2 + p_y^2} - 21.65 \leq 0, & \text{if } p_z \leq 21.65 \text{ m} \\ p_x^2 + p_y^2 + (p_z - 21.65)^2 - (21.65)^2 \leq 0, & \text{if } p_z > 21.65 \text{ m} \end{cases} \quad (11)$$

2.3 Hagia Sophia (Central Dome + Exedrae)

For the central nave within radius $r = \sqrt{p_x^2 + p_y^2} \leq 15.5 \text{ m}$:

$$p_z \leq 25.0 + 30.0 \sqrt{1 - \left(\frac{r}{15.5}\right)^2} \quad (12)$$

Semi-domes and side galleries are capped at $Z \leq 36.0 \text{ m}$ and $Z \leq 18.0 \text{ m}$, respectively.

3 Finite-Amplitude Nonlinear Wave Steepening (*fff* Dynamics)

When a full symphony orchestra plays fortississimo (*fff*), acoustic sound pressure levels near the proscenium reach $L_p \approx 122 \text{ dB SPL}$, corresponding to peak acoustic pressure:

$$p_{\text{peak}} = p_{\text{ref}} \cdot 10^{\frac{L_p}{20}} = (20 \mu\text{Pa}) \cdot 10^{\frac{122}{20}} \approx 25.18 \text{ Pa} \quad (13)$$

3.1 Burgers' Equation and Acoustic Nonlinearity Parameter

One-dimensional finite-amplitude plane acoustic wave propagation is governed by Burgers' equation:

$$\frac{\partial p}{\partial x} - \frac{\beta p}{\rho_0 c_0^3} \frac{\partial p}{\partial t'} = \frac{\delta}{2c_0^3} \frac{\partial^2 p}{\partial t'^2} \quad (14)$$

where:

- $t' = t - x/c_0$ is the retarded time coordinate,
- $\rho_0 = 1.204 \text{ kg/m}^3$ is the quiescent air density,
- $c_0 = 343.2 \text{ m/s}$ is the small-signal speed of sound,
- $\beta = 1 + \frac{B}{2A} \approx 1.201$ is the acoustic nonlinearity parameter for air,
- δ is the acoustic diffusivity coefficient.

3.2 Shock Formation Distance and Distortion Parameter

For an acoustic wave of characteristic frequency ω , the shock formation distance $\bar{x}$ is defined as:

$$\bar{x} = \frac{\rho_0 c_0^3}{\beta \omega p_{\text{peak}}} \quad (15)$$

The dimensionless Goldberg distortion parameter σ along path length d is:

$$\sigma(d) = \frac{d}{\bar{x}} = \frac{\beta \omega p_{\text{peak}} d}{\rho_0 c_0^3} \quad (16)$$

For *fff* symphonic orchestral dynamics ($\sigma \in [0.05, 0.45]$), the acoustic pressure field obeys the **Fubini-Bessel series**:

$$p(d, t') = p_{\text{peak}} \sum_{n=1}^{\infty} \frac{2}{n\sigma(d)} J_n(n\sigma(d)) \sin(n\omega t') \quad (17)$$

where $J_n(\cdot)$ is the Bessel function of the first kind of order n .

3.3 Discrete Nonlinear Waveguide Implementation

In the discrete DSP domain (at sampling rate $f_s = 96$ kHz), the cumulative wave steepening along ray path k of distance d_k is evaluated per sample $x[n]$ through dynamic pressure-perturbed delay modulation and Fubini polynomial waveshaping:

$$\gamma_k = \frac{\beta \cdot p_{\text{peak}} \cdot d_k}{2\rho_0 c_0^3} \quad (18)$$

$$\Delta\tau_k(t) = -\frac{\beta \cdot d_k}{\rho_0 c_0^3} \cdot p(t - \tau_k) \quad (19)$$

$$y_k[n] = \tilde{x}[n + \Delta\tau_k] - \gamma_k \cdot \tilde{x}^3[n + \Delta\tau_k] \quad (20)$$

where $\tilde{x}$ is the 4-point Hermite-interpolated fractional delay read.

3.4 Physical Proof: Loudness-Dependent Timbral Evolution

A critical property of the AetherBeam architecture is that playing sound at varying sound pressure levels (SPL) does **not** merely scale the output amplitude linearly ($y \neq C \cdot x$). Rather, it fundamentally reorganizes the spectral envelope and harmonic distortion structure:

1. **Pianissimo** ($pp \approx 50$ dB SPL, $p_{\text{peak}} \approx 0.0063$ Pa): Here, the Goldberg parameter $\sigma \ll 0.01$. The wave steepening perturbation $\Delta\tau_k \approx 0$ and $\gamma_k \rightarrow 0$. The delay line operates in its linear regime, preserving a dark, pristine, and uncolored reverberant decay governed purely by boundary absorption.
2. **Fortississimo** ($fff \approx 122$ dB SPL, $p_{\text{peak}} \approx 25.18$ Pa): Compressive wave crests heat the medium adiabatically and propagate at local sound velocity $c(p) = c_0 + \frac{\beta-1}{\rho_0 c_0} p$, while rarefaction troughs lag behind. As sound traverses large enclosures ($d_k \geq 25$ m), the steepening perturbation accumulates, transferring fundamental energy into odd and even overtones.

To prove this behavior numerically, an identical 440 Hz pure sinusoidal probe tone was synthesized at two acoustic excitation levels (80 dB SPL vs. 130 dB SPL) and processed through the calibrated waveguide array. Normalizing both responses to identical peak output (0 dBFS) reveals the pure timbral transformation:

Under loud excitations, high-order harmonic density increases by nearly an order of magnitude (+19.87 dB). Furthermore, because higher-order early reflections seed the late diffuse feedback delay network (FDN), this harmonic sizzle dynamically cascades through the entire reverberant decay tail.

Excitation Level	Fundamental ($f_0 = 440$ Hz)	3rd Harmonic ($3f_0 = 1320$ Hz)	Harmonic Ratio (H)
Soft (pp , 80 dB SPL)	0.00 dBFS (ref)	-40.73 dBFS	0.918 %
Loud (fff , 130 dB SPL)	0.00 dBFS (ref)	-20.86 dBFS	9.055 %
Spectral Shift	Normalized Unity	+19.87 dB Excitation	9.86× Harmonic De

Table 1: Measured harmonic energy redistribution under normalized peak output, proving loudness-dependent spectral synthesis in AetherBeam.

4 Frequency-Dependent Air Absorption and Wall Impedance

4.1 ISO 9613-1 Atmospheric Attenuation

Atmospheric attenuation coefficient $\alpha_{\text{air}}(f)$ in dB/m is:

$$\alpha_{\text{air}}(f) = 8.686f^2 \left(1.84 \times 10^{-11} \left(\frac{T}{T_0} \right)^{\frac{1}{2}} + \left(\frac{T}{T_0} \right)^{-\frac{5}{2}} \left[\frac{a_1 f_{r,N}}{f_{r,N}^2 + f^2} + \frac{a_2 f_{r,O}}{f_{r,O}^2 + f^2} \right] \right) \quad (21)$$

In the discrete waveguide, this is synthesized via a calibrated 1st-order IIR lowpass filter:

$$H_{\text{air}}(z, d) = \frac{g_0 + g_1 z^{-1}}{1 - a_1 z^{-1}}, \quad a_1 = e^{-2\pi f_c(d)/f_s} \quad (22)$$

4.2 Wall Reflection Loss

For a ray of order $N(\mathbf{n})$, the net surface reflection gain $R(\mathbf{n})$ is:

$$R(\mathbf{n}) = \prod_{j=1}^{N(\mathbf{n})} \sqrt{1 - \bar{\alpha}_{\text{mat},j}} \quad (23)$$

where $\bar{\alpha}_{\text{mat},j}$ is the absorption coefficient of the boundary intercepted at bounce j .

5 Total Impulse Response Synthesis

The complete binaural impulse response $h_{L,R}(t)$ is synthesized as the superposition of the deterministic early physical beams (Orders $0 \leq n \leq 4$) and the stochastic diffuse late reverberant tail:

$$h_{L,R}(t) = \sum_{k=1}^K A_k \cdot \mathcal{N}_k \left(\delta(t - \tau_k) * h_{\text{air}}(t, d_k) \right) \cdot \text{HRTF}_{L,R}(\theta_k, \phi_k) + h_{\text{late}}(t) \quad (24)$$

where:

- $K \leq 96$ is the total count of valid physical rays,
- $A_k = \frac{R_k}{d_k}$ is the spherical geometric spreading factor and reflection loss,
- $\mathcal{N}_k(\cdot)$ is the nonlinear Burgers wave-steepening operator,
- $\text{HRTF}_{L,R}(\theta_k, \phi_k)$ is the head-related transfer function for incident beam elevation ϕ_k and azimuth θ_k ,
- $h_{\text{late}}(t) = e^{-3 \ln(10)t/RT_{60}} \cdot \xi(t)$ is the late diffuse field matching Sabine-Eyring reverberation decay time.

6 Showcase Enclosure Parameters

Enclosure	Dimensions (m)	Volume (m^3)	RT_{60} (s)	Max Order	Valid Rays	L_p (dB S)
Musikverein Golden Hall	$48.8 \times 19.1 \times 17.7$	15,000	2.05	4	76	122 (<i>ff</i>)
Sydney Opera House	$52.0 \times 26.0 \times 25.0$	16,500	2.00	4	68	122 (<i>ff</i>)
Hagia Sophia Byzantine	$65.0 \times 60.0 \times 55.0$	180,000	11.00	4	84	122 (<i>ff</i>)

Table 2: Physical acoustic parameters of synthesized showcase spaces.