


Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感-量产品规格明细表

Page 1 of 10

ITEM	VERTICAL PHOTO	PART CODE	PART NAME	HORIZONTAL PHOTO	SPECIFICATION	CUSTOMER&MODEL	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
項目	立式示意圖	成品料号	品 名	卧式示意圖	規格（负载下感量）	用戶及機種	A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
1		1.1.086	PFC 電感 PFC INDUCTANCE		PFC 10A-200uH扁線款 (EMC效果佳)	AUX-EMC优化款 1P/1.5P-60kHz频率	49.00	26.00	47.00	11.00	11.00	20.00
2		1.1.087	PFC 電感 PFC INDUCTANCE		PFC 10A-200uH	AUX-常规款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
3		1.1.088	PFC 電感 PFC INDUCTANCE		PFC 10A-200uH	AUX-限流款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
4		1.1.089	PFC 電感 PFC INDUCTANCE		PFC 10A-250uH	H客户-常规款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
5		1.1.090	PFC 電感 PFC INDUCTANCE		PFC 10A-250uH	H客户-优化款 1P/1.5P-60kHz频率	40.00	26.00	43.00	11.00	11.00	20.00
6		1.1.091	PFC 電感 PFC INDUCTANCE		PFC 10A-250uH扁線款 (EMC效果佳)	M客户-EMC优化款 1P/1.5P	49.00	26.00	47.00	11.00	11.00	20.00
7		1.1.092	PFC 電感 PFC INDUCTANCE		PFC 10A-300uH	T客户-常规款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
8		1.1.093	PFC 電感 PFC INDUCTANCE		PFC 10A-300uH	T客户-限流款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
9		1.1.094	PFC 電感 PFC INDUCTANCE		PFC 10A-300uH扁線款 (EMC效果佳)	T客户-EMC优化款 1P/1.5P-60kHz频率	49.00	26.00	47.00	11.00	11.00	20.00
10		1.1.095	PFC 電感 PFC INDUCTANCE		PFC 10A-300uH	H客户-常规款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表








Page 2 of 10

ITEM	VERTICAL PHOTO	PART CODE	PART NAME	HORIZONTAL PHOTO	SPECIFICATION	CUSTOMER&MODEL	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
項目	立式示意图	成品料号	品 名	卧式示意图	规格（负载下感量）	用户及机种	A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
11		1.1.096	PFC 电感 PFC INDUCTANCE		PFC 10A-300uH	H客户-限流款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
12		1.1.097	PFC 电感 PFC INDUCTANCE		PFC 10A-300uH-A1	M客户-常规款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
13		1.1.098	PFC 电感 PFC INDUCTANCE		PFC 10A-300uH-A2	M客户-优化款 1P/1.5P-60kHz频率	42.00	26.00	45.00	11.00	11.00	20.00
14		1.1.099	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH	T客户-常规款 1P/1.5P-40kHz频率	47.00	35.00	50.00	11.00	11.00	21.00
15		1.1.100	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH	1P/1.5P-40kHz频率	47.00	35.00	50.00	11.00	11.00	21.00
16		1.1.101	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH	PHILIPS降本款 1P/1.5P-40kHz频率	47.00	35.00	50.00	11.00	11.00	21.00
17		1.1.102	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH扁线款 (EMC效果佳)	H客户-常规款 1P/1.5P-40kHz频率	57.00	35.00	60.00	13.00	13.00	21.00
18		1.1.103	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH扁线款 (EMC效果佳)	H客户-优化款D 1P/1.5P-40kHz频率	57.00	35.00	60.00	13.00	13.00	21.00
19		1.1.104	PFC 电感 PFC INDUCTANCE		PFC 10A-350uH-A扁线款 (EMC效果佳)	M客户-常规款 1P/1.5P-50kHz频率	51.00	31.00	60.00	11.00	11.00	20.00
20		1.1.105	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH-A扁线款 (EMC效果佳)	H客户-海外款 1P/1.5P-40kHz频率	51.00	31.00	60.00	11.00	11.00	20.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表












Page 3 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格（负载下感量）	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
21		1.1.106	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH-A扁线款 (EMC效果佳)	M客户-常规款 1P/1.5P-40kHz频率	57.50	35.00	60.00	13.00	13.00	21.00
22		1.1.107	PFC 电感 PFC INDUCTANCE		PFC 16A-220uH-A扁线款 (EMC效果佳)	M客户-常规款 2P-60kHz频率	58.00	36.00	60.00	13.00	13.00	21.00
23		1.1.108	PFC 电感 PFC INDUCTANCE		PFC 16A-220uH-扁线款 (EMC效果佳)	T客户商用-常规款 小3P-60kHz频率	58.00	36.00	60.00	13.00	13.00	21.00
24		1.1.109	PFC 电感 PFC INDUCTANCE		PFC 16A-300uH-A扁线款 (EMC效果佳)	M客户-常规款 2P-60kHz频率	58.00	36.00	60.00	13.00	13.00	24.00
25		1.1.110	PFC 电感 PFC INDUCTANCE		PFC 12A-400uH-扁线款 (EMC效果佳)	TCL德珑-常规款 2P-40kHz频率	57.50	36.00	59.00	13.00	13.00	24.00
26		1.1.111	PFC 电感 PFC INDUCTANCE		PFC 12A-580uH-扁线款 (EMC效果佳)	M客户-常规款 2P-40kHz频率	57.50	36.00	59.00	13.00	13.00	24.00
27		1.1.112	PFC 电感 PFC INDUCTANCE		PFC 13A-520uH-扁线款 (EMC效果佳)	M客户-常规款 2P-40kHz频率	57.50	36.00	59.00	13.00	13.00	24.00
28		1.1.113	PFC 电感 PFC INDUCTANCE		PFC 10A-750uH-扁线款 (EMC效果佳)	M客户-常规款 1.5P-40kHz频率	57.00	36.00	59.00	13.00	13.00	24.00
29		1.1.114	PFC 电感 PFC INDUCTANCE		PFC 10A-550uH-扁线款 (EMC效果佳)	M客户-常规款 1.5P-40kHz频率	57.00	35.00	59.00	13.00	13.00	21.00
30		1.1.115	PFC 电感 PFC INDUCTANCE		PFC 13A-250uH-扁线款 (EMC效果佳)	M客户-常规款 2P-60kHz频率	57.50	36.00	60.00	13.00	13.00	21.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表







Page 4 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格 (负载下感量)	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
31		1.1.116	PFC 电感 PFC INDUCTANCE		PFC 13A-250uH-A扁线款 (EMC效果佳)	M客户-常规款 2P-60kHz频率	57.50	36.00	60.00	13.00	13.00	21.00
32		1.1.117	PFC 电感 PFC INDUCTANCE		PFC 13A-330uH-扁线款 (EMC效果佳)	M客户-常规款 2P-60kHz频率	57.50	36.00	60.00	13.00	13.00	21.00
33		1.1.118	PFC 电感 PFC INDUCTANCE		PFC 13A-500uH-扁线款 (EMC效果佳)	M客户-常规款 2P-40kHz频率	57.50	36.00	60.00	13.00	13.00	21.00
34		1.1.119	PFC 电感 PFC INDUCTANCE		PFC 13A-450uH-扁线款 (EMC效果佳)	M客户-常规款 2P-40kHz频率	57.50	36.00	60.00	13.00	13.00	24.00
35		1.1.120	PFC 电感 PFC INDUCTANCE		PFC 15A-420uH-扁线款 (EMC效果佳)	M客户-常规款 小3P-40kHz频率	58.00	36.00	60.00	13.00	13.00	24.00
36		1.1.121	PFC 电感 PFC INDUCTANCE		PFC 18A-290uH-扁线款 (EMC效果佳)	M客户-常规款 3P-60kHz频率	57.50	36.00	60.00	13.00	13.00	24.00
37		1.1.122	PFC 电感 PFC INDUCTANCE		PFC 20A-250uH-扁线款 (EMC效果佳)	M客户-常规款 3P-60kHz频率	58.50	36.00	60.00	13.00	13.00	24.00
38		1.1.123	PFC 电感 PFC INDUCTANCE		PFC 22A-200uH-扁线款 (EMC效果佳)	M客户-常规款 3P-60kHz频率	57.50	36.00	60.00	13.00	13.00	24.00
39		1.1.124	PFC 电感 PFC INDUCTANCE		PFC 25A-150uH-扁线款 (EMC效果佳)	M客户-常规款 3P-60kHz频率	57.50	36.00	60.00	13.00	13.00	24.00
40		1.1.125	PFC 电感 PFC INDUCTANCE		PFC 15A-510uH-扁线款 (EMC效果佳)	XM客户-常规款 3P-40kHz频率	68.00	36.00	69.00	13.00	13.00	24.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表




Page 5 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格 (负载下感量)	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
41		1.1.126	PFC 电感 PFC INDUCTANCE		PFC 16A-430uH-扁线款 (EMC效果佳)	M客户-常规款 3P-40kHz频率	68.00	36.00	69.00	13.00	13.00	24.00
42		1.1.127	PFC 电感 PFC INDUCTANCE		PFC 18A-310uH-扁线款 (EMC效果佳)	H客户-常规款 3P-60kHz频率	68.00	36.00	69.00	13.00	13.00	24.00
43		1.1.128	PFC 电感 PFC INDUCTANCE		PFC 20A-310uH-扁线款 (EMC效果佳)	H客户-海外款 3P-60kHz频率	68.00	36.00	69.00	13.00	13.00	24.00
44		1.1.129	PFC 电感 PFC INDUCTANCE		PFC 25A-310uH-扁线款 (EMC效果佳)	M客户-常规款 3/4P-60kHz频率	68.00	36.00	69.00	13.00	13.00	24.00
45		1.1.130	PFC 电感 PFC INDUCTANCE		PFC 25A-250uH-扁线款 (EMC效果佳)	M客户-常规款 3/4P-60kHz频率	68.00	36.00	69.00	13.00	13.00	24.00
46		1.1.131	PFC 电感 PFC INDUCTANCE		PFC 27A-240uH-扁线款 (EMC效果佳)	M客户-常规款 3/4P-60kHz频率	68.00	36.00	70.00	13.00	13.00	24.00
47		1.1.132	PFC 电感 PFC INDUCTANCE		PFC 28A-220uH-扁线款 (EMC效果佳)	M客户-常规款 3/4P-60kHz频率	71.00	38.00	72.00	13.00	13.00	24.00
48		1.1.133	PFC 电感 PFC INDUCTANCE		PFC 30A-200uH-扁线款 (EMC效果佳)	M客户-常规款 3/5P-60kHz频率	71.00	38.00	72.00	13.00	13.00	24.00
49		1.1.134	PFC 电感 PFC INDUCTANCE		PFC 30A-350uH-扁线款 (EMC效果佳)	G客户-常规款 3/5P-60kHz频率	73.00	63.00	72.00	25.00	25.00	50.00
50		1.1.135	PFC 电感 PFC INDUCTANCE		PFC 35A-310uH-扁线款 (EMC效果佳)	G客户-常规款 3/5P-60kHz频率	73.00	63.00	72.00	25.00	25.00	50.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表

Page 6 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格 (负载下感量)	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
51		1.1.136	PFC 电感 PFC INDUCTANCE		PFC 40A-260uH-扁线款 (EMC效果佳)	J客户-常规款 5/6P-60kHz频率	73.00	63.00	72.00	25.00	25.00	55.00
52		1.1.137	PFC 电感 PFC INDUCTANCE		PFC 45A-230uH-扁线款 (EMC效果佳)	J客户-常规款 5/6P-60kHz频率	88.00	76.00	85.00	27.00	27.00	58.00
53		1.1.138	PFC 电感 PFC INDUCTANCE		PFC 50A-200uH-扁线款 (EMC效果佳)	J客户-常规款 6/8P-60kHz频率	88.00	76.00	85.00	27.00	27.00	58.00
54		1.1.139	PFC 电感 PFC INDUCTANCE		PFC 13A-500uH	T客户-常规款 2P-40kHz频率	57.00	36.00	59.00	13.00	13.00	21.00
55		1.1.140	PFC 电感 PFC INDUCTANCE		PFC 16A-430uH	M客户-常规款 3P-40kHz频率	65.00	36.00	68.00	13.00	13.00	21.00
56		1.1.141	PFC 电感 PFC INDUCTANCE		PFC 16A-250uH-扁线款 (EMC效果佳)	TB客户-常规款 3P-60kHz频率	61.00	31.00	62.00	18.00	18.00	24.50
57		1.1.142	PFC 电感 PFC INDUCTANCE		PFC 15A-510uH	C&XM客户-常规款 3P-40kHz频率	65.00	36.00	68.00	13.00	13.00	21.00
58		1.1.143	PFC 电感 PFC INDUCTANCE		PFC 18A-250uH	T&A&G客户-常规款 3P-40kHz频率	58.00	36.00	59.00	13.00	13.00	21.00
59		1.1.144	PFC 电感 PFC INDUCTANCE		PFC 20A-220uH	M客户-常规款 3P-60kHz频率	58.00	36.00	59.00	13.00	13.00	21.00
60		1.1.145	PFC 电感 PFC INDUCTANCE		PFC 22A-320uH	M客户-常规款 3P-60kHz频率	66.00	36.00	59.00	13.00	13.00	24.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表





Page 7 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格 (负载下感量)	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
61		1.1.146	PFC 电感 PFC INDUCTANCE		PFC 25A-265uH	Z客户-常规款 3P-60kHz频率	66.00	36.00	59.00	13.00	13.00	24.00
62		1.1.147	PFC 电感 PFC INDUCTANCE		PFC 27A-240uH	Z客户-常规款 3P-60kHz频率	66.00	36.00	59.00	13.00	13.00	24.00
63		1.1.148	PFC 电感 PFC INDUCTANCE		PFC 30A-200uH	Z客户-常规款 3P-60kHz频率	66.00	36.00	59.00	13.00	13.00	24.00
64		1.1.149	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH-扁线款 (EMC效果佳)	XM客户-常规款 1/1.5P-40kHz频率	52.00	31.00	52.00	13.00	13.00	21.00
65		1.1.150	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH-扁线款 (EMC效果佳)	XT客户-常规款 1/1.5P-40kHz频率	52.00	31.00	52.00	18.00	18.00	20.00
66		1.1.151	PFC 电感 PFC INDUCTANCE		PFC 10A-450uH-扁线款 (EMC效果佳)	XT客户-常规款 1/1.5P-40kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
67		1.1.152	PFC 电感 PFC INDUCTANCE		PFC 10A-450uH-A扁线款 (EMC效果佳)	XT客户-优化款 1/1.5P-40kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
68		1.1.153	PFC 电感 PFC INDUCTANCE		PFC 16A-260uH-扁线款 (EMC效果佳)	XT客户-常规款 2P-60kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
69		1.1.154	PFC 电感 PFC INDUCTANCE		PFC 16A-260uH-A扁线款 (EMC效果佳)	XT客户-优化款 2P-60kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
70		1.1.155	PFC 电感 PFC INDUCTANCE		PFC 2P-540uH-扁线&IP54款 (EMC效果佳)	MG客户-常规款 2P-40kHz频率	56.00	31.00	57.00	18.00	18.00	24.50

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表





Page 8 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格 (负载下感量)	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
71		1.1.156	PFC 电感 PFC INDUCTANCE		PFC 2P-540uH-扁线&IP54款 (EMC效果佳)	MG客户-常规款 2P-40kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
72		1.1.157	PFC 电感 PFC INDUCTANCE		PFC 2P-540uH-扁线款 (EMC效果佳)	MG客户-常规款 2P-40kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
73		1.1.158	PFC 电感 PFC INDUCTANCE		PFC 1.5P-650uH-扁线&IP54款 (EMC效果佳)	MG客户-常规款 1P/1.5P-40kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
74		1.1.159	PFC 电感 PFC INDUCTANCE		PFC 16A-270uH-扁线款 (EMC效果佳)	MG客户-常规款 2P-60kHz频率	56.00	31.00	57.00	18.00	18.00	20.00
75		1.1.160	PFC 电感 PFC INDUCTANCE		PFC 1.5P-650uH-扁线&IP54款 (EMC效果佳)	MG客户-常规款 1P/1.5P-40kHz频率	53.00	31.00	57.00	18.00	18.00	24.50
76		1.1.161	PFC 电感 PFC INDUCTANCE		PFC 1.5P-650uH-扁线&IP54款 (EMC效果佳)	MG客户-常规款 1P/1.5P-40kHz频率	53.00	31.00	57.00	18.00	18.00	20.00
77		1.1.162	PFC 电感 PFC INDUCTANCE		PFC 1.5P-650uH-扁线&IP54款 (EMC效果佳)	MG客户-常规款 1P/1.5P-40kHz频率	53.00	31.00	57.00	18.00	18.00	24.50
78		1.1.163	PFC 电感 PFC INDUCTANCE		PFC 1.5P-650uH-扁线款 (EMC效果佳)	MG客户-常规款 1P/1.5P-40kHz频率	52.00	31.00	57.00	18.00	18.00	20.00
79		1.1.164	PFC 电感 PFC INDUCTANCE		PFC 13A-500uH-扁线款 (EMC效果佳)	TB客户-常规款 2P-40kHz频率	61.00	31.00	60.00	18.00	18.00	24.50
80		1.1.165	PFC 电感 PFC INDUCTANCE		PFC 6A-600uH-扁线款 (EMC效果佳)	Z客户-常规款 1P-40kHz频率	52.00	31.00	55.00	18.00	18.00	20.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST



群丰-PFC电感量产品-规格明细表

Page 9 of 10

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格 (负载下感量)	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
81		1.1.166	PFC 电感 PFC INDUCTANCE		PFC 10A-400uH扁线款 (EMC效果佳)	XM客户-EMC优化款 1P/1.5P-40kHz频率	48.50	26.00	49.00	11.00	11.00	20.00
82		1.1.167	PFC 电感 PFC INDUCTANCE		PFC 12A-200uH扁线款 (EMC效果佳)	M客户-EMC优化款 1.5P-40kHz频率	48.50	26.00	49.00	11.00	11.00	20.00
83		1.1.168	PFC 电感 PFC INDUCTANCE		PFC 18A-250uH-扁线款 (EMC效果佳)	Z客户-常规款 2/3P-60kHz频率	68.00	35.00	70.00	13.00	13.00	24.00
84		1.1.169	PFC 电感 PFC INDUCTANCE		PFC 15A-300uH-扁线款 (EMC效果佳)	Z客户-常规款 2/3P-60kHz频率	68.00	35.00	70.00	13.00	13.00	24.00
85		1.1.170	PFC 电感 PFC INDUCTANCE		PFC 10A-590uH-扁线款 (EMC效果佳)	XL客户-常规款 2/3P-60kHz频率	57.00	35.00	59.00	18.00	18.00	20.00
86		1.1.171	PFC 电感 PFC INDUCTANCE		PFC 60A-150uH-扁线款 (EMC效果佳)	JC客户-商用款 6P-40kHz频率	78.00	70.00	80.00	27.00	27.00	58.00
87		1.1.172	PFC 电感 PFC INDUCTANCE		PFC 72A-120uH-扁线款 (EMC效果佳)	JC客户-商用款 小8P-40kHz频率	78.00	70.00	80.00	27.00	27.00	58.00
88		1.1.173	PFC 电感 PFC INDUCTANCE		PFC 80A-100uH-扁线款 (EMC效果佳)	JC客户-商用款 8P-40kHz频率	78.00	70.00	80.00	27.00	27.00	58.00
89		1.1.174	PFC 电感 PFC INDUCTANCE		PFC 90A-110uH-扁线款 (EMC效果佳)	JC客户-商用款 小10P-40kHz频率	78.00	82.00	80.00	27.00	27.00	69.00
90		1.1.175	PFC 电感 PFC INDUCTANCE		PFC 100A-100uH-扁线款 (EMC效果佳)	JC客户-商用款 10P-40kHz频率	80.00	89.00	82.00	27.00	27.00	76.00
91		1.1.176	PFC 电感 PFC INDUCTANCE		PFC 120A-70uH-扁线款 (EMC效果佳)	JC客户-商用款 12P-40kHz频率	82.00	96.00	84.00	27.00	27.00	83.00

Q-PHONE PFC INDUCTOR SPECIFICATION LIST

群丰-PFC电感量产品-规格明细表

ITEM 項目	VERTICAL PHOTO 立式示意图	PART CODE 成品料号	PART NAME 品 名	HORIZONTAL PHOTO 卧式示意图	SPECIFICATION 规格（负载下感量）	CUSTOMER&MODEL 用户及机种	MAX EXTERNAL SIZE/最大外型尺寸			PIN TO PIN DISTANCE/PIN脚脚距		
							A-mm	B-mm	C-mm	D-mm	E-mm	F-mm
92		1.1.177	PFC 电感 PFC INDUCTANCE		PFC 18A-310uH-扁线款 (EMC效果佳)	H客户-常规款 2/3P-60kHz频率	68.00	35.00	70.00	13.00	13.00	24.00
93		1.1.178	PFC 电感 PFC INDUCTANCE		PFC 16A-260uH-IP67款	MG/TB客户-常规款 2P-60kHz频率	56.00	31.00	59.00	18.00	18.00	24.50
94		1.1.179	PFC 电感 PFC INDUCTANCE		PFC 13A-500uH-扁线款 (EMC效果佳)	TB客户-限高款 2P-40kHz频率	50.00	35.00	52.00	18.00	18.00	24.50
95		1.1.180	PFC 电感 PFC INDUCTANCE		PFC 16A-450uH-扁线款 (EMC效果佳)	TB客户-限高款 小3P-40kHz频率	50.00	40.00	52.00	18.00	18.00	24.50
96		1.1.181	PFC 电感 PFC INDUCTANCE		PFC 18A-360uH-扁线款 (EMC效果佳)	TB客户-限高款 3P-40kHz频率	51.00	45.00	52.00	18.00	18.00	24.50
97		1.1.182	PFC 电感 PFC INDUCTANCE		PFC 16A-430uH-扁线款 (EMC效果佳)	TB客户-优化款 小3P-40kHz频率	62.00	31.00	63.00	18.00	18.00	24.50
98		1.1.183	PFC 电感 PFC INDUCTANCE		PFC 1.5P-650uH-扁线款 (EMC效果佳)	TB客户-优化款 1P/1.5P-40kHz频率	52.00	31.00	57.00	18.00	18.00	24.50

备注说明:

- 1、上述为我司已量产的常规品，如有不同参数要求，请联系我司出新的设计方案，常规方案：1个工作日。
- 2、业务信息： 昆山群丰精密电子有限公司&地址： 江苏省昆山市淀山湖镇上洪路90号&联系人： 卢先生/15900970176&邮箱： Qphonesales@163.com

