



LEIBNIZ UNIVERSITÄT HANNOVER

Faculty of Electrical Engineering and Computer Science

Human-Computer Interaction Group

CASUAL INTERACTION WITH A BRACELET

A Thesis presented for the degree of Master of Science

by
KAROLINE BUSSE
December 2014

First Examiner : Prof. Michael Rohs

Second Examiner : Prof. Franz-Erich Wolter

Supervisor : M.Sc. Henning Pohl

Karoline Busse: *Casual Interaction with a Bracelet*, , © December 2014

[September 27, 2014 at 1:36 – classicthesis]

ABSTRACT

Short summary of the contents in English...

ZUSAMMENFASSUNG

Kurze Zusammenfassung des Inhaltes in deutscher Sprache...

CONTENTS

1	INTRODUCTION	1
2	USAGE SCENARIO	3
3	RELATED WORK	5
4	THE BRACELET	7
4.1	Manufacturing Techniques	7
4.1.1	Computer Aided Design	7
4.1.2	3D Printing	8
4.1.3	Silicone Casting	9
4.2	Design Process and Prototype Manufacturing	10
4.2.1	Rigid Designs	10
4.2.2	Segmented Designs	12
4.2.3	Modified Tri-Part Design	12
4.2.4	Silicone Bracelet	13
4.2.5	One-Piece Silicone Bracelet	13
4.3	Touch slider	14
5	INTERACTIVE LIGHT SOURCE	15
6	INTERACTION	17
6.1	Pairing the Bracelet with a Light Source	17
6.2	Gesture Recognition	17
6.3	Casual Touch Input	17
6.4	Precise Touch Input	17
6.5	Presets and Configuration	17
7	EVALUATION	19
7.1	Study Design	19
7.2	Results	19
7.3	Discussion	19
8	CONCLUSION AND FUTURE WORK	21
	BIBLIOGRAPHY	23

LIST OF FIGURES

Figure 1	Shore hardness scales and everyday examples	10
Figure 2	First rigid design with uniform thickness	11
Figure 3	Second design featuring a tapered shape	11
Figure 4	Third design with removable lid	12

LIST OF TABLES

Table 1	Test setups for Shore types	9
---------	-----------------------------	---

LISTINGS

ACRONYMS

STL	Stereolithography
HCI	Human-Computer Interaction
IR	Infrared
LED	Light Emitting Diode
SPP	Serial Port Profile
CAD	Computer-Aided Design
MIT	Massachusetts Institute of Technology
USB	Universal Serial Bus

1

INTRODUCTION

2

USAGE SCENARIO

Alice comes home from grocery shopping. While carrying her stuff to the kitchen, she quickly turns on the light using a simple hand gesture.

After storing everything, she decides to relax in the living room by reading a book. After turning the kitchen lights off with a gesture, she makes herself comfortable on the sofa and picks up the book. To feel more comfortable, Alice dims the living room light a little by touching the bracelet rim and sliding towards her body. The living room lights dim accordingly, so she doesn't need to look any closer at the bracelet.

Later that day, Alice prepares the dinner. While the food is finally in the oven, Alice returns to the living room and prepares the table for dining with her friends that will show up later. She uses the bracelet's e-paper display and touch controls to specify exact colors and brightnesses for each light source in the room. Alice saves three lighting setups together with unique activation gestures: A colorful setting for their guests' arrival and enjoying the welcoming drinks, a well-matched dining setup with focus on the table and foods, and a darker, lounge-like mood for the after-dinner party. Changing between these presets with hand gestures allows Alice to focus on her guests and on the meal instead of wasting time and focus by fiddling with wall panels or switches.

This scenario illustrates three different levels of casual interaction with a device: Eyes-free gestures without touching the bracelet, touch and slide interaction with optional eye contact, and focused fine-tuning of different settings with touch input and visual feedback on a display.

The mentioned interactions induce several requirements for the device. First, the device should stay where it is needed without encumbering the user. Typical remotes or smartphones occupy at least one hand for every interaction they offer. This is not desired, so traditional hand-held devices do not fit the scenario presented above. Instead, there is the need for a wearable device that is attached to the body without getting in the way during everyday activities.

Second, touch-free interaction (i.e. control by gestures) should be possible with respect to the first level of casual interaction pictured above. Capacitive touch input offers flexibility and versatility com-

pared to traditional keypads and enables gestured touch input. The display should be big enough to visualize complex information in order to fulfill the task of focused interaction, while at the same time a long battery life is required of the device.

A bracelet-typed device can fulfill all the requirements stated above. It is slim and doesn't encumber you, so it can be worn on the arm all day.

3

RELATED WORK

4

THE BRACELET

The interactive bracelet consists mainly of an electronic ink display and several touch sensors for conscious interaction and a motion sensor for gesture recognition. The bracelet's design focuses on wearing comfort, low weight and small error of unintended activation.

4.1 MANUFACTURING TECHNIQUES

In this section, the various methods and tools used for designing and manufacturing the bracelet prototypes will be explained in detail.

4.1.1 *Computer Aided Design*

In the beginning of a design iteration, a virtual model of the desired object is built with a 3D Computer-Aided Design (CAD) program. For all designs in the context of this thesis, the open source CAD modeler FreeCAD[3] was used. This program classifies itself as a general purpose 3D parametric modeler. A typical work-flow when designing a bracelet is as follows:

The model's basis is a circumference sketch for the bracelet. As the human wrist does not follow a circular shape, all designs made for this thesis are based on an oval circumference. In FreeCAD, this is realized by a composition of arcs and straight lines. It is important to constraint the sketch with radii, lengths and angles as well as symmetries or perpendicular constraints. The sketch should be fully constrained (i.e. leaving no degrees of freedom) before moving on to the next step, also with respect to the printing of the finished design.

In the next step one or more profile cuts are added to the circumference. They define the thickness and shape of the bracelet at different points along the oval circumference. For increased comfort, the bracelet should be as slim as possible, especially on the "backside" below the palm. In more complicated designs, an alternative to complex sketches for the profiles is the creation of multiple, overlaid sketches as a preparation for a subtraction operation in the later process. All those profiles need to be fully constrained as well.

After the circumference as well as one or more profiles are added to the design, a first solid is created by sweeping the profile(s) around the circumference curve. This operation creates a basic shape that can be refined further on, typically by chamfering or filleting the edges with respect to increased wearing comfort. If a complex shape is desired, multiple sweeps can be generated and used in boolean oper-

ations such as union or subtraction. This is the usual approach for most bracelet designs.

The last step in the design process is usually the finishing of the CAD model. In the bracelet case, this translates to edge smoothing with chamfer or fillet tools. Smoothed edges increase the overall wearing comfort of a bracelet, so they are very desired on edges that contact with the skin.

The finished designs are then exported as mesh files (usually in Sterolithography (STL) format) for printing.

4.1.2 3D Printing

The Human-Computer Interaction (HCI) group's workshop includes a powder bed and inkjet head 3D printer, a ProJet 360 by 3DSystems, Inc[2]. This manufacturing technique was developed in 1989 by the Massachusetts Institute of Technology (MIT) [5] and then licensed to the Z Corporation in 1995. On January 3, 2012, Z Corporation was acquired by 3DSystems, Inc.

When printing an object, the print bed is filled first with a base layer of powder. The powder used by the printer is called VisiJet PXL, a plaster-like substance. After filling the bed, a standard inkjet print-head is cleaned and prepared for the printing process. Immediately after this setup is complete, the additive manufacturing process starts.

The model is created by printing the binder fluid onto the plaster. After each printed layer, a new thin layer of powder is added to the print bed. The ProJet360 allows for a layer thickness of 0.1 mm with a vertical build speed of 2 cm per hour[1]. This allows even delicate structures without any additional supports, since the printed object is surrounded and therefore supported by plaster powder during the production process. The only drawback of this printing process is that it doesn't support closed, hollow objects since there is no possibility of removing the enclosed excess powder after the process has finished. When designing models for 3D printing, this constraint has to be kept in mind.

The finished object is then carefully removed from the build bed and any excess powder is gently brushed or blown off. The printer offers a cleaning chamber with a pressurized air pistol and a vacuuming system to assist in that task. Without further hardening, the objects are very fragile and easy to break, even with the pressurized air pistol included in the printer. In order to drastically increase the strength of the prints, they are infiltrated with a fluid after they were thoroughly cleaned. Prints produced by the ProJet 360 can be infiltrated with one of three different substances with varying characteristics: The ColorBond "instant-cure infiltrant", the two-part Strength-Max infiltrant "ideal for functional models", and the Salt Water Cure

TYPE	CONFIGURATION	DIAMETER	SPRING FORCE
A	35°	1.4 mm	8.06 N
D	30°	1.4 mm	44.46 N
OO	1.2 mm in spherical radius	2.4 mm	1.11 N

Table 1: Test setups for Shore types A, D, and OO[?]

"eco-friendly and hazard-free infiltrant"[1]. All prints produced for this thesis were infiltrated with ColorBond.

The infiltration step adds strength and hardens the material, resulting in a sturdy printed object. However, the objects created with this technique are very rigid and any bending load might break them easily. Wall strengths of 1.5 mm and up have been proven sturdy enough for a bracelet shape, although this also depends on the object geometry.

4.1.3 *Silicone Casting*

Another manufacturing process for bracelet prototypes used in this thesis is liquid silicone casting. Two different types of silicone were used for making various bracelet prototypes, both from manufacturer Smooth-On: Sorta-Clear 37 and Mold Star 15 Slow.

The most important characteristic for silicone in prototype production is the hardness, measured in Shore (after Albert F. Shore) or Durometer. It measures the indentation of a material with a special device which is also called Shore Durometer. It consists of a hardened steel rod with a finer tip and is available in two versions, since there are two different scales for Shore hardness (cf. table 1). The Shore A scale is designed for softer materials and the Shore D scale for harder ones, but they do overlap, so a material classified in Shore D hardness is not necessarily harder than another material classified in Shore A hardness. Each scale ranges from values 0 to 100, higher numbers indicate higher material resistance. The Shore hardness is specified in EN ISO 868.

When dealing with silicone, the Shore A scale is sometimes too "hard" for soft rubbers. Another standard (ISO 7619????) therefore specifies twelve different Durometer types, where the OO scale is commonly used for soft silicones. Figure 1 shows the three Shore hardness scales A, D, and OO, as well as some examples for everyday objects and their corresponding Shore values.

The silicone rubbers used for casting bracelet prototypes are both located on the Shore A scale. The softer Mold Star 15 Slow has a Shore A hardness of 15 that could be roughly compared to that of a rubber



Figure 1: Shore types A, D, and OO in comparison with everyday examples of various hardnesses.[?]

band according to figure 1, while the slightly harder Sorta-Clear 37 has a Shore A rating of 37, similar to that of a pencil eraser.

Both silicone products are two compound mixes that have to be added up and stirred before casting. While the Mold Star silicone has a rather low viscosity, casting the Sorta-Clear requires careful mold design, since it does not distribute well and is rather viscous. A vibrating table can help in filling the mold completely, but nonetheless were casts with the Sorta-Clear silicone much less fruitful, especially for the detailed molds of the one-piece designs (cf. section ??).

4.2 DESIGN PROCESS AND PROTOTYPE MANUFACTURING

The design process for the interactive bracelet presented in this thesis went through different stages. At first, a 3D-printed casing was favored, but later on a cast silicone bracelet turned out to be more comfortable for the user. The different prototypes are explained in detail in the following sections.

4.2.1 *Rigid Designs*

The first approach that comes to mind when thinking about bracelet design is a cuff-like, rigid shape. From the CAD point of view, the first bracelet prototype consisted of a single rectangular profile rotated around a oval curve which was derived from a measured wrist. The bracelet's inside was hollow, that would be the storage space for all electronic components. The cuff's gap was just large enough for the wrist to fit through, although in reality, this lead to light scratches on the skin in combination with the rough texture of the printed material. In addition, the uniform thickness made this first prototype uncomfortable to wear, especially at the open ends. So this first prototype had some clear downsides that were eliminated in the next iteration.




Figure 2: First rigid design with uniform thickness

Due to a settings error in the PC that controls the 3D printer, the printout of this first design was aborted after one third of the process.

In the following iteration, a bracelet of varying thickness was designed to make wearing the prototype more comfortable. Decreasing the thickness from XX cm to YY cm made the look more appealing and wearing a little less clumsy. At the same time, the wall strength was decreased from X.Y mm to 0.7 mm, which made it very fragile in fabrication and usage, both prints broke during post-processing. Wearing the cuff while working on a PC feels only slightly uncomfortable, but twisting the hand is encumbered by the tight-fitting bracelet. A design goal for future prototypes derived from this prototype was adding more space between the arm and the bracelet to ensure better comfort while wearing it.





Figure 3: Second design featuring a tapered shape

A modified design of the aforementioned prototype featured a removable lid since the tapered shape made it hard to access the inside space of the bracelet. The lid design was inspired by battery case covers commonly found in remote controls or small electronic devices. It features two nubs on the one side that support the lid in its place and another, smaller nub with a cavity in the material right next to it, so the nub can snap just inside the lid gap when it closes.



(a) Lid in CAD view

(b) Printed bracelet

Figure 4: Third design with removable lid

It turned out that the lid features were designed too fine, especially the flexible part was too thin to work as intended. The lid had to be opened and closed very cautiously and overall, the construction seemed not reliable for daily use. In addition, the rigid shape still lead to clumsiness in wearing the bracelet, so the whole concept of rigid bracelets was left behind.

4.2.2 Segmented Designs

The search for a more flexible printed bracelet shape lead to an entry for an activity bracelet design contest by Daniel Muschke on a 3D printing template exchange site called *GrabCAD* [4]. Muschke created a CAD file for a bracelet consisting of three segments that are connected by slow hinges. This design considered the electronic components like a micro-controller and a micro Universal Serial Bus (USB) port which made a good start for further modification, but unfortunately the file format made it impossible to alter the design in detail. A print was possible since STL files were included in the upload. However, the design turned out to be too small to be actually wearable, but it demonstrated that printed hinges work well with a pivot made from wire. The style felt more comfortable to wear than the precious prototypes and felt leaner on the wrist than the rigid prototypes. Overall, the printed design looked promising so the idea of a tri-part bracelet was investigated further.

A print of the tri-part design by Daniel Muschke on GrabCAD turned out to be a little too small, but the style felt more comfortable than the previous prototypes.

4.2.3 Modified Tri-Part Design

A re-work of Prototype 3 involves hinge research. The first draft turned out way too small, the second iteration was too big. Further

research into this shape was paused because a long, bracelet-like display was considered instead of a small one.

4.2.4 *Silicone Bracelet*

After some consideration on a flexible, bracelet-shaped e-ink display, a prototype of silicone was considered. Mold design turned out a little tricky but finally succeeded. I printed a two-piece mold which only needed a little post-processing to fit properly together. The mold was coated with black spray paint to make the inside a little smoother, but this didn't work as intended so the paining step can be omitted in future mold making processes. The filling holes for the silicone were too small, and the silicone was more viscous than expected.

The first cast with a closed mold and filling through the holes was unsuccessful; it produced two small end pieces and nothing in between. For following casts, one part of the mold was filled with silicone and closed afterwards; this turned out significantly better. The orientation the mold is placed during dry period is also relevant, as air bubbles will float towards the "top" of the mold, leading to instabilities. Getting the silicone part out of the mold was no problem.

The bracelet design involved a magnet clasp, but it was infeasible to strongly attach magnets to silicone with anything but silicone itself and they will likely jump out of place and snap together if placed closely in the design.

Two casts were made, one with each of the available silicone mixtures. The softer one was slightly too soft and had a disappearing color. As of yet, no tests have been conducted regarding the tightness of the display inside the bracelet.

4.2.5 *One-Piece Silicone Bracelet*

The next step was to cast a ring-like bracelet in one piece, so the issue with the clasp was no concern. The mold for this prototype consists of three pieces, two rings and a bottom plate. Unfortunately, the molds could not be recovered after the cast and had to be destroyed. In order to prevent unnecessary waste of material, the wall strength was reduced to 2.5 mm which turned out to be strong enough to survive the cast. However, one-time molds allow for tunnels in the display area.

This mold was much harder to fill with silicone than the previous one. Especially the Sortaclear silicone was too viscous to fill the complete mold, resulting in broken casts. The green Mold Star silicone turned out to work quite well.

4.3 TOUCH SLIDER

The major input interface of the bracelet is a touch surface which consists of cut copper foil placed underneath the electrophorus display.

5

INTERACTIVE LIGHT SOURCE

The previously mentioned light source for the scenario is built around a 12V powered RGB Light Emitting Diode (LED) strip with approximately XX LEDs. The original controller box which included an Infrared (IR) receiver for a remote was taken off and replaced by an Arduino Uno with a custom shield featuring a Roving Networks RN42 Bluetooth module. The whole setup is powered by a standard 12V an Arduino-controlled LED strip. Communication with the bracelet will take place via Bluetooth. The RN42 module implements the Bluetooth Serial Port Profile (SPP) and can be accessed easily with the SoftwareSerial module from the Arduino standard library. For a color change, the RGB color code is transmitted in a 9-digit string composed of three values from 000 to 255. Note that all values must have three digits, leading zeros must not be omitted. Those color values are transmitted directly to the red, green, and blue channels of the LED strip, a simple fading algorithm prevents disruptive flashing when switching colors.

6

INTERACTION

6.1 PAIRING THE BRACELET WITH A LIGHT SOURCE

6.2 GESTURE RECOGNITION

6.3 CASUAL TOUCH INPUT

6.4 PRECISE TOUCH INPUT

6.5 PRESETS AND CONFIGURATION

7

EVALUATION

7.1 STUDY DESIGN

7.2 RESULTS

7.3 DISCUSSION

8

CONCLUSION AND FUTURE WORK

BIBLIOGRAPHY

- [1] 3D Systems, Inc. ProJet x60 Series - Professional 3D Printers, 2014. URL <http://www.3dsystems.com/about-us>.
- [2] 3D Systems, Inc. About 3D Systems, 2014. URL <http://www.3dsystems.com/about-us>.
- [3] Freecad. An open source parametric 3D CAD modeler, 2014. URL <http://freecadweb.org>.
- [4] Daniel Muschke. Amico Bracelet, June 2012. URL <http://grabcad.com/library/amico-bracelet--9>.
- [5] E.M. Sachs, J.S. Haggerty, M.J. Cima, and P.A. Williams. Three-dimensional printing techniques, August 23 1994. URL <http://www.google.com/patents/US5340656>. US Patent 5,340,656.

EIDESSTATTLICHE ERKLÄRUNG

Hiermit versichere ich, die vorliegende Arbeit ohne Hilfe Dritter und nur mit den angegebenen Quellen und Hilfsmitteln angefertigt zu haben. Alle Stellen, die wörtlich oder inhaltlich aus den Quellen entnommen wurden, sind als solche kenntlich gemacht worden. Diese Arbeit hat in gleicher oder ähnlicher Form noch keiner Prüfungsbehörde vorgelegen.

Hannover, December 2014

Karoline Busse