

CSE 135 HW3 — REST API Routes

Aaron Chiuwei, Kile Hsu, Varun Sharma

Host: `reporting.lehum.site`

Sessions

Method	Route	Description
GET	<code>/api/sessions</code>	Retrieve all sessions
GET	<code>/api/sessions/{id}</code>	Retrieve a specific session
POST	<code>/api/sessions</code>	Create a new session
PUT	<code>/api/sessions/{id}</code>	Update a session
DELETE	<code>/api/sessions/{id}</code>	Delete a session and cascading data

Pageviews (Static + Performance)

Method	Route	Description
GET	<code>/api/pageviews</code>	Retrieve all pageviews
GET	<code>/api/pageviews/{id}</code>	Retrieve a specific pageview
POST	<code>/api/pageviews</code>	Add a new pageview
PUT	<code>/api/pageviews/{id}</code>	Update a pageview
DELETE	<code>/api/pageviews/{id}</code>	Delete a pageview

Activity Events

Method	Route	Description
GET	<code>/api/activity</code>	Retrieve all activity events
GET	<code>/api/activity/{id}</code>	Retrieve a specific activity event
POST	<code>/api/activity</code>	Add a new activity event
PUT	<code>/api/activity/{id}</code>	Update an activity event
DELETE	<code>/api/activity/{id}</code>	Delete an activity event

Page Exits

Method	Route	Description
GET	/api/exits	Retrieve all page exits
GET	/api/exits/{id}	Retrieve a specific page exit
POST	/api/exits	Add a new page exit
PUT	/api/exits/{id}	Update a page exit
DELETE	/api/exits/{id}	Delete a page exit

Errors

Method	Route	Description
GET	/api/errors	Retrieve all errors
GET	/api/errors/{id}	Retrieve a specific error
POST	/api/errors	Add a new error
PUT	/api/errors/{id}	Update an error
DELETE	/api/errors/{id}	Delete an error

Notes

- GET without an ID returns all records; with an ID returns one.
- POST does not take an ID (auto-generated). PUT and DELETE require an ID.
- Data stored in PostgreSQL. Session IDs from `sessionStorage`.
- Collector ingest (POST /collect) lives on `collector.lehum.site`, separate from these routes.