



Professionally approved products.

Product Datasheet

RS-12

DIGITAL MULTIMETER

EN



Features

2000 Digital display counts
 Display backlight
 Data Hold
 Diode Check
 Continuity Test
 EN61010-1 CATIII 600V
 Double molded plastic housing

SPECIFICATIONS

Function	Range	Resolution	Accuracy
DC Voltage (V DC)	200mV	0.1mV	$\pm (0.5\% \text{ reading} + 2 \text{ digits})$
	2000mV	1mV	
	20V	0.01V	
	200V	0.1V	$\pm (0.8\% \text{ reading} + 2 \text{ digits})$
	600V	1V	
AC Voltage (V AC)	200V	0.1V	$\pm (1.2\% \text{ reading} + 10 \text{ digits} + 50/60\text{Hz})$
	600V	1V	
DC Current (A DC)	2000 μ A	1 μ A	$\pm (1.0\% \text{ reading} + 2 \text{ digits})$
	20mA	10 μ A	
	200mA	100 μ A	$\pm (1.2\% \text{ reading} + 2 \text{ digits})$
	10A	10mA	$\pm (2.0\% \text{ reading} + 2 \text{ digits})$

Resistance	200 Ω	0.1 Ω	$\pm$ (0.8% reading + 2 digits)
	2000 Ω	1 Ω	
	20k Ω	0.01k Ω	
	200k Ω	0.1k Ω	
	2000k Ω	1k Ω	$\pm$ (1.0% reading + 2 digits)
Battery Test	9V	10mV	$\pm$ (1.0% reading + 2 digits)
	1.5V	1mV	

NOTE: Accuracy specifications consist of two elements:

- (% reading) – This is the accuracy of the measurement circuit.
- (+ digits) – This is the accuracy of the analog to digital converter.

NOTE: Accuracy is stated at 65°F to 83°F (18°C to 28°C) and less than 75% RH.

SPECIFICATIONS

Diode Test	Test current of 1mA maximum, open circuit voltage 2.8V DC typical
Continuity Check	Audible signal will sound if the resistance is less than approximately 30Ω
Battery Test current	9V (6mA); 1.5V (100mA)
Input Impedance	>1MΩ
ACV Bandwidth	45Hz to 450Hz
DCA voltage drop	200mV
Display	3 ½ digit, 2000 count LCD, 1.1" digits
Overrange indication	"1" is displayed
Polarity	Automatic (no indication for positive polarity); Minus (-) sign for negative polarity.
Measurement Rate	2 times per second, nominal
Low Battery Indication	"BAT" is displayed if battery voltage drops below operating voltage
Battery	one 9 volt (NEDA 1604) battery
Fuses	mA, μA ranges; ceramic 0.2A/250V fast blow 5mm x 20mm 10A range; ceramic 10A/250V fast blow 5mm x 20mm
Operating Temperature	32°F to 122°F (0°C to 50°C)

Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Relative Humidity	<70% operating, <80% storage
Operating Altitude	7000ft. (2000) meters maximum.
Weight	255g
Size	150mm x 70mm x 48mm
Safety	Indoor use only Pollution Degree 2 Installation Category III 600V

Accessories:

Test leads, 9V battery, User manual.