Budget-Aware Controller Blending: Post-Hoc Damage-Budget Pacing for Pre-Trained RL Policies

Julian Quick*
Marcus Binder Nilsen
DTU Wind Energy, Technical University of Denmark

April 26, 2026

Abstract

A pre-trained, unconstrained RL policy faces a new cumulative operational constraint at deployment: a damage budget per year, a duty-cycle limit, a spending cap. We propose a closed-form schedule $\sigma(u)$ that *blends two existing controllers at inference*: the deployed performance policy π_{perf} and a domain-specific safety controller π_{safe} (a factory wind-tracking yaw setpoint, an artificial-potential-field navigator). The blend weight $\sigma(u) \in [0, 1]$ is a monotone function of the *urgency ratio* $u = \rho/\tau$ (remaining-budget / remaining-time fractions): on pace ($u \geq 1$) the performance policy runs; in deficit ($u \to 0$) the safety controller takes over. **This is a budget-aware *pacing* mechanism, not a hard enforcement guarantee.** On wind-farm yaw control ($\kappa \approx 0.72$) the schedule retains 99.3–101.8% of unconstrained power while satisfying a 15-step neg-yaw surrogate budget across 4 training seeds. On Safety Gymnasium ($\kappa \approx 0.02$) the explicit blend gives a favorable reward-cost trade-off (cost from 49.4 to 15.3 at $d = 10$, retaining 45% of unconstrained reward) but does not reliably satisfy expected cost at tight budgets. We compare against retraining baselines (SAC-Lagrangian at three hyperparameter settings; SAUTE [Sootla et al., 2022], which uses the same urgency variable our schedule does); the best retraining variant tested attains $R = 2.3$, $C = 24$ at 500k steps, putting the blend on the Pareto-favorable side of the reward axis but *not* dominating in the constrained sense (some baselines satisfy budget more tightly at the cost of reward). A gradient-correction variant of the same schedule works when the action-to-cost coupling strength $\kappa = \mathbb{E}\|\nabla_a Q_c\|/\mathbb{E}\|\nabla_s Q_c\|$ is large; when it is small, the explicit-π_{safe} blend is required.

1 Introduction

Scenario. A wind-farm operator deploys an RL controller that maximises power via coordinated yaw wake steering; it was trained unconstrained and works well. Six months later, a bearing inspection tightens the constraint: turbine 2's yaw may be negative for at most 15 hours per year. Retraining the RL controller is expensive and slow; the operator already has a certified wake-steering fallback (e.g., WakeAdapt [Siemens Gamesa, 2023], a calibrated yaw-setpoint table). What the operator needs is a way to *pace between* the aggressive RL policy and the domain-specific safety controller so the cumulative constraint is satisfied, without retraining either.

The pattern is pervasive. Wind turbines have load budgets [van Dijk et al., 2025]; grid batteries have cycle-life limits; fleet vehicles have maintenance intervals; advertisers have spending caps [Balseiro et al., 2024]. Unlike an instantaneous safety constraint, a *lifetime budget* requires choosing *when* to spend limited capacity in a risky regime—and a fixed scalarisation $\alpha P - (1 - \alpha)D$ is memoryless.

Retraining is not the operator-realistic answer. We test four standard retraining baselines starting from the deployed Safety-Gymnasium actor: SAC-Lagrangian at default settings, with μ-warmup + reward

*juqu@dtu.dk



Figure 1: Two domains, two safety controllers, one schedule. (a) Wind farm: π_{safe} is a zero-yaw setpoint (Jensen wake field shown for the budget-satisfying blend, $d=5$, neg-yaw $[5,5,5]$). (b) Safety Gymnasium: π_{safe} is an artificial-potential-field navigator. The trajectory is colour-coded by blend weight $\sigma(u)$: navy when the RL actor drives ($\sigma \to 0$), crimson when the APF safety controller drives ($\sigma \to 1$). The faded gray trace shows the unconstrained baseline plowing through hazards on the same seed; the blend curves around them as σ rises in budget deficit.

scaling, with aggressive dual ascent, and SAUTE [Sootla et al., 2022] (state augmentation with ρ_t). At 500,000 extra training steps—more than the original unconstrained training—every variant either violates the budget while preserving partial reward or satisfies the budget by collapsing the policy's reward to ≈ 0 (Figure 2, Table 7). The Lagrangian dual destroys goal-seeking before budget-aware behaviour emerges; SAUTE's ρ-augmentation does not by itself recover usefulness.

Our proposal: urgency-ratio controller blending. Borrowing the pacing intuition from optimal execution [Almgren and Chriss, 2001], define

$$u_t = \frac{\rho_t}{\tau_t}, \qquad \rho_t = \frac{d - C_t}{d}, \qquad \tau_t = \frac{T - t}{T}, \tag{1}$$

and blend two pre-existing controllers at inference:

$$a_t = (1 - \sigma(u_t))\,\pi_{\text{perf}}(s_t) + \sigma(u_t)\,\pi_{\text{safe}}(s_t). \tag{2}$$

$\sigma : \mathbb{R}_{\geq 0} \to [0,1]$ is monotone-decreasing in u (Section 3). On pace $\Rightarrow$ performance; deficit $\Rightarrow$ safety.

Contributions. (1) A *closed-form urgency-ratio schedule* $\sigma(u)$ with one sharpness parameter, derived from a budget-balanced pacing argument (§3; Prop. 1). (2) *Two-controller blending* that treats an existing safety controller as a first-class primitive rather than retraining the policy (§4). (3) A *gradient-correction variant* (§4.2) where π_{safe} is implicitly a step of $-\nabla_a Q_c$; this works when the coupling strength $\kappa = \mathbb{E}\|\nabla_a Q_c\| / \mathbb{E}\|\nabla_s Q_c\|$ is large (Table 1). (4) *Empirical validation* on wind-farm yaw control ($\kappa \approx 0.72$) and Safety Gymnasium ($\kappa \approx 0.02$), under the *same* schedule with *different* safety controllers chosen by κ. On the reward axis, the post-hoc blend is Pareto-favorable to four distinct retraining baselines (SAC-Lagrangian at three hyperparameter

settings, plus SAUTE) on SG at every compute checkpoint we measured; on the cost axis some baselines satisfy the constraint more tightly at the cost of reward (§5.2).

Deployment claim. The method drops into systems that already have an RL performance policy, a domain-specific safety controller, and a damage estimator—none of which are retrained. The schedule decides when to pace toward the safety controller as budget pressure builds. We *do not* claim hard budget enforcement: APF on Safety Gym is reactive and can still incur cost (§5.2); true enforcement requires a backup invariant such as $C_t + B_{\text{safe}}(t) \leq d$ where B_{safe} upper-bounds future π_{safe} cost, which we leave to future work.

Constraint type. We adopt the *expected-cost CMDP* formulation: $\mathbb{E}_\pi[\sum_t c_t] \leq d$. Expected-cost feasibility is what tables score; per-episode satisfaction rate is reported as a separate operational-reliability metric.

2 Background

Constrained MDPs and Lagrangian methods. A CMDP [Altman, 1999] adds cost-return constraints to the MDP objective: $\max_\pi \mathbb{E}_\pi[\sum_t r_t]$ subject to $\mathbb{E}_\pi[\sum_t c_t] \leq d$ [Ray et al., 2019, Achiam et al., 2017]. SAC-Lagrangian [Stooke et al., 2020] learns a dual variable μ during training; PID-Lag and CPO [Achiam et al., 2017] add stability tweaks. None of these are post-hoc: changing d requires a new policy.

SAUTE [Sootla et al., 2022] augments the state with ρ_t—the very urgency variable our schedule uses—and trains SAC on the augmented MDP with a budget-violation penalty. This is the closest CMDP method to ours conceptually, and we run it as a baseline (§5.2).

Post-hoc composition. Energy composition [Urain et al., 2023, Gladstone et al., 2025], classifier guidance [Zhang et al., 2025], control-barrier functions [Xiao et al., 2025], and input-convex corrections [Durkin et al., 2025] modify pre-trained policies at inference for *instantaneous* constraints. We extend this tradition to *cumulative* budgets via a time-varying weight.

Multi-objective scalarisation. A fixed $\alpha P - (1-\alpha)D$ trade-off is memoryless. Our schedule turns α into a time-varying weight that paces against the realised damage trajectory.

3 Urgency-Ratio Schedule

Proposition 1 (Pacing motivation)**.** *Under an idealised Boltzmann response $P(\text{risky} \mid \lambda) = P_0 \exp(-\alpha\lambda)$, the penalty weight that maintains budget-rate balance takes the multiplicative form $w^*(u) = 1/u$ relative to the TWAP baseline ($u{=}1$).*

Proof sketch. Balance $(T-t)P(\text{risky} \mid \lambda) = d - C_t$ with the Boltzmann substitution gives $\lambda = \frac{1}{\alpha} \ln \frac{(T-t)P_0}{d-C_t}$. The multiplicative weight relative to TWAP reduces to $\tau/\rho = 1/u$. Full derivation in Appendix A.1. □

This is a *motivating* pacing argument, not a derivation of the actual schedule. The Boltzmann response is a strong assumption; real policies do not respond linearly in log-probability to scalar penalties. What we use from Prop. 1 is the *state-variable identification*: u is the natural argument and the schedule should be monotone-decreasing in u.

Practical schedule. We use the parametric family $w(u) = \exp(\eta(1/u - 1))$ with $\eta \geq 0$, clamped at $\lambda_{\max} = 10^6$ (Appendix Fig. 3). For Eq. 2 we map $w(u)$ to a bounded $\sigma \in [0, 1]$:

$$\sigma(u) = \begin{cases} 0 & u \geq 1, \\ 1 - \exp(-\eta(1/u - 1)) & u < 1. \end{cases} \tag{3}$$

On pace ($u \geq 1$): pure performance policy. Deficit ($u < 1$): smooth ramp toward pure safety controller, sharpness η. A hard-wall backstop drives $\sigma \to 1$ for $u < 0.05$.

4 Method

The method has three independent components: **(i)** the schedule $\sigma(u)$ (*how much* safety); **(ii)** the performance policy π_{perf} (what we deploy on pace); **(iii)** the safety controller π_{safe} (what we revert to in deficit).

4.1 Two-Controller Blend (primary formulation)

$$a_t = (1 - \sigma(u_t))\, \pi_{\text{perf}}(s_t) + \sigma(u_t)\, \pi_{\text{safe}}(s_t). \tag{4}$$

Wind-farm instantiation. π_{perf} is an Energy-Based Transformer (EBT) actor trained unconstrained with SAC for 100k steps. $\pi_{\text{safe}} \equiv 0$ is a zero-yaw setpoint, minimising our per-turbine fatigue surrogate $c = (|y|/\bar{y})^p (v/v_{\text{ref}})^q$ ($p{=}2$, $q{=}3$). In production, π_{safe} would be a WakeAdapt-style [Siemens Gamesa, 2023] setpoint table minimising farm-level DEL.

Safety Gymnasium instantiation. π_{perf} is a SAC/MLP actor trained unconstrained for 200k steps. π_{safe} is an artificial-potential-field navigator: $F_{\text{goal}} = \text{norm}(g - x) + F_{\text{rep}} = k_r \sum_i (x - h_i)/\|x - h_i\|^3$, mapped to body-frame $(\text{thrust}, \text{turn})$. No learning; uses only the hazard/goal geometry that every CBF-based safe-RL method assumes access to.

4.2 Gradient-Correction Variant

When an action-dependent cost $\nabla_a c$ or $\nabla_a Q_c$ is available, a single gradient step replaces the explicit π_{safe}:

$$a_t \leftarrow \pi_{\text{perf}}(s_t) - \lambda_{\text{gs}} \cdot w(u_t) \cdot \alpha_{\text{g}} \cdot \nabla_a c(s_t, a_t), \tag{5}$$

iterated K steps. This is Eq. 4 with $\pi_{\text{safe}}(s) \approx \pi_{\text{perf}}(s) - \alpha_{\text{g}} \nabla_a c$ implicitly defined.

4.3 Coupling Strength κ: Which Variant?

The gradient variant requires a non-trivial $\nabla_a Q_c$. We quantify this by

$$\kappa := \mathbb{E}_{(s,a)\sim\pi} \|\nabla_a Q_c(s,a)\|_2 \,/\, \mathbb{E}_{(s,a)\sim\pi} \|\nabla_s Q_c(s,a)\|_2, \tag{6}$$

measured on logged rollouts. Large κ: gradient correction suffices. Small κ: action-gradient is weak; explicit π_{safe} is required.

Table 1: Coupling strength κ per domain (2000 on-policy samples). Large κ: gradient correction suffices. Small κ: explicit π_{safe} blend required.

Domain	$\mathbb{E}\|\nabla_a Q_c\|$	$\mathbb{E}\|\nabla_s Q_c\|$	κ	Recommended variant
Wind farm (3-turb)	0.69±0.34	0.97±0.26	**0.72**	gradient correction (Eq. 5)
Safety Gym (PointGoal)	0.99±0.69	49.8±12.5	**0.02**	explicit π_{safe} blend (Eq. 4)

5 Experiments

5.1 Wind Farm: High Coupling, Two Working Variants

Setup. WindGym [Nilsen et al., 2025] with PyWake [Pedersen et al., 2023] backend; 3-turbine row; wind speed 10–14 m/s, direction 225–315°. We use *per-turbine* budgets: each turbine i has its own $d^i = d$, C_t^i, u_t^i,

Algorithm 1 Urgency-Ratio Controller Blending (with safeguards)

Require: Performance policy π_{perf}, safety controller π_{safe}, budget $d > 0$, horizon T, sharpness η, hard-wall threshold $u_{\text{hw}} = 0.05$, action bounds $[a_{\min}, a_{\max}]$

$C_0 \leftarrow 0$
for $t = 0, 1, \ldots, T-1$ **do**
  $\rho_t \leftarrow \max((d - C_t)/d,\, 0)$; $\tau_t \leftarrow \max((T-t)/T,\, 1/T)$
  if $\rho_t = 0$ **or** $\tau_t \le 1/T$ **then**
    $\sigma_t \leftarrow 1$ {budget exhausted or last step: π_{safe} takes over}
  else
    $u_t \leftarrow \rho_t / \tau_t$
    $\sigma_t \leftarrow 0$ if $u_t \ge 1$ else $1 - \exp(-\eta(1/u_t - 1))$
    if $u_t < u_{\text{hw}}$ **then** $\sigma_t \leftarrow 1$ {hard-wall backstop}
  end if
  $a_t \leftarrow \text{clip}((1-\sigma_t)\,\pi_{\text{perf}}(s_t) + \sigma_t\,\pi_{\text{safe}}(s_t),\ a_{\min},\ a_{\max})$
  Execute a_t; observe c_t; $C_{t+1} \leftarrow C_t + c_t$
end for

and σ_t^i, computed independently. A turbine in budget deficit pulls only its own action toward π_{safe}; other turbines remain unaffected. π_{perf} is an EBT actor trained unconstrained with SAC for 100k steps.

Cost variables. Throughout this section, "cost" refers to the cumulative quantity governed by the urgency schedule. We test two cost choices: (a) the binary *NegYaw* cost $c = \mathbf{1}[y < 0]$ used in the main budget tables (Tables 2, 3); and (b) the *nonlinear fatigue* surrogate $c = (|y|/\bar{y})^p (v/v_{\text{ref}})^q$ used in Tables 8 (App. A.4) and 9. Reported NegYaw arrays are diagnostics, not the cost in the latter tables.

Gradient-correction variant (Table 2). Since $\kappa \approx 0.72$, gradient correction is effective. At $(\eta = 5, \lambda_{\text{gs}} = 0.1)$: 98.9% of unconstrained power single-seed and 95.9±3.1% across 4 training seeds, with all seeds satisfying the budget. An oracle-tuned constant penalty (15-step bisection per budget) achieves 96.7% and must be re-tuned every time d changes.

Table 2: Wind-farm gradient-correction variant (3-turbine, $d = 15/200$ steps, 50 ep). Baseline differs across tables because each uses independently sampled episodes / wind ranges; within-table comparisons use the same episodes.

Method	Power (MW)	% Uncon	NegYaw [T0,T1,T2]	Notes
Unconstrained (seed 1)	27.1±0.6	100%	[49, 56, 61]	—
Oracle constant ($k = 5.86$)	26.2±0.7	96.7%	[11, 13, 14]	15-step bisection
AC ($\eta = 5$, gs=0.1)	26.9±0.5	**98.9%**	[8, 9, 10]	Zero per-budget tuning
AC ($\eta = 5$, gs=0.1) — 4 seeds	25.7±0.5	**95.9±3.1%**	[11, 12, 12]	All seeds satisfy

Explicit zero-yaw blend variant (Table 3). Replacing the gradient step with $\pi_{\text{safe}} \equiv 0$ and the urgency blend gives matching results with one fewer hyperparameter (η only). Across 4 seeds and three $\eta \in \{1, 3, 10\}$ values, the blend satisfies the budget every time and retains 99.3–101.8% of unconstrained power. The blend power exceeding 100% at $\eta = 1$ is within seed variance (±0.9%) and likely reflects mild over-yawing in the unconstrained actor: the constraint nudge happens to also remove sub-optimal yaw excursions. We do not interpret this as the blend universally outperforming an ideal π_{perf}; we interpret it as evidence that the actor was not Pareto-optimal on the power axis to begin with.

Cost function matters (Appendix A.4). A binary cost $c = \mathbf{1}[y < 0]$ *inflates* fatigue 4.2× over unconstrained; the nonlinear surrogate avoids this trap.

Wind-farm ablation: schedule vs simpler blends (Table 4). Mirroring the SG ablation, we sweep five alternative blend modes sharing π_{perf} and $\pi_{\text{safe}} \equiv 0$. Constant $\sigma \in \{0.3, 0.5, 0.7\}$ violates the budget at all values: linearly scaling the actor's output toward zero does not suppress the negative-yaw fraction enough to satisfy

Table 3: Wind-farm zero-yaw blend variant (3-turbine, $d=15$, 50 ep, 4 training seeds). $\bar{\sigma}$: mean blend weight; $\pi_{\text{safe}} \equiv 0$.

Method	% Uncon power	NegYaw	$\bar{\sigma}$	Seeds sat.	Notes
Unconstrained	100%	$[70.2, 74.3, 83.7]$	—	0/4	Far over budget
Blend ($\eta=1$)	$\mathbf{101.8 \pm 0.9}$%	$[11.3, 11.3, 11.8]$	0.56	**4/4**	✓
Blend ($\eta=3$)	99.5 ± 2.2%	$[11.5, 12.1, 12.2]$	0.63	**4/4**	✓
Blend ($\eta=10$)	99.3 ± 2.4%	$[11.0, 11.3, 11.3]$	0.59	**4/4**	✓

$d=15$. Hard threshold switching ($\sigma=1$ if $u<\theta$ else 0) and projected-budget override both satisfy the budget across all seeds with power retention statistically indistinguishable from the urgency schedule (98.7–100.9% vs. urgency's 99.5%). Pure π_{safe} (zero yaw, no wake-steering) also retains 100.7% of unconstrained power across 4 seeds—an unexpected finding that suggests the unconstrained actor's negative-yaw use is not contributing meaningful wake-steering benefit in this setting; we discuss this in §7.

Table 4: Wind-farm ablation matching the SG counterpart (Table 6). Five alternative blend modes share $\pi_{\text{perf}} + \pi_{\text{safe}} \equiv 0$; only the σ schedule changes. Hard threshold switching matches the urgency schedule; constant σ blends violate the budget; pure π_{safe} is feasible and retains nominal power.

Mode	% Uncon power	NegYaw	$\bar{\sigma}$	Seeds sat.
π_{safe} alone (zero yaw)	100.7 ± 2.5%	$[0.4, 0.6, 0.5]$	1.00	**4/4**
const $\sigma=0.3$	100.9 ± 2.1%	$[75.0, 72.9, 77.4]$	0.30	0/4
const $\sigma=0.5$	100.6 ± 2.5%	$[67.9, 66.8, 68.6]$	0.50	0/4
const $\sigma=0.7$	98.7 ± 0.9%	$[64.9, 64.8, 68.5]$	0.70	0/4
switch $u<0.5$	98.8 ± 1.6%	$[11.1, 11.1, 11.5]$	0.49	**4/4**
switch $u<0.8$	98.7 ± 1.7%	$[10.9, 11.1, 11.8]$	0.49	**4/4**
projected override	100.9 ± 3.6%	$[11.6, 11.5, 12.0]$	0.56	2/2
urgency $\eta=3$ (ours)	99.5 ± 2.2%	$[11.5, 12.1, 12.2]$	0.63	**4/4**

5.2 Safety Gymnasium: Low Coupling, Reward-Favorable Soft-Budget Operating Point

Setup. SafetyPointGoal1-v0 [Ji et al., 2023]: point robot navigates among fixed hazard disks to reach a moving goal. Cost $c=\mathbf{1}[\text{in hazard}]$ is position-dependent; action is 2D. π_{perf} is a SAC/MLP actor trained unconstrained for 200k steps (5 seeds).

Why the gradient variant fails here. $\kappa \approx 0.02$: $\nabla_a Q_c$ is $\sim 50\times$ smaller than $\nabla_s Q_c$. Appendix A.7 documents nine attempted gradient-based rescues (pessimistic Q_c, online Q_c refit, learned-dynamics MPC, true-env MPC in three configurations, full MBRL, 1-step and multi-step CBF), all failing structurally.

Explicit-π_{safe} blend results (Table 5). The APF blend reduces cost by 59–68% at $d=10$ while retaining 45% of unconstrained reward; at $d=40$ it retains 71% of reward and satisfies the budget in 56% of episodes.

Honest reading. The APF blend is a useful post-hoc cost-reduction mechanism: at $d=10$ it cuts expected cost from 49 to 15 (a 3.2× reduction) at the price of half the unconstrained reward. But it *does not enforce* tight budgets in expectation: $\mathbb{E}[C]=15.3>10$. At $d=40$ expected-cost feasibility is achieved. The mechanism gives a favorable reward-cost trade-off, not a hard budget guarantee; for hard guarantees a backup invariant (e.g., projected-budget override; Table 6) or a cost-zero π_{safe} is needed.

Ablation: how much does the urgency schedule contribute? Table 6 compares the urgency schedule against five alternative blend strategies sharing the same π_{perf} and π_{safe}: (i) pure π_{safe} (APF alone, no RL); (ii) constant $\sigma \in \{0.3, 0.5, 0.7\}$ (no urgency adaptation); (iii) hard threshold switch ($\sigma = 1$ if $u < \theta$ else 0);

Table 5: Safety Gymnasium with urgency-ratio APF blend (5 seeds × 20 ep). $\mathbb{E}[C] \leq d$: expected-cost CMDP feasibility (mean cost vs. budget). **Sat**: per-episode satisfaction rate. Unconstrained: $C = 49.4$, $R = 27.1$. The blend reduces expected cost substantially but *does not reliably enforce* tight budgets ($d \leq 25$); only $d = 40$ is feasible in expectation.

Method	d	Reward	% Uncon	Cost (mean±SE)	$\mathbb{E}[C] \leq d$	Sat
Unconstrained	—	27.1±0.1	100%	49.4±3.4	—	—
Blend ($\eta = 0$, control)	10	27.1±0.1	100%	49.4±3.4	×	12%
Blend ($\eta = 1$)	10	12.1±0.9	45%	**15.3±1.0**	×	25%
Blend ($\eta = 3$)	10	12.3±0.9	45%	18.6±1.2	×	23%
Blend ($\eta = 10$)	10	12.0±0.9	44%	17.8±1.3	×	28%
Blend ($\eta = 3$)	25	15.8±0.8	58%	28.6±1.6	×	39%
Blend ($\eta = 3$)	40	19.1±0.8	71%	34.5±2.0	✓	**56%**

(iv) projected-budget override ($\sigma = 1$ if linear extrapolation of cost rate predicts violation); (v) urgency schedule with $\eta = 3$ (the proposed method). Pure π_{safe} and constant $\sigma = 0.7$ are the only configurations that achieve expected-cost feasibility at $d = 10$ ($C = 0.5, 0.6$ respectively), at the cost of $R \leq 5.5$. The urgency schedule, threshold switch, and projected variants achieve $R \in [11, 17]$ but cost $C \in [16, 29]$ (infeasible at $d \in \{10, 25\}$). The urgency schedule is *not* uniquely valuable here—a hard threshold switch achieves comparable reward-cost trade-off ($d = 25$: switch $R = 16.9$, urgency $R = 15.8$). What the schedule *does* provide over simpler alternatives is a single η parameter that smoothly interpolates between high-reward-high-cost (low η) and low-reward-low-cost (high η) operating points without requiring per-budget retuning of σ or θ.

Table 6: Ablation: blending strategies sharing the same $\pi_{\text{perf}} + \pi_{\text{safe}}$ on Safety Gymnasium (5 seeds × 20 ep). The urgency schedule sits on a Pareto frontier between feasible-but-low-reward (π_{safe} alone, const $\sigma = 0.7$) and high-reward-infeasible (const $\sigma = 0.3$); hard threshold switching achieves comparable reward-cost trade-off without the closed-form schedule.

Mode	d	Reward	Cost	Sat	$\mathbb{E}[C] \leq d$
π_{safe} alone (no RL)	10	3.1±0.4	0.5±0.2	100%	✓
const $\sigma = 0.3$	10	22.7±0.3	49.3±3.4	10%	×
const $\sigma = 0.5$	10	5.5±0.5	39.0±10.6	57%	×
const $\sigma = 0.7$	10	5.3±0.5	0.6±0.3	97%	✓
switch $u < 0.5$	10	12.6±0.9	16.8±1.2	22%	×
switch $u < 0.8$	10	13.0±0.9	16.5±1.1	25%	×
projected override	10	11.2±0.9	20.6±1.3	20%	×
urgency $\eta = 3$ (ours)	10	**12.3±0.9**	18.6±1.2	23%	×
π_{safe} alone	25	3.1±0.4	0.5±0.2	100%	✓
const $\sigma = 0.3$	25	22.4±0.3	50.1±3.7	32%	×
const $\sigma = 0.7$	25	5.5±0.5	1.0±0.4	100%	✓
switch $u < 0.8$	25	**16.9±0.9**	28.7±1.7	33%	×
projected override	25	14.4±0.9	25.9±1.5	44%	×
urgency $\eta = 3$ (ours)	25	15.8±0.8	28.6±1.6	39%	×

Comparison: time-to-deployment under four retraining baselines. The right operator-side baseline is retraining from the deployed actor. Figure 2 plots reward vs. extra training steps after the constraint is revealed. Four retraining variants share the same starting actor as the blend: **(i)** Lagrangian finetune at default settings (cost-only objective); **(ii)** Lagrangian + μ-warmup (50k pure-reward steps before dual ascent) and reward scaling (5×) for stable Lagrangian dynamics; **(iii)** aggressive Lagrangian ($\mu_0 = 0.5$, $\mu_{\text{lr}} = 0.05$, no warmup); **(iv)** SAUTE [Sootla et al., 2022] state augmentation with ρ_t (the same urgency variable our schedule uses) and reward masking when $\rho < 0$. At 500k extra steps, the best of these baselines (warmup at $d = 25$) reaches $R = 2.32$ at $C = 24.1$; the APF blend sits at $R = 15.8$ with *zero* extra training.



Figure 2: Time-to-deployment on Safety Gymnasium PointGoal1, both budgets and both axes. *Top row*: reward over extra training steps. *Bottom row*: cost over the same axis with budget line. Blue dashed: APF-blend reward and cost at zero retraining. Curves: four CMDP retraining variants starting from the same pretrained actor (single seed each, four hyperparameter regimes); star: SAUTE [Sootla et al., 2022] at 500k. The blend retains higher reward than every retraining variant tested at every checkpoint, but its cost (18.6 at $d=10$, 28.6 at $d=25$) exceeds the budget; some retraining variants satisfy the budget tightly at the price of $R\approx 0$. The two methods occupy different points on the reward-cost frontier.

Two distinct operating regimes appear. The post-hoc blend gives the highest reward at every compute checkpoint but violates the cost constraint in expectation at $d\in\{10,25\}$ (it is feasible at $d=40$, Table 5). Retraining baselines either violate the budget while preserving partial reward (warmup at intermediate checkpoints) or satisfy it by collapsing reward to ≈ 0 (aggressive Lagrangian, SAUTE). **Neither method dominates in the strict constrained-optimisation sense; they occupy different points on the reward-cost frontier.** A practitioner should choose based on whether their constraint is operationally a soft pacing target (favour the blend, retain useful policy) or a hard expected-cost limit (favour SAC-Lag warmup or SAUTE, accept reward collapse). We do not claim retraining cannot eventually reach better operating points with more compute; under the budgets we tested, the blend offers a competitive position on the reward axis with zero retraining.

Table 7: Final-step (500k) baseline summary on Safety Gymnasium. $\mathbb{E}[C] \leq d$: expected-cost feasibility. The APF blend dominates the retraining baselines *on the reward axis* at the same compute budget. Some retraining baselines satisfy the cost constraint more tightly at the price of near-zero reward.

Method	d	Reward	Cost	$\mathbb{E}[C] \leq d$
APF blend (zero retraining)	10	**12.3**	18.6	×
APF blend (zero retraining)	25	**15.8**	28.6	×
SAC-Lag default	10	−0.41	65.0	×
SAC-Lag default	25	−0.10	12.5	✓
SAC-Lag warmup + reward-scale	10	−0.24	10.4	×
SAC-Lag warmup + reward-scale	25	2.32	24.1	✓
SAC-Lag aggressive	10	0.07	23.6	×
SAC-Lag aggressive	25	−0.32	3.1	✓
SAUTE (state aug, uses ρ_t)	10	−1.0	4.8	✓
SAUTE (state aug, uses ρ_t)	25	−9.5	0.0	✓

6 Related Work

Constrained MDPs. Lagrangian methods [Altman, 1999, Achiam et al., 2017, Stooke et al., 2020, Chen et al., 2025] learn dual variables during training. SAUTE [Sootla et al., 2022] augments state with ρ_t but retrains per budget; we run it as a baseline (§5.2). TREBI [Lin et al., 2023] handles real-time budget changes via diffusion-specific training. We freeze both controllers and use a closed-form $\sigma(u)$ at inference.

Post-hoc composition. Energy composition [Urain et al., 2023], classifier guidance [Zhang et al., 2025], CBFs [Xiao et al., 2025], and input-convex corrections [Durkin et al., 2025] handle instantaneous constraints. Blending with an explicit safety controller is long-standing in robotics (reactive hierarchies, shielding, override layers); our contribution is the budget-aware temporal weighting.

Budget pacing. Budget allocation in advertising [Balseiro et al., 2024] and bandits with knapsacks [Agrawal and Devanur, 2014] share the allocation-across-time structure. We adopt the urgency-ratio framework from optimal execution [Almgren and Chriss, 2001].

Wind-farm wake steering. WakeAdapt [Siemens Gamesa, 2023] and related load-aware controllers compute calibrated yaw setpoints minimising farm-level damage. Our framework sits above such controllers: π_{perf} squeezes more power when the budget allows; π_{safe} is the certified fallback.

Coupling-strength scope. We are not aware of prior scalar predictors specifically targeting post-hoc action-space correction scope. κ is the gradient *ratio* between state and action, usable as an a-priori diagnostic on logged data.

7 Discussion

What we are *not* claiming. We do not claim CMDP retraining cannot work; we claim that under the operator-realistic compute budgets we tested ($\leq$ 500k extra steps from the pretrained actor, four hyperparameter settings), every retraining variant we tried is dominated on reward by post-hoc blending. A fully-converged CMDP method at $\sim$10$\times$ our compute may reach a better Pareto frontier, but does so at a cost the deployment scenario cannot tolerate.

Limitations. (1) The wind-farm cost is a per-turbine fatigue surrogate; real deployment needs a DEL-calibrated farm-level cost [Álvaro-García et al., 2024, Galán-García et al., 2024] and a π_{safe} like WakeAdapt that minimises farm DEL. (2) Our sim uses analytical wakes (Jensen) and 200-step episodes, not FAST.Farm aeroelastics over year-scale operation; a yearly damage budget is the operational target the urgency-ratio framing was designed for, but our experiments validate at episode scale only. (3) The APF navigator on SG

is a simple reactive heuristic that uses hazard/goal geometry; a learned safety policy would likely improve π_{safe}'s reward at fixed $\sigma = 1$. The APF benefits from privileged geometry that the RL policy and retraining baselines do not directly use; the ablation table shares this privilege across all blend modes. (4) Action blending assumes meaningful convex combinations of π_{perf} and π_{safe} outputs. This holds for our continuous yaw and thrust/turn action spaces but may not for systems with discrete or non-convex action sets; in those cases a hard switch (Table 6) is more appropriate. (5) We test 4 seeds on WF and 5 on SG; retraining baselines use a single seed each at one hyperparameter setting per regime, covering three qualitatively different Lagrangian configurations (default, warmup, aggressive) plus SAUTE. Lagrangian methods are sensitive to reward scale and dual learning rate; we explored three settings, not a full sweep. (6) κ depends on state and action scaling and on the quality of the learned Q_c. Comparing across two domains is suggestive, not definitive; broader validation across continuously varying coupling regimes (e.g. synthetic gridworlds) would strengthen the diagnostic claim. (7) Hard budget enforcement is not provided. A safe-future-cost upper bound $B_{\text{safe}}(t)$ giving $C_t + B_{\text{safe}}(t) \leq d$ would be required and is left as future work. (8) The unconstrained EBT actor's wake-steering benefit appears small in our experiments: pure π_{safe} (zero yaw) retains 100.7% of unconstrained power (Table 4). This indicates the actor we trained is not Pareto-optimal on the power axis, so the wind-farm experiments should be read as validating the *blend mechanism's correctness* (correct fatigue budget tracking under various σ choices) rather than as a demonstration that RL wake-steering yields large power gains here. A stronger π_{perf} (longer training, multi-layout, DEL-aware reward) would be required for that demonstration; the blend mechanism would compose with it identically.

Path to deployment. Minimum-viable bridge from simulation to field operation: (a) replace the fatigue surrogate with a DEL-calibrated model; (b) precompute a WakeAdapt-equivalent setpoint table to use as π_{safe}; (c) retrospective SCADA counterfactual on real operational data; (d) online refit of Q_c / the DEL surrogate under non-stationary wind. All four leverage the same schedule; none require retraining π_{perf}.

Summary. A single closed-form schedule composes a pre-trained performance policy with a domain-specific safety controller to enforce cumulative damage budgets at inference. κ diagnoses which variant to use. On both domains, post-hoc blending is not dominated by Lagrangian finetune at the compute budgets an operator can realistically afford—and it gives up the single-budget training commitment: one model, any d, instantly. Code and checkpoints: `[anonymized]`.

A Derivations, Protocols, and Negative Results

A.1 Full Proof of Proposition 1

Proof. Budget balance: $(T - t) \cdot P(\text{risky} \mid \lambda) = d - C_t$. With $P(\text{risky} \mid \lambda) = P_0 \exp(-\alpha\lambda)$: $\lambda = \frac{1}{\alpha} \ln \frac{(T-t)P_0}{d-C_t}$. At TWAP ($u = 1$), $\lambda_0 = \frac{1}{\alpha} \ln \frac{TP_0}{d}$. $w = \exp(\alpha(\lambda - \lambda_0)) = \frac{(T-t)/T}{(d-C_t)/d} = \tau/\rho = 1/u$. □

A.2 Schedule Approximation

A.3 Safety Controllers

APF navigator (Safety Gym). Agent position x, goal g, hazard centres $\{h_i\}$ with radius r, influence distance r_{inf}: $F_{\text{goal}} = (g - x)/\|g - x\|$, $F_{\text{rep}} = k_r \sum_{i:\|x-h_i\|<r+r_{\text{inf}}} (x - h_i)/\|x - h_i\|^3$, $d^\star = \text{norm}(\alpha F_{\text{goal}} + (1 - \alpha)F_{\text{rep}})$. Mapped to body-frame action: thrust $= \langle d^\star, \hat{\mathbf{e}}_{\text{fwd}} \rangle$, turn $= \text{clip}(\Delta\theta/(\pi/2), -1, 1)$. We use $\alpha = 0.5$, $r_{\text{inf}} = 0.6$ m, $k_r = 1.0$.

Zero-yaw / WakeAdapt (wind farm). $\pi_{\text{safe}}(s) \equiv 0$ in normalized yaw-action space, minimising the per-turbine surrogate cost. Deployment replaces with a precomputed table $T(\bar{v}, \bar{\phi}) \to \{y_i\}$ minimising farm-level DEL.



Figure 3: (a) $\exp(\eta(1/u-1))$ (solid) vs. $u^{-\eta}$ (dashed). Red: $u < 0.05$ hard-wall zone. (b) Relative approximation error $< 10\%$ for $u > 0.5$.

A.4 Binary vs Nonlinear Cost (Wind Farm)

Table 8: Binary vs. nonlinear fatigue cost (3-turbine wind farm, 10 ep at 12–16 m/s).

Method	Power (MW)	NegYaw	Fatigue
Unconstrained	29.7	[66, 75, 71]	20.3
Binary AC (η=2)	28.1	[8, 8, 10]	86.2
Nonlinear AC (η=5)	**29.2**	[80, 81, 83]	**12.8**

A.5 Learned Cost Critic on Wind Farm

Table 9: Learned Q_c on 3-turbine wind farm (10 ep). Q_c trained on 100 ep with the nonlinear fatigue cost.

Method	Power (MW)	NegYaw	Fatigue	Fatigue ×
Unconstrained	24.6±5.6	[84, 96, 94]	54.6	1.0×
Q_c, η=2, gs=0.05	**28.1±2.7**	[43, 44, 43]	**9.5**	5.7×
Q_c, η=5, gs=0.5	28.8±2.0	[55, 54, 51]	10.4	5.3×
Analytical surrogate (η=5)	29.2	[80, 81, 83]	12.8	4.3×

A.6 Reward–Cost Scatter: from-scratch SAC-Lag (additional ablation)

A.7 Nine Attempted Gradient-Variant Rescues on SG

When the gradient variant is forced to work on SG (low κ), the following all fail:

1. **Pessimistic Q_c ensemble.** 10 heads, $\nabla_a(\bar{Q} + q\sigma_Q)$ with $q \in \{0, 1, 4\}$. $q=0$ ties or wins at every budget.
2. **Online Q_c refit.** Episode-boundary MC refit with L2 anchor; no improvement.
3. **MPC with learned $f_\theta + Q_c$.** Matches unconstrained (55 cost, 17% sat at $d=10$).



Figure 4: From-scratch SAC-Lag (red stars), 500k steps per budget, vs. APF blend (blue/orange/green) and unconstrained (X). Same qualitative failure mode as the from-pretrained Lagrangian finetune in Figure 2; the choice of warm-start does not rescue CMDP at this compute.

4. **MPC true-env + oracle cost, cost-only.** Reward collapses to -120; 26% sat via "agent stuck in corner."
5. **MPC true-env reward-weighted.** λ (to 10^6) dominates $\beta \cdot r$; same outcome.
6. **MPC true-env feasibility-filtered.** Few feasible candidates; falls back to min-violation; same outcome.
7. **Full MBRL post-hoc.** Ensemble $f_\theta + Q_r + Q_c$ + CEM + online refit. Cost $\approx$ uncon, reward $\approx$ uncon, sat $\approx$ uncon.
8. **CBF 1-step kinematic.** Reward preserved, cost barely drops; 1-step insufficient for momentum.
9. **CBF multi-step (constant-action rollout).** Errors compound; reward degrades, cost rises.

The explicit π_{safe} blend (main body) succeeds because π_{safe} is *not* constrained to lie near π_{perf}'s action distribution. When the performance policy was trained for short-path navigation, its action support does not cover the safe-corridor actions; a local gradient correction cannot reach them. An APF navigator can.

A.8 Coupling-Strength Measurement Protocol

20 episodes per domain under the frozen policy; uniform subsample of 2000 (s, a) pairs; $\|\nabla_a Q_c\|_2$ and $\|\nabla_s Q_c\|_2$ via autodiff; κ = ratio of sample means; nonparametric bootstrap with 1000 resamples for CIs.

A.9 Retraining-Baseline Hyperparameters

SAC-Lagrangian default: $\mu_0 = 0.1$, $\mu_{\text{lr}} = 0.005$, no warmup, no reward scaling. **Warmup variant**: μ held at 0 for the first 50k steps (pure-reward warmup), $\mu_0 = 0.05$ after, $\mu_{\text{lr}} = 0.005$, reward$\times$5. **Aggressive**:

$\mu_0 = 0.5$, $\mu_{\text{lr}} = 0.05$, reward$\times 5$, no warmup. All start from the pretrained unconstrained actor; $\alpha_{\text{ent}} = 0.2$ fixed. **SAUTE**: state-augmentation with ρ_t, reward replaced with $-1/(1-\gamma)$ when $\rho_t < 0$; otherwise standard SAC; trained from the pretrained actor for 500k steps.

A.10 Path to Wind-Farm Deployment

1. **DEL-calibrated cost**: replace per-turbine surrogate with a control-oriented DEL model [Álvaro-García et al., 2024, Galán-García et al., 2024].
2. **WakeAdapt-equivalent** π_{safe}: precompute $T(\bar{v}, \bar{\phi}) \to \{y_i\}$ minimising farm DEL.
3. **SCADA counterfactual**: retrospective evaluation on real operational data.
4. **Non-stationary wind**: online refit of Q_c / DEL surrogate; concept-drift detection.
5. **High-fidelity validation**: FAST.Farm calibrated to SCADA.

References

Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. In *International Conference on Machine Learning*, 2017.

Shipra Agrawal and Nikhil R Devanur. Bandits with concave rewards and convex knapsacks. In *ACM Conference on Economics and Computation*, 2014.

Robert Almgren and Neil Chriss. Optimal execution of portfolio transactions. *Journal of Risk*, 3:5–39, 2001.

Eitan Altman. *Constrained Markov decision processes*. Chapman and Hall/CRC, 1999.

Alberto Álvaro-García et al. Data-driven surrogate model for wind turbine damage equivalent load. *Wind Energy Science*, 9:2039–2058, 2024.

Santiago Balseiro et al. A field guide for pacing budget and ROS constraints. *International Conference on Machine Learning*, 2024.

Yuxiang Chen et al. Predictive Lagrangian optimization for constrained reinforcement learning. *arXiv preprint arXiv:2501.15217*, 2025.

Shashank Durkin et al. Safe deployment for counterfactual learning to rank with exposure-based constraints via input convex action correction. *arXiv preprint arXiv:2507.22640*, 2025.

Marcos Galán-García et al. Control-oriented load surrogate for waked, wake-steering, and curtailed wind turbines. In *Journal of Physics: Conference Series*, volume 2767, page 032019, 2024.

Ruairidh Gladstone et al. Energy-based transformers are scalable learners and thinkers. *arXiv preprint arXiv:2507.02092*, 2025.

Jiaming Ji, Borong Zhang, Jiayi Zhou, Juntao Pan, Hantao Dai, Ruiyang Sun, Shunyu Huang, Yiran Gong, Junting Zhang, and Yaodong Yang. Safety-gymnasium: A unified safe reinforcement learning benchmark. In *Advances in Neural Information Processing Systems*, 2023.

Qian Lin et al. Safe offline reinforcement learning with real-time budget constraints. In *International Conference on Machine Learning*, 2023.

Marcus Binder Nilsen, Julian Quick, Ernestas Simutis, and Teodor Åstrand. WindGym: A wind farm reinforcement learning environment. `https://github.com/DTUWindEnergy/WindGym`, 2025.

Mads Mølgaard Pedersen et al. PyWake: An open-source wind farm simulation tool. `https://topfarm.pages.windenergy.dtu.dk/PyWake/`, 2023.

Alex Ray, Joshua Achiam, and Dario Amodei. Benchmarking safe exploration in deep reinforcement learning. *arXiv preprint arXiv:1910.01708*, 2019.

Siemens Gamesa. Wake Adapt: Wake-steering control for wind farms. Commercial product documentation, 2023.

Aivar Sootla, Alexander I Cowen-Rivers, Taher Jafferjee, Ziyan Wang, David H Mguni, Jun Wang, and Haitham Bou Ammar. Sauté RL: Almost surely safe reinforcement learning using state augmentation. In *International Conference on Machine Learning*, 2022.

Adam Stooke, Joshua Achiam, and Pieter Abbeel. Responsive safety in reinforcement learning by PID Lagrangian methods. In *International Conference on Machine Learning*, 2020.

Julen Urain, Anqi Li, Puze Liu, Carlo D'Eramo, and Jan Peters. Composable energy policies for reactive motion generation and reinforcement learning. In *International Journal of Robotics Research*, 2023.

Mike van Dijk et al. Load assessment of a wind farm considering negative and positive yaw misalignment for wake steering. *Wind Energy Science*, 10:1033–1051, 2025.

Wei Xiao, Tsun-Hsuan Wang, Chuang Zhan, Karthik Narasimhan Ramamurthy, Ramin Hasani, and Daniela Rus. SafeDiffuser: Safe planning with diffusion probabilistic models. *International Conference on Learning Representations*, 2025.

Zheyu Zhang et al. Constrained diffusers for safe planning and control. *Advances in Neural Information Processing Systems*, 2025.