

트리플 여행지(도시) 관리 API

Table of Contents

- City 등록
- City 수정
- City 삭제
- City 단일 조회
- City 사용자 별 조회
- Travel 등록
- Travel 수정
- Travel 삭제
- Travel 단일 조회

City 등록

Request

HTTP

```
POST /api/v1/city HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 97
Host: localhost:8080

{
  "userId" : 1,
  "cityName" : "한국",
  "cityIntroContent" : "간단한 한국 소개"
}
```

Path	Type	Description
userId	Number	userId
cityName	String	city 이름
cityIntroContent	String	city 소개

Response

HTTP

```
POST /api/v1/city HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 97
Host: localhost:8080

{
  "userId" : 1,
  "cityName" : "한국",
  "cityIntroContent" : "간단한 한국 소개"
}
```

Path	Type	Description
code	String	Business code
message	String	response message

Path	Type	Description
data.name	String	city 이름
data.introContent	String	city 에 대한 소개
data.createdAt	String	city 내용 생성 일자
data.updatedAt	String	city 내용 수정 일자

City 수정

Request

```
PUT /api/v1/city HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 97
Host: localhost:8080

{
  "cityId" : 1,
  "cityName" : "한국",
  "cityIntroContent" : "간단한 한국 소개"
}
```

HTTP

Path	Type	Description
cityId	Number	city id
cityName	String	city 이름
cityIntroContent	String	city 소개

Response

```
PUT /api/v1/city HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 97
Host: localhost:8080

{
  "cityId" : 1,
  "cityName" : "한국",
  "cityIntroContent" : "간단한 한국 소개"
}
```

HTTP

Path	Type	Description
code	String	Business code

Path	Type	Description
message	String	response message
data.name	String	city 이름
data.introContent	String	city 에 대한 소개
data.createdAt	String	city 내용 생성 일자
data.updatedAt	String	city 내용 수정 일자

City 삭제

Request

```
DELETE /api/v1/city/1 HTTP/1.1
Host: localhost:8080
```

HTTP

Table 1. /api/v1/city/{id}

Parameter	Description
id	삭제할 city id

Response

```
DELETE /api/v1/city/1 HTTP/1.1
Host: localhost:8080
```

HTTP

Path	Type	Description
code	String	Business code
message	String	response message
data	String	empty String

City 단일 조회

Request

```
GET /api/v1/city/1 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Host: localhost:8080
```

HTTP

Table 2. /api/v1/city/{id}

Parameter	Description
id	조회할 city id

Response

```
GET /api/v1/city/1 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Host: localhost:8080
```

HTTP

Path	Type	Description
code	String	Business code
message	String	response message
data.name	String	city 이름
data.introContent	String	city 에 대한 소개
data.createdAt	String	city 내용 생성 일자
data.updatedAt	String	city 내용 수정 일자

City 사용자 별 조회

Request

```
GET /api/v1/city/users/1 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Host: localhost:8080
```

HTTP

Table 3. /api/v1/city/users/{userId}

Parameter	Description
userId	조회할 user id

Response

```
GET /api/v1/city/users/1 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Host: localhost:8080
```

HTTP

Path	Type	Description
code	String	Business code

Path	Type	Description
message	String	response message
data.cityInfos.[].name	String	city 이름
data.cityInfos.[].introContent	String	city 에 대한 소개
data.cityInfos.[].createdAt	String	city 내용 생성 일자
data.cityInfos.[].updatedAt	String	city 내용 수정 일자

Travel 등록

Request

```

POST /api/v1/travel HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 123
Host: localhost:8080

{
  "cityId" : 1,
  "userId" : 1,
  "travelStartAt" : [ 2022, 11, 18, 22, 38, 8, 444955700 ],
  "travelEndAt" : null
}
```

HTTP

Path	Type	Description
cityId	Number	city id
userId	Number	user id
travelStartAt	Array	travel 시작 일자
travelEndAt	Null	travel 끝나는 일자

Response

HTTP

```
POST /api/v1/travel HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 123
Host: localhost:8080

{
  "cityId" : 1,
  "userId" : 1,
  "travelStartAt" : [ 2022, 11, 18, 22, 38, 8, 444955700 ],
  "travelEndAt" : null
}
```

Path	Type	Description
code	String	Business code
message	String	response message
data.cityName	String	city 이름
data.userName	String	여행 등록한 사용자 이름
data.startTravelAt	String	travel 시작 일자
data.endTravelAt	Null	travel 끝나는 일자

Travel 수정

Request

HTTP

```
PUT /api/v1/travel HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 176
Host: localhost:8080

{
  "travelId" : 1,
  "cityId" : 1,
  "userId" : 1,
  "travelStartAt" : [ 2022, 11, 16, 22, 38, 8, 572960600 ],
  "travelEndAt" : [ 2022, 11, 16, 22, 38, 8, 572960600 ]
}
```

Path	Type	Description
travelId	Number	travel id
cityId	Number	city id
userId	Number	user id

Path	Type	Description
travelStartAt	Array	travel 시작 일자
travelEndAt	Array	travel 끝나는 일자

Response

PUT /api/v1/travel HTTP/1.1

Content-Type: application/json;charset=UTF-8

Content-Length: 176

Host: localhost:8080

```
{
  "travelId" : 1,
  "cityId" : 1,
  "userId" : 1,
  "travelStartAt" : [ 2022, 11, 16, 22, 38, 8, 572960600 ],
  "travelEndAt" : [ 2022, 11, 16, 22, 38, 8, 572960600 ]
}
```

HTTP

Path	Type	Description
code	String	Business code
message	String	response message
data.cityName	String	city 이름
data.userName	String	여행 등록한 사용자 이름
data.startTravelAt	String	travel 시작 일자
data.endTravelAt	String	travel 끝나는 일자

Travel 삭제

Request

DELETE /api/v1/travel/1 HTTP/1.1

Content-Type: application/json;charset=UTF-8

Host: localhost:8080

HTTP

Table 4. /api/v1/travel/{id}

Parameter	Description
id	삭제할 travel id

Response

DELETE /api/v1/travel/1 HTTP/1.1

Content-Type: application/json;charset=UTF-8

Host: localhost:8080

HTTP

Path	Type	Description
code	String	Business code
message	String	response message
data	String	empty String

Travel 단일 조회

Request

GET /api/v1/travel/1 HTTP/1.1

Content-Type: application/json;charset=UTF-8

Host: localhost:8080

HTTP

Table 5. /api/v1/travel/{id}

Parameter	Description
id	조회할 travel id

Response

GET /api/v1/travel/1 HTTP/1.1

Content-Type: application/json;charset=UTF-8

Host: localhost:8080

HTTP

Path	Type	Description
code	String	Business code
message	String	response message
data.cityName	String	city 이름
data.userName	String	여행 등록한 사용자 이름
data.startTravelAt	String	travel 시작 일자
data.endTravelAt	String	travel 끝나는 일자