

# GOOD MORNING!

早上好!

안녕하세요!

---

DAY 3



# DAY2 RECAP

---



# DAY I

---

- Welcome
- Project Introduction
- Introduction to Project Development Process
- Business Requirement Development
- System Requirement Development
- System and Development environment Setup

# DAY 2 (MINI PROJECT)

---

- Yolo객체 인식 모델 활용과 성능 평가 방법 이해
  - Custom Dataset과 Fine Tuning으로 자체 객체 인식 모델 구현 및 평가
  - (Optional)경량화 모델 등 개별 요구사항에 적합한 모델 탐색 및 성능 검증

# DAY 2 (MINI PROJECT)

---

## WEB-CAM 기반 객체 인식

### (IF NEEDED)

- YOLOv8 기반 데이터 수집/학습/deploy (Detection Alert)
  - 감시용 데이터 수집(rc\_car, dummy, 등)
  - 감시용 데이터 라벨링
  - YOLOv8 기반 학습
  - YOLOv8 Object Detection

## AMR-CAM 기반 객체 인식

- AMR(Autonomous Mobile Robot) Turtlebot4 개발 환경 구축
- 로봇 개발 환경에 완성 모델 서빙 및 테스트 / 로봇 H/W, 제반 환경의 한계점 도출
  - Tracking 데이터 수집((rc\_car, dummy, 등)
  - Tracking 데이터 라벨링
  - YOLOv8 기반 학습
  - YOLOv8 Object **Tracking**



# DAY 3 (MINI PROJECT)

---

- Auto. Driving 시스템 학습
  - Digital Mapping of environment
  - Operate AMR (Sim. & Real)
  - Tutorial 실행
  - Detection, Depth and AMR 주행
  - 로봇 개발 환경에 적용 및 테스트 / 로봇 H/W, 제반 환경의 한계점 도출

## TURTLEBOT4 시뮬레이션 DEMO

- SLAM과 AutoSLAM으로 맵 생성
- Sim.Tutorial 실행
- Detection, Depth and AMR 주행 example

# DAY 3 (MINI PROJECT)

---

## REAL ROBOT

- Manually operating the AMR (Teleops)
- autonomous driving 시스템 with obstacle avoidance
  - Digital Mapping of environment
  - Launching Localization, Nav2, and using Rviz to operate a robot
  - Goal Setting and Obstacle Avoidance using Navigation

## TUTORIAL

- Turtlebot4 API를 활용한 Initial Pose Navigate\_to Pose 구현
- Turtlebot4 API를 활용한 Navigate\_Through\_pose, Follow Waypoints 구현

# DAY 4 (MINI PROJECT)

---

- System(High Level) Design (Mini Project)
  - System Architectural Diagram
- Detail Design to Acceptance - Agile Development (SPRINTs)
  - Detection
  - AMR Control



# DAY 4 (MINI PROJECT)

---

## CODING, TEST & INTEGRATION

- Coding and Test all modules
- Porting to ROS
- And finally, Integration and Test of Detection Alert & AMR Controller

## MINI PROJECT DEMO

- Prepare and demo completed project

프로젝트 RULE NUMBER ONE!!!

---

Have Fun Fun Fun!



# HOMEWORK CHECK

---

- Object Detection
  - Collect various datasets (i.e. different topics/images sizes)
  - Create various models (i.e. v5, v8, v11, etc; arg: Epoch, Batch, Imgsz, augmentation, etc)
  - Analyze the results
  - Determine using key metrics which model best fit your solution
  - Using .pt file to predict/inference on pc
- Depth
  - Find and display the distance to the center of the detected objects
- Update System Requirement

# SYSTEM REQUIREMENT PRESENTATION BY EACH TEAM

---

Using the posted notes and flipchart as needed



# KEY SUBSYSTEM (MODULES) TO DEVELOP

---

- Detection Alert
  - Camera Capture
  - Object Detection
  - Send messages to other subsystems
- AMR Controller
  - Receive messages and act accordingly
  - Move using (SLAM) with Obstruction avoidance
  - Target Acquisition (Obj. Det.) and Tracking
  - Approach target using camera and motor control



# OPERATING AMR

---



# AMR (TURTLEBOT4)

---

- [Features](#) · [User Manual](#)
- <https://turtlebot.github.io/turtlebot4-user-manual/overview/features.html>
- Review the content



# SIMULATION DEMO

---



# TUTORIAL(SIM)

---

- [TurtleBot 4 Navigator · User Manual](https://turtlebot.github.io/turtlebot4-user-manual/tutorials/turtlebot4_navigator.html)

[https://turtlebot.github.io/turtlebot4-user-manual/tutorials/turtlebot4\\_navigator.html](https://turtlebot.github.io/turtlebot4-user-manual/tutorials/turtlebot4_navigator.html)

# SETUP BASH

---

- Make sure bashrc has:
  - `ROS_DOMAIN_ID = 0`
- Make sure discovery setup.bash is **not** sourced!
- `source ~/.bashrc`



# OPERATING A ROBOT(SIM) – GAZEBO

---

## TERM1

- `ros2 launch turtlebot4_ignition_bringup turtlebot4_ignition.launch.py`

## TERM2

- `ros2 topic list`
- `ros2 topic echo <topic> --once`
  - `/oakd/rgb/preview/image_raw`
  - `/oakd/rgb/preview/depth`
  - ....

# OPERATING A ROBOT(SIM)

---

- Dock/Undock
- Manual Driving
  - Teleops
- Camera Display
  - RGB/Depth
- Navigation with rviz
  - 2D\_Pose\_Estimate (initial position)
  - Nav2\_Goal

# DIGITAL MAPPING USING SLAM (SIM)

---

## TERMI

- `ros2 launch turtlebot4_ignition_bringup turtlebot4_ignition.launch.py`  
**`nav2:=true slam:=true rviz:=true`**

## ON GAZEBO

- Undock the robot
- Use keyboard to operate and complete the map

# DIGITAL MAPPING WITH AUTO – SLAM (SIM)

---

## TERM1

- `ros2 launch turtlebot4_ignition_bringup turtlebot4_ignition.launch.py`  
**`nav2:=true slam:=true rviz:=true`**
- Undock the robot
- Set init pose from rviz

## TERM2

- `ros2 launch explore_lite explore.launch.py`

# TUTORIAL(SIM)

---

## TERMINAL 1

```
$ ros2 launch turtlebot4_ignition_bringup  
  turtlebot4_ignition.launch.py nav2:=true  
  slam:=false localization:=true rviz:=true
```

- Undock and set init pose

## TERMINAL 2

```
$ ros2 run turtlebot4_python_tutorials nav_to_pose
```

```
$ ros2 run turtlebot4_python_tutorials  
  nav_through_poses
```

```
$ ros2 run turtlebot4_python_tutorials  
  follow_waypoints
```

```
$ ros2 run turtlebot4_python_tutorials create_path
```

```
$ ros2 run turtlebot4_python_tutorials mail_delivery
```

```
$ ros2 run turtlebot4_python_tutorials patrol_loop
```



# USING DEPTH (SIM)

---

```
3_1_a_depth_checker.py
3_1_b_depth_to_3d.py
3_1_c_depth_to_nav_goal.py
3_1_d_nav_to_person.py
```

## TERMINAL 2 (

```
$ ros2 run <pkg_name> <exec_name>
```

For example,

```
$ ros2 run day3 nav_to_person
```

# OPERATING THE ROBOT (AUTONOMOUSLY)

---



# SETUP BASH

---

- Make sure bashrc has:
  - `ROS_DOMAIN_ID = 0`
- `echo "alias ros-restart=ros2 daemon stop; ros2 daemon start" >> ~/.bashrc`
- Make sure discovery setup.bash **is** sourced!
- `source ~/.bashrc`

# DIGITAL MAPPING (SLAM)

---

- [Generating a map · User Manual](https://turtlebot.github.io/turtlebot4-user-manual/tutorials/generate_map.html)

[https://turtlebot.github.io/turtlebot4-user-manual/tutorials/generate\\_map.html](https://turtlebot.github.io/turtlebot4-user-manual/tutorials/generate_map.html)

# SLAM 개요

Aa 이름

status

+








DAY 3 - SLAM & Navigation

New

Aa 이름


상태

+

 SLAM 개요	● 시작 전
 Robot_SLAM	● 시작 전
 Auto SLAM 개요	● 시작 전
 Robot SLAM_explore_lite	● 시작 전
 Nav2 개요	● 시작 전
 Robot_Navigation	● 시작 전
 TF Transform 개요	● 시작 전

+

New page



## SLAM 개요

상태

● 시작 전

수정

대기

차시

3-0

환경

ubuntu22.04

humble


+

Add a property

Comments

A

Add a comment...



### SLAM(Simultaneous Localization and Mapping) 이란?

Simultaneous

동시적



# SLAM WITH ROBOT

Aa 이름

status

+

DAY 3 - SLAM & Navigation

Aa 이름

상태

+

SLAM 개요	● 시작 전
Robot_SLAM	● 시작 전
Auto SLAM 개요	● 시작 전
Robot SLAM_explore_lite	● 시작 전
Nav2 개요	● 시작 전
Robot_Navigation	● 시작 전
TF Transform 개요	● 시작 전

+ New page



## Robot\_SLAM

상태

● 시작 전

수정

대기

차시

3-1

환경

ubuntu22.04

humble

+ Add a property

Comments


A

Add a comment...

### ! 주의

- .baschrc 에 Robot Turtlebot4와 연결을 위한 설정 내용을 활성화해야 한다.

# AUTO SLAM CONCEPT/ALGORITHM



# ALGORITHM DETAIL

- Map Subscription

explore\_lite subscribes to the SLAM-generated occupancy grid (/map topic) and identifies:


- Free space: known, unoccupied areas
- Occupied space: obstacles
- Unknown space: unexplored

- Frontier Detection

The map is scanned for cells that:


- Are free, and
- Are adjacent to at least one unknown cell.

These are marked as frontier cells.



# ALGORITHM DETAIL

- Frontier Grouping
  - Frontier cells are clustered into connected regions.
  - Each group represents a potential exploration target.
- Goal Selection
  - For each frontier group, a representative point (typically the centroid or closest point) is selected.
  - The robot scores each group based on:
    - Distance from the robot
    - Information gain (how much new area might be revealed)
  - The best-scoring frontier is chosen as the next goal.





# ALGORITHM DETAIL

---

- Termination

- While (frontiers exist and reachable)

- Select best frontier

- Send as goal

- If goal fails → blacklist

- If (no frontiers or all blacklisted)

- Terminate exploration



# AUTO SLAM 개요

Aa 이름

status

+

DAY 3 - SLAM & Navigation

add below  
add a block above

상태

+

SLAM 개요	● 시작 전
Robot_SLAM	● 시작 전
Auto SLAM 개요	● 시작 전
Robot SLAM_explore_lite	● 시작 전
Nav2 개요	● 시작 전
Robot_Navigation	● 시작 전
TF Transform 개요	● 시작 전

+ New page



## Auto SLAM 개요

상태

● 시작 전

수정

Empty

차시

Empty

환경

ubuntu22.04

WSL2

humble

+ Add a property

Comments

A Add a comment...

### 핵심 개념

`explore_lite` 는 TurtleBot4 같은 로봇이 미지의 환경을 자율적으로 탐색하도록 도와주는 패키지이다.

# AUTO SLAM

Aa 이름

status

+








Settings

DAY 3 - SLAM & Navigation

Aa 이름

상태

+

 SLAM 개요	● 시작 전
 Robot_SLAM	● 시작 전
 Auto SLAM 개요	● 시작 전
 Robot SLAM_explore_lite	● 시작 전
 Nav2 개요	● 시작 전
 Robot_Navigation	● 시작 전
 TF Transform 개요	● 시작 전

+ New page



## Robot SLAM\_explore\_lite

상태

● 시작 전

수정

대기

차시

3-2

환경

ubuntu22.04

humble

+ Add a property

Comments

A Add a comment...



Auto SLAM


# SIMPLE NAV2 PARAM ADJUSTMENT

```
$ cd
```

```
~/turtlebot4_ws/src/turtlebot4/turtlebot4_navigation/config
```

- Change/adjust “inflation\_radius” to fit your environment

```
139
140 local_costmap:
141   local_costmap:
142     ros__parameters:
143       update_frequency: 5.0
144       publish_frequency: 2.0
145       global_frame: odom
146       robot_base_frame: base_link
147       use_sim_time: True
148       rolling_window: true
149       width: 3
150       height: 3
151       resolution: 0.06
152       robot_radius: 0.175
153       plugins: ["static_layer", "voxel_layer", "inflation_layer"]
154       inflation_layer:
155         plugin: "nav2_costmap_2d::InflationLayer"
156         cost_scaling_factor: 4.0
157
158       #inflation_radius: 0.45
159       inflation_radius: 0.25
160       #changed by aak
161
162       voxel_layer:
163         plugin: "nav2_costmap_2d::VoxelLayer"
164         enabled: True
```



# NAV2 개요

Aa 이름

status

+

DAY 3 - SLAM & Navigation








≡ ⬆ ⬇ 🔍 ↗ ⚙

New ▾

Aa 이름

상태

+

 SLAM 개요	● 시작 전	
 Robot_SLAM	● 시작 전	
 Auto SLAM 개요	● 시작 전	
 Robot SLAM_explore_lite	● 시작 전	
 Nav2 개요	● 시작 전	
 Robot_Navigation	● 시작 전	
 TF Transform 개요	● 시작 전	

+

New page



## Nav2 개요

상태	● 시작 전
수정	Empty
차시	Empty
환경	Empty
+ Add a property	

### Comments

A Add a comment...

### 💡 Nav2는 무엇인가?

- Nav2 (Navigation2): ROS2 기반 로봇 자율 주행 프레임워크

# NAV2

**DAY 3 - SLAM & Navigation** New

Aa 이름	상태
SLAM 개요	● 시작 전
Robot_SLAM	● 시작 전
Auto SLAM 개요	● 시작 전
Robot SLAM_explore_lite	● 시작 전
Nav2 개요	● 시작 전
Robot_Navigation	● 시작 전
TF Transform 개요	● 시작 전

+ New page

## Robot\_Navigation

● 시작 전

수정 Empty

차시 Empty

환경 Empty

+ Add a property

Comments

A Add a comment...

### Navigation w/ map

- Reference



# TUTORIAL EXERCISE

---

Make copy and Update the tutorial code to successfully execute in the project environment with real robot

Tutorial Codes are found in:

**`$HOME/turtlebot4_ws/src/turtlebot4_tutorials/turtlebot4_python_tutorials/  
turtlebot4_python_tutorials`**

# TUTORIAL

---

## TERMINAL 1

```
$ ros2 launch turtlebot4_navigation  
localization.launch.py namespace:=/robot <n>  
map:=$HOME/Documents/room/room_map.  
yaml
```

## TERMINAL 2

```
$ ros2 launch turtlebot4_viz view_robot.launch.py  
namespace:=/robot <n>
```

- Undock and set init pose

## TERMINAL 3

```
$ ros2 launch turtlebot4_navigation nav2.launch.py  
namespace:=/robot <n>
```

# TUTORIAL

---

```
3_2_a_nav_to_pose.py
3_2_b_nav_through_poses.py
3_2_c_follow_waypoints.py
3_2_d_create_path.py
3_2_e_mail_delivery.py
3_2_f_patrol_loop.py
```

## TERMINAL 4


```
$ ros2 run day3 create_path --ros-args -r __ns:=/robot<n>
$ ros2 run day3 nav_to_poses --ros-args -r __ns:=/robot<n>
$ ros2 run day3 follow_waypoints --ros-args -r
__ns:=/robot<n>
$ ros2 run day3 nav_through_poses --ros-args -r
__ns:=/robot<n>
$ ros2 run day3 mail_delivery --ros-args -r __ns:=/robot<n>
$ ros2 run day3 patrol_loop --ros-args -r __ns:=/robot<n>
```

# USING DEPTH TO GET COORDINATES (TF TRANSFORM)

---



# CAMERA INTRINSIC AND REPROJECTION




$$X = \frac{(u - c_x) \cdot Z}{f_x}, \quad Y = \frac{(v - c_y) \cdot Z}{f_y}, \quad Z = Z$$



# ROS TRANSFORM EXPLAINED

- [Transform Explained \(I\)](#)
- <https://indecisive-freedom-6e8.notion.site/Transform-Explained-I-22f8e215779c809eb2d4cb0be5538056>



# TF TRANSFORM 개요

Aa 이름

status








+

DAY 3 - SLAM & Navigation

Aa 이름

상태

+

 SLAM 개요	● 시작 전	
 Robot_SLAM	● 시작 전	
 Auto SLAM 개요	● 시작 전	
 Robot SLAM_explore_lite	● 시작 전	
 Nav2 개요	● 시작 전	
 Robot_Navigation	● 시작 전	
 TF Transform 개요	● 시작 전	

+ New page



## TF Transform 개요

상태

● 시작 전

수정

Empty

차시

Empty

환경

Empty

+ Add a property

Comments

A Add a comment...



### TF

TF는 ROS(Robot Operating System)에서 여러 좌표계(Frame) 간의 변환 관계(Transform)를 실시간으로 관리하고 계산해주는 시스템이다.

# SETUP BASH(ROBOT)

---

- Make sure bashrc has:
  - `ROS_DOMAIN_ID = 0`
- Make sure discovery setup.bash **is** sourced!
- `source ~/.bashrc`

# USING DEPTH (ROBOT)

---

## TERMINAL 1

```
$ ros2 launch turtlebot4_navigation  
localization.launch.py namespace:=/robot <n>  
map:=$HOME/Documents/room/room_map.  
yaml
```

## TERMINAL 2

```
$ ros2 launch turtlebot4_viz  
view_robot.launch.py namespace:=/robot  
<n>
```

- Set Init Pose using 2D\_PoseEstimate

## TERMINAL 3

```
$ ros2 launch turtlebot4_navigation  
nav2.launch.py namespace:=/robot <n>
```

# USING DEPTH (ROBOT)

---

- 3\_1\_a\_depth\_checker.py
- 3\_1\_b\_depth\_to\_3d.py
- 3\_1\_c\_depth\_to\_nav\_goal.py
- 3\_1\_d\_nav\_to\_person.py
- 3\_2\_a\_nav\_to\_pose.py
- 3\_2\_b\_nav\_through\_poses.py
- 3\_2\_c\_follow\_waypoints.py
- 3\_2\_d\_create\_path.py
- 3\_2\_e\_mail\_delivery.py
- 3\_2\_f\_patrol\_loop.py
- 3\_3\_a\_depth\_checker.py
- 3\_3\_b\_depth\_to\_3d.py
- 3\_3\_c\_depth\_to\_nav\_goal.py

- 3\_3\_a\_depth\_checker.py
- 3\_3\_b\_depth\_to\_3d.py
- 3\_3\_c\_depth\_to\_nav\_goal.py

**Exercise:** using the simulation code develop the code for the actual robot



# USING DEPTH (ROBOT)

---

```
3_3_a_depth_checker.py
3_3_b_depth_to_3d.py
3_3_c_depth_to_nav_goal.py
```

```
$ ros2 run day4 depth_checker --ros-args -r __ns:=/robot<n>

$ ros2 run day4 depth_to_3d --ros-args -r __ns:=/robot<n> -r /tf:=/robot<n>/tf -r /tf_static:=/robot<n>/tf_static

$ ros2 run day4 depth_to_goal --ros-args -r __ns:=/robot<n> -r /tf:=/robot<n>/tf -r /tf_static:=/robot<n>/tf_static
```

# 프로젝트 RULE NUMBER ONE!!!

---

Are we still having  
**FUN!**

